

#### **OSRAM Customer Service Centre**

OSRAM Ltd.  
Neills Road  
Bold Industrial Park  
St Helens WA9 4XG  
Tel: 01744 812221  
Fax: 01744 831900  
E-mail: csc@osram.co.uk

[www.osram.com](http://www.osram.com)



UK edition November 2010 Subject to modification without notice. Errors and omissions excepted. Printed on paper treated with chlorine-free bleach.

## **Buyers Guide 2010 | 2011**

[www.osram.com](http://www.osram.com)



# **OSRAM Buyers Guide 2010 | 2011**

General Lighting  
LED systems/ LED lamps  
Luminaires  
Electronic Control Gear  
Automotive  
Display Optic

SEE THE WORLD IN A NEW LIGHT



Any manipulation of our products or packaging, including but not limited to modification, reworking or restamping, is prohibited and infringes our registered trademark rights. Such modifications may impair the technical properties of our products, destroy them or cause consequential damage or injury, for which OSRAM cannot under any circumstances be held responsible.

For more information on our products go to:

**[www.osram.com](http://www.osram.com)**




Printed on paper treated with chlorine-free bleach.

Subject to change without notice.

Errors and omission excepted.

|  |            |
|--|------------|
| <b>General Lighting Service</b>                        | <b>2</b>   |
| <hr/>  |            |
| <b>Tungsten Halogen Lamps</b>                          | <b>12</b>  |
| <hr/>  |            |
| <b>Compact Fluorescent Lamps</b>                       | <b>34</b>  |
| <hr/>  |            |
| <b>LED Lamps</b>                                       | <b>68</b>  |
| <hr/>  |            |
| <b>Fluorescent Tubes</b>                               | <b>84</b>  |
| <hr/>  |            |
| <b>High Pressure Discharge Lamps</b>                   | <b>120</b> |
| <hr/>  |            |
| <b>LED Modules</b>                                     | <b>150</b> |
| <hr/>  |            |
| <b>Automotive Lamps</b>                                | <b>172</b> |
| <hr/>  |            |
| <b>Display/Optic Lamps</b>                             | <b>188</b> |
| <hr/>  |            |
| <b>Electronic Control Gear</b>                         | <b>234</b> |
| <hr/>  |            |
| <b>Light Management Systems</b>                        | <b>266</b> |
| <hr/>  |            |
| <b>Luminaires (and NEW Traxon LED luminaire range)</b> | <b>308</b> |
| <hr/>  |            |
| <b>Glossary</b>  | <b>382</b> |
| <hr/>  |            |



## A world fit to live in – today and tomorrow.

The consequences of global warming are already evident. The polar ice caps and glaciers are melting, sea levels are rising and deserts are expanding. The problem lies with increasing CO<sub>2</sub> emissions throughout the world. As a globally active company we are aware of our enormous responsibility towards people and the environment. This is why sustainability is the basic principle behind all of OSRAM's actions. We are careful with natural resources, avoid waste wherever possible, and help reduce the greenhouse effect by developing energy-saving lamps and systems.




### **Efficient products.**

Our energy-efficient products are helping to restore the balance. By using OSRAM energy-saving lamps for example it is possible to reduce power consumption for lighting by up to 80%. At the same time, because of its long life a single compact fluorescent lamp replaces up to 15 ordinary light bulbs. OSRAM energy-saving lamps therefore not only lead to a considerable reduction in CO<sub>2</sub> emissions they help avoid waste and cut down on purchase costs and electricity costs. Innovative IRC technology is providing impressive savings in halogen lamps. OSRAM HALOGEN ENERGY SAVER CLASSIC is a simple direct replacement for ordinary light bulbs.

### **Economical systems.**

To make lighting even more efficient we are focusing more and more on developing systems comprising of lamps, electronic control gear and lighting management. Electronic operation not only ensures long life but also energy-saving operation and high-quality light. In this way, the enormous potential of our innovative lamps can be fully exploited.



### Extensive recycling, real sustainability.

Even when they come to the end of their lives, OSRAM lamps are almost completely recyclable and provide valuable raw materials. We make use of eco-friendly waste disposal systems and closed material cycles; the recycled materials are then used as far as possible for manufacturing new products. Our packaging is generally made of recycled paper, and in the OEM sector we mainly use multi-use packaging. For OSRAM, sustainability is more than a buzz word.

### Clear labeling, clear statement.

We label products that are particularly energy efficient with the symbol of a green tree. These climate protection products are part of our Global Care Program, to which we have made the following commitment:

**As a globally active company we act responsibly towards society and the environment, meet global challenges with sustainable products and pioneering processes and therefore make a contribution to maintaining the environment for the benefit of future generations.**

With products from the OSRAM Global Care Program you too can make a significant contribution to climate protection and boost your reputation for eco-friendliness.

Each of the 25 million UK households were to replace five 60 W light bulbs with HALOGEN ES 42 W<sup>1,2</sup>.

- ✖ 1.1 million tonnes of CO<sub>2</sub><sup>3</sup>
- ✖ 2.25 billion kWh of electricity
- ✖ £225 million<sup>4</sup>

Six OSRAM DULUX® EL 12 W lamps<sup>2</sup> were to be used in a home<sup>1,2</sup>.

- ✖ 144 kg CO<sub>2</sub>
- ✖ 288 kWh electricity
- ✖ £28.80<sup>4</sup>

- 1.1 million tonnes of CO<sub>2</sub> is equivalent to the average emissions of approx. 513,333 cars per year<sup>5</sup>
- One tree absorbs around 20 kg of carbon dioxide per year
- To absorb 1.1 million tonnes of CO<sub>2</sub> you would need 55,000.00 trees.
- 562,500 tonnes of crude oil would be needed to produce 2.25 billion kWh of electricity

<sup>1</sup> Operating for 1000 hours per year

<sup>2</sup> Instead of a 60 W light bulb

<sup>3</sup> Energy mix for the UK

0.5 kg CO<sub>2</sub>/kWh

<sup>4</sup> Electricity price £0.10/kWh

<sup>5</sup> Calculated for CO<sub>2</sub> emissions of 165 g/km, 13,000 km p.a.

# Energy-saving alternatives to standard products

On the basis of the climate protection objectives laid down in Kyoto in 1997 the EU defined a series of measures relating to the economical and sustainable use of natural resources. Following the ban on conventional control gear embodied in directive 2000/55/EC, the reduction of hazardous substances in line with directive 2002/95/EC (RoHS) and the directive for the disposal of waste electrical and electronic equipment 2002/96/EC (WEEE), the EU issued directive 2005/32/EC to define the design requirements (Ecodesign) that energy-using products (EuP) have to meet in terms of their environmental impact. This directive was superseded in November 2009 by the more extensive 2009/125/EC directive relating to the eco-design of energy-relevant products (ErP), but this does not have any additional consequences for the lighting industry.





In March 2009 the EU Commission issued two regulations known as "implementation measures" on the basis of Article 15 of the EuP directive. These regulations impose specific requirements for sections of the electrical lighting market. Regulation EC 244/2009 (amended by regulation EC 859/2009) defines requirements relating to the eco-design of non-directional household lamps. This EC 244/2009 regulation covers the technologies that are generally used in the residential sector, namely incandescent lamps, halogen lamps, compact fluorescent lamps with integrated control gear, and LED retrofits. By contrast, regulation EC 245/2009 defines requirements for the eco-design of products used mainly in street, industry and office lighting, namely fluorescent lamps, compact fluorescent lamps with plug bases, high-intensity discharge lamps with E27, E40 and PGZ12 bases, and control gear and luminaires for fluorescent lamps and high-intensity discharge lamps.

The obvious consequence of the two implementation measures has been the phase-out of various types of lamp, which started on September 1, 2009. Under the provisions of EC 244/2009, incandescent lamps (with the exception of lamps for defined special applications) will be phased out completely by 2012<sup>1)</sup>. Halogen lamps and compact fluorescent lamps with integrated control gear must also meet defined minimum requirements if they are to be marketed in the EU. The criteria used to assess the lamps include efficiency, lamp life and lumen maintenance.

Compliance with the implementation measures of the Ecodesign directive will be indicated by the CE symbol. This means that in future the CE symbol will no longer stand only for compliance with safety regulations but also for compliance with the quality requirements defined in the Ecodesign implementation measures.

Another requirement of EC 245/2009 and EC 244/2009 is the obligation to publish particular product information from April or September 2010. This information must be shown on the packaging and/or published on the internet, depending on which of the two implementation measures applies to the product. This information includes for example the mercury content of the lamp and details of lumen maintenance. The implementation measures already define products that will be phased out by 2016 (EC 244/2009) and 2017 (EC 245/2009). Both EU regulations will be subjected

to a review by 2014 at the latest, which is standard practice for such regulations.

At present the EU Commission is working on a further implementation measure for household lighting which will define the eco-design requirements of household lamps with directional light and all household luminaires. This regulation is expected to be issued at the end of 2010/start of 2011.

The following pages show the impact of the implementation measures on OSRAM's product range. In view of the ongoing change procedure for the products affected by EC 245/2009, there may be further changes.

Irrespective of the statutory requirements, OSRAM is committed to sustainability and therefore already offers energy-saving alternatives to its standard products. The ECO versions of the line-voltage halogen products HALOPIN and HALOLINE already meet the energy efficiency requirements of the regulation, whereas the standard versions will have to be gradually removed from the market. As things stand at present, after 2016 these Energy Class C products may continue to be marketed because of the exemption for G9 and R7s bases.

In addition to direct replacement of high-pressure sodium lamps for which only an adequate ignition voltage needs to be tested OSRAM offers further energy-efficient solutions with the transition to metal halide lamps with ceramic burners. In these cases, it may be necessary to change the control gear. With regard to T12 fluorescent lamps, OSRAM goes beyond the requirements of the regulation and will be removing these products from the market in 2010 – two years before the official deadline. Control gear from OSRAM already meets the efficiency requirements of tomorrow. For example, it already meets the threshold values for standby losses that need to be met by 2012.

For the latest information on the products affected and the energy-efficient alternatives available go to our website at [www.osram.com](http://www.osram.com).

1) Further information at [www.elcfed.org/documents/Special%20Purpose%20Lamps\\_090515.pdf](http://www.elcfed.org/documents/Special%20Purpose%20Lamps_090515.pdf)

## Implementation measure for non-directional household lighting

|  | Sep. 2009  | Sep. 2010   | Sep. 2011                                     | Sep. 2012                    | Sep. 2013                             | Sep. 2014 | Sep. 2015                           | Sep. 2016 |
|--|--|---|---|------------------------------|---------------------------------------|-----------|-------------------------------------|-----------|
|  Incandescent lamp, clear lamps | 15 W<br>25 W<br>40 W<br>60 W<br>75 W<br>> 100 W  | 15 W<br>25 W<br>40 W<br>60 W<br>75 W<br>100 W     | 15 W<br>25 W<br>40 W<br>60 W<br>75 W<br>100 W |                              |                                       |           | Ban on all clear incandescent lamps |           |
|  Frosted lamps                  |  |   |   |                              |                                       |           |                                     |           |
|  HALOLUX BT clear               |  |   |   |                              |                                       |           |                                     |           |
|  HALOGEN ECO Classic clear      | 18 W<br>28 W<br>42 W<br>52 W<br>70 W<br>105 W  |   |   | 18 W                         | 28 W<br>42 W<br>52 W<br>70 W<br>105 W | 18 W      | Alternatives planned                |           |
|  HALOLUX CERAM ECO clear        |  |   |   |                              |                                       |           |                                     |           |
|  HALOSTAR klar                  |  |   |   |                              |                                       |           |                                     |           |
|  HALOSTAR ECO clear             |  |   |   |                              |                                       |           |                                     |           |
|  HALOPIN clear                 | 25 W<br>40 W<br>60 W<br>75 W   | 25 W<br>40 W<br>60 W<br>75 W                      | 25 W<br>40 W<br>60 W<br>75 W                  | 25 W<br>40 W<br>60 W<br>75 W |                                       |           |                                     |           |
|  HALOPIN ECO clear            |  |   |   |                              |                                       |           | Exception:<br>G9 in Energy Class C  |           |
|  HALOLINE clear               | 60 W<br>100 W<br>150 W<br>200 W<br>300 W<br>500 W  | 60 W<br>100 W<br>150 W<br>200 W<br>300 W<br>500 W |   |                              |                                       |           |                                     |           |
|  HALOLINE P15 clear           | 750 W<br>1000 W<br>1500 W<br>2000 W  |   |   |                              |                                       |           |                                     |           |
|  HALOLINE ECO clear           |  |   |   |                              |                                       |           | Exception:<br>R7s in Energy Class C |           |
|  HALOLUX T clear              |  |   |   |                              |                                       |           |                                     |           |
|  Special                      | Further information at <a href="http://www.elcfed.org/documents/Special%20Purpose%20Lamps_090515.pdf">www.elcfed.org/documents/<br/>Special%20Purpose%20Lamps_090515.pdf</a> |   |   |                              |                                       |           |                                     |           |
|  Directional household lamps  | The implementation measure for directional light sources will be issued at the end of 2010/start of 2011   |   |   |                              |                                       |           |                                     |           |

## Implementation measure for tertiary lighting

|   | Apr. 2010  | Apr. 2011  | Apr. 2012                                    | Apr. 2013 | Apr. 2014             | Apr. 2015 | Apr. 2016 |
|---|--|--|--|-----------|-----------------------|-----------|-----------|
|  NAV-E             | NAV-E STANDARD<br>NAV-E/I<br>NAV-E 4Y > 70 W<br>NAV-E 4Y ≤ 70 W<br>NAV-E/I 4Y ≤ 70 W<br>NAV-E SUPER 4Y |  | NAV-E STANDARD<br>NAV-E/I<br>NAV-E 4Y > 70 W |           |                       |           |           |
|  NAV-E Plug-in     |  | NAV-E Plug-in ≥ 210 W<br>NAV-E Plug-in 110 W<br>NAV-E Plug-in 68 W                 |  |           | NAV-E Plug-in ≥ 210 W |           |           |
|  NAV-T             |  | NAV-T STANDARD<br>NAV-T 4Y<br>NAV-T SUPER 4Y                                       | NAV-T STANDARD<br>NAV-T 4Y                   |           |                       |           |           |
|  HQL               |  |  |  |           |                       |           |           |
|  HWL               |  | Exempt from the directive because of the spectrum of the lamp                      |  |           |                       |           |           |
|  HQI clear         |  |  |  |           |                       |           |           |
|  HQI non-clear     |  |  |  |           |                       |           |           |
|  HCI               |  |  |  |           |                       |           |           |
|  T8                | T8 BASIC<br>T8 BASIC U-shape<br>T8 LUMILUX<br>T8 LUMILUX U-shape                                       |  |  |           |                       |           |           |
|  T12 halophosphate | OSRAM withdrawal<br>T8 LUMILUX   | T12  |  |           |                       |           |           |
|  Ring lamp         | T9 BASIC ring lamp<br>T9 LUMILUX ring lamp   |  |  |           |                       |           |           |
|  DULUX 2pin      |  |  |  |           |                       |           |           |
|  DULUX 4pin      |  |  |  |           |                       |           |           |
| Standby losses FL   | P <sub>0%</sub> 1 W  | P <sub>0%</sub> ≤ 0,5 W  |  |           |                       |           |           |
|  Non-DIM QT      |  |  |  |           |                       |           |           |
|  DIM QT          |  |  |  |           |                       |           |           |
|  PT              |  |  |  |           |                       |           |           |
|  Luminaire       | Only losses of the integrated control gear   | The luminaire must be compatible with at least Class A2 control gear (except IP4X) |  |           |                       |           |           |

Changes are possible as a result of the change procedure

Review by the EU Commission

 In portfolio

 Not in portfolio

## SERVICE ON THE INTERNET

# See the world in a new light – [www.osram.com](http://www.osram.com)

On the OSRAM website you can find more than just the fascinating world of light and lighting, the latest information and interesting links, you can also download various practical tools and services for commercial customers and consumers.

### Focusing on your needs.

To help you find what you're looking for even faster we have reorganised the OSRAM website so it fits better with your requirements. Products for lighting professionals are now all together in the PROFESSIONAL section. You will find advice, costings, business services, downloads and everything to do with training and know-how in the TOOLS & SERVICES section. Consumers can experience the entire OSRAM world of lighting in the CONSUMER section – lamps, luminaires and accessories for the home and automobile, the latest campaigns and competitions.



### OSRAM brochure download centre

The OSRAM download centre enables you to quickly download the information you need to your computer.

### [www.voltimum.co.uk](http://www.voltimum.co.uk)

The aim of the portal is to provide information and services to all professionals in the electrical installation market thereby helping to save time and money in the design, specification and estimation of electrical projects. Visit the site to view the most comprehensive OSRAM UK product range catalogue, ask our panel of technical experts for advice and answers to your technical questions or simply to keep abreast of the latest industry news.





### Web-based training online service.

Our interactive product training program, comprising eight coordinated and clearly structured modules, is the quick stress-free way of acquiring extensive knowledge relating to light, lamps and lighting. At the end of each module you can monitor your progress by answering twelve questions. When you have successfully completed the training program we will issue you with your own personal certificate.

The screenshot shows the 'Product Training Program' section of the OSRAM website. It features a large image of a light fixture and a central text area with the heading 'More knowledge, more success:'. Below this, it says 'The online training program gives you a basic understanding on light and lighting.' There are several navigation links on the right side, including 'Home Page', 'Product Training Program', 'Lamp & LED Catalogue', 'OSRAM Applications', 'OSRAM Case Studies', and 'Contact Us'.

### Information on EU directives.

The screenshot shows the 'EU Directives' section of the OSRAM website. It features a large image of a person working at a desk with a lamp. Below the image, there is a video player showing a video about the lighting market in transition. To the right, there is a text box with the heading 'The lighting market in transition' and a link to 'EU Directives'. Navigation links are visible on the right side.

At [www.osram.com](http://www.osram.com) you can read the latest information on the new EU directives and alternative products for the lamps that have to be removed from the market.

### Theres no business like E-business

[www.myOSRAM.com](http://www.myOSRAM.com)

- The information and shopping portal 24/7

MyOSRAM.com is the exclusive customer information and shopping portal. Simple to use, fast and convenient providing 24/7 access to ordering online.

If you are already a registered OSRAM customer and you do not have access to the site please contact the OSRAM customer service centre 01744 812221.





### OSRAM Lighting Consultant.

The screenshot shows the 'Lighting Consultant' section of the OSRAM website. It features a large image of a modern interior space with recessed lighting. Below the image, there is a text box with the heading 'Business and energy-efficient lighting systems' and a link to 'Lighting Consultant'. Navigation links are visible on the right side.

At [www.osram.com/light-consultant](http://www.osram.com/light-consultant) you can find the right lighting system for optimum illumination of commercial premises and can calculate the savings in energy, costs and CO<sub>2</sub> emissions.

GENERAL LIGHTING SERVICE LAMPS




# General Lighting Service Lamps

## Contents.

|                   |    |
|-------------------|----|
| GLS clear         | 4  |
| Candle 35mm clear | 5  |
| Globe 45mm clear  | 6  |
| Reflectors        | 8  |
| PAR 38            | 9  |
| Appliance lamps   | 9  |
| Oven lamps        | 10 |
| Rough service     | 10 |
| Striplight        | 11 |



## General Lighting Service Lamps




### GLS clear BC

- CLASSIC A
- Classic shape basic incandescent lamps
- Ideal for creating more sparkle in general lighting

| Product ID Code          | EAN (Single Pack) | Product Description | W  | V   | lm  |         | FINISH |     | PPG |
|--------------------------|-------------------|---------------------|----|-----|-----|---------|--------|-----|-----|
| 24015B22 <sup>2)</sup>   | 4050300285856     | CLASSIC A CL15      | 15 | 240 | 90  | BC/B22d | Clear  | 25  | 2   |
| 24025B22 <sup>2)</sup>   | 4050300290041     | CLASSIC A CL25      | 25 | 240 | 220 | BC/B22d | Clear  | 25  | 1   |
| 24040B22 <sup>2)</sup>   | 4050300285436     | CLASSIC A CL40      | 40 | 240 | 415 | BC/B22d | Clear  | 100 | 1   |
| 24060B22 <sup>1)</sup>   | 4050300285450     | CLASSIC A CL60      | 60 | 240 | 710 | BC/B22d | Clear  | 100 | 1   |
| <b>Twin pack carton</b>  |                   |                     |    |     |     |         |        |     |     |
| 24060B22P2 <sup>1)</sup> | 4008321083517     | CLASSIC A CL60 TC   | 60 | 240 | 710 | BC/B22d | Clear  | 20  | 6   |

- 1) Banned from 1.9.2011 as per EU phase-out plan  
2) Banned from 1.9.2012 as per EU phase-out plan

**Alternative: HALOGEN CLASSIC A ECO, PARATHOM® CLASSIC A LED or OSRAM DULUX® retrofit compact fluorescent lamps**



### GLS clear ES

- CLASSIC A
- Classic shape basic GLS lamps
- Ideal for creating more sparkle in general lighting

| Product ID Code         | EAN (Single Pack) | Product Description | W  | V   | lm  |        | FINISH |     | PPG |
|-------------------------|-------------------|---------------------|----|-----|-----|--------|--------|-----|-----|
| 24040 <sup>2)</sup>     | 405030023328      | CLASSIC A CL40      | 40 | 240 | 415 | ES/E27 | Clear  | 100 | 1   |
| 24060 <sup>1)</sup>     | 405030023342      | CLASSIC A CL60      | 60 | 240 | 710 | ES/E27 | Clear  | 100 | 1   |
| <b>Twin pack carton</b> |                   |                     |    |     |     |        |        |     |     |
| 24060P2 <sup>2)</sup>   | 4008321081674     | CLASSIC A CL60 TC   | 60 | 240 | 710 | ES/E27 | Clear  | 20  | 6   |

**Alternative: HALOGEN CLASSIC A ECO, PARATHOM® CLASSIC A LED or OSRAM DULUX® retrofit compact fluorescent lamps**

All orders must be multiples of sales pack



## General Lighting Service Lamps

**Candle 35mm clear BC**


- CLASSIC B
- 35mm plain candle lamps
- Ideal for decorative wall, ceiling and table luminaires where more sparkle is required

| Product ID Code            | EAN (Single Pack) | Product Description | W  | V   | lm  |         | FINISH |     | PPG |
|----------------------------|-------------------|---------------------|----|-----|-----|---------|--------|-----|-----|
| 240B25B22 <sup>2)</sup>    | 4050300032948     | CLASSIC B CL25      | 25 | 240 | 200 | BC/B22d | Clear  | 100 | 3   |
| 240B40B22 <sup>2)</sup>    | 4050300033143     | CLASSIC B CL40      | 40 | 240 | 400 | BC/B22d | Clear  | 100 | 3   |
| 240B60B22 <sup>1)</sup>    | 4050300033594     | CLASSIC B CL60      | 60 | 240 | 660 | BC/B22d | Clear  | 100 | 3   |
| <b>Four pack carton</b>    |                   |                     |    |     |     |         |        |     |     |
| 240B60B22P4 <sup>1)</sup>  | 4050300797717     | CLASSIC B CL60C     | 60 | 240 | 660 | BC/B22d | Clear  | 100 | 3   |
| <b>Twin blister</b>        |                   |                     |    |     |     |         |        |     |     |
| 240B40B22BL2 <sup>2)</sup> | 4050300149882     | CLASSIC B CL40 BL   | 40 | 240 | 400 | BC/B22d | Clear  | 20  | 6   |
| 240B60B22BL2 <sup>1)</sup> | 4050300149899     | CLASSIC B CL60 BL   | 60 | 240 | 660 | BC/B22d | Clear  | 20  | 6   |

1) Banned from 1.9.2011 as per EU phase-out plan

2) Banned from 1.9.2012 as per EU phase-out plan

Alternative: HALOGEN CLASSIC B ECO, the direct replacement for classic incandescent lamps.

**Candle 35mm clear SBC**

- CLASSIC B ECO
- 35mm plain candle lamps
- Ideal for decorative wall, ceiling and table luminaires where more sparkle is required

| Product ID Code            | EAN (Single Pack) | Product Description | W  | V   | lm  |          | FINISH |     | PPG |
|----------------------------|-------------------|---------------------|----|-----|-----|----------|--------|-----|-----|
| 240B25B15 <sup>1)</sup>    | 4050300032900     | CLASSIC B CL25      | 25 | 240 | 200 | SBC/B15d | Clear  | 100 | 3   |
| 240B40B15 <sup>1)</sup>    | 4050300033082     | CLASSIC B CL40      | 40 | 240 | 400 | SBC/B15d | Clear  | 100 | 3   |
| 240B60B15 <sup>1)</sup>    | 4050300033570     | CLASSIC B CL60      | 60 | 240 | 660 | SBC/B15d | Clear  | 100 | 3   |
| <b>Twin blister</b>        |                   |                     |    |     |     |          |        |     |     |
| 240B40B15BL2 <sup>1)</sup> | 4050300164229     | CLASSIC B CL40 BL   | 40 | 240 | 400 | SBC/B15d | Clear  | 20  | 6   |


1) Banned from 1.9.2012 as per EU phase-out plan

Alternative: HALOGEN CLASSIC B ECO, the direct replacement for classic incandescent lamps.

All orders must be multiples of sales pack



## General Lighting Service Lamps




### Candle 35mm clear SES

- CLASSIC B
- 35mm plain candle lamps
- Ideal for decorative wall, ceiling and table luminaires where more sparkle is required

| Product ID Code         | EAN (Single Pack) | Product Description | W  | V   | lm  |  | FINISH  |       | PPG   |
|-------------------------|-------------------|---------------------|----|-----|-----|--|---------|-------|-------|
| 240B25 <sup>2)</sup>    | 4050300033020     | CLASSIC B CL25      | 25 | 240 | 200 |  | SES/E14 | Clear | 100 3 |
| 240B40 <sup>2)</sup>    | 4050300033471     | CLASSIC B CL40      | 40 | 240 | 400 |  | SES/E14 | Clear | 100 3 |
| 240B60 <sup>1)</sup>    | 4050300328980     | CLASSIC B CL60      | 60 | 240 | 660 |  | SES/E14 | Clear | 100 3 |
| <b>Twin blister</b>     |                   |                     |    |     |     |  |         |       |       |
| 240B25BLI <sup>2)</sup> | 4050300829449     | CLASSIC B CL25 BL   | 25 | 240 | 200 |  | SES/E14 | Clear | 20 6  |
| 240B40BLI <sup>2)</sup> | 4050300174907     | CLASSIC B CL40 BL   | 40 | 240 | 400 |  | SES/E14 | Clear | 20 6  |
| 240B60BLI <sup>2)</sup> | 4050300174501     | CLASSIC B CL60 BL   | 60 | 240 | 660 |  | SES/E14 | Clear | 20 6  |

- 1) Banned from 1.9.2011 as per EU phase-out plan
- 2) Banned from 1.9.2012 as per EU phase-out plan

Alternative: HALOGEN CLASSIC B ECO, PARATHOM® CLASSIC B LED, or OSRAM DULUX® retrofit compact fluorescent lamps



### Globe 45mm clear BC

- CLASSIC P
- 45mm small globe lamps
- Ideal for smaller decorative luminaires where more sparkle is required

| Product ID Code            | EAN (Single Pack) | Product Description | W  | V   | lm  |  | FINISH  |       | PPG  |
|----------------------------|-------------------|---------------------|----|-----|-----|--|---------|-------|------|
| 240P40B22 <sup>2)</sup>    | 4050300187846     | CLASSIC P CL40      | 40 | 240 | 400 |  | BC/B22d | Clear | 50 5 |
| <b>Twin blister</b>        |                   |                     |    |     |     |  |         |       |      |
| 240P40B22BLI <sup>2)</sup> | 4050300164267     | CLASSIC P CL40 BL   | 40 | 240 | 400 |  | BC/B22d | Clear | 20 6 |
| 240P60B22BLI <sup>2)</sup> | 4050300164328     | CLASSIC P CL60 BL   | 60 | 240 | 660 |  | BC/B22d | Clear | 20 6 |


- 1) Banned from 1.9.2011 as per EU phase-out plan
- 2) Banned from 1.9.2012 as per EU phase-out plan

Alternative: HALOGEN CLASSIC P ECO, or OSRAM DULUX® retrofit compact fluorescent lamps

All orders must be multiples of sales pack



## General Lighting Service Lamps

**Globe 45mm clear SES**

- CLASSIC P
- 45mm small globe lamps
- Ideal for smaller decorative luminaires where more sparkle is required

| Product ID Code | EAN (Single Pack) | Product Description | W | V | Im |  | FINISH |  | PPG |
|-----------------|-------------------|---------------------|---|---|----|--|--------|--|-----|
|-----------------|-------------------|---------------------|---|---|----|--|--------|--|-----|

**Twin blister**

|                          |               |                |    |     |     |         |       |    |   |
|--------------------------|---------------|----------------|----|-----|-----|---------|-------|----|---|
| 240P40BLI2 <sup>1)</sup> | 4050300134772 | CLASSIC P CL40 | 40 | 240 | 400 | SES/E14 | Clear | 20 | 6 |
|--------------------------|---------------|----------------|----|-----|-----|---------|-------|----|---|


1) Banned from 1.9.2012 as per EU phase-out plan

Alternative: HALOGEN CLASSIC P ECO, or OSRAM DULUX® retrofit compact fluorescent lamps

All orders must be multiples of sales pack



## General Lighting Service Lamps



### Reflectors

- CONCENTRA® SPOT
- Blown glass
- Focused shape
- Ideal for commercial and domestic display lighting

| Product ID Code       | EAN (Single Pack) | Product Description   | W   | V   |         | No. |     | PPG |
|-----------------------|-------------------|-----------------------|-----|-----|---------|-----|-----|-----|
| <b>R50</b>            |                   |                       |     |     |         |     |     |     |
| 240R5040              | 4050300302263     | CONCENTRA R50 SP40    | 40  | 240 | SES/E14 | 1   | 25  | 7   |
| <b>Twin blister</b>   |                   |                       |     |     |         |     |     |     |
| 240R5040BLI2          | 4050300164427     | CONCENTRA R50 SP40 BL | 40  | 240 | SES/E14 | 1   | 20  | 6   |
| <b>R63</b>            |                   |                       |     |     |         |     |     |     |
| 240R6340              | 4050300023397     | CONCENTRA R63 SP40    | 40  | 240 | ES/E27  | 2   | 25  | 7   |
| 240R6360              | 4050300023380     | CONCENTRA R63 SP60    | 60  | 240 | ES/E27  | 2   | 25  | 7   |
| <b>Twin blister</b>   |                   |                       |     |     |         |     |     |     |
| 240R6340BLI2          | 4050300134826     | CONCENTRA R63 SP40BL  | 40  | 240 | ES/E27  | 1   | 20  | 6   |
| 240R6360BLI2          | 4050300164403     | CONCENTRA R63 SP60BL  | 60  | 240 | ES/E27  | 1   | 20  | 6   |
| <b>R80</b>            |                   |                       |     |     |         |     |     |     |
| 240R8060              | 4050300066059     | CONCENTRA R80 60      | 60  | 240 | ES/E27  | 3   | 100 | 9   |
| 240R8075              | 4050300066066     | CONCENTRA R80 75      | 75  | 240 | ES/E27  | 3   | 100 | 9   |
| 240R80100             | 4050300066073     | CONCENTRA R80 100     | 100 | 240 | ES/E27  | 3   | 100 | 9   |
| <b>Single blister</b> |                   |                       |     |     |         |     |     |     |
| 240R8060BLI1          | 4050300041728     | CONCENTRA R80 60 BL   | 60  | 240 | ES/E27  | 3   | 10  | 6   |

Alternative: HALOGEN SPOT R50/R63 ECO, PARATHOM® R50/R63 LED or OSRAM DULUX® retrofit compact fluorescent lamps

All orders must be multiples of sales pack



## General Lighting Service Lamps

**PAR 38**

- CONCENTRA® PAR
- Hard glass
- Flood beam angle
- Ideal for display and garden lighting

| Product ID Code | EAN (Single Pack) | Product Description     |    |     |        |              |      |
|-----------------|-------------------|-------------------------|----|-----|--------|--------------|------|
| <b>Coloured</b> |                   |                         |    |     |        |              |      |
| PAR80RE         | 4050300007656     | CONCENTRA PAR 38 Red    | 80 | 240 | ES/E27 | Red Flood    | 12 5 |
| PAR80GR         | 4050300007670     | CONCENTRA PAR 38 Green  | 80 | 240 | ES/E27 | Green Flood  | 12 5 |
| PAR80BL         | 4050300007687     | CONCENTRA PAR 38 Blue   | 80 | 240 | ES/E27 | Blue Flood   | 12 5 |
| PAR80YE         | 4050300007663     | CONCENTRA PAR 38 Yellow | 80 | 240 | ES/E27 | Yellow Flood | 12 5 |

**Appliance lamps**


- Small lamps with a clear finish
- Ideal for domestic appliances such as sewing machines and fridges

| Product ID Code       | EAN (Single Pack) | Product Description |    |     |     |          |            |
|-----------------------|-------------------|---------------------|----|-----|-----|----------|------------|
| <b>Single blister</b> |                   |                     |    |     |     |          |            |
| FRIDGE15BLI1          | 4050300092928     | SPCT FRIDGE CL      | 15 | 240 | 110 | SES/E14  | Clear 10 6 |
| T5715B15BLI1          | 4050300092935     | SPCT26/57 CL        | 15 | 240 | 190 | SBC/B15d | Clear 10 6 |

All orders must be multiples of sales pack




## General Lighting Service Lamps



### Oven lamps

- SPC. (pygmy) oven lamp
- 300°C
- Ideal for oven lighting

| Product ID Code | EAN (Single Pack) | Product Description  | W  | V   | lm  | FINISH  | Light No.    | PPG      |
|-----------------|-------------------|----------------------|----|-----|-----|---------|--------------|----------|
| OVEN15BLI1      | 4050300065052     | SPC T OVEN CL 15 OBL | 15 | 240 | 90  | SES/E14 | Clear – 22mm | 1 10 6   |
| 64428           | 4050300308050     | SPC OVEN CL G4       | 20 | 12  | 320 | G4      | Clear        | 2 40 38  |
| OVEN40FR        | 4050300008486     | SPC P OVEN FR 40     | 40 | 240 | –   | SES/E14 | Clear        | 3 100 38 |



### Rough service

- CENTRA®
- Basic GLS shape
- Extra filament supports
- Ideal for hand inspection lamps

| Product ID Code | EAN (Single Pack) | Product Description | W   | V   | lm   | FINISH  | Light No.    | PPG |
|-----------------|-------------------|---------------------|-----|-----|------|---------|--------------|-----|
| 120CTR60FRB22   | 4050300615073     | CENTRA 60/120       | 60  | 120 | –    | BC/B22d | Pearl 1 25 1 |     |
| 240CTR60FRB22   | 4050300200910     | CENTRA 60/240BC     | 60  | 240 | 505  | BC/B22d | Pearl 1 25 1 |     |
| 240CTR60FR      | 4050300200866     | CENTRA 60/240       | 60  | 240 | 505  | ES/E27  | Pearl 2 25 1 |     |
| 240CTR100FRB22  | 4050300425771     | CENTRA 100/240BC    | 100 | 240 | 1000 | BC/B22d | Pearl 1 25 1 |     |
| 240CTR100FR     | 4050300230757     | CENTRA 100/240      | 100 | 240 | 1000 | ES/E27  | Pearl 2 25 1 |     |


All orders must be multiples of sales pack



## General Lighting Service Lamps



1



2

**Striplight**


- Linear, double ended incandescent lamps
- 221mm or 284mm long
- Ideal for shaving and furniture lights

| Product ID Code               | EAN (Single Pack) | Product Description      | W  | V   | Im  |     | FINISH |   | No. |    | PPG |
|-------------------------------|-------------------|--------------------------|----|-----|-----|-----|--------|---|-----|----|-----|
| <b>221mm</b>                  |                   |                          |    |     |     |     |        |   |     |    |     |
| 24022130CL <sup>1)</sup>      | 4050300047768     | Striplight 221mm         | 30 | 240 | 230 | S15 | Clear  | 1 | 25  | 11 |     |
| <b>221mm (Single blister)</b> |                   |                          |    |     |     |     |        |   |     |    |     |
| 24022130SILBLI <sup>1)</sup>  | 4050300164465     | Striplight 221mm Blister | 30 | 240 | 230 | S15 | Opal   | 2 | 10  | 6  |     |
| <b>284mm</b>                  |                   |                          |    |     |     |     |        |   |     |    |     |
| 24028460CL <sup>1)</sup>      | 4050300292229     | Striplight 284mm         | 60 | 240 | 200 | S15 | Clear  | 1 | 25  | 11 |     |
| 24028460SIL <sup>1)</sup>     | 4050300090504     | Striplight 284mm         | 60 | 240 | 450 | S15 | Opal   | 2 | 25  | 11 |     |
| <b>284mm (Single blister)</b> |                   |                          |    |     |     |     |        |   |     |    |     |
| 24028460SILBLI <sup>1)</sup>  | 4050300164502     | Striplight 284mm Blister | 60 | 240 | -   | S15 | Opal   | 2 | 10  | 6  |     |

1) Banned from 1.9.2012 as per EU phase-out plan

All orders must be multiples of sales pack

TUNGSTEN HALOGEN LAMPS



# Tungsten Halogen Lamps

## Contents.

### MAIN VOLTAGE HALOGEN LAMPS

|                          |    |
|--------------------------|----|
| HALOPIN® ECO             | 14 |
| HALOPIN®                 | 14 |
| DECOPIN®                 | 15 |
| OSRAM HALOPAR® 16 ECO    | 15 |
| OSRAM HALOPAR® 16        | 16 |
| OSRAM HALOPAR® 20        | 16 |
| OSRAM HALOPAR® 30        | 17 |
| OSRAM HALOPAR® 38        | 17 |
| HALOGEN CLASSIC ECO      | 18 |
| HALOGEN SPOT R50/R63 ECO | 21 |
| HALOLUX CERAM®           | 21 |
| HALOLINE® ECO            | 22 |
| HALOLINE®                | 22 |

### LOW VOLTAGE HALOGEN LAMPS

|                         |    |
|-------------------------|----|
| HALOSTAR® ECO           | 23 |
| HALOSTAR STARLITE®      | 24 |
| HALOSTAR® STANDARD      | 24 |
| HALOSPOT® 111 ECO       | 25 |
| HALOSPOT® 111           | 26 |
| HALOSPOT® 70, 48        | 27 |
| DECOSTAR® 51 ECO        | 28 |
| DECOSTAR® 51 TITAN      | 29 |
| DECOSTAR® 35 TITAN      | 30 |
| DECOSTAR® 51 STANDARD   | 30 |
| DECOSTAR® 51S STANDARD  | 31 |
| DECOSTAR® 51 ALU        | 31 |
| DECOSTAR® 51 COOL BLUE® | 32 |
| DECOSTAR® 35 STANDARD   | 32 |
| TRAFFIC SIGNAL LAMPS    | 33 |





## HALOGEN LAMPS – MAINS VOLTAGE

HALOGEN  
ECO

### HALOPIN® ECO

- Mains voltage compact G9 halogen lamps, no transformer required
- 1:1 direct replacement for a standard HALOPIN® lamps
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for modern compact luminaires

| Product ID Code | EAN (Single Pack) | Product Description          | W  | V   | Im  | t [h] | FINISH | PPG         |
|-----------------|-------------------|------------------------------|----|-----|-----|-------|--------|-------------|
| 66720           | 4008321945556     | 66720 ECO 20W 240V G9        | 20 | 240 | 200 | 2,000 | G9     | Clear 20 17 |
| 24066733        | 4008321226341     | HEHP33 66733 ECO 33W 240V G9 | 33 | 240 | 460 | 2,000 | G9     | Clear 20 17 |
| 66748           | 4008321945617     | 66748 ECO 48W 240V G9        | 48 | 240 | 740 | 2,000 | G9     | Clear 20 17 |
| 66760           | 4008321945655     | 66760 ECO 60W 240V G9        | 60 | 240 | 980 | 2,000 | G9     | Clear 20 17 |

NEW  
NEW  
NEW

### HALOPIN®



- Mains voltage compact G9 halogen lamp, no transformer required
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for modern compact luminaires

| Product ID Code        | EAN (Single Pack) | Product Description      | W  | V   | Im  | t [h] | FINISH | PPG         |
|------------------------|-------------------|--------------------------|----|-----|-----|-------|--------|-------------|
| <b>Clear</b>           |                   |                          |    |     |     |       |        |             |
| 24066725 <sup>1)</sup> | 4050300791814     | HP25CC 66725 25W 240V G9 | 25 | 240 | 260 | 2,000 | G9     | Clear 20 17 |
| 24066740 <sup>1)</sup> | 4050300791852     | HP40CC 66740 40W 240V G9 | 40 | 240 | 490 | 2,000 | G9     | Clear 20 17 |

1) Banned from 1.9.2012 as per EU phase-out plan

All orders must be multiples of sales pack


## Halogen Lamps – Mains Voltage

**DECOPIN®**

- World's smallest mains voltage halogen reflector lamp
- 41.5mm diameter
- Polished Alu reflector with matt exterior finish
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable

| Product ID Code        | EAN (Single Pack) | Product Description       | W  | V   | lm  | t [h] |    |     |    | PPG |
|------------------------|-------------------|---------------------------|----|-----|-----|-------|----|-----|----|-----|
| 24060040 <sup>1)</sup> | 4008321122797     | DP40 60040 FL 40W 240V G9 | 40 | 240 | 550 | 2,000 | G9 | 40° | 20 | 17  |

1) Banned from 1.9.2012 as per EU phase-out plan




**OSRAM HALOPAR® 16 ECO**

- GU10 mains voltage reflector lamp, no transformer required
- Approved for use in open luminaires to IEC 60432-3
- Fully dimmable
- Ideal for display and down lighting

| Product ID Code | EAN (Single Pack) | Product Description               | W  | V   | lm  | t [h] |      |                            |    | PPG |
|-----------------|-------------------|-----------------------------------|----|-----|-----|-------|------|----------------------------|----|-----|
| 24064819HPES    | 4008321934369     | 64819 ECO FL 28W 240V GU10        | 28 | 240 | 570 | 2,000 | GU10 | Flood aluminised reflector | 20 | 17  |
| 24064823FL      | 4008321226389     | HE1640 64823 ECO FL 40W 240V GU10 | 40 | 240 | 900 | 2,000 | GU10 | Flood aluminised reflector | 20 | 17  |

All orders must be multiples of sales pack



## Halogen Lamps – Mains Voltage



### OSRAM HALOPAR® 16

- Mains voltage reflector lamp, no transformer required
- Aluminium or dichroic reflector
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- 51mm diameter
- Ideal for display and down lighting

| Product ID Code | EAN (Single Pack) | Product Description              | W   | V     | t [h]   | FINISH                     | No. | PPG   |
|-----------------|-------------------|----------------------------------|-----|-------|---------|----------------------------|-----|-------|
| 24064820FL      | 4050300727226     | P163FA 64820 FL 35W 240V GU10 35 | 240 | 2,000 | GU10    | Flood aluminised reflector | 1   | 20 17 |
| 24064822FL      | 4050300772080     | P164FA 64822FL 40W 240V E14 40   | 240 | 2,000 | SES/E14 | Flood aluminised reflector | 3   | 20 17 |
| 24064824FL      | 4050300580159     | P165FA 64824FL 50W 240V GU10 50  | 240 | 2,000 | GU10    | Flood aluminised reflector | 1   | 20 17 |
| 24064826        | 4050300522708     | P165FD 64826 FL 50W 240V GZ10 50 | 240 | 2,000 | GZ10    | Flood dichroic reflector   | 2   | 20 17 |





### OSRAM HALOPAR® 20

- Mains voltage, no transformer required
- 64.5mm diameter
- Aluminium or dichroic reflector
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for display lighting

| Product ID Code | EAN (Single Pack) | Product Description              | W   | V     | t [h]  | FINISH                     | No. | PPG   |
|-----------------|-------------------|----------------------------------|-----|-------|--------|----------------------------|-----|-------|
| 24064832SP      | 4050300435268     | P205SA 64832 SP 50W 240V E27 50  | 240 | 2,000 | ES/E27 | Spot aluminised reflector  | 1   | 15 17 |
| 24064832FL      | 4050300435282     | P205FA 64832 FL 50W 240V E27 50  | 240 | 2,000 | ES/E27 | Flood aluminised reflector | 1   | 15 17 |
| 24064836SP      | 4050300435305     | P205SD 64836 SP 50W 240V E27 50  | 240 | 2,000 | ES/E27 | Spot dichroic reflector    | 1   | 15 17 |
| 24064836FL      | 4050300435329     | P205FD 64836 FL 50W 240V E27 50  | 240 | 2,000 | ES/E27 | Flood dichroic reflector   | 1   | 15 17 |
| 24064830FL      | 4050300856995     | P207FA 64830 FL 75W 240V GU10 75 | 240 | 2,000 | GU10   | Flood aluminised reflector | 2   | 20 17 |


All orders must be multiples of sales pack

## Halogen Lamps – Mains Voltage

**OSRAM HALOPAR® 30**

- Mains voltage, no transformer required
- 97mm diameter
- Aluminium or dichroic reflector
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for display lighting

| Product ID Code | EAN (Single Pack) | Product Description             | W  | V   | t [h] | FINISH | PPG                              |
|-----------------|-------------------|---------------------------------|----|-----|-------|--------|----------------------------------|
| 24064841SP      | 4050300435343     | P307SA 64841 SP 75W 240V E27    | 75 | 240 | 2,000 | ES/E27 | Spot aluminised reflector 15 17  |
| 24064841FL      | 4050300435367     | P307FA 64841 FL 75W 240V E27    | 75 | 240 | 2,000 | ES/E27 | Flood aluminised reflector 15 17 |
| 24064845SP      | 4050300435381     | P307SD 64845 SP CB 75W 240V E27 | 75 | 240 | 2,000 | ES/E27 | Spot dichroic reflector 15 17    |
| 24064845FL      | 4050300435404     | P307FD 64845 FL CB 75W 240V E27 | 75 | 240 | 2,000 | ES/E27 | Flood dichroic reflector 15 17   |



**OSRAM HALOPAR® 38**

- Halogen PAR 38 reflector
- 1:1 replacement to a standard incandescent PAR 38 lamp
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for decorative and highlighting effects

| Product ID Code | EAN (Single Pack) | Product Description   | W  | V   | t [h] | FINISH     | PPG   |
|-----------------|-------------------|-----------------------|----|-----|-------|------------|-------|
| 64838FL50       | 4008321380364     | 64838 FL 50W 240V E27 | 50 | 240 | 2,000 | ES/E27 30° | 12 17 |
| 64838FL75       | 4008321380340     | 64838 FL 75W 240V E27 | 75 | 240 | 2,000 | ES/E27 30° | 12 17 |
| 64838SP75       | 4008321380401     | 64838 SP 75W 240V E27 | 75 | 240 | 2,000 | ES/E27 12° | 12 17 |

All orders must be multiples of sales pack

## Halogen Lamps – Mains Voltage

**HALOGEN CLASSIC A ECO**

- Mains voltage Classic "A" shape lamps, no transformer required
- Fully dimmable
- Direct eco replacement for classic "A" shape GLS lamps



| Product ID Code              | EAN (Single Pack) | Product Description              | W   | V   | lm   | t [h] |         | FINISH |    | PPG |
|------------------------------|-------------------|----------------------------------|-----|-----|------|-------|---------|--------|----|-----|
| 24064541AESB22 <sup>1)</sup> | 4008321934239     | 64541 A ECO 18W 240V B22D        | 18  | 240 | 220  | 2,000 | BC/B22d | Clear  | 20 | 17  |
| 24064542AB22                 | 4008321918949     | HEA2CB 64542 A ECO 28W 240V B22D | 28  | 240 | 345  | 2,000 | BC/B22d | Clear  | 20 | 17  |
| 24064543AB22                 | 4008321919083     | HEA4CB 64543 A ECO 42W 240V B22D | 42  | 240 | 630  | 2,000 | BC/B22d | Clear  | 20 | 17  |
| 64544AESB22                  | 4008321403339     | 64544 A ECO 53W 240V B22D        | 52  | 240 | 820  | 2,000 | BC/B22d | Clear  | 20 | 17  |
| 64547AESB22                  | 4008321936073     | 64547 A ECO 70W 240V B22D        | 70  | 240 | 1200 | 2,000 | BC/B22d | Clear  | 20 | 17  |
| 64548AESB22                  | 4008321403391     | 64548 A ECO 105W 240V B22D       | 105 | 240 | 1900 | 2,000 | BC/B22d | Clear  | 20 | 17  |
| 24064542A                    | 4008321229267     | HEA2CE 64542 A ECO 28W 240V E27  | 28  | 240 | 345  | 2,000 | ES/E27  | Clear  | 20 | 17  |
| 24064543A                    | 4008321229281     | HEA4CE 64543 A ECO 42W 240V E27  | 42  | 240 | 630  | 2,000 | ES/E27  | Clear  | 20 | 17  |
| 64544AES                     | 4008321403315     | 64544 A ECO 53W 240V E27         | 52  | 240 | 820  | 2,000 | ES/E27  | Clear  | 20 | 17  |
| 64547AES                     | 4008321936059     | 64547 A ECO 70W 240V E27         | 70  | 240 | 1200 | 2,000 | ES/E27  | Clear  | 20 | 17  |
| 64548AES                     | 4008321403377     | 64548 A ECO 105W 240V E27        | 105 | 240 | 1900 | 2,000 | ES/E27  | Clear  | 20 | 17  |

1) Banned from 1.9.2012 as per EU phase-out plan



All orders must be multiples of sales pack

## Halogen Lamps – Mains Voltage

**HALOGEN CLASSIC B ECO**


- Mains voltage candle shape lamps, no transformer required
- Fully dimmable
- Direct eco replacement for basic incandescent candle lamps

| Product ID Code              | EAN (Single Pack) | Product Description              | W  | V   | lm  | t [h] |         | FINISH |    | PPG |
|------------------------------|-------------------|----------------------------------|----|-----|-----|-------|---------|--------|----|-----|
| 24064541BESB22 <sup>1)</sup> | 4008321934291     | 64541 B ECO 18W 240V B22D        | 18 | 240 | 220 | 2,000 | BC/B22d | Clear  | 20 | 17  |
| 24064541BES <sup>1)</sup>    | 4008321934307     | 64541 B ECO 18W 240V E14         | 18 | 240 | 220 | 2,000 | SES/E14 | Clear  | 20 | 17  |
| 24064542BB22                 | 4008321919045     | HEB2CB 64542 B ECO 28W 240V B22D | 28 | 240 | 345 | 2,000 | BC/B22d | Clear  | 20 | 17  |
| 24064542B                    | 4008321229304     | HEB2CE 64542 B ECO 28W 240V E14  | 28 | 240 | 345 | 2,000 | SES/E14 | Clear  | 20 | 17  |
| 24064543BESB22               | 4008321934321     | 64543 B ECO 42W 240V B22D        | 42 | 240 | 630 | 2,000 | BC/B22d | Clear  | 20 | 17  |
| 24064543BES                  | 4008321934338     | 64543 B ECO 42W 240V E14         | 42 | 240 | 630 | 2,000 | SES/E14 | Clear  | 20 | 17  |

1) Banned from 1.9.2012 as per EU phase-out plan



All orders must be multiples of sales pack

## Halogen Lamps – Mains Voltage

**HALOGEN CLASSIC BW ECO**

- Mains voltage twisted candle shape lamps, no transformer required
- Fully dimmable
- Direct eco replacement for basic incandescent candle lamps

| Product ID Code | EAN (Single Pack) | Product Description       | W  | V   | lm  | t [h] | FINISH        | PPG   |
|-----------------|-------------------|---------------------------|----|-----|-----|-------|---------------|-------|
| 24064542BWES    | 4008321934352     | 64542 BW ECO 28W 240V E14 | 28 | 240 | 345 | 2,000 | SES/E14 Clear | 20 17 |

**HALOGEN CLASSIC P ECO**


- Mains voltage globe shape lamps, no transformer required
- Fully dimmable
- Direct eco replacement for basic incandescent candle lamps

| Product ID Code | EAN (Single Pack) | Product Description       | W  | V   | lm  | t [h] | FINISH  | LED No. | PPG   |
|-----------------|-------------------|---------------------------|----|-----|-----|-------|---------|---------|-------|
| 64542PSE14      | 4008321952851     | 64542 P ECO 28W 240V E14  | 28 | 240 | 320 | 2,000 | SES/E14 | Clear 2 | 20 17 |
| 64543PES        | 4008321952875     | 64543 P ECO 42W 240V E14  | 42 | 240 | 580 | 2,000 | SES/E14 | Clear 2 | 20 17 |
| 64542PES        | 4008321952912     | 64542 P ECO 28W 240V E27  | 28 | 240 | 320 | 2,000 | ES/E27  | Clear 3 | 20 17 |
| 64542PESB22     | 4008321952950     | 64542 P ECO 28W 240V B22D | 28 | 240 | 320 | 2,000 | BC/B22d | Clear 1 | 20 17 |
| 64543PESB22     | 4008321952998     | 64543 P ECO 42W 240V B22D | 42 | 240 | 580 | 2,000 | BC/B22d | Clear 1 | 20 17 |


NEW  
NEW  
NEW  
NEW  
NEW

All orders must be multiples of sales pack


## Halogen Lamps – Mains Voltage



SES




ES

HALOGEN  
ECO**HALOGEN SPOT R50/R63 ECO**

- Mains voltage reflector shape lamps, no transformer required
- R50 and R63 sizes
- Fully dimmable
- Direct eco replacement for basic incandescent reflector lamps

| Product ID Code | EAN (Single Pack) | Product Description              | W  | V   | Im  | t [h] |  |         |     | PPG   |
|-----------------|-------------------|----------------------------------|----|-----|-----|-------|--|---------|-----|-------|
| 24064545        | 4008321229328     | HER528 64545 R50ECO 28W 240V E14 | 28 | 240 | 430 | 2,000 |  | SES/E14 | 30° | 20 17 |
| 24064546        | 4008321229342     | HER642 64546 R63ECO 42W 240V E27 | 42 | 240 | 960 | 2,000 |  | ES/E27  | 30° | 20 17 |


**HALOLUX CERAM® ECO**

- New generation single ended mains voltage lamps
- Up to 20% more lumen per watt
- Lamp life 2,000 hours
- Ideal for uplighting and wall washing

| Product ID Code | EAN (Single Pack) | Product Description     | W   | V   | Im   | t [h] |  |        | PPG         |
|-----------------|-------------------|-------------------------|-----|-----|------|-------|--|--------|-------------|
| 64401           | 4008321393906     | 64401 ECO 100W 240V E27 | 100 | 240 | 1800 | 2,000 |  | ES/E27 | Clear 12 17 |
| 64402           | 4008321393920     | 64402 ECO 150W 240V E27 | 150 | 240 | 2870 | 2,000 |  | ES/E27 | Clear 12 17 |
| 64404           | 4008321393944     | 64404 ECO 205W 240V E27 | 200 | 240 | 4200 | 2,000 |  | ES/E27 | Clear 12 17 |

All orders must be multiples of sales pack

## Halogen Lamps – Mains Voltage



**HALOGEN  
ECO**

**HALOLINE® ECO**

- Mains voltage double ended linear lamps, no transformer required
- Fully dimmable
- Ideal for uplighters, floodlights and security lighting

| Product ID Code | EAN (Single Pack) | Product Description            | W   | V   | lm   | t [h] | FINISH | PPG         |
|-----------------|-------------------|--------------------------------|-----|-----|------|-------|--------|-------------|
| 64684ECO        | 4008321945112     | 64684 ECO 48W 240V R7S         | 48  | 240 | 800  | 2,000 | R7s    | Clear 20 15 |
| 24064690ES      | 4008321325396     | 64690 ECO 80W 240V R7S         | 80  | 240 | 1500 | 2,000 | R7s    | Clear 20 15 |
| 24064695ES      | 4008321325419     | 64695 ECO 120W 240V R7S        | 120 | 240 | 2300 | 2,000 | R7s    | Clear 20 15 |
| 64696ECO        | 4008321952677     | 64696 ECO 120W 240V R7S        | 120 | 240 | 2300 | 2,000 | R7s    | Clear 20 15 |
| 64698           | 4008321955630     | 64698 ECO 160W 240V R7S        | 160 | 240 | 3300 | 2,000 | R7s    | Clear 20 15 |
| 24064701ES      | 4008321275622     | HEK230 64701 ECO 230W 240V R7S | 230 | 240 | 5060 | 2,000 | R7s    | Clear 20 15 |
| 24064702ES      | 4008321275646     | HEK400 64702 ECO 400W 240V R7S | 400 | 240 | 9200 | 2,000 | R7s    | Clear 20 15 |

NEW

NEW

NEW

**HALOLINE®**

- Double ended linear halogen lamps
- Mains voltage
- Fully dimmable
- Ideal for uplighters, floodlights and security lighting




| Product ID Code | EAN (Single Pack) | Product Description          | W    | V   | lm   | t [h] | FINISH | PPG         |
|-----------------|-------------------|------------------------------|------|-----|------|-------|--------|-------------|
| 12064702        | 4050300297040     | K1LV 64700 500W 115-120V R7S | 500  | 110 | –    | 2,000 | R7s    | Clear 20 16 |
| 24064740        | 4050300209906     | K4 64740 1000W 240V R7S      | 1000 | 240 | 2200 | 2,000 | R7s    | Clear 12 16 |
| 24064760        | 4050300209920     | K5 64760 1500W 240V R7S      | 1500 | 240 | 3600 | 2,000 | R7s    | Clear 12 16 |

■

All orders must be multiples of sales pack

## Halogen Lamps – Low Voltage

## HALOGEN LAMPS – LOW VOLTAGE



## HALOSTAR® ECO

- Low voltage capsule lamps
- New G4 base the smallest HALOSTAR® ECO
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal eco alternative for open luminaires and free-burning applications

HALOGEN  
ECO

| Product ID Code | EAN (Single Pack) | Product Description               | W  | V  | lm   | t [h] |        | No. |    | PPG |
|-----------------|-------------------|-----------------------------------|----|----|------|-------|--------|-----|----|-----|
| 64417           | 4008321963192     | 64417 ECO 7W 12V G4               | 7  | 12 | -    | 4,000 | G4     | 1   | 40 | 13  |
| 64423ES         | 4008321317964     | 64423 ECO 14W 12V G4              | 14 | 12 | 240  | 4,000 | G4     | 1   | 40 | 13  |
| 64429ES         | 4050300987262     | 64429IRC 64429 ECO 25W 12V GY6.35 | 25 | 12 | 500  | 4,000 | GY6.35 | 2   | 40 | 13  |
| 64432ES         | 4050300615905     | M75IR 64432 ECO 35W 12V GY6.35    | 35 | 12 | 900  | 4,000 | GY6.35 | 2   | 40 | 13  |
| 64440ES         | 4050300615936     | M74IR 64440 ECO 50W 12V GY6.35    | 50 | 12 | 1250 | 4,000 | GY6.35 | 2   | 40 | 13  |
| 64447ES         | 4050300785400     | M205IR 64447 ECO 60W 12V GY6.35   | 60 | 12 | 1700 | 4,000 | GY6.35 | 2   | 40 | 13  |

Perfectly matched with HALOTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## Halogen Lamps – Low Voltage

**HALOSTAR STARLITE®**


- Low voltage capsule lamps
- Provides decorative and brilliant points of light
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for open luminaires and free-burning applications

| Product ID Code      | EAN (Single Pack) | Product Description         | W  | V  | lm   | t [h] |        |  | No. |    | PPG |
|----------------------|-------------------|-----------------------------|----|----|------|-------|--------|--|-----|----|-----|
| 64405S <sup>2)</sup> | 4050300335032     | M9 64405 S 5W 12V G4        | 5  | 12 | 60   | 4,000 | G4     |  | 1   | 40 | 13  |
| 64410S <sup>2)</sup> | 4050300335131     | M42 64410 S 10W 6V G4       | 10 | 6  | 110  | 4,000 | G4     |  | 1   | 40 | 13  |
| 64415S <sup>2)</sup> | 4050300335087     | M91 64415 S 10W 12V GX4     | 10 | 12 | 130  | 4,000 | G4     |  | 1   | 40 | 13  |
| 64425S <sup>2)</sup> | 4050300335162     | M47 64425 S 20W 12V G4      | 20 | 12 | 300  | 4,000 | G4     |  | 1   | 40 | 13  |
| 64427S <sup>2)</sup> | 4050300328171     | M76 64427 S 20W 12V GY6,35  | 20 | 12 | 300  | 4,000 | GY6.35 |  | 2   | 40 | 13  |
| 64432S <sup>2)</sup> | 4050300017426     | M75 64432 S 35W 12V GY6,35  | 35 | 12 | 600  | 4,000 | GY6.35 |  | 2   | 40 | 13  |
| 64440S <sup>2)</sup> | 4050300328201     | M74 64440 S 50W 12V GY6,35  | 50 | 12 | 910  | 4,000 | GY6.35 |  | 2   | 40 | 13  |
| 64450S <sup>2)</sup> | 4050300490151     | M154 64450 S 75W 12V GY6,35 | 75 | 12 | 1450 | 4,000 | GY6.35 |  | 2   | 40 | 13  |
| 64458S <sup>2)</sup> | 4050300490182     | M180 64458 S 90W 12V GY6,35 | 90 | 12 | 1800 | 4,000 | GY6.35 |  | 2   | 40 | 13  |

Perfectly matched with HALOTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

2) Banned from 1.9.2016 as per EU phase-out plan

**HALOSTAR® STANDARD**

- Low voltage capsule lamps
- Economical choice for general applications
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for enclosed luminaires



| Product ID Code     | EAN (Single Pack) | Product Description            | W   | V  | lm   | t [h] |        |  | No. |    | PPG |
|---------------------|-------------------|--------------------------------|-----|----|------|-------|--------|--|-----|----|-----|
| 64435U              | 4050300335513     | M88 64435 U 20W 24V G4         | 20  | 24 | 320  | 2,000 | G4     |  | 1   | 40 | 13  |
| 64440 <sup>1)</sup> | 4050300324432     | M32 64440 50W 12V GY6,35       | 50  | 12 | 910  | 2,000 | GY6.35 |  | 2   | 40 | 13  |
| 64445U              | 4050300335544     | M89 64445 U AX 50W 24V GY6,35  | 50  | 24 | 900  | 2,000 | GY6.35 |  | 2   | 40 | 13  |
| 64460U              | 4050300335667     | M90 64460 U AX 100W 24V GY6,35 | 100 | 24 | 2200 | 2,000 | GY6.35 |  | 2   | 40 | 13  |
| 64465U              | 4050300335698     | M196 64465 150W 24V GY6,35     | 150 | 24 | 3200 | 2,000 | GY6.35 |  | 2   | 40 | 13  |

Perfectly matched with HALOTRONIC® electronic control gear

1) Banned from 1.9.2016 as per EU phase-out plan

All orders must be multiples of sales pack

## Halogen Lamps – Low Voltage

**HALOSPOT® 111 ECO**

- Low voltage aluminium reflector lamps
- 111mm diameter
- 48% cost saving due to Infra-red coating (IRC)
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for shop lighting restaurants, hotels, art galleries etc



| Product ID Code | EAN (Single Pack) | Product Description               | W  | V  | lm   | t [h] |     |                |      |
|-----------------|-------------------|-----------------------------------|----|----|------|-------|-----|----------------|------|
| 48832ESFL       | 4008321201201     | 47832 ECO FL UVS 35W 12V G53      | 35 | 12 | 4200 | 4,000 | G53 | Flood 24°      | 6 17 |
| 48832SPES       | 4050300656823     | M202IR 48832 ECO SP 35W 12V G53   | 35 | 12 | —    | 4,000 | G53 | Spot 8°        | 6 17 |
| 48832FLES       | 4050300656847     | M353IR 48832 ECO FL 35W 12V G53   | 35 | 12 | —    | 4,000 | G53 | Flood 24°      | 6 17 |
| 48835SPES       | 4050300656861     | M101IR 48835 ECO SP 50W 12V G53   | 50 | 12 | —    | 4,000 | G53 | Spot 8°        | 6 17 |
| 48835FLES       | 4050300656885     | M161IR 48835 ECO FL 50W 12V G53   | 50 | 12 | —    | 4,000 | G53 | Flood 24°      | 6 17 |
| 48835WFLES      | 4008321909237     | 48835WFL 48835 ECOWFL 50W 12V G53 | 50 | 12 | —    | 4,000 | G53 | Wide flood 45° | 6 17 |
| 48837SPES       | 4050300786070     | M203IR 48837 ECO SP 60W 12V G53   | 65 | 12 | —    | 4,000 | G53 | Spot 8°        | 6 17 |
| 48837FLES       | 4050300786094     | M204IR 48837 ECO FL 60W 12V G53   | 65 | 12 | —    | 4,000 | G53 | Flood 24°      | 6 17 |
| 48837WFLES      | 4008321909251     | 48837WFL 48837 ECOWFL 60W 12V G53 | 65 | 12 | —    | 4,000 | G53 | Wide flood 45° | 6 17 |

Perfectly matched with HALOTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## Halogen Lamps – Low Voltage

**HALOSPOT® 111**




- Low voltage aluminium reflector lamps
- 111mm diameter
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for accent lighting over large distances

| Product ID Code | EAN (Single Pack) | Product Description            | W   | V  | t [h] | FINISH | PPG                 |
|-----------------|-------------------|--------------------------------|-----|----|-------|--------|---------------------|
| 41830SSP        | 4050300011141     | M163 41830 SSP 35W 6V G53      | 35  | 6  | 3,000 | G53    | Super Spot 4° 6 17  |
| 41832SSP        | 4050300335728     | M351 41832 SSP 35W 12V G53     | 35  | 12 | 3,000 | G53    | Super Spot 4° 6 17  |
| 41832FL         | 4050300335766     | M353 UVS 35W 12V G53           | 35  | 12 | 3,000 | G53    | Flood 24° 6 17      |
| 41835SSP        | 4050300011165     | M100 41835 SSP 50W 12V G53     | 50  | 12 | 3,000 | G53    | Super Spot 4° 6 17  |
| 41835SP         | 4050300011752     | M101 41835 SP 50W 12V G53      | 50  | 12 | 3,000 | G53    | Spot 8° 6 17        |
| 41835FL         | 4050300011769     | M161 41835 FL 50W 12V G53      | 50  | 12 | 3,000 | G53    | Flood 24° 6 17      |
| 41835WFL        | 4008321909213     | 41835 WFL 50W 12V G53          | 50  | 12 | 3,000 | G53    | Wide flood 45° 6 17 |
| 41840SP         | 4050300011776     | M102 41840 SP ND 75W 12V G53   | 75  | 12 | 3,000 | G53    | Spot 8° 6 17        |
| 41840FL         | 4050300011783     | M162 41840 FL ND 75W 12V G53   | 75  | 12 | 3,000 | G53    | Flood 24° 6 17      |
| 41840WFL        | 4050300011790     | M103 41840 WFL ND 75W 12V G53  | 75  | 12 | 3,000 | G53    | Wide flood 45° 6 17 |
| 41850SP         | 4050300358604     | M114 41850 SP ND 100W 12V G53  | 100 | 12 | 3,000 | G53    | Spot 8° 6 17        |
| 41850FL         | 4050300358628     | M152 41850 FL ND 100W 12V G53  | 100 | 12 | 3,000 | G53    | Flood 24° 6 17      |
| 41850WFL        | 4050300358642     | M191 41850 WFL ND 100W 12V G53 | 100 | 12 | 3,000 | G53    | Wide flood 45° 6 17 |

Perfectly matched with HALOTRONIC® electronic control gear

All orders must be multiples of sales pack

## Halogen Lamps – Low Voltage


**HALOSPOT® 70, 48**

- Low voltage aluminium reflector lamps
- 70mm and 48mm diameter
- Ideal for accent lighting

| Product ID Code      | EAN (Single Pack) | Product Description         | W  | V  | t [h] | FINISH | No.       | PPG     |
|----------------------|-------------------|-----------------------------|----|----|-------|--------|-----------|---------|
| <b>70mm diameter</b> |                   |                             |    |    |       |        |           |         |
| 41970SP              | 4050300010656     | M155 41970 SP 20W 12V BA15D | 20 | 12 | 3,000 | B15d   | Spot 8°   | 1 10 17 |
| 41970FL              | 4050300011110     | M156 41970 FL 20W 12V BA15D | 20 | 12 | 3,000 | B15d   | Flood 24° | 1 10 17 |
| 41990SP              | 4050300011158     | M157 41990 SP 50W 12V BA15D | 50 | 12 | 3,000 | B15d   | Spot 8°   | 1 10 17 |
| 41990FL              | 4050300004020     | M158 41990 FL 50W 12V BA15D | 50 | 12 | 3,000 | B15d   | Flood 24° | 1 10 17 |
| <b>48mm diameter</b> |                   |                             |    |    |       |        |           |         |
| 41900SP              | 4050300003962     | M108 41900 SP 20W 12V GY4   | 20 | 12 | 2,000 | GY4    | Spot 8°   | 2 10 17 |
| 41930SP              | 4050300003979     | M107 41930 SP 20W 24V GY4   | 20 | 24 | 1,000 | GY4    | Spot 8°   | 2 10 17 |

Perfectly matched with HALOTRONIC® electronic control gear

## Halogen Lamps – Low Voltage

HALOGEN  
ECO**DECOSTAR® 51 ECO**

- Long life low voltage dichroic reflector lamps
- Up to 65% cost saving due to Infra-red coating (IRC)
- 51mm diameter with cover glass
- Fully dimmable
- Approved for use in open luminaires to IEC 60598-1
- Ideal for reduced running costs in display lighting



| Product ID Code | EAN (Single Pack) | Product Description                 | W  | V  | lm    | t [h] | FINISH                    | PPG   |
|-----------------|-------------------|-------------------------------------|----|----|-------|-------|---------------------------|-------|
| 48855ESSP       | 4008321945020     | 48855 ECO SP 14W 12V GU5,3          | 14 | 12 | 2800  | 5,000 | GU5.3 Spot 10°            | 20 17 |
| 48855ESWFL      | 4008321945044     | 48855 ECO WFL 14W 12V GU5,3         | 14 | 12 | 480   | 5,000 | GU5.3 Wide flood 36°      | 20 17 |
| 48860SP         | 4050300620169     | M268IR 48860 SP 20W 12V GU5,3       | 20 | 12 | 5500  | 5,000 | GU5.3 Spot 10°            | 20 17 |
| 48860FL         | 4050300620183     | M294IR 48860 FL 20W 12V GU5,3       | 20 | 12 | 2000  | 5,000 | GU5.3 Flood 24°           | 20 17 |
| 48860WFL        | 4050300620206     | M269IR 48860 ECO WFL 20W 12V GU5,3  | 20 | 12 | 1000  | 5,000 | GU5.3 Wide flood 36°      | 20 17 |
| 48860WWFL       | 4050300620220     | M290IR 48860 ECO WWFL 20W 12V GU5,3 | 20 | 12 | 450   | 5,000 | GU5.3 Very wide flood 60° | 20 17 |
| 48865SP         | 4050300516592     | M271IR 48865 SP 35W 12V GU5,3       | 35 | 12 | 11000 | 5,000 | GU5.3 Spot 10°            | 20 17 |
| 48865FL         | 4050300516615     | M270IR 48865 ECO FL 35W 12V GU5,3   | 35 | 12 | 4100  | 5,000 | GU5.3 Flood 24°           | 20 17 |
| 48865WFL        | 4050300516639     | M281IR 48865 ECO WFL 35W 12V GU5,3  | 35 | 12 | 2200  | 5,000 | GU5.3 Wide flood 36°      | 20 17 |
| 48865WWFL       | 4050300516653     | M224IR 48865 ECO VVFL 35W 12V GU5,3 | 35 | 12 | 1050  | 5,000 | GU5.3 Very wide flood 60° | 20 17 |
| 48870SP         | 4050300516677     | M249IR 48870 SP 50W 12V GU5,3       | 50 | 12 | 15000 | 5,000 | GU5.3 Spot 10°            | 20 17 |
| 48870FL         | 4050300516691     | M250IR 48870 FL 50W 12V GU5,3       | 50 | 12 | 5300  | 5,000 | GU5.3 Flood 24°           | 20 17 |
| 48870WFL        | 4050300516714     | M258IR 48870 WFL 50W 12V GU5,3      | 50 | 12 | 2850  | 5,000 | GU5.3 Wide flood 36°      | 20 17 |
| 48870WWFL       | 4050300516738     | M280IR 48870 VVFL 50W 12V GU5,3     | 50 | 12 | 1450  | 5,000 | GU5.3 Very wide flood 60° | 20 17 |

Perfectly matched with HALOTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## Halogen Lamps – Low Voltage

**DECOSTAR® 51 TITAN**

- Long life low voltage dichroic reflector lamps
- 51mm diameter with cover glass
- Dichroic reflector reduces the heat in the light beam up to 66%
- Fully dimmable and approved for use in open luminaires to IEC 60598-1
- Ideal for professional display lighting

| Product ID Code | EAN (Single Pack) | Product Description            | W  | V  | t [h] | FINISH                    | PPG   |
|-----------------|-------------------|--------------------------------|----|----|-------|---------------------------|-------|
| 46860SP         | 4050300428635     | M268T 46860 SP 20W 12V GU5,3   | 20 | 12 | 4,000 | GU5.3 Spot 10°            | 20 13 |
| 46860WFL        | 4050300428659     | M269T 46860 WFL 20W 12V GU5,3  | 20 | 12 | 4,000 | GU5.3 Wide flood 36°      | 20 13 |
| 46860VWFL       | 4050300428673     | M290T 46860 VWFL 20W 12V GU5,3 | 20 | 12 | 4,000 | GU5.3 Very wide flood 60° | 20 13 |
| 46865SP         | 4050300428697     | M271T 46865 SP 35W 12V GU5,3   | 35 | 12 | 4,000 | GU5.3 Spot 10°            | 20 13 |
| 46865FL         | 4050300476414     | M270T 46865 FL 35W 12V GU5,3   | 35 | 12 | 4,000 | GU5.3 Flood 24°           | 20 13 |
| 46865WFL        | 4050300428710     | M281T 46865 WFL 35W 12V GU5,3  | 35 | 12 | 4,000 | GU5.3 Wide flood 36°      | 20 13 |
| 46865VWFL       | 4050300428734     | M224T 46865 VWFL 35W 12V GU5,3 | 35 | 12 | 4,000 | GU5.3 Very wide flood 60° | 20 13 |
| 46870SP         | 4050300428758     | M249T 46870 SP 50W 12V GU5,3   | 50 | 12 | 4,000 | GU5.3 Spot 10°            | 20 13 |
| 46870FL         | 4050300465708     | M250T 46870 FL 50W 12V GU5,3   | 50 | 12 | 4,000 | GU5.3 Flood 24°           | 20 13 |
| 46870WFL        | 4050300428772     | M258T 46870 WFL 50W 12V GU5,3  | 50 | 12 | 4,000 | GU5.3 Wide flood 36°      | 20 13 |
| 46870VWFL       | 4050300428796     | M280T 46870 VWFL 50W 12V GU5,3 | 50 | 12 | 4,000 | GU5.3 Very wide flood 60° | 20 13 |


Perfectly matched with HALOTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



All orders must be multiples of sales pack


## Halogen Lamps – Low Voltage

**DECOSTAR® 35 TITAN**

- Long life low voltage dichroic reflector lamps
- 35mm diameter
- Dichroic reflector reduces the heat in the light beam up to 66%
- Fully dimmable and approved for use in open luminaires to IEC 60598-1
- Ideal for professional display lighting

| Product ID Code | EAN (Single Pack) | Product Description         | W  | V  | t [h] | Im  | FINISH         | PPG   |
|-----------------|-------------------|-----------------------------|----|----|-------|-----|----------------|-------|
| 46890SP         | 4050300529301     | M252T 46890 SP 20W 12V GU4  | 20 | 12 | 4,000 | GU4 | Spot 10°       | 20 13 |
| 46890WFL        | 4050300529325     | M221T 46890 WFL 20W 12V GU4 | 20 | 12 | 4,000 | GU4 | Wide flood 36° | 20 13 |
| 46892SP         | 4050300529349     | M265T 46892 SP 35W 12V GU4  | 35 | 12 | 4,000 | GU4 | Spot 10°       | 20 13 |
| 46892WFL        | 4050300529363     | M223T 46892 WFL 35W 12V GU4 | 35 | 12 | 4,000 | GU4 | Wide flood 36° | 20 13 |

Perfectly matched with HALOTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)**DECOSTAR® 51 STANDARD**





- Low voltage dichroic reflector lamps
- 51mm diameter
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for economical display lighting

| Product ID Code | EAN (Single Pack) | Product Description            | W  | V  | Im   | t [h] | FINISH | PPG            |
|-----------------|-------------------|--------------------------------|----|----|------|-------|--------|----------------|
| 41860SP         | 4050300012612     | M68 41860 SP 20W 12V GU5,3     | 20 | 12 | 3000 | 2,000 | GU5.3  | Spot 10°       |
| 41860WFL        | 4050300012629     | M69 41860 WFL 20W 12V GU5,3    | 20 | 12 | –    | 2,000 | GU5.3  | Wide flood 36° |
| 41865SP         | 4050300026527     | M71 41865 SP 35W 12V GU5,3     | 35 | 12 | –    | 2,000 | GU5.3  | Spot 10°       |
| 41865WFL        | 4050300026541     | M81 41865 WFL AX 35W 12V GU5,3 | 35 | 12 | –    | 2,000 | GU5.3  | Wide flood 36° |
| 41870SP         | 4050300012636     | M49 41870 SP 50W 12V GU5,3     | 50 | 12 | –    | 2,000 | GU5.3  | Spot 10°       |
| 41870FL         | 4050300012551     | M50 41870 FL 50W 12V GU5,3     | 50 | 12 | –    | 2,000 | GU5.3  | Flood 24°      |
| 41870WFL        | 4050300012575     | M58 41870 WFL 50W 12V GU5,3    | 50 | 12 | –    | 2,000 | GU5.3  | Wide flood 36° |

Perfectly matched with HALOTRONIC® electronic control gear

All orders must be multiples of sales pack




## Halogen Lamps – Low Voltage

**DECOSTAR® 51S STANDARD**

- Low voltage dichroic reflector lamps
- 51mm diameter
- With cover glass
- Approved for use in open luminaires to IEC 60598-1
- Fully dimmable
- Ideal for economical display lighting

| Product ID Code | EAN (Single Pack) | Product Description          | W  | V  | t [h] | FINISH               |    | PPG |
|-----------------|-------------------|------------------------------|----|----|-------|----------------------|----|-----|
| 44860SP         | 4050300272474     | M268 44860 SP 20W 12V GU5,3  | 20 | 12 | 2,000 | GU5.3 Spot 10°       | 20 | 14  |
| 44860WFL        | 4050300272511     | M269 44860 WFL 20W 12V GU5,3 | 20 | 12 | 2,000 | GU5.3 Wide flood 36° | 20 | 14  |
| 44865SP         | 4050300272559     | M271 44865 SP 35W 12V GU5,3  | 35 | 12 | 2,000 | GU5.3 Spot 10°       | 20 | 14  |
| 44865WFL        | 4050300272634     | M281 44865 WFL 35W 12V GU5,3 | 35 | 12 | 2,000 | GU5.3 Wide flood 36° | 20 | 14  |
| 44870SP         | 4050300272672     | M249 44870 SP 50W 12V GU5,3  | 50 | 12 | 2,000 | GU5.3 Spot 10°       | 20 | 14  |
| 44870WFL        | 4050300272719     | M250 44870 FL 50W 12V GU5,3  | 50 | 12 | 2,000 | GU5.3 Flood 24°      | 20 | 14  |
| 44870WFL        | 4050300272795     | M258 44870 WFL 50W 12V GU5,3 | 50 | 12 | 2,000 | GU5.3 Wide flood 36° | 20 | 14  |

Perfectly matched with HALOTRONIC® electronic control gear

**DECOSTAR® 51 ALU**

- Low voltage aluminised reflector lamps
- 51mm diameter
- Without cover glass
- Fully dimmable
- Approved for use in open luminaires to IEC 60598-1
- Ideal for reducing heat build up in luminaires

| Product ID Code | EAN (Single Pack) | Product Description          | W  | V  | t [h] | FINISH               |    | PPG |
|-----------------|-------------------|------------------------------|----|----|-------|----------------------|----|-----|
| 41861WFL        | 4050300428819     | M69A 41861 WFL 20W 12V GU5,3 | 20 | 12 | 2,000 | GU5.3 Wide flood 36° | 20 | 13  |
| 41866WFL        | 4050300428833     | M81A 41866 WFL 35W 12V GU5,3 | 35 | 12 | 2,000 | GU5.3 Wide flood 36° | 20 | 13  |
| 41871WFL        | 4050300428857     | M58A 41871WFL 50W 12V GU5,3  | 50 | 12 | 2,000 | GU5.3 Wide flood 36° | 20 | 13  |

Perfectly matched with HALOTRONIC® electronic control gear

All orders must be multiples of sales pack

## Halogen Lamps – Low Voltage

**DECOSTAR® 51 COOL BLUE®**

- 4500K cool colour dichroic lamp
- Low voltage
- 51mm diameter
- Dichroic reflector reduces the heat in the light beam up to 66%
- Fully dimmable and approved for use in open luminaires to IEC 60598-1
- Ideal for jewellers, galleries and any other installation where a "cool light" is required

| Product ID Code | EAN (Single Pack) | Product Description               | W  | V  | t [h] | FINISH | PPG                  |
|-----------------|-------------------|-----------------------------------|----|----|-------|--------|----------------------|
| 46871WFL        | 4050300816661     | M258CB 46871 WFL 50W 12V CB GU5,3 | 50 | 12 | 4,000 | GU5.3  | Wide flood 36° 20 13 |

Perfectly matched with HALOTRONIC® electronic control gear

**DECOSTAR® 35 STANDARD**


- Low voltage dichroic reflector lamps
- 35mm diameter
- Fully dimmable and approved for use in open luminaires to IEC 60598-1
- Ideal for economical display lighting

| Product ID Code | EAN (Single Pack) | Product Description        | W  | V  | t [h] | FINISH | PPG                  |
|-----------------|-------------------|----------------------------|----|----|-------|--------|----------------------|
| 44888WFL        | 4050300443935     | M200 44888 WFL 10W 12V GU4 | 10 | 12 | 2,000 | GU4    | Wide flood 36° 10 13 |
| 44890SP         | 4050300346090     | M252 44890 SP 20W 12V GU4  | 20 | 12 | 2,000 | GU4    | Spot 10° 10 13       |
| 44890WFL        | 4050300346168     | M221 44890 WFL 20W 12V GU4 | 20 | 12 | 2,000 | GU4    | Wide flood 36° 10 13 |
| 44892SP         | 4050300346182     | M265 44892 SP 35W 12V GU4  | 35 | 12 | 2,000 | GU4    | Spot 10° 10 13       |
| 44892WFL        | 4050300346229     | M223 44892 WFL 35W 12V GU4 | 35 | 12 | 2,000 | GU4    | Wide flood 36° 10 13 |

Perfectly matched with HALOTRONIC® electronic control gear

All orders must be multiples of sales pack

## Halogen Lamps – Low Voltage

**TRAFFIC SIGNAL LAMPS**

- Low voltage capsule lamps for traffic signalling

| Product ID Code | EAN (Single Pack) | Product Description            |    |    |     |        | FINISH |     | PPG |
|-----------------|-------------------|--------------------------------|----|----|-----|--------|--------|-----|-----|
| SIG64015        | 4050300217543     | M133 SIG 64015 50W 10V PKX22S  | 50 | 10 | 750 | PKX22S | Clear  | 100 | 38  |
| SIG64016        | 4050300837741     | M32TS SIG 64016 50W 12V GY6,35 | 50 | 12 | 900 | GY6,35 | Clear  | 100 | 13  |
| SIG64004        | 4050300245225     | M135 SIG 64004 CL 50W 10V K23D | 50 | 10 | 350 | K23d   | Clear  | 10  | 38  |

Perfectly matched with HALOTRONIC® electronic control gear

All orders must be multiples of sales pack

## COMPACT FLUORESCENT LAMPS



# Compact Fluorescent Lamps

## Contents.

### RETROFIT COMPACT FLUORESCENT LAMPS

|                                       |    |
|---------------------------------------|----|
| OSRAM DULUX® INTELLIGENT LONGLIFE     | 36 |
| OSRAM DULUX® INTELLIGENT VARIO & DIM  | 37 |
| OSRAM DULUX® INTELLIGENT FACILITY     | 38 |
| OSRAM DULUX® INTELLIGENT SENSOR       | 39 |
| OSRAM DULUX® INTELLIGENT SOLAR 12V DC | 40 |
| OSRAM DULUX® SUPERSTAR                | 40 |
| OSRAM DULUX® SUPERSTAR CLASSIC        | 42 |
| OSRAM DULUX® SUPERSTAR MICRO TWIST    | 43 |
| OSRAM DULUX SUPERSTAR CIRCOLUX® EL    | 44 |
| OSRAM DULUXSTAR® STICK                | 45 |
| OSRAM DULUXSTAR® CLASSIC              | 46 |
| OSRAM DULUXSTAR® MINI BALL            | 47 |
| OSRAM DULUXSTAR® MINI BULLET P        | 47 |
| OSRAM DULUXSTAR® Mini Globe and Globe | 49 |
| OSRAM DULUXSTAR® Mini Twist           | 50 |
| OSRAM DULUXSTAR® Nano Twist           | 51 |



### PIN BASED COMPACT FLUORESCENT LAMPS

|                                     |    |
|-------------------------------------|----|
| OSRAM DULUX® T PLUS                 | 52 |
| OSRAM DULUX® T/E PLUS               | 53 |
| OSRAM DULUX® T/E CONSTANT (IN PLUS) | 54 |
| OSRAM DULUX® T/E High Efficiency    | 55 |
| OSRAM DULUX® T/E XT for ECG         | 55 |
| OSRAM DULUX® D                      | 56 |
| OSRAM DULUX® D ENERGY SAVER         | 57 |
| OSRAM DULUX® D /E                   | 58 |
| OSRAM DULUX® D/E XT for ECG         | 59 |
| OSRAM DULUX® S                      | 60 |
| OSRAM DULUX® S COLOURED             | 61 |
| OSRAM DULUX® S/E                    | 61 |
| OSRAM DULUX® L LUMILUX®             | 62 |
| OSRAM DULUX® L CONSTANT             | 63 |
| OSRAM DULUX® L LUMILUX® DE LUXE     | 63 |
| OSRAM DULUX® L SP                   | 64 |
| OSRAM DULUX® L HIGH EFFICIENCY      | 64 |
| OSRAM DULUX® L XT                   | 65 |
| OSRAM DULUX® F                      | 66 |
| OSRAM CFL SQUARE                    | 67 |
| OSRAM ENDURA®                       | 67 |





## COMPACT FLUORESCENT LAMPS – RETROFIT



### OSRAM DULUX® INTELLIGENTONGLIFE

- Retrofit “stick shape” electronic energy saving compact fluorescent lamp
- Up to 80% energy saving
- New QUICKlight technology improves run up time by >50%
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for replacing inefficient incandescent lamps




| Product ID Code | EAN (Single Pack) | Product Description  | t [n]  | W  | V       | lm   | lm/W    | Color | l No. | Box | PPG |
|-----------------|-------------------|----------------------|--------|----|---------|------|---------|-------|-------|-----|-----|
| DEL5*           | 4050300357430     | DINT LL 5W/825 E27   | 20,000 | 5  | 220-240 | 250  | ES/E27  | 825   | 4     | 10  | 27  |
| DEL7*           | 4050300288819     | DINT LL 7W/825 E27   | 20,000 | 7  | 220-240 | 365  | ES/E27  | 825   | 4     | 10  | 27  |
| DEL11*          | 4050300811598     | DINT LL 11W/825 E27  | 20,000 | 11 | 220-240 | 620  | ES/E27  | 825   | 5     | 10  | 27  |
| DEL14B25*       | 4008321394965     | DINT LL 14W/825 E27  | 20,000 | 14 | 220-240 | 800  | ES/E27  | 825   | 5     | 10  | 27  |
| DEL18B25*       | 4008321394989     | DINT LL 18W/825 E27  | 20,000 | 18 | 220-240 | 1050 | ES/E27  | 825   | 5     | 10  | 27  |
| DEL22LL         | 4008321953469     | DINT LL 22W/825 E27  | 20,000 | 22 | 220-240 | 1410 | ES/E27  | 825   | 5     | 10  | 27  |
| DEL30B27*       | 4008321935939     | DINT LL 30W/825 E27  | 20,000 | 30 | 220-240 | 1920 | ES/E27  | 825   | 6     | 10  | 27  |
| DEL7B22         | 4050300240329     | DINT LL 7W/825 B22D  | 20,000 | 7  | 220-240 | 365  | BC/B22d | 825   | 7     | 10  | 27  |
| DEL11B22        | 4050300811611     | DINT LL 11W/827 B22D | 20,000 | 11 | 220-240 | 620  | BC/B22d | 825   | 7     | 10  | 27  |
| DEL14B22        | 4008321440440     | DINT LL 14W/825 B22D | 20,000 | 14 | 220-240 | 800  | BC/B22d | 825   | 8     | 10  | 27  |
| DEL18B22        | 4008321440464     | DINT LL 18W/825 B22D | 20,000 | 18 | 220-240 | 1050 | BC/B22d | 825   | 8     | 10  | 27  |
| DEL22B22        | 4008321440488     | DINT LL 22W/825 B22D | 20,000 | 22 | 220-240 | 1410 | BC/B22d | 825   | 8     | 10  | 27  |
| DEL30B22        | 4050300856889     | DINT LL 30W/825 B22D | 20,000 | 30 | 220-240 | 1920 | BC/B22d | 825   | 9     | 10  | 27  |
| DEL5E14*        | 4050300314747     | DINT LL 5W/825 E14   | 20,000 | 5  | 220-240 | 250  | SES/E14 | 825   | 1     | 10  | 27  |
| DEL7E14*        | 4050300315157     | DINT LL 7W/825 E14   | 20,000 | 7  | 220-240 | 365  | SES/E14 | 825   | 2     | 10  | 27  |
| DEL11E14*       | 4050300811451     | DINT LL 11W/825 E14  | 20,000 | 11 | 220-240 | 620  | SES/E14 | 825   | 3     | 10  | 27  |

\* Also available on request in colour 840 (Cool White) for further information contact OSRAM

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUX® INTELLIGENT VARIO & DIM**

- VARIO offers two stage dimming 100% and 30% light using a standard on/off light switch
- DIM offers stepless dimming from 7% to 100% light output using a standard household rotary dimmer switch
- New QUICKlight technology improves run up time by >50%
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for providing relaxed lighting in the home



| Product ID Code | EAN (Single Pack) | Product Description              | t [h]  | W  | V       | lm   |         |     |   | No. |    | PPG |
|-----------------|-------------------|----------------------------------|--------|----|---------|------|---------|-----|---|-----|----|-----|
| <b>VARIO</b>    |                   |                                  |        |    |         |      |         |     |   |     |    |     |
| DEL18VAR        | 4008321953421     | DINT VARIO STICK 18W/825 E27     | 20,000 | 18 | 220-240 | 1200 | ES/E27  | 825 | 2 | 10  | 27 |     |
| DEL18VARB22     | 4008321954503     | DINT VARIO STICK 18W/825 B22D    | 20,000 | 18 | 220-240 | 1200 | BC/B22d | 825 | 2 | 10  | 27 |     |
| <b>DIM</b>      |                   |                                  |        |    |         |      |         |     |   |     |    |     |
| DEL18DIMB22     | 4008321954541     | DINT DIM STICK 18W/825 B22D      | 20,000 | 18 | 220-240 | 1050 | BC/B22d | 825 | 1 | 10  | 27 |     |
| DEL18DIM        | 4008321953445     | DINT DIM STICK 18W/825 E27       | 20,000 | 18 | 220-240 | 1050 | ES/E27  | 825 | 1 | 10  | 27 |     |
| DEL15DIMGL      | 4008321924209     | DINT DIM GLOBE 15W/825 E27       | 20,000 | 15 | 220-240 | 830  | ES/E27  | 825 | 5 | 10  | 27 |     |
| -               | 4008321953520*    | DINT DIM MINIBALL 15W/825 E27    | 20,000 | 15 | 220-240 | -    | ES/E27  | 825 | 3 | 10  | 27 |     |
| -               | 4008321953568*    | DINT DIM MINI CANDLE 11W/825 E27 | 20,000 | 11 | 220-240 | -    | ES/E27  | 825 | 4 | 10  | 27 |     |
| DEL20DIMTW      | 4008321953605     | DINT DIM TWIST 20W/825 E27       | 20,000 | 20 | 220-240 | -    | ES/E27  | 825 | 6 | 10  | 27 |     |

\*In preparation at time of print. For further information please contact OSRAM

All orders must be multiples of sales pack


## Compact Fluorescent Lamps – Retrofit



1



2

**OSRAM DULUX® INTELLIGENT FACILITY**

- Retrofit electronic energy saving compact fluorescent lamp for unlimited switching
- New QUICKlight technology improves run up time by >50%
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal where energy saving lamps need to be switched on and off frequently


| Product ID Code | EAN (Single Pack) | Product Description   | t <sub>l</sub> h | W  | V       | lm   | W       | W   | No. | PPG   |
|-----------------|-------------------|-----------------------|------------------|----|---------|------|---------|-----|-----|-------|
| <b>SES Cap</b>  |                   |                       |                  |    |         |      |         |     |     |       |
| DEL10FCYE14     | 4008321126276     | DINT FCY 10W/825 E14  | 20,000           | 10 | 220-240 | 550  | SES/E14 | 825 | 1   | 10 27 |
| <b>ES Cap</b>   |                   |                       |                  |    |         |      |         |     |     |       |
| DEL10FCY        | 4008321126290     | DINT FCY 10W/825 E27  | 20,000           | 10 | 220-240 | 550  | ES/E27  | 825 | 2   | 10 27 |
| DEL14FCY        | 4050300631905     | DINT FCY 14W/825 E27  | 20,000           | 14 | 220-240 | 780  | ES/E27  | 825 | 2   | 10 27 |
| DEL18FCY        | 4008321118356     | DINT FCY 18W/825 E27  | 20,000           | 18 | 220-240 | 1030 | ES/E27  | 825 | 2   | 10 27 |
| DEL22FCY        | 4008321948519     | DINT FCY 22W/825 E27  | 20,000           | 22 | 220-240 | 1360 | ES/E27  | 825 | 2   | 10 27 |
| <b>BC Cap</b>   |                   |                       |                  |    |         |      |         |     |     |       |
| DEL14FCYB22     | 4050300633718     | DINT FCY 14W/825 B22D | 20,000           | 14 | 220-240 | 780  | BC/B22d | 825 | 1   | 10 27 |

NEW

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Retrofit



1

2

**OSRAM DULUX® INTELLIGENT SENSOR**


- Retrofit electronic energy saving compact fluorescent lamp with light sensor
- Fully automatic operation
- New QUICKlight technology improves run up time by >50%
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for automatic dusk till dawn switching in outdoor security lighting

| Product ID Code | EAN (Single Pack) | Product Description       | t [h]  | W  | V       | lm  |         |     | No. |    | PPG |
|-----------------|-------------------|---------------------------|--------|----|---------|-----|---------|-----|-----|----|-----|
| <b>ES Cap</b>   |                   |                           |        |    |         |     |         |     |     |    |     |
| DEL11SEN        | 4008321102300     | DINT SENSOR 11W/825 E27   | 20,000 | 11 | 220-240 | 560 | ES/E27  | 825 | 1   | 10 | 27  |
| DEL15SEN        | 4050300451299     | DINT SENSOR 15W/825 E27   | 20,000 | 15 | 220-240 | 820 | ES/E27  | 825 | 1   | 10 | 27  |
| DSENS11MIBA     | 4008321377722     | DINT SENSMBIA 11W/825 E27 | 20,000 | 11 | 220-240 | 630 | ES/E27  | 825 | 2   | 10 | 27  |
| <b>BC Cap</b>   |                   |                           |        |    |         |     |         |     |     |    |     |
| DEL15SENB22     | 4050300487694     | DINT SENSOR 15W/825 B22D  | 20,000 | 15 | 220-240 | 820 | BC/B22d | 825 | 1   | 10 | 27  |




All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUX® INTELLIGENT 12V SOLAR DC**

- Retrofit electronic energy saving compact fluorescent lamp
- Can be used with a 12V DC electrical supply
- New QUICKlight technology improves run up time by >50%
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for camping and outdoor pursuits where mains electricity is not available

| Product ID Code | EAN (Single Pack) | Product Description         | t [h]  | W  | V  | lm  |        |     |    | PPG |
|-----------------|-------------------|-----------------------------|--------|----|----|-----|--------|-----|----|-----|
| <b>ES cap</b>   |                   |                             |        |    |    |     |        |     |    |     |
| DEL11DC         | 4008321118370     | OSRAM DINT 11W/825 DC       | 10,000 | 11 | 12 | 540 | ES/E27 | 825 | 10 | 27  |
| DEL11840DC      | 4008321118394     | OSRAM DINT 11W/840 DC       | 10,000 | 11 | 12 | 540 | ES/E27 | 840 | 10 | 27  |
| DEL11DCVAR      | 4008321118417     | OSRAM DINT VARIO 11W/825 DC | 10,000 | 11 | 12 | 600 | ES/E27 | 825 | 10 | 27  |
| DEL11840DCVAR   | 4008321118936     | OSRAM DINT VARIO 11W/840 DC | 10,000 | 11 | 12 | 600 | ES/E27 | 840 | 10 | 27  |

**OSRAM DULUX® SUPERSTAR STICK**

- Retrofit “stick shape” electronic energy saving compact fluorescent lamp
- New QUICKlight technology improves run up time by >50%
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for replacing inefficient incandescent lamps

| Product ID Code | EAN (Single Pack) | Product Description | t [h]  | W | V       | lm  |         |     | No. | PPG |    |
|-----------------|-------------------|---------------------|--------|---|---------|-----|---------|-----|-----|-----|----|
| DSU5825E14      | 4008321942845     | DSST 5W/825 E14     | 15,000 | 5 | 220-240 | 250 | SES/E14 | 825 | 1   | 10  | 27 |
| DSU5840E14      | 4008321948571     | DSST 5W/840 E14     | 15,000 | 5 | 220-240 | 250 | SES/E14 | 840 | 1   | 10  | 27 |
| DSU5865E14*     | 4008321948588     | DSST 5W/865 E14     | 15,000 | 5 | 220-240 | –   | SES/E14 | 865 | 1   | 10  | 27 |
| DSU5825         | 4008321942852     | DSST 5W/825 E27     | 15,000 | 5 | 220-240 | 250 | ES/E27  | 825 | 4   | 10  | 27 |
| DSU5840         | 4008321948595     | DSST 5W/840 E27     | 15,000 | 5 | 220-240 | 250 | ES/E27  | 840 | 4   | 10  | 27 |
| DSU5865*        | 4008321948601     | DSST 5W/865 E27     | 15,000 | 5 | 220-240 | –   | ES/E27  | 865 | 4   | 10  | 27 |


\*Available on request in colour 865 (Cool Daylight)

Continued

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Retrofit



## OSRAM DULUX® SUPERSTAR STICK (continued)



| Product ID Code | EAN (Single Pack) | Product Description | t [h]  | W  | V       | Im   |         |     | No. |    | PPG |
|-----------------|-------------------|---------------------|--------|----|---------|------|---------|-----|-----|----|-----|
| DSU5825B22      | 4008321942869     | DSST 5W/825 B22D    | 15,000 | 5  | 220-240 | 250  | BC/B22d | 825 | 7   | 10 | 27  |
| DSU7825E14      | 4008321942876     | DSST 7W/825 E14     | 15,000 | 7  | 220-240 | 365  | SES/E14 | 825 | 2   | 10 | 27  |
| DSU7840E14      | 4008321948618     | DSST 7W/840 E14     | 15,000 | 7  | 220-240 | 365  | SES/E14 | 840 | 2   | 10 | 27  |
| DSU7865E14*     | 4008321948625     | DSST 7W/865 E14     | 15,000 | 7  | 220-240 | 380  | SES/E14 | 865 | 2   | 10 | 27  |
| DSU7825         | 4008321942883     | DSST 7W/825 E27     | 15,000 | 7  | 220-240 | 365  | ES/E27  | 825 | 4   | 10 | 27  |
| DSU7840         | 4008321942890     | DSST 7W/840 E27     | 15,000 | 7  | 220-240 | 365  | ES/E27  | 840 | 4   | 10 | 27  |
| DSU7865*        | 4008321948632     | DSST 7W/865 E27     | 15,000 | 7  | 220-240 | 380  | ES/E27  | 865 | 4   | 10 | 27  |
| DSU7825B22      | 4008321942906     | DSST 7W/825 B22D    | 15,000 | 7  | 220-240 | 365  | BC/B22d | 825 | 7   | 10 | 27  |
| DSU11825E14     | 4008321942913     | DSST 11W/825 E14    | 15,000 | 11 | 220-240 | 620  | SES/E14 | 825 | 3   | 10 | 27  |
| DSU11840E14     | 4008321948649     | DSST 11W/840 E14    | 15,000 | 11 | 220-240 | 620  | SES/E14 | 840 | 3   | 10 | 27  |
| DSU11865E14*    | 4008321948656     | DSST 11W/865 E14    | 15,000 | 11 | 220-240 | 600  | SES/E14 | 865 | 3   | 10 | 27  |
| DSU11825        | 4008321942920     | DSST 11W/825 E27    | 15,000 | 11 | 220-240 | 620  | ES/E27  | 825 | 5   | 10 | 27  |
| DSU11840        | 4008321942937     | DSST 11W/840 E27    | 15,000 | 11 | 220-240 | 620  | ES/E27  | 840 | 5   | 10 | 27  |
| DSU11865*       | 4008321942944     | DSST 11W/865 E27    | 15,000 | 11 | 220-240 | 600  | ES/E27  | 865 | 5   | 10 | 27  |
| DSU11825B22     | 4008321942951     | DSST 11W/825 B22D   | 15,000 | 11 | 220-240 | 620  | BC/B22d | 825 | 7   | 10 | 27  |
| DSU14825        | 4008321942968     | DSST 14W/825 E27    | 15,000 | 14 | 220-240 | 800  | ES/E27  | 825 | 5   | 10 | 27  |
| DSU14840        | 4008321942975     | DSST 14W/840 E27    | 15,000 | 14 | 220-240 | 800  | ES/E27  | 840 | 5   | 10 | 27  |
| DSU14865*       | 4008321942982     | DSST 14W/865 E27    | 15,000 | 14 | 220-240 | 855  | ES/E27  | 865 | 5   | 10 | 27  |
| DSU14825B22     | 4008321942999     | DSST 14W/825 B22D   | 15,000 | 14 | 220-240 | 800  | BC/B22d | 825 | 8   | 10 | 27  |
| DSU18825        | 4008321943002     | DSST 18W/825 E27    | 15,000 | 18 | 220-240 | 1050 | ES/E27  | 825 | 5   | 10 | 27  |
| DSU18840        | 4008321943019     | DSST 18W/840 E27    | 15,000 | 18 | 220-240 | 1050 | ES/E27  | 840 | 5   | 10 | 27  |
| DSU18865*       | 4008321943026     | DSST 18W/865 E27    | 15,000 | 18 | 220-240 | 1140 | ES/E27  | 865 | 5   | 10 | 27  |
| DSU18825B22     | 4008321943033     | DSST 18W/825 B22D   | 15,000 | 18 | 220-240 | 1050 | BC/B22d | 825 | 8   | 10 | 27  |
| DSST22825       | 4008321953360     | DSST 22W/825 E27    | 15,000 | 22 | 220-240 | 1410 | ES/E27  | 825 | 5   | 10 | 27  |
| DSST22840       | 4008321953384     | DSST 22W/840 E27    | 15,000 | 22 | 220-240 | 1410 | ES/E27  | 840 | 5   | 10 | 27  |
| DSST22B22       | 4008321954626     | DSST 22W/825 B22D   | 15,000 | 22 | 220-240 | 1410 | BC/B22d | 825 | 8   | 10 | 27  |
| DSU30825        | 4008321942753     | DSST 30W/825 E27    | 15,000 | 30 | 220-240 | 1920 | ES/E27  | 825 | 6   | 10 | 27  |
| DSU30840        | 4008321942760     | DSST 30W/840 E27    | 15,000 | 30 | 220-240 | 1920 | ES/E27  | 840 | 6   | 10 | 27  |
| DSST30B22       | 4008321953346     | DSST 30W/825 B22D   | 15,000 | 30 | 220-240 | 1920 | BC/B22d | 825 | 9   | 10 | 27  |

\*Available on request in colour 865 (Cool Daylight)



All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Retrofit

500000  
on/off**OSRAM DULUX® SUPERSTAR CLASSIC**

- Retrofit “look-a-like” electronic energy saving compact fluorescent lamp
- New QUICKlight technology improves run up time by >50%
- Up to 80% energy saving
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- NEW compact versions: mini ball/ mini globe/ mini candle/globe/reflector
- Ideal for replacing inefficient incandescent lamps

| Product ID Code    | EAN (Single Pack) | Product Description    | t [h]  | W  | V       | lm   |         | No. |   | PPG   |
|--------------------|-------------------|------------------------|--------|----|---------|------|---------|-----|---|-------|
| <b>Mini Candle</b> |                   |                        |        |    |         |      |         |     |   |       |
| DSST5MICA E14      | 4008321944535     | DSST MICA 5W/825 E14   | 15,000 | 5  | 220-240 | 240  | SES/E14 | 825 | 1 | 10 27 |
| DSST5MICA          | 4008321944542     | DSST MICA 5W/825 E27   | 15,000 | 5  | 220-240 | 240  | ES/E27  | 825 | 1 | 10 27 |
| DSST7MICA E14      | 4008321944559     | DSST MIBA 7W/825 E14   | 15,000 | 7  | 220-240 | 300  | SES/E14 | 825 | 1 | 10 27 |
| DSST7MICA          | 4008321944566     | DSST MIBA 7W/825 E27   | 15,000 | 7  | 220-240 | 300  | ES/E27  | 825 | 1 | 10 27 |
| <b>Globe</b>       |                   |                        |        |    |         |      |         |     |   |       |
| DSU14GL            | 4008321943873     | DSST GL 14W/825 E27    | 15,000 | 14 | 220-240 | 830  | ES/E27  | 825 | 2 | 10 27 |
| DSU18GL            | 4008321943880     | DSST GL 18W/825 E27    | 15,000 | 18 | 220-240 | 1040 | ES/E27  | 825 | 2 | 10 27 |
| <b>Mini Globe</b>  |                   |                        |        |    |         |      |         |     |   |       |
| DSST5MIGL          | 4008321943637     | DSST MIGL 5W/825 E27   | 15,000 | 5  | 220-240 | 250  | ES/E27  | 825 | 3 | 10 27 |
| DSST7MIGL          | 4008321943675     | DSST MIGL 7W/825 E27   | 15,000 | 7  | 220-240 | 360  | ES/E27  | 825 | 3 | 10 27 |
| DSST11MIGL         | 4008321943712     | DSST MIGL 11W/825 E27  | 15,000 | 11 | 220-240 | 630  | ES/E27  | 825 | 3 | 10 27 |
| DSST15MIGL         | 4008321943736     | DSST MIGL 15W/825 E27  | 15,000 | 15 | 220-240 | 850  | ES/E27  | 825 | 3 | 10 27 |
| DSST20MIGL         | 4008321943663     | DSST MIGL 20W/825 E27  | 15,000 | 20 | 220-240 | 1160 | ES/E27  | 825 | 3 | 10 27 |
| DSST20MIGLB22      | 4008321414984     | DSST MIGL 20W/825 B22D | 15,000 | 20 | 220-240 | 1160 | BC/B22d | 825 | 3 | 10 27 |
| DSST5MIGLE14       | 4008321943651     | DSST MIGL 5W/825 E14   | 15,000 | 5  | 220-240 | 250  | SES/E14 | 825 | 3 | 10 27 |
| DSST7MIGLE14       | 4008321943699     | DSST MIGL 7W/825 E14   | 15,000 | 7  | 220-240 | 360  | SES/E14 | 825 | 3 | 10 27 |
| <b>Miniball</b>    |                   |                        |        |    |         |      |         |     |   |       |
| DSST5MIBA          | 4008321943439     | DSST MIBA 5W/825 E14   | 15,000 | 5  | 220-240 | 250  | SES/E14 | 825 | 4 | 10 27 |
| DSST7MIBA          | 4008321943453     | DSST MIBA 7W/825 E14   | 15,000 | 7  | 220-240 | 360  | ES/E27  | 825 | 4 | 10 27 |
| DSST11MIBA         | 4008321943477     | DSST MIBA 11W/825 E27  | 15,000 | 11 | 220-240 | 630  | ES/E27  | 825 | 4 | 10 27 |
| DSST11MIBAB22      | 4008321943491     | DSST MIBA 11W/825 E27  | 15,000 | 11 | 220-240 | 630  | BC/B22d | 825 | 4 | 10 27 |
| DSST15MIBA         | 4008321943507     | DSST MIBA 15W/825 E27  | 15,000 | 15 | 220-240 | 850  | ES/E27  | 825 | 4 | 10 27 |
| DSST15MIBAB22      | 4008321943521     | DSST MIBA 15W/825 B22D | 15,000 | 15 | 220-240 | 850  | BC/B22d | 825 | 4 | 10 27 |
| DSST20MIBA         | 4008321943549     | DSST MIBA 20W/825 E27  | 15,000 | 20 | 220-240 | 1160 | ES/E27  | 825 | 4 | 10 27 |
| DSST20MIBAB22      | 4008321943566     | DSST MIBA 20W/825 B22D | 15,000 | 20 | 220-240 | 1160 | BC/B22d | 825 | 4 | 10 27 |
| <b>Reflector</b>   |                   |                        |        |    |         |      |         |     |   |       |
| DSST14R825         | 4008321396440     | DSST R 14W/825 E27     | 15,000 | 14 | 220-240 |      | ES/E27  | 825 | 5 | 10 27 |
| DSST14R840         | 4008321396464     | DSST R 14W/840 E27     | 15,000 | 14 | 220-240 |      | ES/E27  | 840 | 5 | 10 27 |
| DSST18R825         | 4008321396396     | DSST R 18W/825 E27     | 15,000 | 18 | 220-240 |      | ES/E27  | 825 | 5 | 10 27 |
| DSST18R840         | 4008321396419     | DSST R 18W/840 E27     | 15,000 | 18 | 220-240 |      | ES/E27  | 840 | 5 | 10 27 |

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUX® SUPERSTAR MICRO TWIST**

- New micro twist retrofit energy saving compact fluorescent lamp
- Up to 80% energy saving
- New QUICKlight technology improves run up time by >50%
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for replacing inefficient incandescent lamps




| Product ID Code     | EAN (Single Pack) | Product Description   | t [h]  | W  | V       | lm   |         |     |    | PPG |
|---------------------|-------------------|-----------------------|--------|----|---------|------|---------|-----|----|-----|
| MICROTWIST7825E14   | 4008321948922     | MICRO TW 7W/825 E14   | 12,000 | 7  | 220-240 | 420  | SES/E14 | 825 | 10 | 27  |
| MICROTWIST7840E14   | 4008321948939     | MICRO TW 7W/840 E14   | 12,000 | 7  | 220-240 | 420  | SES/E14 | 840 | 10 | 27  |
| MICROTWIST7865E14*  | 4008321948946     | MICRO TW 7W/865 E14   | 12,000 | 7  | 220-240 | 400  | SES/E14 | 865 | 10 | 27  |
| MICROTWIST7825      | 4008321948953     | MICRO TW 7W/825 E27   | 12,000 | 7  | 220-240 | 420  | ES/E27  | 825 | 10 | 27  |
| MICROTWIST7840      | 4008321948960     | MICRO TW 7W/840 E27   | 12,000 | 7  | 220-240 | 420  | ES/E27  | 840 | 10 | 27  |
| MICROTWIST7865*     | 4008321948977     | MICRO TW 7W/865 E27   | 12,000 | 7  | 220-240 | 400  | ES/E27  | 865 | 10 | 27  |
| MICROTWIST7825B22   | 4008321948984     | MICRO TW 7W/825 B22D  | 12,000 | 7  | 220-240 | 420  | BC/B22d | 825 | 10 | 27  |
| MICROTWIST11825     | 4008321948991     | MICRO TW 11W/825 E27  | 12,000 | 11 | 220-240 | 650  | ES/E27  | 825 | 10 | 27  |
| MICROTWIST11825E14  | 4008321949004     | MICRO TW 11W/825 E14  | 12,000 | 11 | 220-240 | 650  | SES/E14 | 825 | 10 | 27  |
| MICROTWIST11840     | 4008321949011     | MICRO TW 11W/840 E27  | 12,000 | 11 | 220-240 | 650  | ES/E27  | 840 | 10 | 27  |
| MICROTWIST11840E14  | 4008321949028     | MICRO TW 11W/840 E14  | 12,000 | 11 | 220-240 | 650  | SES/E14 | 840 | 10 | 27  |
| MICROTWIST11865*    | 4008321949035     | MICRO TW 11W/865 E27  | 12,000 | 11 | 220-240 | 620  | ES/E27  | 865 | 10 | 27  |
| MICROTWIST11865E14* | 4008321949042     | MICRO TW 11W/865 E14  | 12,000 | 11 | 220-240 | 620  | SES/E14 | 865 | 10 | 27  |
| MICROTWIST11825B22  | 4008321949059     | MICRO TW 11W/825 B22D | 12,000 | 11 | 220-240 | 650  | BC/B22d | 825 | 10 | 27  |
| MICROTWIST14825     | 4008321949066     | MICRO TW 14W/825 E27  | 12,000 | 14 | 220-240 | 860  | ES/E27  | 825 | 10 | 27  |
| MICROTWIST14840     | 4008321949073     | MICRO TW 14W/840 E27  | 12,000 | 14 | 220-240 | 860  | ES/E27  | 840 | 10 | 27  |
| MICROTWIST14865*    | 4008321949080     | MICRO TW 14W/865 E27  | 12,000 | 14 | 220-240 | 820  | ES/E27  | 865 | 10 | 27  |
| MICROTWIST14825B22  | 4008321949097     | MICRO TW 14W/825 B22D | 12,000 | 14 | 220-240 | 860  | BC/B22d | 825 | 10 | 27  |
| MICROTWIST18825     | 4008321949103     | MICRO TW 18W/825 E27  | 12,000 | 18 | 220-240 | 1200 | ES/E27  | 825 | 10 | 27  |
| MICROTWIST18840     | 4008321949110     | MICRO TW 18W/840 E27  | 12,000 | 18 | 220-240 | 1200 | ES/E27  | 840 | 10 | 27  |
| MICROTWIST18865*    | 4008321949127     | MICRO TW 18W/865 E27  | 12,000 | 18 | 220-240 | 1140 | ES/E27  | 865 | 10 | 27  |
| MICROTWIST18825B22  | 4008321949134     | MICRO TW 18W/825 B22D | 12,000 | 18 | 220-240 | 1200 | BC/B22d | 825 | 10 | 27  |
| MICROTWIST23825     | 4008321949141     | MICRO TW 23W/825 E27  | 12,000 | 23 | 220-240 | 1600 | ES/E27  | 825 | 10 | 27  |
| MICROTWIST23840     | 4008321949158     | MICRO TW 23W/840 E27  | 12,000 | 23 | 220-240 | 1600 | ES/E27  | 840 | 10 | 27  |
| MICROTWIST23865*    | 4008321949165     | MICRO TW 23W/865 E27  | 12,000 | 23 | 220-240 | 1520 | ES/E27  | 865 | 10 | 27  |
| MICROTWIST23825B22  | 4008321949172     | MICRO TW 18W/825 B22D | 12,000 | 23 | 220-240 | 1600 | BC/B22d | 825 | 10 | 27  |

\*Available on request in colour 865 (Cool Daylight)

All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUX® SUPERSTAR CIRCOLUX® EL**

- Circular retrofit electronic energy saving compact fluorescent lamp
- Circular low-profile design
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for use in shaded pendant luminaires


| Product ID Code | EAN (Single Pack) | Product Description          | t [h]  | W  | V       | lm   |  |  |  | PPG   |
|-----------------|-------------------|------------------------------|--------|----|---------|------|--|--|--|-------|
| CEL24825        | 4050300626628     | DSST CIRCOLUX EL 24W/827 E27 | 15,000 | 24 | 220-240 | 1700 |  |  |  | 10 27 |
| CEL24840        | 4050300623603     | DSST CIRCOLUX 24W/840 E27    | 15,000 | 24 | 220-240 | 1700 |  |  |  | 10 27 |



All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUXSTAR® STICK**

- Retrofit "stick shape" electronic energy saving compact fluorescent lamp
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for replacing inefficient incandescent lamps

| Product ID Code | EAN (Single Pack) | Product Description | t [h]  | W  | V       | lm   |         |     | PPG   |
|-----------------|-------------------|---------------------|--------|----|---------|------|---------|-----|-------|
| DST5E14         | 4008321063175     | DSTAR 5W/825 E14    | 10,000 | 5  | 220-240 | 250  | SES/E14 | 825 | 10 27 |
| DST5B22         | 4008321063328     | DSTAR 5W/825 B22D   | 10,000 | 5  | 220-240 | 250  | BC/B22d | 825 | 10 27 |
| DST5            | 4008321063144     | DSTAR 5W/825 E27    | 10,000 | 5  | 220-240 | 250  | ES/E27  | 825 | 10 27 |
| DST8E14         | 4008321063236     | DSTAR 8W/825 E14    | 10,000 | 8  | 220-240 | 400  | SES/E14 | 825 | 10 27 |
| DST8            | 4008321063205     | DSTAR 8W/825 E27    | 10,000 | 8  | 220-240 | 400  | ES/E27  | 825 | 10 27 |
| DST8B22         | 4008321063359     | DSTAR 8W/825 B22D   | 10,000 | 8  | 220-240 | 400  | BC/B22d | 825 | 10 27 |
| DST8840E14      | 4008321361721     | DSTAR 8W/840 E14    | 10,000 | 8  | 220-240 | 400  | SES/E14 | 840 | 10 27 |
| DST8840         | 4008321361752     | DSTAR 8W/840 E27    | 10,000 | 8  | 220-240 | 400  | ES/E27  | 840 | 10 27 |
| DST8865E14*     | 4008321361783     | DSTAR 8W/865 E14    | 10,000 | 8  | 220-240 | 380  | SES/E14 | 865 | 10 27 |
| DST8865*        | 4008321361813     | DSTAR 8W/865 E27    | 10,000 | 8  | 220-240 | 380  | ES/E27  | 865 | 10 27 |
| DST11           | 4008321063267     | DSTAR 11W/825 E27   | 10,000 | 11 | 220-240 | 600  | ES/E27  | 825 | 10 27 |
| DST11B22        | 4008321063380     | DSTAR 11W/825 B22D  | 10,000 | 11 | 220-240 | 600  | BC/B22d | 825 | 10 27 |
| DST11B40        | 4008321319197     | DSTAR 11W/840 E27   | 10,000 | 11 | 220-240 | 600  | ES/E27  | 840 | 10 27 |
| DST11B60*       | 4008321246783     | DSTAR 11W/865 E27   | 10,000 | 11 | 220-240 | 570  | ES/E27  | 865 | 10 27 |
| DST14           | 4008321063298     | DSTAR 14W/825 E27   | 10,000 | 14 | 220-240 | 750  | ES/E27  | 825 | 10 27 |
| DST14B22        | 4008321063410     | DSTAR 14W/825 B22D  | 10,000 | 14 | 220-240 | 750  | BC/B22d | 825 | 10 27 |
| DST14B40        | 4008321319159     | DSTAR 14W/840 E27   | 10,000 | 14 | 220-240 | 750  | ES/E27  | 840 | 10 27 |
| DST14B60*       | 4008321246820     | DSTAR 14W/865 E27   | 10,000 | 14 | 220-240 | 710  | ES/E27  | 865 | 10 27 |
| DST17           | 4008321063441     | DSTAR 17W/825 E27   | 10,000 | 17 | 220-240 | 950  | ES/E27  | 825 | 10 27 |
| DST17B22        | 4008321063465     | DSTAR 17W/825 B22D  | 10,000 | 17 | 220-240 | 950  | BC/B22d | 825 | 10 27 |
| DST17B40        | 4008321945891     | DSTAR 17W/840 E27   | 10,000 | 17 | 220-240 | 950  | ES/E27  | 840 | 10 27 |
| DST21           | 4008321063526     | DSTAR 21W/825 E27   | 10,000 | 21 | 220-240 | 1230 | ES/E27  | 825 | 10 27 |
| DST21B22        | 4008321131928     | DSTAR 21W/825 B22D  | 10,000 | 21 | 220-240 | 1230 | BC/B22d | 825 | 10 27 |
| DST21B40        | 4008321319210     | DSTAR 21W/840 E27   | 10,000 | 21 | 220-240 | 1230 | ES/E27  | 840 | 10 27 |
| DST24           | 4008321063502     | DSTAR 24W/825 E27   | 10,000 | 24 | 220-240 | 1500 | ES/E27  | 825 | 10 27 |
| DST24B22        | 4008321063540     | DSTAR 24W/825 B22   | 10,000 | 24 | 220-240 | 1500 | BC/B22d | 825 | 10 27 |
| DST24B40        | 4008321396518     | DSTAR 24W/840 E27   | 10,000 | 24 | 220-240 | 1500 | ES/E27  | 840 | 10 27 |
| -               | 4008321945990**   | DSTAR 24W/865 E27   | 10,000 | 24 | 220-240 | 1400 | ES/E27  | 865 | 10 27 |
| DST30B25        | 4008321181213     | DSTAR 30W/825 E27   | 10,000 | 30 | 220-240 | 1920 | ES/E27  | 825 | 10 27 |
| DST30B40        | 4008321181237     | DSTAR 30W/840 E27   | 10,000 | 30 | 220-240 | 1920 | ES/E27  | 840 | 10 27 |
| DST30B65*       | 4008321181251     | DSTAR 30W/865 E27   | 10,000 | 30 | 220-240 | 1830 | ES/E27  | 865 | 10 27 |

\* Also available on request in colour 865 (Cool Daylight)


\*\* In preparation at time of print. For further information please contact OSRAM



NEW

All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUXSTAR® CLASSIC**

- Retrofit “look-a-like” electronic energy saving compact fluorescent lamp
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Up to 80% energy saving
- NEW compact Mini candle version
- Ideal for replacing inefficient incandescent lamps


| Product ID Code          | EAN (Single Pack) | Product Description          | t [h]  | W  | V       | lm   |         |     |   | No. |    | PPG |
|--------------------------|-------------------|------------------------------|--------|----|---------|------|---------|-----|---|-----|----|-----|
| <b>Mini Candle shape</b> |                   |                              |        |    |         |      |         |     |   |     |    |     |
| DST5MICA E14             | 4008321944450     | DSTAR MICA 5W/825 E14        | 10,000 | 5  | 220-240 | 250  | SES/E14 | 825 | 1 | 10  | 27 |     |
| DST5MICA                 | 4008321944467     | DSTAR MICA 5W/825 E27        | 10,000 | 5  | 220-240 | 250  | ES/E27  | 825 | 2 | 10  | 27 |     |
| DST7MICA E14             | 4008321944474     | DSTAR MICA 7W/825 E14        | 10,000 | 7  | 220-240 | 340  | SES/E14 | 825 | 1 | 10  | 27 |     |
| DST7MICA                 | 4008321944481     | DSTAR MICA 7W/825 E27        | 10,000 | 7  | 220-240 | 340  | ES/E27  | 825 | 2 | 10  | 27 |     |
| DST10MICA E14            | 4008321946621     | DSTAR MICA 9W/825 E14        | 10,000 | 10 | 220-240 | 550  | SES/E14 | 825 | 1 | 10  | 27 |     |
| DST10MICA                | 4008321946645     | DSTAR MICA 9W/825 E27        | 10,000 | 10 | 220-240 | 550  | ES/E27  | 825 | 2 | 10  | 27 |     |
| <b>GLS shape</b>         |                   |                              |        |    |         |      |         |     |   |     |    |     |
| DST11CLA                 | 4008321946263     | DSTAR CLA 11W/825 E27        | 10,000 | 10 | 220-240 | 580  | ES/E27  | 825 | 3 | 10  | 27 |     |
| -                        | 4008321946287*    | OSRAM DSTAR CLA 11W/825 B22d | 10,000 | 10 | 220-240 | 580  | BC/B22d | 825 | 4 | 10  | 27 |     |
| DST20CLLA                | 4008321399878     | DSTAR CL A 20W/825 E27       | 10,000 | 20 | 220-240 | 1160 | ES/E27  | 825 | 3 | 10  | 27 |     |
| DST20CLLAB2              | 4008321399854     | DSTAR CL A 20W/825 B22D      | 10,000 | 20 | 220-240 | 1160 | BC/B22d | 825 | 4 | 10  | 27 |     |
| <b>R50</b>               |                   |                              |        |    |         |      |         |     |   |     |    |     |
| DST7R50                  | 4008321234223     | DSTAR R50 7W/825 E14         | 10,000 | 7  | 220-240 |      | SES/E14 | 825 | 5 | 10  | 27 |     |
| DST7R50GU10              | 4008321938572     | DSTAR R50 7W/825 GU10        | 10,000 | 7  | 220-240 |      | GU10    | 825 | 6 | 10  | 27 |     |
| DST9R50E14               | 4008321946706     | DSTAR R50 9W/825 E14         | 10,000 | 9  | 220-240 |      | SES/E14 | 825 | 5 | 10  | 27 |     |
| DST9R50GU10              | 4008321946720     | DSTAR R50 9W/825 GU10        | 10,000 | 9  | 220-240 |      | GU10    | 825 | 6 | 10  | 27 |     |
| <b>R63</b>               |                   |                              |        |    |         |      |         |     |   |     |    |     |
| DST11R63                 | 4008321938602     | DSTAR R63 11W/825 E27        | 10,000 | 11 | 220-240 |      | ES/E27  | 825 | 7 | 10  | 27 |     |
| DST13R63                 | 4008321946744     | DSTAR R63 13W/825 E27        | 10,000 | 13 | 220-240 |      | ES/E27  | 825 | 7 | 10  | 27 |     |
| <b>PAR 38</b>            |                   |                              |        |    |         |      |         |     |   |     |    |     |
| DSTPAR3820               | 4008321162878     | DSTAR PAR 38 20W/827 E27     | 10,000 | 20 | 220-240 |      | ES/E27  | 825 | 8 | 10  | 27 |     |

\* In preparation at time of print. For further information please contact OSRAM

All orders must be multiples of sales pack




## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUXSTAR® MINI BALL**

- Retrofit mini ball shape energy saving compact fluorescent lamp
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for replacing inefficient incandescent lamps

| Product ID Code | EAN (Single Pack) | Product Description     | t [h]  | W  | V       | lm   |         |     |    | PPG |
|-----------------|-------------------|-------------------------|--------|----|---------|------|---------|-----|----|-----|
| DST5MIBA        | 4008321946300     | DSTAR MIBA 5W/825 E14   | 10,000 | 5  | 220-240 | 250  | SES/E14 | 825 | 10 | 27  |
| DST7MIBA        | 4008321946324     | DSTAR MIBA 7W/825 E14   | 10,000 | 7  | 220-240 | 360  | SES/E14 | 825 | 10 | 27  |
| DST11MIBA       | 4008321125705     | DSTAR MIBA 11W/825 E27  | 10,000 | 11 | 220-240 | 630  | ES/E27  | 825 | 10 | 27  |
| DST11MIBAB22    | 4008321125668     | DSTAR MIBA 11W/825 B22D | 10,000 | 11 | 220-240 | 630  | BC/B22d | 825 | 10 | 27  |
| DST15MIBA       | 4008321125644     | DSTAR MIBA 15W/825 E27  | 10,000 | 15 | 220-240 | 850  | ES/E27  | 825 | 10 | 27  |
| DST15MIBAB22    | 4008321125682     | DSTAR MIBA 15W/825 B22D | 10,000 | 15 | 220-240 | 850  | BC/B22d | 825 | 10 | 27  |
| DST20MIBA       | 4008321946409     | DSTAR MIBA 20W/825 E27  | 10,000 | 20 | 220-240 | 1160 | ES/E27  | 825 | 10 | 27  |
| DST20MIBAB22    | 4008321946416     | DSTAR MIBA 20W/825 B22D | 10,000 | 20 | 220-240 | 1160 | BC/B22d | 825 | 10 | 27  |

20000  
on/off**OSRAM DULUXSTAR® MINI BULLET P**


- Retrofit mini globe substitute to a Classic P shape lamp
- Smaller dimensions
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for energy saving substitute to a Classic P shape lamp

10000  
on/off

| Product ID Code | EAN (Single Pack) | Product Description  | t [h]  | W | V       | lm  |         |     |    | PPG |
|-----------------|-------------------|----------------------|--------|---|---------|-----|---------|-----|----|-----|
| DSMIBUP5E14     | 4008321956200     | DS MIBU P 5W/825 E14 | 10,000 | 5 | 220-240 | 210 | SES/E14 | 825 | 10 | 27  |
| DSMIBUP7E14     | 4008321956286     | DS MIBU P 7W/825 E14 | 10,000 | 7 | 220-240 | 320 | SES/E14 | 825 | 10 | 27  |
| DSMIBUP5        | 4008321956187     | DS MIBU P 5W/825 E27 | 10,000 | 5 | 220-240 | 210 | ES/E27  | 825 | 10 | 27  |
| DSMIBUP7        | 4008321956262     | DS MIBU P 7W/825 E27 | 10,000 | 7 | 220-240 | 320 | ES/E27  | 825 | 10 | 27  |

All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUXSTAR® Mini Bullet T**

- Retrofit mini globe substitute to a Classic T shape lamp
- Smaller dimensions
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for energy saving substitute to a Classic T shape lamp


| Product ID Code | EAN (Single Pack) | Product Description  | t [h]  | W | V       | lm  |  |  | PPG |
|-----------------|-------------------|----------------------|--------|---|---------|-----|--|--|-----|
| DSMIBUT7        | 4008321956774     | DS MIBU T 5W/825 E14 | 10,000 | 5 | 220-240 | 210 |  |  | 27  |
| DSMIBUT7E14     | 4008321956811     | DS MIBU T 7W/825 E14 | 10,000 | 7 | 220-240 | 320 |  |  | 27  |
| DSMIBUT5        | 4008321956750     | DS MIBU T 5W/825 E27 | 10,000 | 5 | 220-240 | 210 |  |  | 27  |
| DSMIBUT7        | 4008321956798     | DS MIBU T 7W/825 E27 | 10,000 | 7 | 220-240 | 320 |  |  | 27  |

NEW  
NEW  
NEW  
NEW

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUXSTAR® Mini Globe and Globe**


- Retrofit mini globe and globe shape energy saving compact fluorescent lamp
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- Ideal for replacing inefficient incandescent lamps

| Product ID Code   | EAN (Single Pack) | Product Description     | t [h]  | W  | V       | lm   |         |     | No. | PPG |    |
|-------------------|-------------------|-------------------------|--------|----|---------|------|---------|-----|-----|-----|----|
| <b>Mini Globe</b> |                   |                         |        |    |         |      |         |     |     |     |    |
| DST5MIGL          | 4008321205476     | DSTAR MIGL 5W/825 E27   | 10,000 | 5  | 220-240 | 250  | ES/E27  | 825 | 1   | 10  | 27 |
| DST5MIGLE14       | 4008321205490     | DSTAR MIGL 5W/825 E14   | 10,000 | 5  | 220-240 | 250  | SES/E14 | 825 | 2   | 10  | 27 |
| DST7MIGL          | 4008321205537     | DSTAR MIGL 7W/825 E27   | 10,000 | 7  | 220-240 | 360  | ES/E27  | 825 | 1   | 10  | 27 |
| DST7MIGLE14       | 4008321205551     | DSTAR MIGL 7W/825 E14   | 10,000 | 7  | 220-240 | 360  | SES/E14 | 825 | 2   | 10  | 27 |
| DST11MIGL         | 4008321205575     | DSTAR MIGL 11W/825 E27  | 10,000 | 11 | 220-240 | 630  | ES/E27  | 825 | 1   | 10  | 27 |
| DST15MIGL         | 4008321205599     | DSTAR MIGL 15W/825 E27  | 10,000 | 15 | 220-240 | 850  | ES/E27  | 825 | 1   | 10  | 27 |
| DST20MIGL         | 4008321946546     | DSTAR MIGL 20W/825 E27  | 10,000 | 20 | 220-240 | 1160 | ES/E27  | 825 | 1   | 10  | 27 |
| DST20MIGLB22      | 4008321415127     | DSTAR MIGL 20W/825 B22D | 10,000 | 20 | 220-240 | 1160 | BC/B22d | 825 | –   | 10  | 27 |
| <b>Globe</b>      |                   |                         |        |    |         |      |         |     |     |     |    |
| DST14GL           | 4008321946560     | DSTAR GL 14W/825 E27    | 10,000 | 14 | 220-240 | 870  | ES/E27  | 825 | 3   | 10  | 27 |
| DST18GL           | 4008321946577     | DSTAR GL 18W/825 E27    | 10,000 | 18 | 220-240 | 1100 | ES/E27  | 825 | 3   | 10  | 27 |



All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUXSTAR® Mini Twist**

- Retrofit twist energy saving compact fluorescent lamp
- NEW Colour 825 – Warm comfort light the first CFLi light colour with the appearance of GLS
- NEW compact T3 Mini Twist version 24% shorter than stick version
- Ideal for replacing inefficient incandescent lamps


| Product ID Code    | EAN (Single Pack) | Product Description    | t [h] | W  | V       | lm   | W           | PPG     |
|--------------------|-------------------|------------------------|-------|----|---------|------|-------------|---------|
| DMINITWIST5825E14  | 4008321334633     | DSTAR MTW 5W/825 E14   | 8,000 | 5  | 220-240 | 270  | SES/E14 825 | 1 10 27 |
| DMINITWIST5825     | 4008321334602     | DSTAR MTW 5W/825 E27   | 8,000 | 5  | 220-240 | 270  | ES/E27 825  | 2 10 27 |
| DMINITWIST5840E14  | 4008321334695     | DSTAR MTW 5W/840 E14   | 8,000 | 5  | 220-240 | 270  | SES/E14 840 | 1 10 27 |
| DMINITWIST5840     | 4008321334664     | DSTAR MTW 5W/840 E27   | 8,000 | 5  | 220-240 | 270  | ES/E27 840  | 2 10 27 |
| DMINITWIST5865*    | 4008321343925     | DSTAR MTW 5W/865 E14   | 8,000 | 5  | 220-240 | 270  | SES/E14 865 | 1 10 27 |
| DMINITWIST5865*    | 4008321941770     | DSTAR MTW 5W/865 E27   | 8,000 | 5  | 220-240 | 270  | ES/E27 865  | 2 10 27 |
| DMINITWIST8827     | 4008321334510     | DSTAR MTW 8W/825 E14   | 8,000 | 8  | 220-240 | 470  | SES/E14 825 | 3 10 27 |
| DMINITWIST8825E27  | 4008321334480     | DSTAR MTW 8W/825 E27   | 8,000 | 8  | 220-240 | 470  | ES/E27 825  | 2 10 27 |
| DMINITWIST8840E14  | 4008321334572     | DSTAR MTW 8W/840 E14   | 8,000 | 8  | 220-240 | 470  | SES/E14 840 | 3 10 27 |
| DMINITWIST8840     | 4008321334541     | DSTAR MTW 8W/840 E27   | 8,000 | 8  | 220-240 | 470  | ES/E27 840  | 2 10 27 |
| DMINITWIST8865E14* | 4008321343956     | DSTAR MTW 8W/865 E14   | 8,000 | 8  | 220-240 | 470  | SES/E14 865 | 3 10 27 |
| DMINITWIST8865*    | 4008321343864     | DSTAR MTW 8W/865 E27   | 8,000 | 8  | 220-240 | 470  | ES/E27 865  | 2 10 27 |
| DMINITWIST11825    | 4008321334398     | DSTAR MTW 11W/825 E14  | 8,000 | 11 | 220-240 | 680  | SES/E14 825 | 3 10 27 |
| DMINITWIST11825E27 | 4008321334367     | DSTAR MTW 11W/825 E27  | 8,000 | 11 | 220-240 | 680  | ES/E27 825  | 4 10 27 |
| DMINITWIST11840E14 | 4008321334459     | DSTAR MTW 11W/840 E14  | 8,000 | 11 | 220-240 | 680  | SES/E14 840 | 3 10 27 |
| DMINITWIST11840    | 4008321334428     | DSTAR MTW 11W/840 E27  | 8,000 | 11 | 220-240 | 680  | ES/E27 840  | 4 10 27 |
| DMINITWIST11865*   | 4008321343895     | DSTAR MTW 11W/865 E27  | 8,000 | 11 | 220-240 | 640  | ES/E27 865  | 4 10 27 |
| DTWIST13825        | 4008321293985     | DSTAR MTW 13W/825 E27  | 8,000 | 13 | 220-240 | 850  | ES/E27 825  | 4 10 27 |
| DTWIST13840        | 4008321294920     | DSTAR MTW 13W/840 E27  | 8,000 | 13 | 220-240 | 850  | ES/E27 840  | 4 10 27 |
| DTWIST13865*       | 4008321294005     | DSTAR MTW 13W/865 E27  | 8,000 | 13 | 220-240 | 800  | ES/E27 865  | 4 10 27 |
| DTWIST13825B22     | 4008321299154     | DSTAR MTW 13W/825 B22D | 8,000 | 13 | 220-240 | 850  | BC/B22d 825 | 4 10 27 |
| DTWIST18           | 4008321294029     | DSTAR MTW 18W/825 E27  | 8,000 | 18 | 220-240 | 1200 | ES/E27 825  | 5 10 27 |
| DTWIST18865*       | 4008321294043     | DSTAR MTW 18W/865 E27  | 8,000 | 18 | 220-240 | 1140 | ES/E27 865  | 5 10 27 |
| DTWIST18840        | 4008321294944     | DSTAR MTW 18W/840 E27  | 8,000 | 18 | 220-240 | 1200 | ES/E27 840  | 5 10 27 |
| DTWIST18827B22     | 4008321299178     | DSTAR MTW 18W/825 B22D | 8,000 | 18 | 220-240 | 1200 | BC/B22d 825 | 5 10 27 |
| DTWIST23           | 4008321294067     | DSTAR MTW 23W/825 E27  | 8,000 | 23 | 220-240 | 1500 | ES/E27 825  | 5 10 27 |
| DTWIST23840        | 4008321294968     | DSTAR MTW 23W/840 E27  | 8,000 | 23 | 220-240 | 1500 | ES/E27 840  | 5 10 27 |
| DTWIST23865*       | 4008321294081     | DSTAR MTW 23W/865 E27  | 8,000 | 23 | 220-240 | 1470 | ES/E27 865  | 5 10 27 |
| DTWIST23825        | 4008321299192     | DSTAR MTW 23W/825 B22D | 8,000 | 23 | 220-240 | 1500 | BC/B22d 825 | 5 10 27 |

\* Also available on request in colour 865 (Cool Daylight)

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Retrofit

**OSRAM DULUXSTAR® NANO TWIST**

- Nano-sized CFLi
- Substitution for standard luminaires
- Ideal for small luminaires





| Product ID Code   | EAN (Single Pack) | Product Description    | t [h] | W | V       | Im  |         | No. |   | PPG |    |
|-------------------|-------------------|------------------------|-------|---|---------|-----|---------|-----|---|-----|----|
| DSTNANOTW5        | 4008321510730     | DST NANOTW 5W/825 G9   | 8,000 | 5 | 220-240 | 270 | G9      | 825 | 2 | 10  | 27 |
| DSTNANOTW7        | 4008321510792     | DST NANOTW 7W/825 G9   | 8,000 | 7 | 220-240 | 400 | G9      | 825 | 3 | 10  | 27 |
| DSTNANOTW9        | 4008321510853     | DST NANOTW 9W/825 G9   | 8,000 | 9 | 220-240 | 480 | G9      | 825 | 6 | 10  | 27 |
| DSTNANOTW5        | 4008321956149     | DST NANOTW 5W/840 G9   | 8,000 | 5 | 220-240 | 270 | G9      | 840 | 2 | 10  | 27 |
| DSTNANOTW7        | 4008321956163     | DST NANOTW 7W/840 G9   | 8,000 | 7 | 220-240 | 400 | G9      | 840 | 3 | 10  | 27 |
| DSTNANOTW9        | 4008321956934     | DST NANOTW 9W/840 G9   | 8,000 | 9 | 220-240 | 480 | G9      | 840 | 6 | 10  | 27 |
| DSTNANOTW5E14     | 4008321510914     | DST NANOTW 5W/825 E14  | 8,000 | 5 | 220-240 | 270 | SES/E14 | 825 | 1 | 10  | 27 |
| DSTNANOTW7E14     | 4008321510976     | DST NANOTW 7W/825 E14  | 8,000 | 7 | 220-240 | 400 | SES/E14 | 825 | 3 | 10  | 27 |
| DSTNANOTW9E14     | 4008321511034     | DST NANOTW 9W/825 E14  | 8,000 | 9 | 220-240 | 480 | SES/E14 | 825 | 5 | 10  | 27 |
| DSTNANOTW5840E14  | 4008321508898     | DST NANOTW 5W/840 E14  | 8,000 | 5 | 220-240 | 270 | SES/E14 | 840 | 1 | 10  | 27 |
| DSTNANOTW7840E14  | 4008321509000     | DST NANOTW 7W/840 E14  | 8,000 | 7 | 220-240 | 400 | SES/E14 | 840 | 3 | 10  | 27 |
| DSTNANOTW9840E14  | 4008321509062     | DST NANOTW 9W/840 GU10 | 8,000 | 9 | 220-240 | 480 | SES/E14 | 840 | 5 | 10  | 27 |
| DSTNANOTW5825GU10 | 4008321548900     | DST NANOTW 5W/825 GU10 | 8,000 | 5 | 220-240 | 270 | GU10    | 825 | 7 | 10  | 27 |
| DSTNANOTW7825GU10 | 4008321549082     | DST NANOTW 7W/825 GU10 | 8,000 | 7 | 220-240 | 400 | GU10    | 825 | 7 | 10  | 27 |
| DSTNANOTW9825GU10 | 4008321549228     | DST NANOTW 9W/825 GU10 | 8,000 | 9 | 220-240 | 480 | GU10    | 825 | 7 | 10  | 27 |
| DSTNANOTW5840GU10 | 4008321548979     | DST NANOTW 5W/840 GU10 | 8,000 | 5 | 220-240 | 270 | GU10    | 840 | 7 | 10  | 27 |
| DSTNANOTW7840GU10 | 4008321549167     | DST NANOTW 7W/840 GU10 | 8,000 | 7 | 220-240 | 400 | GU10    | 840 | 7 | 10  | 27 |
| DSTNANOTW9840GU10 | 4008321549280     | DST NANOTW 9W/840 GU10 | 8,000 | 9 | 220-240 | 480 | GU10    | 840 | 7 | 10  | 27 |

All orders must be multiples of sales pack



## COMPACT FLUORESCENT LAMPS – PIN BASED



### OSRAM DULUX® T PLUS



- Triple-turn tube
- 2-pin compact fluorescent lamp
- With integral starter for CCG
- Ideal for downlights with shallow mounting depths

| Product ID Code | EAN (Single Pack) | Product Description        | t [h]  | W  | lm   |         |     | PPG   |
|-----------------|-------------------|----------------------------|--------|----|------|---------|-----|-------|
| DT13830         | 4050300446929     | DULUX T 13W/830 PLUS GX24D | 10,000 | 13 | 900  | GX24d-1 | 830 | 10 23 |
| DT13840         | 4050300446905     | DULUX T 13W/840 PLUS GX24D | 10,000 | 13 | 900  | GX24d-1 | 840 | 10 23 |
| DT18827         | 4050300333502     | DULUX T 18W/827 PLUS GX24D | 10,000 | 18 | 1200 | GX24d-2 | 827 | 10 23 |
| DT18830         | 4050300333489     | DULUX T 18W/830 PLUS GX24D | 10,000 | 18 | 1200 | GX24d-2 | 830 | 10 23 |
| DT18840         | 4050300333465     | DULUX T 18W/840 PLUS GX24D | 10,000 | 18 | 1200 | GX24d-2 | 840 | 10 23 |
| DT26827         | 4050300342085     | DULUX T 26W/827 PLUS GX24D | 10,000 | 26 | 1800 | GX24d-3 | 827 | 10 23 |
| DT26830         | 4050300342061     | DULUX T 26W/830 PLUS GX24D | 10,000 | 26 | 1800 | GX24d-3 | 830 | 10 23 |
| DT26840         | 4050300342047     | DULUX T 26W/840 PLUS GX24D | 10,000 | 26 | 1800 | GX24d-3 | 840 | 10 23 |

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® T/E PLUS**


- Triple-turn tube
- 4-pin compact fluorescent lamp
- 20,000 lifetime with warm start ECG
- For use with ECG and dimming systems
- Ideal for downlights with shallow mounting depths

| Product ID Code | EAN (Single Pack) | Product Description          | t [h]  | W  | lm   |         |     | PPG   |
|-----------------|-------------------|------------------------------|--------|----|------|---------|-----|-------|
| DTE13827        | 4050300447001     | DULUX T/E 13W/827 PLUS GX24Q | 20,000 | 13 | 900  | GX24q-1 | 827 | 10 23 |
| DTE13830        | 4050300446981     | DULUX T/E 13W/830 PLUS GX24Q | 20,000 | 13 | 900  | GX24q-1 | 830 | 10 23 |
| DTE13840        | 4050300446967     | DULUX T/E 13W/840 PLUS GX24Q | 20,000 | 13 | 900  | GX24q-1 | 840 | 10 23 |
| DTE18827        | 4050300342269     | DULUX T/E 18W/827 PLUS GX24Q | 20,000 | 18 | 1200 | GX24q-2 | 827 | 10 23 |
| DTE18830        | 4050300342245     | DULUX T/E 18W/830 PLUS GX24Q | 20,000 | 18 | 1200 | GX24q-2 | 830 | 10 23 |
| DTE18840        | 4050300342221     | DULUX T/E 18W/840 PLUS GX24Q | 20,000 | 18 | 1200 | GX24q-2 | 840 | 10 23 |
| DTE26827        | 4050300342320     | DULUX T/E 26W/827 PLUS GX24Q | 20,000 | 26 | 1800 | GX24q-3 | 827 | 10 23 |
| DTE26830        | 4050300342306     | DULUX T/E 26W/830 PLUS GX24Q | 20,000 | 26 | 1800 | GX24q-3 | 830 | 10 23 |
| DTE26840        | 4050300342283     | DULUX T/E 26W/840 PLUS GX24Q | 20,000 | 26 | 1800 | GX24q-3 | 840 | 10 23 |
| DTE32827        | 4050300348605     | DULUX T/E 32W/827 PLUS GX24Q | 20,000 | 32 | 2400 | GX24q-3 | 827 | 10 23 |
| DTE32830        | 4050300348582     | DULUX T/E 32W/830 PLUS GX24Q | 20,000 | 32 | 2400 | GX24q-3 | 830 | 10 23 |
| DTE32840        | 4050300348568     | DULUX T/E 32W/840 PLUS GX24Q | 20,000 | 32 | 2400 | GX24q-3 | 840 | 10 23 |
| DTE42827        | 4050300425665     | DULUX T/E 42W/827 PLUS GX24Q | 20,000 | 42 | 3200 | GX24q-4 | 827 | 10 23 |
| DTE42830        | 4050300425641     | DULUX T/E 42W/830 PLUS GX24Q | 20,000 | 42 | 3200 | GX24q-4 | 830 | 10 23 |
| DTE42840        | 4050300425627     | DULUX T/E 42W/840 PLUS GX24Q | 20,000 | 42 | 3200 | GX24q-4 | 840 | 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® T/E CONSTANT (IN PLUS)**

- Triple-turn tube
- 4-pin compact fluorescent lamp
- 20,000 lifetime with warm start ECG
- With amalgam technology
- For use with ECG and dimming systems
- Ideal for operation at low and high ambient temperatures


| Product ID Code | EAN (Single Pack) | Product Description              | t [h]  | W  | lm   |         |     | PPG   |
|-----------------|-------------------|----------------------------------|--------|----|------|---------|-----|-------|
| DTE26830IN      | 4050300425467     | DULUX T/E 26W/830 CONSTANT GX24Q | 20,000 | 26 | 1800 | GX24q   | 830 | 10 23 |
| DTE26840IN      | 4050300425443     | DULUX T/E 26W/840 CONSTANT GX24Q | 20,000 | 26 | 1800 | GX24q   | 840 | 10 23 |
| DTE32827IN      | 4050300425542     | DULUX T/E 32W/827 CONSTANT GX24Q | 20,000 | 32 | 2400 | GX24q-3 | 827 | 10 23 |
| DTE32830IN      | 4050300425528     | DULUX T/E 32W/830 CONSTANT GX24Q | 20,000 | 32 | 2400 | GX24q-3 | 830 | 10 23 |
| DTE32840IN      | 4050300425504     | DULUX T/E 32W/840 CONSTANT GX24Q | 20,000 | 32 | 2400 | GX24q-3 | 840 | 10 23 |
| DTE42827IN      | 4050300425603     | DULUX T/E 42W/827 CONSTANT GX24Q | 20,000 | 42 | 3200 | GX24q-4 | 827 | 10 23 |
| DTE42830IN      | 4050300425580     | DULUX T/E 42W/830 CONSTANT GX24Q | 20,000 | 42 | 3200 | GX24q-4 | 830 | 10 23 |
| DTE42840IN      | 4050300425566     | DULUX T/E 42W/840 CONSTANT GX24Q | 20,000 | 42 | 3200 | GX24q-4 | 840 | 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack




## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® T/E High Efficiency**

- High efficiency 4 pin triple-turn compact fluorescent
- Long lifetime 20,000 hours (with QUICKTRONIC®)
- 30% more efficacy than conventional DULUX® pin base lamps
- New secure fix twist and lock base (GR14q-1)
- For use with ECG and dimming systems
- Ideal for downlights with shallow mounting depths, office lighting, public buildings

| Product ID Code | EAN (Single Pack) | Product Description          | t [h]  | W  | V   | lm   |         |     | PPG   |
|-----------------|-------------------|------------------------------|--------|----|-----|------|---------|-----|-------|
| DTE11830        | 4008321359452     | DULUX T/E 11W/830 HE GR14Q-1 | 20,000 | 11 | 80  | 900  | GR14q-1 | 830 | 10 23 |
| DTE11840        | 4008321359476     | DULUX T/E 11W/840 HE GR14Q-1 | 20,000 | 11 | 80  | 900  | GR14q-1 | 840 | 10 23 |
| DTE14           | 4008321290496     | DULUX T/E 14W/830 HE GR14Q-1 | 20,000 | 14 | 100 | 1200 | GR14q-1 | 830 | 10 23 |
| DTE14840        | 4008321290519     | DULUX T/E 14W/840 HE GR14Q-1 | 20,000 | 14 | 100 | 1200 | GR14q-1 | 840 | 10 23 |
| DTE17           | 4008321290533     | DULUX T/E 17W/830 HE GR14Q-1 | 20,000 | 17 | 120 | 1500 | GR14q-1 | 830 | 10 23 |
| DTE17840        | 4008321290557     | DULUX T/E 17W/840 HE GR14Q-1 | 20,000 | 17 | 120 | 1500 | GR14q-1 | 840 | 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

**OSRAM DULUX® T/E XT for ECG**

- High efficiency 4 pin triple-turn compact fluorescent
- Extremely long lifetime 36,000 hours (with QUICKTRONIC®)
- Extremely compact for miniature luminaires and shallow mounting depth
- Ideal for luminaires that are difficult to access, or long daily operating times


| Product ID Code | EAN (Single Pack) | Product Description        | t [h]  | W  | V    | lm      |     |    | PPG |
|-----------------|-------------------|----------------------------|--------|----|------|---------|-----|----|-----|
| DTE32830XT      | 4008321511911*    | DULUX T/E 32W/830 XT GX24Q | 36,000 | 32 | 2400 | GX24q-3 | 830 | 10 | 23  |
| DTE32840XT      | 4008321511935*    | DULUX T/E 32W/840 XT GX24Q | 36,000 | 32 | 2400 | GX24q-3 | 840 | 10 | 23  |
| DTE42830XT      | 4008321511959*    | DULUX T/E 42W/830 XT GX24Q | 36,000 | 42 | 3200 | GX24q-4 | 830 | 10 | 23  |
| DTE42840XT      | 4008321511973*    | DULUX T/E 42W/840 XT GX24Q | 36,000 | 42 | 3200 | GX24q-4 | 840 | 10 | 23  |

Perfectly matched with QUICKTRONIC® electronic control gear

\*In preparation at time of print. For further information please contact OSRAM

All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® D**


- Double-turn tube
- 2-pin compact fluorescent lamp
- With integral starter for CCG
- Ideal for miniature luminaires and downlights for shallow recesses

| Product ID Code | EAN (Single Pack) | Product Description    | t [h]  | W  | lm   |        |     |    | PPG |
|-----------------|-------------------|------------------------|--------|----|------|--------|-----|----|-----|
| DD10827         | 4050300008110     | DULUX D 10W/827 G24D-1 | 10,000 | 10 | 600  | G24d-1 | 827 | 10 | 24  |
| DD10830         | 4050300025681     | DULUX D 10W/830 G24D-1 | 10,000 | 10 | 600  | G24d-1 | 830 | 10 | 24  |
| DD10835         | 4050300028835     | DULUX D 10W/835 G24D-1 | 10,000 | 10 | 600  | G24d-1 | 835 | 10 | 24  |
| DD10840         | 4050300010595     | DULUX D 10W/840 G24D-1 | 10,000 | 10 | 600  | G24d-1 | 840 | 10 | 24  |
| DD13827         | 4050300008127     | DULUX D 13W/827 G24D-1 | 10,000 | 13 | 900  | G24d-1 | 827 | 10 | 24  |
| DD13830         | 4050300025698     | DULUX D 13W/830 G24D-1 | 10,000 | 13 | 900  | G24d-1 | 830 | 10 | 24  |
| DD13835         | 4050300028859     | DULUX D 13W/835 G24D-1 | 10,000 | 13 | 900  | G24d-1 | 835 | 10 | 24  |
| DD13840         | 4050300010625     | DULUX D 13W/840 G24D-1 | 10,000 | 13 | 900  | G24d-1 | 840 | 10 | 24  |
| DD13865         | 4050300487106     | DULUX D 13W/865 G24D-1 | 10,000 | 13 | 855  | G24d-1 | 865 | 10 | 24  |
| DD18827         | 4050300011462     | DULUX D 18W/827 G24D-2 | 10,000 | 18 | 1200 | G24d-2 | 827 | 10 | 24  |
| DD18830         | 4050300025704     | DULUX D 18W/830 G24D-2 | 10,000 | 18 | 1200 | G24d-2 | 830 | 10 | 24  |
| DD18835         | 4050300028873     | DULUX D 18W/835 G24D-2 | 10,000 | 18 | 1200 | G24d-2 | 835 | 10 | 24  |
| DD18840         | 4050300012056     | DULUX D 18W/840 G24D-2 | 10,000 | 18 | 1200 | G24d-2 | 840 | 10 | 24  |
| DD18865         | 4050300487120     | DULUX D 18W/865 G24D-2 | 10,000 | 18 | 1140 | G24d-2 | 865 | 10 | 24  |
| DD26827         | 4050300011912     | DULUX D 26W/827 G24D-3 | 10,000 | 26 | 1800 | G24d-3 | 827 | 10 | 24  |
| DD26830         | 4050300025711     | DULUX D 26W/830 G24D-3 | 10,000 | 26 | 1800 | G24d-3 | 830 | 10 | 24  |
| DD26835         | 4050300028897     | DULUX D 26W/835 G24D-3 | 10,000 | 26 | 1800 | G24d-3 | 835 | 10 | 24  |
| DD26840         | 4050300012049     | DULUX D 26W/840 G24D-3 | 10,000 | 26 | 1800 | G24d-3 | 840 | 10 | 24  |
| DD26865         | 4050300486987     | DULUX D 26W/865 G24D-3 | 10,000 | 26 | 1710 | G24d-3 | 865 | 10 | 24  |

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® D ENERGY SAVER**

- 2 pin double-turn energy saving compact fluorescent
- 10% energy saving (CCG only) compared to DULUX® D
- 1:1 replacement for a standard 18w and 26w DULUX® D
- With integral starter for CCG
- Ideal for miniature luminaires and downlights for shallow recesses




| Product ID Code | EAN (Single Pack) | Product Description      | t [h]  | W  | lm   |        |     |    | PPG |
|-----------------|-------------------|--------------------------|--------|----|------|--------|-----|----|-----|
| DD16827ES       | 4008321940773     | DULUX D 16W/827ES G24D-2 | 10,000 | 16 | 1150 | G24d-2 | 827 | 10 | 24  |
| DD16830ES       | 4008321940797     | DULUX D 16W/830ES G24D-2 | 10,000 | 16 | 1150 | G24d-2 | 830 | 10 | 24  |
| DD16840ES       | 4008321940810     | DULUX D 16W/840ES G24D-2 | 10,000 | 16 | 1150 | G24d-2 | 840 | 10 | 24  |
| DD23827ES       | 4008321940759     | DULUX D 23W/827ES G24D-3 | 10,000 | 23 | 1750 | G24d-3 | 827 | 10 | 24  |
| DD23830ES       | 4008321940711     | DULUX D 23W/830ES G24D-3 | 10,000 | 23 | 1750 | G24d-3 | 830 | 10 | 24  |
| DD23840ES       | 4008321940735     | DULUX D 23W/840ES G24D-3 | 10,000 | 23 | 1750 | G24d-3 | 840 | 10 | 24  |

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® D/E**

- Double-turn tube
- 4-pin compact fluorescent lamp
- 20,000 hours lifetime with warm start ECG
- For use with ECG and dimming systems
- Ideal for dimming and battery-powered emergency lighting applications

| Product ID Code | EAN (Single Pack) | Product Description      | t [h]  | W  | lm   |        |     |    | PPG |
|-----------------|-------------------|--------------------------|--------|----|------|--------|-----|----|-----|
| DDE10827        | 4050300012124     | DULUX D/E 10W/827 G24Q-1 | 20,000 | 10 | 600  | G24q-1 | 827 | 10 | 24  |
| DDE10830        | 4050300419435     | DULUX D/E 10W/830 G24Q-1 | 20,000 | 10 | 600  | G24q-1 | 830 | 10 | 24  |
| DDE10835        | 4050300450933     | DULUX D/E 10W/835 G24Q-1 | 20,000 | 10 | 600  | G24q-1 | 835 | 10 | 24  |
| DDE10840        | 4050300017587     | DULUX D/E 10W/840 G24Q-1 | 20,000 | 10 | 600  | G24q-1 | 840 | 10 | 24  |
| DDE13827        | 4050300012131     | DULUX D/E 13W/827 G24Q-1 | 20,000 | 13 | 900  | G24q-1 | 827 | 10 | 24  |
| DDE13830        | 4050300389059     | DULUX D/E 13W/830 G24Q-1 | 20,000 | 13 | 900  | G24q-1 | 830 | 10 | 24  |
| DDE13835        | 4050300450957     | DULUX D/E 13W/835 G24Q-1 | 20,000 | 13 | 900  | G24q-1 | 835 | 10 | 24  |
| DDE13840        | 4050300017594     | DULUX D/E 13W/840 G24Q-1 | 20,000 | 13 | 900  | G24q-1 | 840 | 10 | 24  |
| DDE18827        | 4050300012148     | DULUX D/E 18W/827 G24Q-2 | 20,000 | 18 | 1200 | G24q-2 | 827 | 10 | 24  |
| DDE18830        | 4050300327211     | DULUX D/E 18W/830 G24Q-2 | 20,000 | 18 | 1200 | G24q-2 | 830 | 10 | 24  |
| DDE18835        | 4050300450971     | DULUX D/E 18W/835 G24Q-2 | 20,000 | 18 | 1200 | G24q-2 | 835 | 10 | 24  |
| DDE18840        | 4050300017617     | DULUX D/E 18W/840 G24Q-2 | 20,000 | 18 | 1200 | G24q-2 | 840 | 10 | 24  |
| DDE18865        | 4050300564944     | DULUX D/E 18W/865 G24Q-2 | 20,000 | 18 | 1200 | G24q-3 | 865 | 10 | 24  |
| DDE26827        | 4050300012230     | DULUX D/E 26W/827 G24Q-3 | 20,000 | 26 | 1800 | G24q-3 | 827 | 10 | 24  |
| DDE26830        | 4050300327235     | DULUX D/E 26W/830 G24Q-3 | 20,000 | 26 | 1800 | G24q-3 | 830 | 10 | 24  |
| DDE26835        | 4050300450995     | DULUX D/E 26W/835 G24Q-3 | 20,000 | 26 | 1800 | G24q-3 | 835 | 10 | 24  |
| DDE26840        | 4050300020303     | DULUX D/E 26W/840 G24Q-3 | 20,000 | 26 | 1800 | G24q-3 | 840 | 10 | 24  |
| DDE26865        | 4008321185877     | DULUX D/E 26W/865 G24Q-3 | 20,000 | 26 | 1800 | G24q-3 | 865 | 10 | 24  |

Perfectly matched with QUICKTRONIC® electronic control gear

NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® D/E XT for ECG**

- Double-turn tube
- 4-pin compact fluorescent lamp
- Extremely long lifetime 36,000 hours (with QUICKTRONIC®)
- Extremely compact for miniature luminaires and shallow mounting depth
- Ideal for shop lighting, hotel & restaurant lighting, office lighting and public buildings



| Product ID Code | EAN (Single Pack) | Product Description         | t [h]  | W  |        |     |    | PPG |
|-----------------|-------------------|-----------------------------|--------|----|--------|-----|----|-----|
| DDE18830XT      | 4008321507532*    | DULUX D/E 18W/830 XT G24Q-2 | 36,000 | 18 | G24q-2 | 830 | 10 | 24  |
| DDE18840XT      | 4008321507556*    | DULUX D/E 18W/840 XT G24Q-2 | 36,000 | 18 | G24q-2 | 840 | 10 | 24  |
| DDE26830XT      | 4008321508782*    | DULUX D/E 26W/830 XT G24Q-3 | 36,000 | 26 | G24q-3 | 830 | 10 | 24  |
| DDE26840XT      | 4008321508829*    | DULUX D/E 26W/840 XT G24Q-3 | 36,000 | 26 | G24q-3 | 840 | 10 | 24  |

NEW  
NEW  
NEW  
NEW

Perfectly matched with QUICKTRONIC® electronic control gear

\*In preparation at time of print. For further information please contact OSRAM

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® S**

- Single-turn tube
- 2-pin compact fluorescent lamp
- With integral starter for CCG
- Extremely compact dimensions
- Ideal for creative luminaire design and modern lighting systems

| Product ID Code | EAN (Single Pack) | Product Description | t [h]  | W  | lm  |     |     |    | PPG |
|-----------------|-------------------|---------------------|--------|----|-----|-----|-----|----|-----|
| DS5827          | 4050300006130     | DULUX S 5W/827 G23  | 10,000 | 5  | 250 | G23 | 827 | 10 | 25  |
| DS5840          | 4050300010564     | DULUX S 5W/840 G23  | 10,000 | 5  | 250 | G23 | 840 | 10 | 25  |
| DS7827          | 4050300005997     | DULUX S 7W/827 G23  | 10,000 | 7  | 400 | G23 | 827 | 10 | 25  |
| DS7830          | 4050300025735     | DULUX S 7W/830 G23  | 10,000 | 7  | 400 | G23 | 830 | 10 | 25  |
| DS7835          | 4050300451039     | DULUX S 7W/835 G23  | 10,000 | 7  | 400 | G23 | 835 | 50 | 25  |
| DS7840          | 4050300010571     | DULUX S 7W/840 G23  | 10,000 | 7  | 400 | G23 | 840 | 10 | 25  |
| DS9827          | 4050300006000     | DULUX S 9W/827 G23  | 10,000 | 9  | 600 | G23 | 827 | 10 | 25  |
| DS9830          | 4050300025742     | DULUX S 9W/830 G23  | 10,000 | 9  | 600 | G23 | 830 | 10 | 25  |
| DS9835          | 4050300451053     | DULUX S 9W/835 G23  | 10,000 | 9  | 600 | G23 | 835 | 50 | 25  |
| DS9840          | 4050300010588     | DULUX S 9W/840 G23  | 10,000 | 9  | 600 | G23 | 840 | 10 | 25  |
| DS9860          | 4050300355320     | DULUX S 9W/865 G23  | 10,000 | 9  | 570 | G23 | 865 | 10 | 25  |
| DS11827         | 4050300006017     | DULUX S 11W/827 G23 | 10,000 | 11 | 900 | G23 | 827 | 10 | 25  |
| DS11830         | 4050300025759     | DULUX S 11W/830 G23 | 10,000 | 11 | 900 | G23 | 830 | 10 | 25  |
| DS11835         | 4050300451077     | DULUX S 11W/835 G23 | 10,000 | 11 | 900 | G23 | 835 | 50 | 25  |
| DS11840         | 4050300010618     | DULUX S 11W/840 G23 | 10,000 | 11 | 900 | G23 | 840 | 10 | 25  |

NEW


NEW

NEW

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® S COLOURED**

- Single-turn tube
- 2-pin compact fluorescent lamp
- With integral starter for CCG
- Ideal for creative illumination and decoration

| Product ID Code | EAN (Single Pack) | Product Description | W | lm  | G23 | Red   | 10 | 25 |
|-----------------|-------------------|---------------------|---|-----|-----|-------|----|----|
| DS960           | 4050300015927     | DULUX S 9W/60 G23   | 9 | 400 | G23 | Red   | 10 | 25 |
| DS966           | 4050300015934     | DULUX S 9W/66 G23   | 9 | 800 | G23 | Green | 10 | 25 |
| DS967           | 4050300015941     | DULUX S 9W/67 G23   | 9 | 200 | G23 | Blue  | 10 | 25 |

**OSRAM DULUX® S/E**


- Single-turn tube
- 4-pin compact fluorescent lamp
- For use with ECG and dimming systems
- Extremely compact dimensions
- Ideal for versatile lighting operation on almost any power supply

| Product ID Code | EAN (Single Pack) | Product Description   | W  | lm  | G27 | 827 | 10 | 25 |
|-----------------|-------------------|-----------------------|----|-----|-----|-----|----|----|
| DSE7827         | 4050300017648     | DULUX S/E 7W/827 2G7  | 7  | 400 | 2G7 | 827 | 10 | 25 |
| DSE7830         | 4050300591988     | DULUX S/E 7W/830 2G7  | 7  | 400 | 2G7 | 830 | 10 | 25 |
| DSE7840         | 4050300020167     | DULUX S/E 7W/840 2G7  | 7  | 400 | 2G7 | 840 | 10 | 25 |
| DSE9827         | 4050300017655     | DULUX S/E 9W/827 2G7  | 9  | 600 | 2G7 | 827 | 10 | 25 |
| DSE9830         | 4050300589398     | DULUX S/E 9W/830 2G7  | 9  | 600 | 2G7 | 830 | 10 | 25 |
| DSE9840         | 4050300020174     | DULUX S/E 9W/840 2G7  | 9  | 600 | 2G7 | 840 | 10 | 25 |
| DSE11827        | 4050300017662     | DULUX S/E 11W/827 2G7 | 11 | 900 | 2G7 | 827 | 10 | 25 |
| DSE11830        | 4050300589374     | DULUX S/E 11W/830 2G7 | 11 | 900 | 2G7 | 830 | 10 | 25 |
| DSE11840        | 4050300020181     | DULUX S/E 11W/840 2G7 | 11 | 900 | 2G7 | 840 | 10 | 25 |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® L LUMILUX®**

- Longer single-turn tube
- 4-pin compact fluorescent lamp
- Higher wattage lamp with high luminous flux
- Long lifetime of 20,000 hours with warm start ECG
- For CCG with external starter or ECG and dimming systems
- Ideal for modular luminaires


| Product ID Code | EAN (Single Pack) | Product Description           | W  | lm   |      |     |    | PPG |
|-----------------|-------------------|-------------------------------|----|------|------|-----|----|-----|
| DL18827         | 4050300010748     | DULUX L 18W/827 2G11          | 18 | 1200 | 2G11 | 827 | 10 | 26  |
| DL18830         | 4050300010731     | DULUX L 18W/830 2G11          | 18 | 1200 | 2G11 | 830 | 10 | 26  |
| DL18835         | 4050300295893     | DULUX L 18W/835 2G11          | 18 | 1200 | 2G11 | 835 | 10 | 26  |
| DL18840         | 4050300010724     | DULUX L 18W/840 2G11          | 18 | 1200 | 2G11 | 840 | 10 | 26  |
| DL24827         | 4050300010779     | DULUX L 24W/827 2G11          | 24 | 1800 | 2G11 | 827 | 10 | 26  |
| DL24830         | 4050300010762     | DULUX L 24W/830 2G11          | 24 | 1800 | 2G11 | 830 | 10 | 26  |
| DL24835         | 4050300295916     | DULUX L 24W/835 2G11          | 24 | 1800 | 2G11 | 835 | 10 | 26  |
| DL24840         | 4050300010755     | DULUX L 24W/840 2G11          | 24 | 1800 | 2G11 | 840 | 10 | 26  |
| DL36827         | 4050300010809     | DULUX L 36W/827 2G11          | 36 | 2900 | 2G11 | 827 | 10 | 26  |
| DL36830         | 4050300010793     | DULUX L 36W/830 2G11          | 36 | 2900 | 2G11 | 830 | 10 | 26  |
| DL36835         | 4050300295930     | DULUX L 36W/835 2G11          | 36 | 2900 | 2G11 | 835 | 10 | 26  |
| DL36840         | 4050300010786     | DULUX L 36W/840 2G11          | 36 | 2900 | 2G11 | 840 | 10 | 26  |
| DL36860         | 4050300328263     | DULUX L 36W/8652G11           | 36 | 2900 | 2G11 | 865 | 10 | 26  |
| DL36880         | 4008321185891     | DULUX L 36W/880 SKYWHITE 2G11 | 36 | 2600 | 2G11 | 880 | 10 | 26  |
| DL40827         | 4050300322285     | DULUX L 40W/827 2G11          | 40 | 3500 | 2G11 | 827 | 10 | 26  |
| DL40830         | 4050300298894     | DULUX L 40W/830 2G11          | 40 | 3500 | 2G11 | 830 | 10 | 26  |
| DL40835         | 4050300295954     | DULUX L 40W/835 2G11          | 40 | 3500 | 2G11 | 835 | 10 | 26  |
| DL40840         | 4050300279909     | DULUX L 40W/840 2G11          | 40 | 3500 | 2G11 | 840 | 10 | 26  |
| DL40860         | 4050300592008     | DULUX L 40W/865 2G11          | 40 | 3500 | 2G11 | 865 | 10 | 26  |
| DL40880         | 4008321185914     | DULUX L 40W/880 SKYWHITE 2G11 | 40 | 3000 | 2G11 | 880 | 10 | 26  |
| DL55827         | 4050300315881     | DULUX L 55W/827 2G11          | 55 | 4800 | 2G11 | 827 | 10 | 26  |
| DL55830         | 4050300298917     | DULUX L 55W/830 2G11          | 55 | 4800 | 2G11 | 830 | 10 | 26  |
| DL55835         | 4050300295978     | DULUX L 55W/835 2G11          | 55 | 4800 | 2G11 | 835 | 10 | 26  |
| DL55840         | 4050300295879     | DULUX L 55W/840 2G11          | 55 | 4800 | 2G11 | 840 | 10 | 26  |
| DL55860         | 4050300553900     | DULUX L 55W/865 2G11          | 55 | 4800 | 2G11 | 865 | 10 | 26  |
| DL55880         | 4008321185938     | DULUX L 55W/880 SKYWHITE 2G11 | 55 | 4100 | 2G11 | 880 | 10 | 26  |
| DL80830         | 4050300665467     | DULUX L 80W/830 2G11          | 80 | 6000 | 2G11 | 830 | 10 | 26  |
| DL80840         | 4050300665481     | DULUX L 80W/840 2G11          | 80 | 6000 | 2G11 | 840 | 10 | 26  |
| DL80880         | 4008321185952     | DULUX L 80W/880 SKYWHITE 2G11 | 80 | 5600 | 2G11 | 880 | 10 | 26  |
| <b>Coloured</b> |                   |                               |    |      |      |     |    |     |
| DL2467          | 4050300354033     | DULUX L 24W/ BLUE 2G11        | 24 | 550  | 2G11 | 67  | 10 | 26  |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® L CONSTANT**

- Longer single-turn tube
- 4-pin compact fluorescent lamp
- >90% luminous flux between +5°C and +70°C
- Ideal for luminaires with high temperatures

| Product ID Code | EAN (Single Pack) | Product Description           | W  | lm   | Ra   | PPG       |
|-----------------|-------------------|-------------------------------|----|------|------|-----------|
| DL40840CO       | 4008321104823     | DULUX L 40W/840 CONSTANT 2G11 | 40 | 3500 | 2G11 | 840 10 26 |
| DL55840CO       | 4008321104847     | DULUX L 55W/840 CONSTANT 2G11 | 55 | 4800 | 2G11 | 840 10 26 |
| DL80840CO       | 4008321104861     | DULUX L 80W/840 CONSTANT 2G11 | 80 | 6000 | 2G11 | 840 10 26 |

Perfectly matched with QUICKTRONIC® electronic control gear

**OSRAM DULUX® L LUMILUX® DE LUXE**


- Longer single-turn tube
- 4-pin compact fluorescent lamp
- Long lifetime of 20,000 hours with warm start ECG
- Excellent colour rendering Ra>90
- For CCG with external starter or ECG and dimming systems
- Ideal for modular luminaires

| Product ID Code | EAN (Single Pack) | Product Description  | W  | lm   | Ra   | PPG       |
|-----------------|-------------------|----------------------|----|------|------|-----------|
| DL18930         | 4050300018324     | DULUX L 18W/930 2G11 | 18 | 750  | 2G11 | 930 10 26 |
| DL18940         | 4050300018560     | DULUX L 18W/940 2G11 | 18 | 750  | 2G11 | 940 10 26 |
| DL18954         | 4050300018423     | DULUX L 18W/954 2G11 | 18 | 750  | 2G11 | 954 10 26 |
| DL24930         | 4050300018386     | DULUX L 24W/930 2G11 | 24 | 1200 | 2G11 | 930 10 26 |
| DL24940         | 4050300018584     | DULUX L 24W/940 2G11 | 24 | 1200 | 2G11 | 940 10 26 |
| DL24954         | 4050300018447     | DULUX L 24W/954 2G11 | 24 | 1200 | 2G11 | 954 10 26 |
| DL36930         | 4050300018393     | DULUX L 36W/930 2G11 | 36 | 1900 | 2G11 | 930 10 26 |
| DL36940         | 4050300018607     | DULUX L 36W/940 2G11 | 36 | 1900 | 2G11 | 940 10 26 |
| DL36954         | 4050300018461     | DULUX L 36W/954 2G11 | 36 | 1900 | 2G11 | 954 10 26 |
| DL40954         | 4050300315799     | DULUX L 40W/954 2G11 | 40 | 2200 | 2G11 | 954 10 26 |
| DL55930         | 4050300370705     | DULUX L 55W/930 2G11 | 55 | 3000 | 2G11 | 930 10 26 |
| DL55940         | 4050300197999     | DULUX L 55W/940 2G11 | 55 | 3000 | 2G11 | 940 10 26 |
| DL55954         | 4050300321400     | DULUX L 55W/954 2G11 | 55 | 3000 | 2G11 | 954 10 26 |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® L SP**

- Longer single-turn tube
- 4-pin compact fluorescent lamp
- Long lifetime of 20,000 hours with warm start ECG
- For operation at low ambient temperatures
- Ideal for low temperature outdoor lighting

| Product ID Code | EAN (Single Pack) | Product Description     | W  | lm   |      |     |    | PPG |
|-----------------|-------------------|-------------------------|----|------|------|-----|----|-----|
| DL18830SP       | 4050300300276     | DULUX L 18W/830 SP 2G11 | 18 | 1200 | 2G11 | 830 | 10 | 38  |
| DL18840SP       | 4008321280497     | DULUX L 18W/840 SP 2G11 | 18 | 1200 | 2G11 | 840 | 10 | 38  |
| DL24830SP       | 4050300300238     | DULUX L 24W/830 SP 2G11 | 24 | 1800 | 2G11 | 830 | 10 | 38  |
| DL24840SP       | 4008321280510     | DULUX L 24W/840 SP 2G11 | 24 | 1800 | 2G11 | 840 | 10 | 26  |
| DL36630SP       | 4008321283757     | DULUX L 36W/830SP 2G11  | 36 | 2900 | 2G11 | 830 | 10 | 26  |
| DL36640SP       | 4008321283771     | DULUX L 36W/840SP 2G11  | 36 | 2900 | 2G11 | 840 | 10 | 26  |

Perfectly matched with QUICKTRONIC® electronic control gear

NEW  
NEW  
NEW  
NEW

**OSRAM DULUX® L HIGH EFFICIENCY**

- High Efficiency 4 pin long single turn compact fluorescent
- Long lifetime of 20,000 hours by 50% mortality
- For CCG with external starter or ECG and dimming systems
- Optimised for light fitting 600 x 600 mm
- Ideal for new short run luminaires

| Product ID Code | EAN (Single Pack) | Product Description      | W  | lm   |       |     |    | PPG |
|-----------------|-------------------|--------------------------|----|------|-------|-----|----|-----|
| DL16830HE       | 4008321507792     | DULUX L 16W/830 HE 2GX11 | 16 | 1600 | 2GX11 | 830 | 10 | 26  |
| DL16840HE       | 4008321507815     | DULUX L 16W/840 HE 2GX11 | 16 | 1600 | 2GX11 | 840 | 10 | 26  |
| DL22830HE       | 4008321507839     | DULUX L 22W/830 HE 2GX11 | 22 | 2200 | 2GX11 | 830 | 10 | 26  |
| DL22840HE       | 4008321508638     | DULUX L 22W/840 HE 2GX11 | 22 | 2200 | 2GX11 | 840 | 10 | 26  |
| DL26830HE       | 4008321508584     | DULUX L 26W/830 HE 2GX11 | 26 | 2600 | 2GX11 | 830 | 10 | 26  |
| DL26840HE       | 4008321508713     | DULUX L 26W/840 HE 2GX11 | 26 | 2600 | 2GX11 | 840 | 10 | 26  |
| DL28830HE       | 4008321296719     | DULUX L 28W/830 HE 2GX11 | 28 | 2800 | 2GX11 | 830 | 10 | 26  |
| DL28840HE       | 4008321296757     | DULUX L 28W/840 HE 2GX11 | 28 | 2800 | 2GX11 | 840 | 10 | 26  |

NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack



## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® L XT**

- Longer single-turn tube
- 4-pin compact fluorescent lamp
- Extremely long lifetime 36,000 hours (with QUICKTRONIC®)
- For direct or indirect lighting
- Ideal for industry lighting, trade and commerce, office lighting, public buildings

| Product ID Code | EAN (Single Pack) | Product Description     | t [h]  | W  | lm   |      |     | PPG   |
|-----------------|-------------------|-------------------------|--------|----|------|------|-----|-------|
| DL18830XT       | 4008321507570*    | DULUX L 18W/830 XT 2G11 | 36,000 | 18 | 1200 | 2G11 | 830 | 10 26 |
| DL18840XT       | 4008321507594*    | DULUX L 18W/840 XT 2G11 | 36,000 | 18 | 1200 | 2G11 | 840 | 10 26 |
| DL24830XT       | 4008321507617*    | DULUX L 24W/830 XT 2G11 | 36,000 | 24 | 1800 | 2G11 | 830 | 10 26 |
| DL24840XT       | 4008321507631*    | DULUX L 24W/840 XT 2G11 | 36,000 | 24 | 1800 | 2G12 | 840 | 10 26 |
| DL36830XT       | 4008321507655*    | DULUX L 36W/830 XT 2G11 | 36,000 | 36 | 2900 | 2G13 | 830 | 10 26 |
| DL36840XT       | 4008321507679*    | DULUX L 36W/840 XT 2G11 | 36,000 | 36 | 2900 | 2G14 | 840 | 10 26 |
| DL55830XT       | 4008321507693*    | DULUX L 55W/830 XT 2G11 | 36,000 | 55 | 4800 | 2G15 | 830 | 10 26 |
| DL55840XT       | 4008321507716*    | DULUX L 55W/840 XT 2G11 | 36,000 | 55 | 4800 | 2G16 | 840 | 10 26 |

Perfectly matched with QUICKTRONIC® electronic control gear

\*In preparation at time of print. For further information please contact OSRAM

All orders must be multiples of sales pack

## Compact Fluorescent Lamps – Pin Based

**OSRAM DULUX® F**

- Flat double-turn tube
- 4-pin compact fluorescent lamp
- For CCG with external starter or ECG and dimming systems
- Ideal for area lighting with modular luminaires


| Product ID Code | EAN (Single Pack) | Product Description  | W  | lm   |      |     |    | PPG |
|-----------------|-------------------|----------------------|----|------|------|-----|----|-----|
| DF18827         | 4050300333564     | DULUX F 18W/827 2G10 | 18 | 1100 | 2G10 | 827 | 10 | 23  |
| DF18830         | 4050300333540     | DULUX F 18W/830 2G10 | 18 | 1100 | 2G10 | 830 | 10 | 23  |
| DF18840         | 4050300333526     | DULUX F 18W/840 2G10 | 18 | 1100 | 2G10 | 840 | 10 | 23  |
| DF24827         | 4050300333625     | DULUX F 24W/827 2G10 | 24 | 1700 | 2G10 | 827 | 10 | 23  |
| DF24830         | 4050300333601     | DULUX F 24W/830 2G10 | 24 | 1700 | 2G10 | 830 | 10 | 23  |
| DF24840         | 4050300333588     | DULUX F 24W/840 2G10 | 24 | 1700 | 2G10 | 840 | 10 | 23  |
| DF36827         | 4050300312187     | DULUX F 36W/827 2G10 | 36 | 2800 | 2G10 | 827 | 10 | 23  |
| DF36830         | 4050300299051     | DULUX F 36W/830 2G10 | 36 | 2800 | 2G10 | 830 | 10 | 23  |
| DF36840         | 4050300299037     | DULUX F 36W/840 2G10 | 36 | 2800 | 2G10 | 840 | 10 | 23  |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack




## Compact Fluorescent Lamps – Pin Based

**OSRAM CFL SQUARE**

- Classic square shape
- Uniform distribution of light
- Ideal for bulkhead luminaires

| Product ID Code | EAN (Single Pack) | Product Description            | W  | Im   |       |     | PPG   |
|-----------------|-------------------|--------------------------------|----|------|-------|-----|-------|
| <b>2 Pin</b>    |                   |                                |    |      |       |     |       |
| CFL168272P      | 4050300816852     | CFL SQUARE 16W/827 2-PIN GR8   | 16 | 1050 | GR8   | 827 | 20 23 |
| CFL168352P      | 4050300816838     | CFL SQUARE 16W/835 2-PIN GR8   | 16 | 1050 | GR8   | 835 | 20 23 |
| CFL288272P      | 4050300816913     | CFL SQUARE 28W/827 2-PIN GR8   | 28 | 2050 | GR8   | 827 | 20 23 |
| CFL288352P      | 4050300816937     | CFL SQUARE 28W/835 2-PIN GR8   | 28 | 2050 | GR8   | 835 | 20 23 |
| <b>4 Pin</b>    |                   |                                |    |      |       |     |       |
| CFL168274P      | 4050300816890     | CFL SQUARE 16W/827 4-PIN GR10Q | 16 | 1050 | GR10q | 827 | 20 23 |
| CFL168354P      | 4050300816876     | CFL SQUARE 16W/835 4-PIN GR10Q | 16 | 1050 | GR10q | 835 | 20 23 |
| CFL288274P      | 4050300816951     | CFL SQUARE 28W/827 4-PIN GR10Q | 28 | 2050 | GR10q | 827 | 20 23 |
| CFL288354P      | 4050300816982     | CFL SQUARE 28W/835 4-PIN GR10Q | 28 | 2050 | GR10q | 835 | 20 23 |
| CFL288274P      | 4050300817002     | CFL SQUARE 38W/827 4-PIN GR10Q | 38 | 2700 | GR10q | 827 | 20 23 |
| CFL288354P      | 4050300817026     | CFL SQUARE 38W/835 4-PIN GR10Q | 38 | 2700 | GR10q | 835 | 20 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

**OSRAM ENDURA®**


- Very long life compact fluorescent lamps
- Ideal for reducing maintenance costs

| Product ID Code | EAN (Single Pack) | Product Description | W   | Im    |       |     | PPG  |
|-----------------|-------------------|---------------------|-----|-------|-------|-----|------|
| ENDURA70830     | 4050300817293     | ENDURA 70W/830      | 70  | 6500  | 2-pin | 830 | 1 38 |
| ENDURA70840     | 4050300817286     | ENDURA 70W/840      | 70  | 6500  | 2-pin | 840 | 1 38 |
| ENDURA100830    | 4050300668420     | ENDURA 100W/830     | 100 | 8000  | 2-pin | 830 | 1 38 |
| ENDURA100840UK  | 4050300668437     | ENDURA 100W/840     | 100 | 8000  | 2-pin | 840 | 1 38 |
| ENDURA150830UK  | 4050300668444     | ENDURA 150W/830     | 150 | 12000 | 2-pin | 830 | 1 38 |
| ENDURA150840UK  | 4050300668451     | ENDURA 150W/840     | 150 | 12000 | 2-pin | 840 | 1 38 |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack

## LED LAMPS



# LED Lamps

## Contents.

|                                  |    |
|----------------------------------|----|
| SubstiTUBE® ST8-SD4              | 70 |
| PARATHOM® PAR 16 20              | 71 |
| PARATHOM® PAR 16 35              | 71 |
| PARATHOM® PRO PAR 16 35 ADVANCED | 72 |
| PARATHOM® PRO PAR 16 50 ADVANCED | 72 |
| PARATHOM® R50                    | 73 |
| PARATHOM® MR16 20                | 73 |
| PARATHOM® PRO MR16 20 ADVANCED   | 74 |
| PARATHOM® PRO MR16 35 ADVANCED   | 74 |
| PARATHOM® CLASSIC A 25           | 75 |
| PARATHOM® CLASSIC A 40           | 75 |
| PARATHOM® PRO CLASSIC A          | 76 |
| PARATHOM® CLASSIC B 25           | 76 |
| PARATHOM® CLASSIC P 25           | 77 |
| PARATHOM® DECO CLASSIC A         | 78 |
| PARATHOM® DECO CLASSIC FROSTED   | 79 |
| PARATHOM® DECO CLASSIC B         | 79 |
| PARATHOM® DECO CLASSIC P         | 80 |
| PARATHOM® G95 40 Warm White      | 81 |
| PARATHOM® DECO GLOBE             | 81 |
| DECOSPOT® LED PAR 16             | 82 |
| PARATHOM® SPECIAL T26            | 82 |
| DULED®                           | 83 |



## LED Lamps



A - B

### SubstiTUBE® ST8-SD4

- Replacement for 36W T8 Fluorescent Tube
- Equipped with OSRAM OSLON LED modules
- Available in 6,500K, 4,000K and 3,000K



| Product ID Code | EAN (Single Pack) | Product Description    | W    | lm   | V/mA    |    | PPG |
|-----------------|-------------------|------------------------|------|------|---------|----|-----|
| ST8SD4830       | 4008321966049     | SubstiTUBE ST8 SD4 830 | 23.5 | 1550 | 200-240 | 10 | 38  |
| ST8SD4840       | 4008321966056     | SubstiTUBE ST8 SD4 840 | 23.5 | 1200 | 200-240 | 10 | 38  |
| ST8SD4765       | 4008321966063     | SubstiTUBE ST8 SD4 765 | 23.5 | 1200 | 200-240 | 10 | 38  |

NEW  
NEW  
NEW


All orders must be multiples of sales pack



## LED Lamps



1



2


**PARATHOM® PAR 16 20**

- Mains voltage LED reflector replacing HALOGEN 20W
- GU10 and ES bases, 35° beam angle

| Product ID Code   | EAN (Single Pack) | Product Description               | W   | cd  | V/mA    |   | No. |    | PPG |
|-------------------|-------------------|-----------------------------------|-----|-----|---------|---|-----|----|-----|
| PARAPAR1620D      | 4008321965721     | PARATHOM PAR16 20 Daylight E27    | 4.5 | 600 | 220-240 | 2 | 10  | 38 |     |
| PARAPAR1620WW     | 4008321965769     | PARATHOM PAR16 20 Warm White E27  | 4.5 | 450 | 220-240 | 2 | 10  | 38 |     |
| PARAPAR1620DGU10  | 4008321965806     | PARATHOM PAR16 20 Daylight GU10   | 4.5 | 600 | 220-240 | 1 | 10  | 38 |     |
| PARAPAR1620WWGU10 | 4008321965844     | PARATHOM PAR16 20 Warm White GU10 | 4.5 | 450 | 220-240 | 1 | 10  | 38 |     |



1



2

**PARATHOM® PAR 16 35**

- Mains voltage LED reflector replacing HALOGEN 35W
- GU10 bases, 25° and 35° beam angle


| Product ID Code | EAN (Single Pack) | Product Description                           | W   | V/mA    |   | No. |    | PPG |
|-----------------|-------------------|---|-----|---------|---|-----|----|-----|
| PAR16P4WWBL1    | 4008321979469     | PARATHOM PAR16 35 25° Warm White GU10 blister | 4.5 | 220-240 | 1 | 6   | 38 |     |
| PAR16P4DGU10    | 4008321980045     | PARATHOM PAR16 35 25° Daylight GU10 blister   | 4.5 | 220-240 | 1 | 6   | 38 |     |
| PAR16P4WW       | 4008321980069     | PARATHOM PAR16 35 25° Warm White E27 blister  | 4.5 | 220-240 | 2 | 6   | 38 |     |
| PAR16P4D        | 4008321980083     | PARATHOM PAR16 35 25° Daylight E27 blister    | 4.5 | 220-240 | 2 | 6   | 38 |     |
| PAR16P5WWGU10   | 4008321979506     | PARATHOM PAR16 35 35° Warm White GU10         | 6   | 220-240 | 1 | 10  | 38 |     |

All orders must be multiples of sales pack


## LED Lamps



1



2

**PARATHOM® PRO PAR 16 35 ADVANCED**


- Dimmable mains voltage LED reflector replacing HALOGEN 35W
- GU10 and ES bases, 35° beam angle

NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW


| Product ID Code  | EAN (Single Pack) | Product Description               | W | cd   | V/mA    |   |    | PPG |
|------------------|-------------------|-----------------------------------|---|------|---------|---|----|-----|
| PAR16PRO8WWGU10  | 4008321963963     | PAR16 35 ADVANCED Warm White GU10 | 8 | 600  | 220-240 | 1 | 10 | 38  |
| PAR16PRO8WW      | 4008321964007     | PAR16 35 ADVANCED Warm White E27  | 8 | 600  | 220-240 | 2 | 10 | 38  |
| PAR16PRO8DGGU10  | 4008321964045     | PAR16 35 ADVANCED Daylight GU10   | 8 | >600 | 220-240 | 1 | 10 | 38  |
| PAR16PRO8D       | 4008321964083     | PAR16 35 ADVANCED Daylight E27    | 8 | >600 | 220-240 | 2 | 10 | 38  |
| PAR16PRO8830GU10 | 4008321980144*    | PAR 16 35 ADVANCED Warm White D2  | 8 | -    | 220-240 | - | 10 | 38  |
| PAR16PRO8765GU10 | 4008321980168*    | PAR 16 35 ADVANCED Daylight D2    | 8 | -    | 220-240 | - | 10 | 38  |



1



2

**PARATHOM® PRO PAR 16 50 ADVANCED**

- Dimmable mains voltage LED reflector replacing HALOGEN 50W
- GU10 and ES bases, 35° beam angle


NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW

| Product ID Code   | EAN (Single Pack) | Product Description                  | W  | cd   | V/mA    |   |    | PPG |
|-------------------|-------------------|--------------------------------------|----|------|---------|---|----|-----|
| PAR16PRO10WWGU10  | 4008321964120     | PAR16 50 ADVANCED Warm White GU10    | 10 | 950  | 220-240 | 1 | 10 | 38  |
| PAR16PRO10WW      | 4008321964168     | PAR16 50 ADVANCED Warm White E27     | 10 | 950  | 220-240 | 2 | 10 | 38  |
| PAR16PRO10DGGU10  | 4008321964205     | PAR16 50 ADVANCED Daylight GU10      | 10 | >950 | 220-240 | 1 | 10 | 38  |
| PAR16PRO10D       | 4008321964243     | PAR16 50 ADVANCED Daylight E27       | 10 | >950 | 220-240 | 2 | 10 | 38  |
| PAR16PRO10830GU10 | 4008321980182*    | PAR16 50 ADVANCED Warm White D2 GU10 | 10 | -    | 220-240 | - | 10 | 38  |
| PAR16PRO10765GU10 | 4008321980205*    | PAR16 50 ADVANCED Daylight D2 GU10   | 10 | -    | 220-240 | - | 10 | 38  |

All orders must be multiples of sales pack




## LED Lamps

**PARATHOM® R50**

- Mains voltage R50 reflector shape LED retrofit lamp
- 3W replaces 25W and 6W replaces 40W incandescent
- Very low energy consumption
- Professional heat management
- 30° beam angle
- Ideal for accent lighting



| Product ID Code | EAN (Single Pack) | Product Description   | W | lm  | V/mA    |    | PPG |
|-----------------|-------------------|-----------------------|---|-----|---------|----|-----|
| PAR3R50AE14     | 4008321965400     | R50 25 Daylight E14   | 3 | 140 | 220-240 | 10 | 38  |
| PAR3R50AWWE14   | 4008321965448     | R50 25 Warm White E14 | 3 | 100 | 220-240 | 10 | 38  |
| PAR3R50AD       | 4008321965486     | R50 25 Daylight E27   | 3 | 140 | 220-240 | 10 | 38  |
| PAR3R50AWW      | 4008321965523     | R50 25 Warm White E27 | 3 | 100 | 220-240 | 10 | 38  |
| PAR6R50ADE14    | 4008321965561     | R50 40 Daylight E14   | 6 | 240 | 220-240 | 10 | 38  |
| PAR6R50AWWE14   | 4008321965608     | R50 40 Warm White E14 | 6 | 170 | 220-240 | 10 | 38  |
| PAR6R50AD       | 4008321965646     | R50 40 Daylight E27   | 6 | 240 | 220-240 | 10 | 38  |
| PAR6R50AWW      | 4008321965684     | R50 40 Warm White E27 | 6 | 170 | 220-240 | 10 | 38  |

**PARATHOM® MR16 20**

- Low voltage LED replacement to a MR16 HALOGEN 20W
- GU5.3 base with a beam angle of 36°

| Product ID Code | EAN (Single Pack) | Product Description             | W   | lm  | V/mA |   | PPG |
|-----------------|-------------------|---------------------------------|-----|-----|------|---|-----|
| PAR4MR16        | 4008321521927     | PARATHOM PRO MR16 20 Warm White | 4.5 | 450 | 12   | 6 | 38  |

All orders must be multiples of sales pack

## LED Lamps

**PARATHOM® PRO MR16 20 ADVANCED**

- Dimmable LED replacement for a MR16 HALOGEN 20W
- GU5.3 base with a beam angle of 36°
- For use on most ECG



| Product ID Code | EAN (Single Pack) | Product Description                      | W   | Im   | V/mA       |    | PPG |
|-----------------|-------------------|--|-----|------|------------|----|-----|
| PAR5MR16        | 4008321963802     | PARATHOM PRO MR16 20 ADVANCED Warm White | 5.5 | 500  | 12 AC/DC 6 | 38 |     |
| PAR5MR16D       | 4008321963840     | PARATHOM PRO MR16 20 ADVANCED Daylight   | 5.5 | >500 | 12 AC/DC 6 | 38 |     |

**PARATHOM® PRO MR16 35 ADVANCED**


- Dimmable LED replacement for a MR16 HALOGEN 35W
- GU5.3 base with a beam angle of 36°
- For use on most ECG
- D2 uses a new design with a more efficient heat sink

| Product ID Code | EAN (Single Pack) | Product Description                             | W  | Im   | V/mA        |    | PPG |
|-----------------|-------------------|---|----|------|-------------|----|-----|
| PAR10MR16       | 4008321963888     | PARATHOM PRO MR16 35 36° ADVANCED Warm White    | 10 | 950  | 12 AC/DC 10 | 38 |     |
| PAR10MR16D      | 4008321963925     | PARATHOM PRO MR16 35 36° ADVANCED Daylight      | 10 | >950 | 12 AC/DC 10 | 38 |     |
| PAR10830MR16    | 4008321980106     | PARATHOM PRO MR16 35 36° ADVANCED Warm White D2 | 10 | –    | 12 AC/DC 10 | 38 |     |
| PAR10765MR16    | 4008321980120     | PARATHOM PRO MR16 35 36° ADVANCED Cool White D2 | 10 | –    | 12 AC/DC 10 | 38 |     |

All orders must be multiples of sales pack



## LED Lamps

**PARATHOM® CLASSIC A 25**

- Mains voltage Classic GLS shape LED retrofit lamp
- Extremely longlife and low energy consumption
- Direct replacement for 25W incandescent lamps

Product  
ID CodeEAN  
(Single Pack)

Product Description

W

lm

V/mA



PPG

NEW  
NEW

PAR6ACLA25D

4008321965042

PARATHOM CLASSIC A 25 Daylight 7W E27

7

380

100-240

10

38

PAR6ACLA25WW

4008321965080

PARATHOM CLASSIC A 25 Warm White 7W E27


7

300

100-240

10

38

**PARATHOM® CLASSIC A 40**

- Mains voltage Classic GLS shape LED retrofit lamp
- Extremely longlife and low energy consumption
- Direct replacement for 40W incandescent lamps
- High luminous flux > 350 lm (Norm GLS: 345 lm)

Product  
ID CodeEAN  
(Single Pack)

Product Description

W

lm

V/mA



PPG

NEW  
NEW

PAR8CLA40

4008321952066

PARATHOM CLASSIC A 40 Warm White 8W E27

8

345

100-240

10

38

PAR8CLA40CW

4008321952141

PARATHOM CLASSIC A 40 Daylight 8W E27

8

450


100-240

10

38

All orders must be multiples of sales pack

## LED Lamps


**PARATHOM® PRO CLASSIC A**

- Mains voltage Classic GLS shape LED retrofit lamp
- Dimmable with extremely longlife and low energy consumption
- A80 is 60W replacement according to ErP and A60 is 60W equivalent according to catalogue data



| Product ID Code | EAN (Single Pack) | Product Description                         | W  | lm  | V/mA    |    | PPG |
|-----------------|-------------------|---|----|-----|---------|----|-----|
| PAR12CLA60      | 4008321965165     | PARATHOM PRO CLASSIC A 60 Warm White 8W E27 | 12 | 640 | 220-240 | 10 | 38  |
| PAR12CLA80      | 4008321960658     | PARATHOM PRO CLASSIC A 80 Warm White 8W E27 | 12 | 806 | 220-240 | 10 | 38  |

NEW  
NEW

**PARATHOM® CLASSIC B 25**

- Mains voltage classic candle shape LED retrofit lamp
- Extremely longlife and low energy consumption
- Direct replacement for 25W incandescent lamps
- Very long lifetime of 25,000 hours


| Product ID Code | EAN (Single Pack) | Product Description                     | W | lm  | V/mA    |    | PPG |
|-----------------|-------------------|---|---|-----|---------|----|-----|
| PAR4CLB25       | 4008321952202     | PARATHOM CLASSIC B 25 Warm White 4W E27 | 4 | 170 | 100-240 | 10 | 38  |

NEW

All orders must be multiples of sales pack



## LED Lamps



1



2

**PARATHOM® CLASSIC P 25**


- Mains voltage golf ball shape LED retrofit lamp
- Extremely longlife and low energy consumption
- Direct replacement for 25W incandescent lamps
- Very long lifetime of 25,000 hours



| Product ID Code | EAN (Single Pack) | Product Description                  | W  | lm  | V/mA    | 1 | 10 | 38 | PPG |
|-----------------|-------------------|--------------------------------------|----|-----|---------|---|----|----|-----|
| PAR4DCLP25      | 4008321965202     | PARATHOM CLASSIC P 25 Daylight E27   | ~4 | 230 | 100-240 | 1 | 10 | 38 |     |
| PAR4CLP25WW     | 4008321965240     | PARATHOM CLASSIC P 25 Warm White E27 | ~4 | 200 | 100-240 | 1 | 10 | 38 |     |
| PAR4DCLP25E14   | 4008321965288     | PARATHOM CLASSIC P 25 Daylight E14   | ~4 | 230 | 100-240 | 2 | 10 | 38 |     |
| PAR4CLP25E14    | 4008321965325     | PARATHOM CLASSIC P 25 Warm White E14 | ~4 | 200 | 100-240 | 2 | 10 | 38 |     |

All orders must be multiples of sales pack

## LED Lamps

**PARATHOM® DECO CLASSIC A**

- Mains voltage Classic GLS shape LED retrofit lamp
- Colour versions produce same light impression as a coloured 25W incandescent
- White versions produce same light impression as a 15W or 10W incandescent
- Extremely longlife and low energy consumption
- Very long lifetime of 25,000 hours
- Ideal for decorative white or coloured lighting both indoors and outdoors



| Product ID Code     | EAN (Single Pack) | Product Description                         | W   | V/mA |    | PPG |
|---------------------|-------------------|---|-----|------|----|-----|
| <b>ES/E27 base</b>  |                   |   |     |      |    |     |
| 80059               | 4008321929273     | 80059 PARATHOM CL A Cool White 2.3W E27     | 2.3 | 240  | 10 | 38  |
| 80061               | 4008321925329     | 80061 PARATHOM CL A Warm White 2.3W E27     | 2.3 | 240  | 10 | 38  |
| 80060               | 4008321918253     | 80060 PARATHOM CL A Colour Change 0.5W E27  | 0.5 | 240  | 10 | 38  |
| 80062               | 4008321918260     | 80062 PARATHOM CL A Blue 1.2W E27           | 1.2 | 240  | 10 | 38  |
| 80063               | 4008321918277     | 80063 PARATHOM CL A Green 1.2W E27          | 1.2 | 240  | 10 | 38  |
| 80064               | 4008321918284     | 80064 PARATHOM CL A Red 1W E27              | 1   | 240  | 10 | 38  |
| 80065               | 4008321918291     | 80065 PARATHOM CL A Yellow 1W E27           | 1   | 240  | 10 | 38  |
| <b>BC/B22d base</b> |                   |   |     |      |    |     |
| 85000               | 4008321935632     | 85000 PARATHOM CL A Cool White 2.3W B22d    | 2.3 | 240  | 10 | 38  |
| 85001               | 4008321935656     | 85001 PARATHOM CL A Warm White 2.3W B22d    | 2.3 | 240  | 10 | 38  |
| 85002               | 4008321935496     | 85002 PARATHOM CL A Colour Change 0.5W B22d | 0.5 | 240  | 10 | 38  |
| 85003               | 4008321935526     | 85003 PARATHOM CL A Blue 1.2W B22d          | 1.2 | 240  | 10 | 38  |
| 85004               | 4008321935670     | 85004 PARATHOM CL A Green 1.2W B22d         | 1.2 | 240  | 10 | 38  |
| 85005               | 4008321935694     | 85005 PARATHOM CL A Red 1W B22d             | 1   | 240  | 10 | 38  |
| 85006               | 4008321935717     | 85006 PARATHOM CL A Yellow 1W B22d          | 1   | 240  | 10 | 38  |


NEW




All orders must be multiples of sales pack



## LED Lamps



1



2




3

**PARATHOM® DECO CLASSIC FROSTED**

- Mains voltage LED retrofit lamp with a frosted bulb for a homogenous light impression
- Available in classic, candle and globe shapes
- Extremely low energy consumption
- Ideal for decorative white lighting both indoors and outdoors



| Product ID Code     | EAN (Single Pack) | Product Description                   | W | lm | V/mA | Light No. | PPG   |
|---------------------|-------------------|---------------------------------------|---|----|------|-----------|-------|
| <b>ES/E27 base</b>  |                   |                                       |   |    |      |           |       |
| PAR2CLAFR           | 4008321951823     | PARATHOM DECO CL A FROSTED Warm White | 1 | 50 | 240  | 1         | 10 38 |
| PAR2DECOCLPFR       | 4008321951861     | PARATHOM DECO CL P FROSTED Warm White | 1 | 50 | 240  | 2         | 10 38 |
| <b>SES/E14 base</b> |                   |                                       |   |    |      |           |       |
| PAR2DECOCLBFR       | 4008321951847     | PARATHOM DECO CL B FROSTED Warm White | 1 | 50 | 240  | 3         | 10 38 |

**PARATHOM® DECO CLASSIC B**


- Mains voltage candle shape LED retrofit lamp
- Colour versions produce same light impression as a coloured 25W incandescent
- White versions produce same light impression as a 15W or 10W incandescent
- Extremely longlife and low energy consumption
- Very long lifetime of 25,000 hours
- Ideal for decorative white or coloured lighting both indoors and outdoors



| Product ID Code | EAN (Single Pack) | Product Description                        | W   | V/mA | PPG   |
|-----------------|-------------------|--|-----|------|-------|
| 80094           | 4008321929310     | 80094 PARATHOM CL B Cool White 1.6W E14    | 1.6 | 240  | 10 38 |
| 80096           | 4008321925404     | 80096 PARATHOM CL B Warm White 1.6W E14    | 1.6 | 240  | 10 38 |
| 80095           | 4008321922625     | 80095 PARATHOM CL B Colour Change 0.5W E14 | 0.5 | 240  | 10 38 |
| 80097           | 4008321922649     | 80097 PARATHOM CL B Blue 1.2W E14          | 1.2 | 240  | 10 38 |
| 80098           | 4008321922663     | 80098 PARATHOM CL B Green 1.2W E14         | 1.2 | 240  | 10 38 |
| 80099           | 4008321922687     | 80099 PARATHOM CL B Red 1W E14             | 1   | 240  | 10 38 |
| 80100           | 4008321922700     | 80100 PARATHOM CL B Yellow 1W E14          | 1   | 240  | 10 38 |

All orders must be multiples of sales pack

## LED Lamps

**PARATHOM® DECO CLASSIC P**

- Mains voltage 45mm round shape LED retrofit lamp
- Colour versions produce same light impression as a coloured 25W incandescent
- White versions produce same light impression as a 15W or 10W incandescent
- Extremely longlife and low energy consumption
- Very long lifetime of 25,000 hours
- Ideal for decorative white or coloured lighting both indoors and outdoors



| Product ID Code     | EAN (Single Pack) | Product Description                        | W   | V/mA |    | PPG |
|---------------------|-------------------|--|-----|------|----|-----|
| <b>ES/E27 base</b>  |                   |  |     |      |    |     |
| 80087               | 4008321929297     | 80087 PARATHOM CL P Cool White 1.6W E27    | 1.6 | 240  | 10 | 38  |
| 80089               | 4008321925367     | 80089 PARATHOM CL P Warm White 1.6W E27    | 1.6 | 240  | 10 | 38  |
| 80088               | 4008321922427     | 80088 PARATHOM CL P Colour Change 0.5W E27 | 0.5 | 240  | 10 | 38  |
| 80090               | 4008321922441     | 80090 PARATHOM CL P Blue 1.2W E27          | 1.2 | 240  | 10 | 38  |
| 80091               | 4008321922465     | 80091 PARATHOM CL P Green 1.2W E27         | 1.2 | 240  | 10 | 38  |
| 80092               | 4008321922489     | 80092 PARATHOM CL P Red 1W E27             | 1   | 240  | 10 | 38  |
| 80093               | 4008321922502     | 80093 PARATHOM CL P Yellow 1W E27          | 1   | 240  | 10 | 38  |
| <b>SES/E14 base</b> |                   |  |     |      |    |     |
| PAR1CLP15           | 4008321962492     | PARATHOM CL P Warm White 2W E14            | 2   | 240  | 10 | 38  |


NEW

NEW

All orders must be multiples of sales pack




## LED Lamps

**PARATHOM® G95 40 Warm White**

- Mains voltage G95 (95mm globe) shape LED retrofit lamp
- Same light output as a 40W incandescent

| Product ID Code | EAN (Single Pack) | Product Description        | W    | V/mA    |    | PPG |
|-----------------|-------------------|----------------------------|------|---------|----|-----|
| PAR10G9540      | 4008321965387     | PARATHOM G95 40 Warm White | 10.5 | 100-240 | 10 | 38  |

**PARATHOM® DECO GLOBE**


- Mains voltage G95 (95mm globe) shape LED retrofit lamp
- Colour versions produce same light impression as a coloured 25W incandescent
- White versions produce same light impression as a 15W or 10W incandescent
- Extremely longlife and low energy consumption
- Very long lifetime of 25,000 hours
- Ideal for decorative white or coloured lighting both indoors and outdoors

| Product ID Code | EAN (Single Pack) | Product Description                     | W   | lm  | V/mA |    | PPG |
|-----------------|-------------------|---|-----|-----|------|----|-----|
| 80845           | 4008321929334     | 80845 PARATHOM G95 Cool White 3W E27    | 3   | 165 | 240  | 10 | 38  |
| 80846           | 4008321929358     | 80846 PARATHOM G95 Warm White 3W E27    | 3   | 165 | 240  | 10 | 38  |
| 80340           | 4008321925442     | 80340 PARATHOM G95 Colour Change 1W E27 | 1   | —   | 240  | 10 | 38  |
| 80341           | 4008321925466     | 80341 PARATHOM G95 Blue 1.8W E27        | 1.8 | 4   | 240  | 10 | 38  |
| 80342           | 4008321925480     | 80342 PARATHOM G95 Green 1.8W E27       | 1.8 | 16  | 240  | 10 | 38  |
| 80343           | 4008321925503     | 80343 PARATHOM G95 Red 1.4W E27         | 1.4 | 16  | 240  | 10 | 38  |
| 80344           | 4008321925527     | 80345 PARATHOM G95 Yellow 1.4W E27      | 1.4 | 10  | 240  | 10 | 38  |

\* B22d/BC versions available on request. For further information contact OSRAM

All orders must be multiples of sales pack


## LED Lamps

**DECOSPOT® LED PAR 16**

- Economical mains voltage retrofit LED lamp in PAR 16 shape
- Available in 4 single colours and colour changing
- Low energy consumption
- Fits into standard fittings with SES/GU10 base
- Ideal for efficient coloured spot lighting



| Product ID Code     | EAN (Single Pack) | Product Description                            | W   | cd     | V/mA |  | No. |   | PPG |
|---------------------|-------------------|--|-----|--------|------|--|-----|---|-----|
| <b>SES/E14 Base</b> |                   |  |     |        |      |  |     |   |     |
| 80001               | 4008321905550     | DECOSPOT LED PAR 16 Colour Change E14 blister  | 0.6 | 8.3-35 | 240  |  | 1   | 6 | 38  |
| 80002               | 4008321905635     | DECOSPOT LED PAR 16 White E14 blister          | 0.8 | 180    | 240  |  | 1   | 6 | 38  |
| 80003               | 4008321905529     | DECOSPOT LED PAR 16 Red E14 blister            | 0.7 | 65     | 240  |  | 1   | 6 | 38  |
| 80004               | 4008321905536     | DECOSPOT LED PAR 16 Green E14 blister          | 0.8 | 325    | 240  |  | 1   | 6 | 38  |
| 80005               | 4008321905543     | DECOSPOT LED PAR 16 Blue E14 blister           | 0.8 | 85     | 240  |  | 1   | 6 | 38  |
| <b>GU10 base</b>    |                   |  |     |        |      |  |     |   |     |
| 80011               | 4008321905598     | DECOSPOT LED PAR 16 Colour Change GU10 blister | 0.6 | 8.3-35 | 240  |  | 2   | 6 | 38  |
| 80012               | 4008321905642     | DECOSPOT LED PAR 16 White GU10 blister         | 0.8 | 180    | 240  |  | 2   | 6 | 38  |
| 80013               | 4008321905567     | DECOSPOT LED PAR 16 Red GU10 blister           | 0.7 | 65     | 240  |  | 2   | 6 | 38  |
| 80014               | 4008321905574     | DECOSPOT LED PAR 16 Green GU10 blister         | 0.8 | 325    | 240  |  | 2   | 6 | 38  |
| 80015               | 4008321905581     | DECOSPOT LED PAR 16 Blue GU10 blister          | 0.8 | 85     | 240  |  | 2   | 6 | 38  |


**PARATHOM® SPECIAL T26**

- Direct replacement for 15W T26 incandescent lamp
- Extremely low energy consumption (<1W)
- Ideal for fridges/freezers/sewing machines

| Product ID Code | EAN (Single Pack) | Product Description                      | W    | lm | V/mA    |    | PPG |
|-----------------|-------------------|--|------|----|---------|----|-----|
| <b>SES/E14</b>  |                   |  |      |    |         |    |     |
| PARAT26         | 4008321951489     | PARATHOM SPECIAL T26 Daylight            | 1    | –  | 240     | 10 | 38  |
| PAR15AT26       | 4008321965004     | PARATHOM SPECIAL CLASSIC T26 15 Daylight | 1.5  | 65 | 220-240 | 10 | 38  |
| PAR10AT26       | 4008321964960     | PARATHOM SPECIAL CLASSIC T26 10 Daylight | ~0.7 | 35 | 220-240 | 10 | 38  |

NEW  
NEW  
NEW

All orders must be multiples of sales pack







## LED Lamps



1



2

**DULED®**

- 2 in 1 energy saving compact fluorescent and LED lamp
- Easy switch between compact fluorescent and LED mode
- Long average life of 6,000 hours
- Available in stick or twist shape
- Ideal for general lighting and as a night light in LED mode



| Product ID Code    | EAN (Single Pack) | Product Description     | W  | lm   | V/mA | No. | PPG |    |
|--------------------|-------------------|-------------------------|----|------|------|-----|-----|----|
| <b>ES/E27 base</b> |                   |                         |    |      |      |     |     |    |
| 80300              | 4008321202314     | DULED 8W/827 E27 Stick  | 8  | 400  | 240  | 1   | 10  | 38 |
| 80302              | 4008321222350     | DULED 12W/827 E27 Stick | 12 | 620  | 240  | 1   | 10  | 38 |
| 80305              | 4008321929372     | DULED 15W/827 E27 Twist | 15 | 830  | 240  | 2   | 10  | 38 |
| 80306              | 4008321929396     | DULED 21W/827 E27 Twist | 21 | 1230 | 240  | 2   | 10  | 38 |

All orders must be multiples of sales pack

## FLUORESCENT TUBES




# Fluorescent Tubes

## Contents.

|  |     |
|--|-----|
| LUMILUX® T5 HE HIGH EFFICIENCY               | 86  |
| LUMILUX® T5 HO HIGH OUTPUT                   | 90  |
| LUMILUX® T5 HO ES HIGH OUTPUT ENERGY SAVER   | 92  |
| LUMILUX® T5 HO XT                            | 94  |
| LUMILUX® T5 HO CONSTANT                      | 95  |
| LUMILUX® DE LUXE T5 HO HIGH OUTPUT           | 96  |
| LUMILUX® T5 DE LUXE                          | 96  |
| LUMILUX® T5 SEAMLESS                         | 97  |
| LUMILUX® T5 SHORT                            | 98  |
| BASIC T5                                     | 98  |
| LUMILUX® T5 OPTIMISED FOR EMERGENCY LIGHTING | 99  |
| T5 BASIC OPTIMISED FOR EMERGENCY LIGHTING    | 99  |
| T5 HE HIGH EFFICIENCY COLOURED               | 100 |
| T5 HO HIGH OUTPUT COLOURED                   | 101 |
| LUMILUX® SPLIT control T5                    | 102 |
| LUMILUX® CHIP control® T5                    | 102 |
| LUMILUX® T5 FC® FLUORESCENT CIRCLINE         | 103 |
| T5 NATURA®                                   | 103 |
| LUMILUX® T8                                  | 104 |
| LUMILUX® T8 ENERGY SAVER                     | 106 |
| LUMILUX® XT T8                               | 107 |
| LUMILUX® XXT T8                              | 108 |
| LUMILUX® DE LUXE T8                          | 109 |
| COLOR proof T8                               | 110 |
| BIOFLUX® T8                                  | 110 |
| FLUORA® T8                                   | 111 |
| Coloured T8                                  | 111 |
| NATURA® T8 and NATURA® SPLIT Control T8      | 112 |
| LUMILUX® SPLIT Control T8                    | 113 |
| LUMILUX® COLOR Control T8                    | 113 |
| LUMILUX® CHIP Control T8                     | 114 |
| U-SHAPED                                     | 114 |
| LUMILUX® CIRCULAR                            | 115 |
| T2 FM® FLUORESCENT MINIATURE                 | 116 |
| T12 FOR EXPLOSION PROOF LUMINAIRES SA TYPE   | 117 |
| T12 FOR EXPLOSION PROOF LUMINAIRES XL TYPE   | 117 |
| FLUORESCENT STARTERS                         | 118 |
| DEOS® FLUORESCENT STARTERS                   | 118 |
| Starter Application Guide                    | 119 |


## Fluorescent Tubes



1)

**LUMILUX® T5 HE HIGH EFFICIENCY without cardboard sleeve**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- As much light as a T8 lamp but up to 20% lower wattage
- 20,000 hours lifetime/16,000 hours service life with prestart ECG
- Environmentally friendly fluorescent lamp with a low mercury content
- Ideal for professional office lighting



| Product ID Code         | EAN (Single Pack) | Product Description  | W  | Color |    | I [mm] |    | PPG |
|-------------------------|-------------------|----------------------|----|-------|----|--------|----|-----|
| FH148271VP <sup>2</sup> | 4050300645933     | LUMILUX T5 HE 14/827 | 14 | 827   | G5 | 549mm  | 40 | 23  |
| FH148301VP <sup>2</sup> | 4050300464824     | LUMILUX T5 HE 14/830 | 14 | 830   | G5 | 549mm  | 40 | 23  |
| FH148351VP <sup>2</sup> | 4050300776514     | LUMILUX T5 HE 14/835 | 14 | 835   | G5 | 549mm  | 40 | 23  |
| FH148401VP <sup>2</sup> | 4050300464688     | LUMILUX T5 HE 14/840 | 14 | 840   | G5 | 549mm  | 40 | 23  |
| FH148651VP <sup>2</sup> | 4050300464848     | LUMILUX T5 HE 14/865 | 14 | 865   | G5 | 549mm  | 40 | 23  |
| FH14880 <sup>2</sup>    | 4008321225009     | LUMILUX T5 HE 14/860 | 14 | 880   | G5 | 549mm  | 40 | 23  |
| FH218271VP <sup>2</sup> | 4050300645971     | LUMILUX T5 HE 21/827 | 21 | 827   | G5 | 849mm  | 40 | 23  |
| FH218301VP <sup>2</sup> | 4050300464800     | LUMILUX T5 HE 21/830 | 21 | 830   | G5 | 849mm  | 40 | 23  |
| FH218351VP <sup>2</sup> | 4050300776538     | LUMILUX T5 HE 21/835 | 21 | 835   | G5 | 849mm  | 40 | 23  |
| FH218401VP <sup>2</sup> | 4050300464701     | LUMILUX T5 HE 21/840 | 21 | 840   | G5 | 849mm  | 40 | 23  |
| FH218651VP <sup>2</sup> | 4050300464626     | LUMILUX T5 HE 21/865 | 21 | 865   | G5 | 849mm  | 40 | 23  |
| FH21880 <sup>2</sup>    | 4008321224989     | LUMILUX T5 HE 21/880 | 21 | 880   | G5 | 849mm  | 40 | 23  |
| FH288271VP <sup>2</sup> | 4050300646015     | LUMILUX T5 HE 28/827 | 28 | 827   | G5 | 1149mm | 40 | 23  |
| FH288301VP <sup>2</sup> | 4050300464787     | LUMILUX T5 HE 28/830 | 28 | 830   | G5 | 1149mm | 40 | 23  |
| FH288351VP <sup>2</sup> | 4050300776552     | LUMILUX T5 HE 28/835 | 28 | 835   | G5 | 1149mm | 40 | 23  |
| FH288401VP <sup>2</sup> | 4050300464725     | LUMILUX T5 HE 28/840 | 28 | 840   | G5 | 1149mm | 40 | 23  |
| FH288651VP <sup>2</sup> | 4050300464640     | LUMILUX T5 HE 28/865 | 28 | 865   | G5 | 1149mm | 40 | 23  |
| FH28880 <sup>2</sup>    | 4008321153517     | LUMILUX T5 HE 28/880 | 28 | 880   | G5 | 1149mm | 40 | 23  |
| FH358271VP <sup>2</sup> | 4050300646053     | LUMILUX T5 HE 35/827 | 35 | 827   | G5 | 1449mm | 40 | 23  |
| FH358301VP <sup>2</sup> | 4050300464763     | LUMILUX T5 HE 35/830 | 35 | 830   | G5 | 1449mm | 40 | 23  |
| FH358401VP <sup>2</sup> | 4050300464749     | LUMILUX T5 HE 35/840 | 35 | 840   | G5 | 1449mm | 40 | 23  |
| FH358651VP <sup>2</sup> | 4050300464664     | LUMILUX T5 HE 35/865 | 35 | 865   | G5 | 1449mm | 40 | 23  |
| FH35880 <sup>2</sup>    | 4008321153531     | LUMILUX T5 HE 38/880 | 35 | 880   | G5 | 1449mm | 40 | 23  |


Perfectly matched with QUICKTRONIC® electronic control gear

- 1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)
- 2) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C

All orders must be multiples of sales pack



## Fluorescent Tubes

**LUMILUX® T5 HE HIGH EFFICIENCY with cardboard sleeve**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- As much light as a T8 lamp but up to 20% lower wattage
- 20,000 hours life time / 16,000 hours service life with prestart ECG
- Environmentally friendly fluorescent lamp with a low mercury content
- Ideal for professional office lighting

| Product ID Code       | EAN (Single Pack) | Product Description          | W  | Color | I [mm] | PPG          |
|-----------------------|-------------------|------------------------------|----|-------|--------|--------------|
| FH14827 <sup>2)</sup> | 4050300645919     | LUMILUX T5 HE 14/827 sleeved | 14 | 827   | G5     | 549mm 20 23  |
| FH14830 <sup>2)</sup> | 4050300591520     | LUMILUX T5 HE 14/830 sleeved | 14 | 830   | G5     | 549mm 20 23  |
| FH14835 <sup>2)</sup> | 4050300771991     | LUMILUX T5 HE 14/835 sleeved | 14 | 835   | G5     | 549mm 20 23  |
| FH14840 <sup>2)</sup> | 4050300591384     | LUMILUX T5 HE 14/840 sleeved | 14 | 840   | G5     | 549mm 20 23  |
| FH14865 <sup>2)</sup> | 4050300591544     | LUMILUX T5 HE 14/865 sleeved | 14 | 865   | G5     | 549mm 20 23  |
| FH21827 <sup>2)</sup> | 4050300645957     | LUMILUX T5 HE 21/827 sleeved | 21 | 827   | G5     | 849mm 20 23  |
| FH21830 <sup>2)</sup> | 4050300591506     | LUMILUX T5 HE 21/830 sleeved | 21 | 830   | G5     | 849mm 20 23  |
| FH21835 <sup>2)</sup> | 4050300776149     | LUMILUX T5 HE 21/835 sleeved | 21 | 835   | G5     | 849mm 20 23  |
| FH21840 <sup>2)</sup> | 4050300591407     | LUMILUX T5 HE 21/840 sleeved | 21 | 840   | G5     | 849mm 20 23  |
| FH21865 <sup>2)</sup> | 4050300591322     | LUMILUX T5 HE 21/865 sleeved | 21 | 865   | G5     | 849mm 20 23  |
| FH28827 <sup>2)</sup> | 4050300645995     | LUMILUX T5 HE 28/827 sleeved | 28 | 827   | G5     | 1149mm 20 23 |
| FH28830 <sup>2)</sup> | 4050300591483     | LUMILUX T5 HE 28/830 sleeved | 28 | 830   | G5     | 1149mm 20 23 |
| FH28835 <sup>2)</sup> | 4050300776392     | LUMILUX T5 HE 28/835 sleeved | 28 | 835   | G5     | 1149mm 20 23 |
| FH28840 <sup>2)</sup> | 4050300591421     | LUMILUX T5 HE 28/840 sleeved | 28 | 840   | G5     | 1149mm 20 23 |
| FH28865 <sup>2)</sup> | 4050300591346     | LUMILUX T5 HE 28/865 sleeved | 28 | 865   | G5     | 1149mm 20 23 |
| FH35827 <sup>2)</sup> | 4050300646039     | LUMILUX T5 HE 35/827 sleeved | 35 | 827   | G5     | 1449mm 20 23 |
| FH35830 <sup>2)</sup> | 4050300591469     | LUMILUX T5 HE 35/830 sleeved | 35 | 830   | G5     | 1449mm 20 23 |
| FH35835 <sup>2)</sup> | 4050300776415     | LUMILUX T5 HE 35/835 sleeved | 35 | 835   | G5     | 1449mm 20 23 |
| FH35840 <sup>2)</sup> | 4050300591445     | LUMILUX T5 HE 35/840 sleeved | 35 | 840   | G5     | 1449mm 20 23 |
| FH35865 <sup>2)</sup> | 4050300591360     | LUMILUX T5 HE 35/865 sleeved | 35 | 865   | G5     | 1449mm 20 23 |


Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)


2) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C

All orders must be multiples of sales pack

## Fluorescent Tubes


**LUMILUX® T5 HE ES HIGH EFFICIENCY ENERGY SAVER without cardboard sleeve**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Energy savings of up to 10%
- Up to 20,000 hours average lifetime
- Environmentally friendly fluorescent lamp with a low mercury content
- Ideal for indoor lighting systems e.g. for offices and shopping centres and general illumination



| Product ID Code       | EAN (Single Pack) | Product Description     | W  | COLOR | I [mm]       | PPG |
|-----------------------|-------------------|-------------------------|----|-------|--------------|-----|
| HE25827 <sup>1)</sup> | 4008321516909*    | LUMILUX T5 HE ES 25/827 | 25 | 827   | G5 1149mm 40 | 23  |
| HE25830 <sup>1)</sup> | 4008321516923*    | LUMILUX T5 HE ES 25/830 | 25 | 830   | G5 1149mm 40 | 23  |
| HE25840 <sup>1)</sup> | 4008321516947*    | LUMILUX T5 HE ES 25/840 | 25 | 840   | G5 1149mm 40 | 23  |
| HE25865 <sup>1)</sup> | 4008321516961*    | LUMILUX T5 HE ES 25/865 | 25 | 865   | G5 1149mm 40 | 23  |
| HE32827 <sup>1)</sup> | 4008321517067*    | LUMILUX T5 HE ES 32/827 | 32 | 827   | G5 1449mm 40 | 23  |
| HE32830 <sup>1)</sup> | 4008321517111*    | LUMILUX T5 HE ES 32/830 | 32 | 830   | G5 1449mm 40 | 23  |
| HE32840 <sup>1)</sup> | 4008321517166*    | LUMILUX T5 HE ES 32/840 | 32 | 840   | G5 1449mm 40 | 23  |
| HE32865 <sup>1)</sup> | 4008321517210*    | LUMILUX T5 HE ES 32/865 | 32 | 865   | G5 1449mm 40 | 23  |

Perfectly matched with QUICKTRONIC® electronic control gear

1) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C

\* In preparation at time of print. For further information please contact OSRAM

NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW

All orders must be multiples of sales pack



## Fluorescent Tubes


**LUMILUX® T5 HE ES HIGH EFFICIENCY ENERGY SAVER with  
cardboard sleeve**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- 10% energy saving compared to standard T5 HE fluorescent tubes
- 20,000 hours lifetime / 16,000 hours service life with prestart ECG
- Ideal for energy saving office lighting

| Product ID Code       | EAN (Single Pack) | Product Description           | W  | Color | I [mm]    | PPG   |
|-----------------------|-------------------|-------------------------------|----|-------|-----------|-------|
| HE25827 <sup>1)</sup> | 4008321957887     | LUMILUX HE 25W/827 ES sleeved | 25 | 827   | G5 1149mm | 20 23 |
| HE25830 <sup>1)</sup> | 4008321957894     | LUMILUX HE 25W/830 ES sleeved | 25 | 830   | G5 1149mm | 20 23 |
| HE25840 <sup>1)</sup> | 4008321957900     | LUMILUX HE 25W/840 ES sleeved | 25 | 840   | G5 1149mm | 20 23 |
| HE25865 <sup>1)</sup> | 4008321957917     | LUMILUX HE 25W/865 ES sleeved | 25 | 865   | G5 1149mm | 20 23 |
| HE32827 <sup>1)</sup> | 4008321957924     | LUMILUX HE 32W/827 ES sleeved | 32 | 827   | G5 1449mm | 20 23 |
| HE32830 <sup>1)</sup> | 4008321957931     | LUMILUX HE 32W/830 ES sleeved | 32 | 830   | G5 1449mm | 20 23 |
| HE32840 <sup>1)</sup> | 4008321957948     | LUMILUX HE 32W/840 ES sleeved | 32 | 840   | G5 1449mm | 20 23 |
| HE32865 <sup>1)</sup> | 4008321957955     | LUMILUX HE 32W/865 ES sleeved | 32 | 865   | G5 1449mm | 20 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C



All orders must be multiples of sales pack


## Fluorescent Tubes



1)

**LUMILUX® T5 HO HIGH OUTPUT without cardboard sleeve**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Up to 50% more light than a T8 lamp from the same length
- 24,000 hours lifetime / 18,000 hours service life with prestart ECG
- Environmentally friendly fluorescent lamp with a low mercury content
- Ideal for applications where more light is required



| Product ID Code           | EAN (Single Pack) | Product Description  | W  | Color | I [mm]    | PPG   |
|---------------------------|-------------------|----------------------|----|-------|-----------|-------|
| FQ248301VP <sup>2</sup> ) | 4050300453491     | LUMILUX T5 HO 24/830 | 24 | 830   | G5 549mm  | 40 23 |
| FQ248351VP <sup>2</sup> ) | 4050300776590     | LUMILUX T5 HO 24/835 | 24 | 835   | G5 549mm  | 40 23 |
| FQ248401VP <sup>2</sup> ) | 4050300453477     | LUMILUX T5 HO 24/840 | 24 | 840   | G5 549mm  | 40 23 |
| FQ248651VP <sup>2</sup> ) | 4050300453453     | LUMILUX T5 HO 24/865 | 24 | 865   | G5 549mm  | 40 23 |
| FQ398271VP <sup>2</sup> ) | 4050300646138     | LUMILUX T5 HO 39/827 | 39 | 827   | G5 849mm  | 40 23 |
| FQ398301VP <sup>2</sup> ) | 4050300453552     | LUMILUX T5 HO 39/830 | 39 | 830   | G5 849mm  | 40 23 |
| FQ398401VP <sup>2</sup> ) | 4050300453538     | LUMILUX T5 HO 39/840 | 39 | 840   | G5 849mm  | 40 23 |
| FQ398651VP <sup>2</sup> ) | 4050300453514     | LUMILUX T5 HO 39/865 | 39 | 865   | G5 849mm  | 40 23 |
| FQ498301VP <sup>2</sup> ) | 4050300657158     | LUMILUX T5 HO 49/830 | 49 | 830   | G5 1449mm | 40 23 |
| FQ498401VP <sup>2</sup> ) | 4050300657134     | LUMILUX T5 HO 49/840 | 49 | 840   | G5 1449mm | 40 23 |
| FQ498651VP <sup>2</sup> ) | 4008321110732     | LUMILUX T5 HO 49/865 | 49 | 865   | G5 1449mm | 40 23 |
| FQ498652)                 | 4050300796628     | LUMILUX T5 HO 49/865 | 49 | 865   | G5 1449mm | 40 23 |
| FQ548271VP <sup>2</sup> ) | 4050300646176     | LUMILUX T5 HO 54/827 | 54 | 827   | G5 1149mm | 40 23 |
| FQ548301VP <sup>2</sup> ) | 4050300453415     | LUMILUX T5 HO 54/830 | 54 | 830   | G5 1449mm | 40 23 |
| FQ548351VP <sup>2</sup> ) | 4050300776637     | LUMILUX T5 HO 54/835 | 54 | 835   | G5 1149mm | 40 23 |
| FQ548401VP <sup>2</sup> ) | 4050300453392     | LUMILUX T5 HO 54/840 | 54 | 840   | G5 1149mm | 40 23 |
| FQ548651VP <sup>2</sup> ) | 4050300453378     | LUMILUX T5 HO 54/865 | 54 | 865   | G5 1149mm | 40 23 |
| FQ808271VP <sup>2</sup> ) | 4050300646213     | LUMILUX T5 HO 80/827 | 80 | 827   | G5 1449mm | 40 23 |
| FQ808301VP <sup>2</sup> ) | 4050300515137     | LUMILUX T5 HO 80/830 | 80 | 830   | G5 1449mm | 40 23 |
| FQ808401VP <sup>2</sup> ) | 4050300515151     | LUMILUX T5 HO 80/840 | 80 | 840   | G5 1449mm | 40 23 |
| FQ808651VP <sup>2</sup> ) | 4050300515113     | LUMILUX T5 HO 80/865 | 80 | 865   | G5 1449mm | 40 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)


2) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C

Colour 880 available on request

All orders must be multiples of sales pack



## Fluorescent Tubes

**LUMILUX® T5 HO HIGH OUTPUT with cardboard sleeve**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Up to 50% more light than a T8 lamp from the same length
- 24,000 hours lifetime / 18,000 hours service life with prestart ECG
- Environmentally friendly fluorescent lamp with a low mercury content
- Ideal for applications where more light is required

| Product ID Code         | EAN (Single Pack) | Product Description          | W  | Color | I [mm] | PPG          |
|-------------------------|-------------------|------------------------------|----|-------|--------|--------------|
| FQ24827 <sup>2)</sup>   | 4050300646077     | LUMILUX T5 HO 24/827 sleeved | 24 | 827   | G5     | 549mm 20 23  |
| FQ24830 <sup>2)</sup>   | 4050300591667     | LUMILUX T5 HO 24/830 sleeved | 24 | 830   | G5     | 549mm 20 23  |
| FQ24835 <sup>2)</sup>   | 4050300776439     | LUMILUX T5 HO 24/835 sleeved | 24 | 835   | G5     | 549mm 20 23  |
| FQ24840 <sup>2)</sup>   | 4050300591643     | LUMILUX T5 HO 24/840 sleeved | 24 | 840   | G5     | 549mm 20 23  |
| FQ24865 <sup>2)</sup>   | 4050300591629     | LUMILUX T5 HO 24/865 sleeved | 24 | 865   | G5     | 549mm 20 23  |
| FQ24880 <sup>2)</sup>   | 4008321081469     | LUMILUX T5 HO 24/880 sleeved | 24 | 880   | G5     | 549mm 20 23  |
| FQ39827 <sup>2)</sup>   | 4050300646114     | LUMILUX T5 HO 39/827 sleeved | 39 | 827   | G5     | 849mm 20 23  |
| FQ39830 <sup>2)</sup>   | 4050300591728     | LUMILUX T5 HO 39/830 sleeved | 39 | 830   | G5     | 849mm 20 23  |
| FQ39840 <sup>2)</sup>   | 4050300591704     | LUMILUX T5 HO 39/840 sleeved | 39 | 840   | G5     | 849mm 20 23  |
| FQ39865 <sup>2)</sup>   | 4050300591681     | LUMILUX T5 HO 39/865 sleeved | 39 | 865   | G5     | 849mm 20 23  |
| FQ39880 <sup>2)</sup>   | 4008321081445     | LUMILUX T5 HO 39/880 sleeved | 39 | 880   | G5     | 849mm 20 23  |
| FQ49827H <sup>02)</sup> | 4008321110664     | LUMILUX T5 HO 49/827 sleeved | 49 | 827   | G5     | 1449mm 40 23 |
| FQ49830H <sup>02)</sup> | 4008321110671     | LUMILUX T5 HO 49/830 sleeved | 49 | 830   | G5     | 1449mm 40 23 |
| FQ49835H <sup>02)</sup> | 4008321110701     | LUMILUX T5 HO 49/835 sleeved | 49 | 835   | G5     | 1449mm 40 23 |
| FQ49840H <sup>02)</sup> | 4008321110688     | LUMILUX T5 HO 49/840 sleeved | 49 | 840   | G5     | 1449mm 40 23 |
| FQ49865VP <sup>2)</sup> | 4008321110732     | LUMILUX T5 HO 49/865 sleeved | 49 | 865   | G5     | 1449mm 40 23 |
| FQ49880H <sup>02)</sup> | 4008321110725     | LUMILUX T5 HO 49/880 sleeved | 49 | 880   | G5     | 1449mm 40 23 |
| FQ54827 <sup>2)</sup>   | 4050300646152     | LUMILUX T5 HO 54/827 sleeved | 54 | 827   | G5     | 1149mm 20 23 |
| FQ54830 <sup>2)</sup>   | 4050300591605     | LUMILUX T5 HO 54/830 sleeved | 54 | 830   | G5     | 1149mm 20 23 |
| FQ54835 <sup>2)</sup>   | 4050300776477     | LUMILUX T5 HO 54/835 sleeved | 54 | 835   | G5     | 1149mm 20 23 |
| FQ54840 <sup>2)</sup>   | 4050300591582     | LUMILUX T5 HO 54/840 sleeved | 54 | 840   | G5     | 1149mm 20 23 |
| FQ54865 <sup>2)</sup>   | 4050300591568     | LUMILUX T5 HO 54/865 sleeved | 54 | 865   | G5     | 1149mm 20 23 |
| FQ54880 <sup>2)</sup>   | 4008321070425     | LUMILUX T5 HO 54/880 sleeved | 54 | 880   | G5     | 1149mm 20 23 |
| FQ80827 <sup>2)</sup>   | 4050300646190     | LUMILUX T5 HO 80/827 sleeved | 80 | 827   | G5     | 1449mm 20 23 |
| FQ80830 <sup>2)</sup>   | 4050300591827     | LUMILUX T5 HO 80/830 sleeved | 80 | 830   | G5     | 1449mm 20 23 |
| FQ80835 <sup>2)</sup>   | 4050300776491     | LUMILUX T5 HO 80/835 sleeved | 80 | 835   | G5     | 1449mm 20 23 |
| FQ80840 <sup>2)</sup>   | 4050300591841     | LUMILUX T5 HO 80/840 sleeved | 80 | 840   | G5     | 1449mm 20 23 |
| FQ80865 <sup>2)</sup>   | 4050300591803     | LUMILUX T5 HO 80/865 sleeved | 80 | 865   | G5     | 1449mm 20 23 |
| FQ80880 <sup>2)</sup>   | 4008321070449     | LUMILUX T5 HO 80/880 sleeved | 80 | 880   | G5     | 1449mm 20 23 |


Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)


2) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C

All orders must be multiples of sales pack

## Fluorescent Tubes

**LUMILUX® T5 HO ES HIGH OUTPUT ENERGY SAVER without cardboard sleeve**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Energy savings of up to 10%
- Up to 24,000 hours average lifetime
- Environmentally friendly fluorescent lamp with a low mercury content
- Ideal for indoor lighting systems e.g. for factories, warehouses and high ceiling areas and outdoor lighting systems



| Product ID Code        | EAN (Single Pack) | Product Description     | W  | COLOR |    | I [mm] |    | PPG |
|------------------------|-------------------|-------------------------|----|-------|----|--------|----|-----|
| H045827 <sup>(1)</sup> | 4008321958129     | LUMILUX T5 HO ES 45/827 | 45 | 827   | G5 | 1149mm | 40 |     |
| H045830 <sup>(1)</sup> | 4008321958136     | LUMILUX T5 HO ES 45/830 | 45 | 830   | G5 | 1149mm | 40 |     |
| H045840 <sup>(1)</sup> | 4008321958143     | LUMILUX T5 HO ES 45/840 | 45 | 840   | G5 | 1149mm | 40 |     |
| H045865 <sup>(1)</sup> | 4008321958150     | LUMILUX T5 HO ES 45/865 | 45 | 865   | G5 | 1149mm | 40 |     |
| H050827 <sup>(1)</sup> | 4008321958167     | LUMILUX T5 HO ES 50/827 | 50 | 827   | G5 | 1149mm | 40 |     |
| H050830 <sup>(1)</sup> | 4008321958174     | LUMILUX T5 HO ES 50/830 | 50 | 830   | G5 | 1149mm | 40 |     |
| H050840 <sup>(1)</sup> | 4008321958181     | LUMILUX T5 HO ES 50/840 | 50 | 840   | G5 | 1149mm | 40 |     |
| H050865 <sup>(1)</sup> | 4008321958198     | LUMILUX T5 HO ES 50/865 | 50 | 865   | G5 | 1149mm | 40 |     |
| H073827 <sup>(1)</sup> | 4008321958204     | LUMILUX T5 HO ES 73/827 | 73 | 827   | G5 | 1449mm | 40 |     |
| H073830 <sup>(1)</sup> | 4008321958211     | LUMILUX T5 HO ES 73/830 | 73 | 830   | G5 | 1449mm | 40 |     |
| H073840 <sup>(1)</sup> | 4008321958228     | LUMILUX T5 HO ES 73/840 | 73 | 840   | G5 | 1449mm | 40 |     |
| H073865 <sup>(1)</sup> | 4008321958235     | LUMILUX T5 HO ES 73/865 | 73 | 865   | G5 | 1449mm | 40 |     |

Perfectly matched with QUICKTRONIC® electronic control gear

1) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C



All orders must be multiples of sales pack



## Fluorescent Tubes


**LUMILUX® T5 HO ES HIGH OUTPUT ENERGY SAVER with cardboard sleeve**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- 10% Energy saving compared to standard T5 HO fluorescent tubes
- 20,000 hours lifetime / 16,000 hours service life with prestart ECG
- Ideal for energy saving office lighting

| Product ID Code       | EAN (Single Pack) | Product Description           | W  | Color | I [mm]       | PPG |
|-----------------------|-------------------|-------------------------------|----|-------|--------------|-----|
| HO45827 <sup>1)</sup> | 4008321515100     | LUMILUX HO 45W/827 ES sleeved | 45 | 827   | G5 1449mm 20 | 23  |
| HO45830 <sup>1)</sup> | 4008321515124     | LUMILUX HO 45W/830 ES sleeved | 45 | 830   | G5 1449mm 20 | 23  |
| HO45840 <sup>1)</sup> | 4008321515148     | LUMILUX HO 45W/840 ES sleeved | 45 | 840   | G5 1449mm 20 | 23  |
| HO45865 <sup>1)</sup> | 4008321515162     | LUMILUX HO 45W/865 ES sleeved | 45 | 865   | G5 1449mm 20 | 23  |
| HO50827 <sup>1)</sup> | 4008321515186     | LUMILUX HO 50W/827 ES sleeved | 50 | 827   | G5 1149mm 20 | 23  |
| HO50830 <sup>1)</sup> | 4008321515209     | LUMILUX HO 50W/830 ES sleeved | 50 | 830   | G5 1149mm 20 | 23  |
| HO50840 <sup>1)</sup> | 4008321515223     | LUMILUX HO 50W/840 ES sleeved | 50 | 840   | G5 1149mm 20 | 23  |
| HO50865 <sup>1)</sup> | 4008321515247     | LUMILUX HO 50W/865 ES sleeved | 50 | 865   | G5 1149mm 20 | 23  |
| HO73827 <sup>1)</sup> | 4008321515261     | LUMILUX HO 73W/827 ES sleeved | 73 | 827   | G5 1449mm 20 | 23  |
| HO73830 <sup>1)</sup> | 4008321515285     | LUMILUX HO 73W/830 ES sleeved | 73 | 830   | G5 1449mm 20 | 23  |
| HO73840 <sup>1)</sup> | 4008321515308     | LUMILUX HO 73W/840 ES sleeved | 73 | 840   | G5 1449mm 20 | 23  |
| HO73865 <sup>1)</sup> | 4008321515322     | LUMILUX HO 73W/865 ES sleeved | 73 | 865   | G5 1449mm 20 | 23  |

Perfectly matched with QUICKTRONIC® electronic control gear

1) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C



All orders must be multiples of sales pack

## Fluorescent Tubes

**LUMILUX® T5 HO XT**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Extremely long lifetime of up to 45,000 hours
- Longer maintenance intervals
- Industry, tunnels, street lighting, high ceilings and difficult luminaire access

| Product ID Code         | EAN (Single Pack) | Product Description   | W  | COLOR | I [mm]    | PPG   |
|-------------------------|-------------------|-----------------------|----|-------|-----------|-------|
| H049827XT <sup>1)</sup> | 4008321958488*    | LUMILUX HO 49W/827 XT | 49 | 827   | G5 1449mm | 20 23 |
| H049830XT <sup>1)</sup> | 4008321958495*    | LUMILUX HO 49W/830 XT | 49 | 830   | G5 1449mm | 20 23 |
| H049840XT <sup>1)</sup> | 4008321958501*    | LUMILUX HO 49W/840 XT | 49 | 840   | G5 1449mm | 20 23 |
| H049865XT <sup>1)</sup> | 4008321958518*    | LUMILUX HO 49W/865 XT | 49 | 865   | G5 1449mm | 20 23 |
| H054827XT <sup>1)</sup> | 4008321958525*    | LUMILUX HO 54W/827 XT | 54 | 827   | G5 1149mm | 20 23 |
| H054830XT <sup>1)</sup> | 4008321958549*    | LUMILUX HO 54W/830 XT | 54 | 830   | G5 1149mm | 20 23 |
| H054840XT <sup>1)</sup> | 4008321958556*    | LUMILUX HO 54W/840 XT | 54 | 840   | G5 1149mm | 20 23 |
| H054865XT <sup>1)</sup> | 4008321958563*    | LUMILUX HO 54W/865 XT | 54 | 865   | G5 1149mm | 20 23 |
| H080827XT <sup>1)</sup> | 4008321958570*    | LUMILUX HO 80W/827 XT | 80 | 827   | G5 1449mm | 20 23 |
| H080830XT <sup>1)</sup> | 4008321958587*    | LUMILUX HO 80W/830 XT | 80 | 830   | G5 1449mm | 20 23 |
| H080840XT <sup>1)</sup> | 4008321958594*    | LUMILUX HO 80W/840 XT | 80 | 840   | G5 1449mm | 20 23 |
| H080865XT <sup>1)</sup> | 4008321958600*    | LUMILUX HO 80W/865 XT | 80 | 865   | G5 1449mm | 20 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C


\* In preparation at time of print. For further information please contact OSRAM



All orders must be multiples of sales pack



## Fluorescent Tubes

**LUMILUX® T5 HO CONSTANT**


- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Perfect solution for very cold and very hot lighting installations
- >90% luminous flux between +5°C and +70°C
- Approved for dimming down to 1% with new OSRAM QTi dimming units
- Ideal for outdoor lighting applications and "hot" company luminaries

| Product ID Code         | EAN (Single Pack) | Product Description           | W  | Color |    | I [mm] |    | PPG |
|-------------------------|-------------------|-------------------------------|----|-------|----|--------|----|-----|
| FQ24827C0 <sup>2)</sup> | 4008321074898     | LUMILUX T5 HO CONSTANT 24/827 | 24 | 827   | G5 | 549mm  | 20 | 23  |
| FQ24830C0 <sup>2)</sup> | 4008321074911     | LUMILUX T5 HO CONSTANT 24/830 | 24 | 830   | G5 | 549mm  | 20 | 23  |
| FQ24840C0 <sup>2)</sup> | 4008321075451     | LUMILUX T5 HO CONSTANT 24/840 | 24 | 840   | G5 | 549mm  | 20 | 23  |
| FQ24865C0 <sup>2)</sup> | 4008321075475     | LUMILUX T5 HO CONSTANT 24/865 | 24 | 865   | G5 | 549mm  | 20 | 23  |
| FQ39830C0 <sup>2)</sup> | 4008321075512     | LUMILUX T5 HO CONSTANT 39/830 | 39 | 830   | G5 | 849mm  | 20 | 23  |
| FQ39840C0 <sup>2)</sup> | 4008321075550     | LUMILUX T5 HO CONSTANT 39/840 | 39 | 840   | G5 | 849mm  | 20 | 23  |
| FQ39865C0 <sup>2)</sup> | 4008321075574     | LUMILUX T5 HO CONSTANT 39/865 | 39 | 865   | G5 | 849mm  | 20 | 23  |
| FQ49830C0 <sup>2)</sup> | 4008321958761     | LUMILUX T5 HO CONSTANT 49/830 | 49 | 830   | G7 | 1449mm | 20 | 23  |
| FQ49840C0 <sup>2)</sup> | 4008321958778     | LUMILUX T5 HO CONSTANT 49/840 | 49 | 840   | G8 | 1449mm | 20 | 23  |
| FQ49865C0 <sup>2)</sup> | 4008321958785     | LUMILUX T5 HO CONSTANT 49/865 | 49 | 865   | G9 | 1449mm | 20 | 23  |
| FQ54830C0 <sup>2)</sup> | 4008321075611     | LUMILUX T5 HO CONSTANT 54/830 | 54 | 830   | G5 | 1149mm | 20 | 23  |
| FQ54840C0 <sup>2)</sup> | 4008321075659     | LUMILUX T5 HO CONSTANT 54/840 | 54 | 840   | G5 | 1149mm | 20 | 23  |
| FQ54865C0 <sup>2)</sup> | 4008321075673     | LUMILUX T5 HO CONSTANT 54/865 | 54 | 865   | G5 | 1149mm | 20 | 23  |
| FQ80830C0 <sup>2)</sup> | 4008321075819     | LUMILUX T5 HO CONSTANT 80/830 | 80 | 830   | G5 | 1449mm | 20 | 23  |
| FQ80840C0 <sup>2)</sup> | 4008321080042     | LUMILUX T5 HO CONSTANT 80/840 | 80 | 840   | G5 | 1449mm | 20 | 23  |
| FQ80865C0 <sup>2)</sup> | 4008321080066     | LUMILUX T5 HO CONSTANT 80/865 | 80 | 865   | G5 | 1449mm | 20 | 23  |

NEW  
NEW  
NEW

Perfectly matched with QUICKTRONIC® electronic control gear

- 1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)
- 2) Suitable for ECG operation only



All orders must be multiples of sales pack

## Fluorescent Tubes


**LUMILUX® DE LUXE T5 HO HIGH OUTPUT**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Superior colour rendering
- Ideal where colour rendition is important

| Product ID Code       | EAN (Single Pack) | Product Description          | W  | COLOR |    | I [mm] |       |
|-----------------------|-------------------|------------------------------|----|-------|----|--------|-------|
| FQ24940 <sup>1)</sup> | 4008321233028     | LUMILUX DE LUXE T5 HO 24/940 | 24 | 940   | G5 | 549mm  | 10 23 |
| F124965 <sup>1)</sup> | 4008321233042     | LUMILUX DE LUXE T5 HO 24/965 | 24 | 965   | G5 | 549mm  | 10 23 |
| FQ49940 <sup>1)</sup> | 4008321234025     | LUMILUX DE LUXE T5 HO 49/940 | 49 | 940   | G5 | 1449mm | 10 23 |
| FQ49965 <sup>1)</sup> | 4008321233066     | LUMILUX DE LUXE T5 HO 49/965 | 49 | 965   | G5 | 1449mm | 10 23 |
| FQ54940 <sup>1)</sup> | 4008321233929     | LUMILUX DE LUXE T5 HO 54/940 | 54 | 940   | G5 | 1149mm | 10 23 |
| FQ54965 <sup>1)</sup> | 4008321233943     | LUMILUX DE LUXE T5 HO 54/965 | 54 | 965   | G5 | 1149mm | 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) Suitable for ECG operation only

**LUMILUX® T5 DE LUXE**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Deluxe triphosphor tube
- Superior colour rendering
- Ideal where colour rendition is important

| Product ID Code | EAN (Single Pack) | Product Description       | W  | COLOR |    | I [mm] |       |
|-----------------|-------------------|---------------------------|----|-------|----|--------|-------|
| L6930           | 4050300015880     | LUMILUX T5 DE LUXE 6/930  | 6  | 930   | G5 | 212mm  | 25 23 |
| L8930           | 4050300015897     | LUMILUX T5 DE LUXE 8/930  | 8  | 930   | G5 | 288mm  | 25 23 |
| L8954           | 4050300018232     | LUMILUX T5 DE LUXE 8/954  | 8  | 954   | G5 | 288mm  | 25 23 |
| L13930          | 4050300015903     | LUMILUX T5 DE LUXE 13/930 | 13 | 930   | G5 | 517mm  | 25 23 |
| L13954          | 4050300327419     | LUMILUX T5 DE LUXE 13/954 | 13 | 954   | G5 | 517mm  | 25 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack



## Fluorescent Tubes

**LUMILUX® T5 SEAMLESS**


- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Innovative base that allows tubes to be side by side
- Provides continuous light for optimal illumination
- Lifetime of up to 12,000 hours
- Ideal for cove lighting without dark spots

| Product ID Code       | EAN (Single Pack) | Product Description    | W  | Color | I [mm]             | PPG   |
|-----------------------|-------------------|------------------------|----|-------|--------------------|-------|
| <b>HE Version</b>     |                   |                        |    |       |                    |       |
| HE14830 <sup>1)</sup> | 4008321957719     | LUMILUX HE 14W/830 SLS | 14 | 830   | 481 <sup>2)</sup>  | 25 23 |
| HE14840 <sup>1)</sup> | 4008321957733     | LUMILUX HE 14W/840 SLS | 14 | 840   | 481 <sup>2)</sup>  | 25 23 |
| HE14865 <sup>1)</sup> | 4008321957757     | LUMILUX HE 14W/865 SLS | 14 | 865   | 481 <sup>2)</sup>  | 25 23 |
| HE21830 <sup>1)</sup> | 4008321957771     | LUMILUX HE 21W/830 SLS | 21 | 830   | 781 <sup>2)</sup>  | 25 23 |
| HE21840 <sup>1)</sup> | 4008321957795     | LUMILUX HE 21W/840 SLS | 21 | 840   | 781 <sup>2)</sup>  | 25 23 |
| HE21865 <sup>1)</sup> | 4008321957818     | LUMILUX HE 21W/865 SLS | 21 | 865   | 781 <sup>2)</sup>  | 25 23 |
| HE28830 <sup>1)</sup> | 4008321957832     | LUMILUX HE 28W/830 SLS | 28 | 830   | 1081 <sup>2)</sup> | 25 23 |
| HE28840 <sup>1)</sup> | 4008321957856     | LUMILUX HE 28W/840 SLS | 28 | 840   | 1081 <sup>2)</sup> | 25 23 |
| HE28865 <sup>1)</sup> | 4008321957870     | LUMILUX HE 28W/865 SLS | 28 | 865   | 1081 <sup>2)</sup> | 25 23 |
| <b>HO Version</b>     |                   |                        |    |       |                    |       |
| HO24830 <sup>1)</sup> | 4008321409959     | LUMILUX HO 24W/830 SLS | 24 | 830   | 582mm              | 25 23 |
| HO24840 <sup>1)</sup> | 4008321357250     | LUMILUX HO 24W/840 SLS | 24 | 840   | 582mm              | 25 23 |
| HO24865 <sup>1)</sup> | 4008321410016     | LUMILUX HO 24W/865 SLS | 24 | 865   | 582mm              | 25 23 |
| H039830 <sup>1)</sup> | 4008321409973     | LUMILUX HO 39W/830 SLS | 39 | 830   | 882mm              | 25 23 |
| H039840 <sup>1)</sup> | 4008321357373     | LUMILUX HO 39W/840 SLS | 39 | 840   | 882mm              | 25 23 |
| H039865 <sup>1)</sup> | 4008321410030     | LUMILUX HO 39W/865 SLS | 39 | 865   | 882mm              | 25 23 |
| H054830 <sup>1)</sup> | 4008321409997     | LUMILUX HO 54W/830 SLS | 54 | 830   | 1182mm             | 25 23 |
| H054840 <sup>1)</sup> | 4008321357434     | LUMILUX HO 54W/840 SLS | 54 | 840   | 1182mm             | 25 23 |
| H054865 <sup>1)</sup> | 4008321410054     | LUMILUX HO 54W/865 SLS | 54 | 865   | 1182mm             | 25 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) Suitable for ECG operation only

2) Min




All orders must be multiples of sales pack

## Fluorescent Tubes


**LUMILUX® T5 SHORT**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Long life triphosphor tube
- Environmentally friendly fluorescent lamp with a low mercury content
- Only 8% loss of luminous flux throughout entire life
- Ideal for professional office lighting



| Product ID Code | EAN (Single Pack) | Product Description     | W  | Color |    | I [mm] |    | PPG |
|-----------------|-------------------|-------------------------|----|-------|----|--------|----|-----|
| L6830           | 4008321959874     | LUMILUX T5 SHORT 6/830  | 6  | 830   | G5 | 212mm  | 25 | 20  |
| L8827           | 4050300008943     | LUMILUX T5 SHORT 8/827  | 8  | 827   | G5 | 288mm  | 25 | 20  |
| L8830           | 4008321959881     | LUMILUX T5 SHORT 8/830  | 8  | 830   | G5 | 288mm  | 25 | 20  |
| L8840           | 4050300241623     | LUMILUX T5 SHORT 8/840  | 8  | 840   | G5 | 288mm  | 25 | 20  |
| L13827          | 4050300008967     | LUMILUX T5 SHORT 13/827 | 13 | 827   | G5 | 517mm  | 25 | 20  |
| L13830          | 4008321959898     | LUMILUX T5 SHORT 13/830 | 13 | 830   | G5 | 517mm  | 25 | 20  |
| L13840          | 4050300241647     | LUMILUX T5 SHORT 13/840 | 13 | 840   | G5 | 517mm  | 25 | 20  |

Perfectly matched with QUICKTRONIC® electronic control gear

**BASIC T5**

- Basic halophosphate tube only 16mm (5/8 in) diameter
- Ideal for small luminaires

| Product ID Code | EAN (Single Pack) | Product Description | W  | Color  |    | I [mm] |    | PPG |
|-----------------|-------------------|---------------------|----|--------|----|--------|----|-----|
| L4640           | 4050300008875     | BASIC T5 4/640      | 4  | 20/640 | G5 | 136mm  | 25 | 22  |
| L4535           | 4050300270722     | BASIC T5 4/535      | 4  | 23/535 | G5 | 136mm  | 25 | 22  |
| L6640           | 4050300008899     | BASIC T5 6/640      | 6  | 20/640 | G5 | 288mm  | 25 | 22  |
| L8640           | 4050300008912     | BASIC T5 8/640      | 8  | 20/640 | G5 | 288mm  | 25 | 22  |
| L8535           | 4050300241807     | BASIC T5 8/535      | 8  | 23/535 | G5 | 288mm  | 25 | 22  |
| L8765           | 4050300035475     | BASIC T5 8/765      | 8  | 765    | G5 | 288mm  | 25 | 22  |
| L13640          | 4050300008974     | BASIC T5 13/640     | 13 | 20/640 | G5 | 517mm  | 25 | 22  |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack





## Fluorescent Tubes

**T5 LUMILUX® OPTIMISED FOR EMERGENCY LIGHTING**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- EL version for emergency lighting
- Ideal for small luminaires

| Product ID Code | EAN (Single Pack) | Product Description     |   |     |    |       |    |
|-----------------|-------------------|-------------------------|---|-----|----|-------|----|
| L6840EL         | 4008321325662     | T5 LUMILUX EMERGENCY 6W | 6 | 840 | G5 | 212mm | 25 |
| L8840EL         | 4008321325846     | T5 LUMILUX EMERGENCY 8W | 8 | 840 | G5 | 288mm | 25 |

Perfectly matched with QUICKTRONIC® electronic control gear

**T5 BASIC OPTIMISED FOR EMERGENCY LIGHTING**

- Basic halophosphate tube only 16mm (5/8 in) diameter
- EL version for emergency lighting
- Ideal for small luminaires

| Product ID Code | EAN (Single Pack) | Product Description   |   |        |    |       |    |    |
|-----------------|-------------------|-----------------------|---|--------|----|-------|----|----|
| L6640EL         | 4008321152381     | T5 BASIC EMERGENCY 6W | 6 | 20/640 | G5 | 212mm | 25 | 22 |
| L8640EL         | 4050300606644     | T5 BASIC EMERGENCY 8W | 8 | 20/640 | G5 | 288mm | 25 | 22 |


Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack

## Fluorescent Tubes

**T5 HE HIGH EFFICIENCY COLOURED**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Available in red, green and blue colours
- Ideal for special effects



| Product ID Code      | EAN (Single Pack) | Product Description  | W  | COLOR    |    | L [mm] |       |
|----------------------|-------------------|----------------------|----|----------|----|--------|-------|
| FH1460 <sup>2)</sup> | 4008321170705     | Coloured T5 HE 14/R  | 14 | Red 60   | G5 | 549mm  | 10 23 |
| FH1466 <sup>2)</sup> | 4008321170729     | Coloured T5 HE 14/G  | 14 | Green 66 | G5 | 549mm  | 10 23 |
| FH1467 <sup>2)</sup> | 4008321170781     | Coloured T5 HE 14/BL | 14 | Blue 67  | G5 | 549mm  | 10 23 |
| FH2160 <sup>2)</sup> | 4008321170682     | Coloured T5 HE 21/R  | 21 | Red 60   | G5 | 849mm  | 10 23 |
| FH2166 <sup>2)</sup> | 4008321170743     | Coloured T5 HE 21/G  | 21 | Green 66 | G5 | 849mm  | 10 23 |
| FH2167 <sup>2)</sup> | 4008321170804     | Coloured T5 HE 21/BL | 21 | Blue 67  | G5 | 849mm  | 10 23 |
| FH2860 <sup>2)</sup> | 4008321161840     | Coloured T5 HE 28/R  | 28 | Red 60   | G5 | 1149mm | 10 23 |
| FH2866 <sup>2)</sup> | 4008321161864     | Coloured T5 HE 28/G  | 28 | Green 66 | G5 | 1149mm | 10 23 |
| FH2867 <sup>2)</sup> | 4008321161888     | Coloured T5 HE 28/BL | 28 | Blue 67  | G5 | 1149mm | 10 23 |
| FH3560 <sup>2)</sup> | 4008321133458     | Coloured T5 HE 35/R  | 35 | Red 60   | G5 | 1449mm | 10 23 |
| FH3566 <sup>2)</sup> | 4008321161925     | Coloured T5 HE 35/G  | 35 | Green 66 | G5 | 1449mm | 10 23 |
| FH3567 <sup>2)</sup> | 4008321161949     | Coloured T5 HE 35/BL | 35 | Blue 67  | G5 | 1449mm | 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear


1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

2) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C

All orders must be multiples of sales pack



## Fluorescent Tubes

**T5 HO HIGH OUTPUT COLOURED**


- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Available in red, green and blue colours
- Ideal for special effects

| Product ID Code       | EAN (Single Pack) | Product Description          | W  | COLOR    |    | I [mm] |       |
|-----------------------|-------------------|------------------------------|----|----------|----|--------|-------|
| FQ2460 <sup>(2)</sup> | 4008321171009     | LUMILUX Coloured T5 HO 24/R  | 24 | Red 60   | G5 | 549mm  | 10 23 |
| FQ2466 <sup>(2)</sup> | 4008321170941     | LUMILUX Coloured T5 HO 24/G  | 24 | Green 66 | G5 | 549mm  | 10 23 |
| FQ2467 <sup>(2)</sup> | 4008321170880     | LUMILUX Coloured T5 HO 24/BL | 24 | Blue 67  | G5 | 549mm  | 10 23 |
| FQ3960 <sup>(2)</sup> | 4008321170989     | LUMILUX Coloured T5 HO 39/R  | 39 | Red 60   | G5 | 849mm  | 10 23 |
| FQ3966 <sup>(2)</sup> | 4008321170927     | LUMILUX Coloured T5 HO 39/G  | 39 | Green 66 | G5 | 849mm  | 10 23 |
| FQ3967 <sup>(2)</sup> | 4008321170866     | LUMILUX Coloured T5 HO 39/BL | 39 | Blue 67  | G5 | 849mm  | 10 23 |
| FQ5460 <sup>(2)</sup> | 4008321170965     | LUMILUX Coloured T5 HO 54/R  | 54 | Red 60   | G5 | 1149mm | 10 23 |
| FQ5466 <sup>(2)</sup> | 4008321170903     | LUMILUX Coloured T5 HO 54/G  | 54 | Green 66 | G5 | 1149mm | 10 23 |
| FQ5467 <sup>(2)</sup> | 4008321170842     | LUMILUX Coloured T5 HO 54/BL | 54 | Blue 67  | G5 | 1149mm | 10 23 |
| FQ8060 <sup>(2)</sup> | 4008321161963     | LUMILUX Coloured T5 HO 80/R  | 80 | Red 60   | G5 | 1449mm | 10 23 |
| FQ8066 <sup>(2)</sup> | 4008321161987     | LUMILUX Coloured T5 HO 80/G  | 80 | Green 66 | G5 | 1449mm | 10 23 |
| FQ8067 <sup>(2)</sup> | 4008321162007     | LUMILUX Coloured T5 HO 80/BL | 80 | Blue 67  | G5 | 1449mm | 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear


1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

2) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C




All orders must be multiples of sales pack

## Fluorescent Tubes

**LUMILUX® SPLIT control T5**

- T5 fluorescent tube with a high temperature resistant sleeve
- 16mm (5/8 in) diameter
- Complies with all HACCP directives
- Average life 20,000 hours (with preheat ECG)
- Eco-friendly thanks to recyclable phosphor
- Ideal for use in the food industry and in sensitive food production



| Product ID Code          | EAN (Single Pack) | Product Description             | W  | COLOR | I [mm] | PPG          |
|--------------------------|-------------------|---------------------------------|----|-------|--------|--------------|
| HE28840SPS <sup>2)</sup> | 4008321233387     | LUMILUX SPLIT Control T5 28/840 | 28 | 840   | G5     | 1149mm 10 23 |
| H054840SPS <sup>2)</sup> | 4008321233363     | LUMILUX SPLIT Control T5 54/840 | 54 | 840   | G5     | 1149mm 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

2) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C

**LUMILUX® CHIP control T5**

- T5 fluorescent tube with excellent filter function at 500 nm
- Very good light performance during the life time (90% lumen maintenance throughout life cycle)
- Complies with the requirements of RoHS
- Average life 20,000 hours (with preheat ECG)
- Ideal for semiconductor fabrication plants and areas where UV radiation and light from the blue end of the spectrum must be reduced to the absolute minimum

| Product ID Code      | EAN (Single Pack) | Product Description          | W  | COLOR  | I [mm] | PPG          |
|----------------------|-------------------|------------------------------|----|--------|--------|--------------|
| HE2862 <sup>2)</sup> | 4008321233424     | LUMILUX CHIP CONTROL T5 28/Y | 28 | Yellow | G5     | 2040mm 10 23 |
| H05462 <sup>2)</sup> | 4008321233400     | LUMILUX CHIP CONTROL T5 54/Y | 54 | Yellow | G5     | 3140mm 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

2) Suitable for ECG operation only. The lamps are designed for internal luminaire temperatures of 30 to 40°C, the optimum luminaire flux is achieved at 35°C

All orders must be multiples of sales pack



## Fluorescent Tubes



**LUMILUX® T5 FC® FLUORESCENT CIRCLINE**

- Circular triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Very even light distribution
- Ideal for professional office lighting



| Product ID Code | EAN (Single Pack) | Product Description           |    |     |       |       |       |
|-----------------|-------------------|-------------------------------|----|-----|-------|-------|-------|
| FC22827         | 4050300646237     | LUMILUX T5 FC Circular 22/827 | 22 | 827 | 2GX13 | 225mm | 12 23 |
| FC22830         | 4050300528489     | LUMILUX T5 FC Circular 22/830 | 22 | 830 | 2GX13 | 225mm | 12 23 |
| FC22840         | 4050300528465     | LUMILUX T5 FC Circular 22/840 | 22 | 840 | 2GX13 | 225mm | 12 23 |
| FC22865         | 4050300528441     | LUMILUX T5 FC Circular 22/865 | 22 | 865 | 2GX13 | 225mm | 12 23 |
| FC40827         | 4050300646251     | LUMILUX T5 FC Circular 40/827 | 40 | 827 | 2GX13 | 300mm | 12 23 |
| FC40830         | 4050300528540     | LUMILUX T5 FC Circular 40/830 | 40 | 830 | 2GX13 | 300mm | 12 23 |
| FC40840         | 4050300528526     | LUMILUX T5 FC Circular 40/840 | 40 | 840 | 2GX13 | 300mm | 12 23 |
| FC40865         | 4050300528502     | LUMILUX T5 FC Circular 40/865 | 40 | 865 | 2GX13 | 300mm | 12 23 |
| FC55827         | 4050300646275     | LUMILUX T5 FC Circular 55/827 | 55 | 827 | 2GX13 | 300mm | 12 23 |
| FC55830         | 4050300528601     | LUMILUX T5 FC Circular 55/830 | 55 | 830 | 2GX13 | 300mm | 12 23 |
| FC55840         | 4050300528588     | LUMILUX T5 FC Circular 55/840 | 55 | 840 | 2GX13 | 300mm | 12 23 |
| FC55865         | 4050300528564     | LUMILUX T5 FC Circular 55/865 | 55 | 865 | 2GX13 | 300mm | 12 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

**T5 NATURA®**

- Triphosphor fluorescent tube only 16mm (5/8 in) diameter
- Displays food in an appetizing light
- Excellent colour rendering = 85
- Special colour rendering R9 = 90
- Average lifetime: 28W = 20,000 hours and 54W = 24000 hours




| Product ID Code | EAN (Single Pack) | Product Description |    |    |    |        |       |
|-----------------|-------------------|---------------------|----|----|----|--------|-------|
| HE2876          | 4008321581716     | NATURA T5 HE 28/76  | 28 | 76 | G5 | 2040mm | 25 23 |
| H05476          | 4008321581693     | NATURA T5 HO 54/76  | 54 | 76 | G5 | 1149mm | 25 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack


## Fluorescent Tubes



1)

**LUMILUX® T8**

- Triphosphor tube 26mm (1in) diameter
- Fewer lamp replacements compared to BASIC tubes due to longer life
- Higher lumen maintenance and colour rendering than BASIC tubes
- Ideal for professional office lighting



NEW!

| Product ID Code       | EAN (Single Pack) | Product Description | W  | COLOR |     | I [mm] |                  | PPG |
|-----------------------|-------------------|---------------------|----|-------|-----|--------|------------------|-----|
| L10827                | 4050300446165     | LUMILUX T8 10/827   | 10 | 827   | G13 | 470mm  | 25               | 20  |
| L15827                | 4050300446042     | LUMILUX T8 15/827   | 15 | 827   | G13 | 438mm  | 25               | 20  |
| L15830                | 4050300446028     | LUMILUX T8 15/830   | 15 | 830   | G13 | 438mm  | 25               | 20  |
| L15840                | 4050300446004     | LUMILUX T8 15/840   | 15 | 840   | G13 | 438mm  | 25               | 20  |
| L15865                | 4050300446189     | LUMILUX T8 15/865   | 15 | 865   | G13 | 438mm  | 25               | 20  |
| L16827                | 4050300446080     | LUMILUX T8 16/827   | 16 | 827   | G13 | 720mm  | 25               | 20  |
| L16830 <sup>2)</sup>  | 4008321959065     | LUMILUX T8 16/830   | 16 | 830   | G13 | 720mm  | 25 <sup>3)</sup> | 20  |
| L16840                | 4050300446066     | LUMILUX T8 16/840   | 16 | 840   | G13 | 720mm  | 25               | 20  |
| L18827                | 4050300517834     | LUMILUX T8 18/827   | 18 | 827   | G13 | 590mm  | 25               | 20  |
| L18830                | 4050300517810     | LUMILUX T8 18/830   | 18 | 830   | G13 | 590mm  | 25               | 20  |
| L18835                | 4050300447964     | LUMILUX T8 18/835   | 18 | 835   | G13 | 590mm  | 25               | 20  |
| L18840                | 4050300517797     | LUMILUX T8 18/840   | 18 | 840   | G13 | 590mm  | 25 <sup>3)</sup> | 20  |
| L18865                | 4050300517773     | LUMILUX T8 18/865   | 18 | 865   | G13 | 590mm  | 25               | 20  |
| L18880                | 4008321027962     | LUMILUX T8 18/880   | 18 | 880   | G13 | 590mm  | 25               | 20  |
| L23830                | 4050300446264     | LUMILUX T8 23/830   | 23 | 830   | G13 | 970mm  | 25               | 20  |
| L23840                | 4050300446240     | LUMILUX T8 23/840   | 23 | 840   | G13 | 970mm  | 25               | 20  |
| L30827                | 4050300518077     | LUMILUX T8 30/827   | 30 | 827   | G13 | 895mm  | 25               | 20  |
| L30830                | 4050300518053     | LUMILUX T8 30/830   | 30 | 830   | G13 | 895mm  | 25               | 20  |
| L30840                | 4050300518039     | LUMILUX T8 30/840   | 30 | 840   | G13 | 895mm  | 25               | 20  |
| L30865                | 4050300518015     | LUMILUX T8 30/865   | 30 | 865   | G13 | 895mm  | 25               | 20  |
| L30880                | 4008321027986     | LUMILUX T8 30/880   | 30 | 880   | G13 | 895mm  | 25               | 20  |
| L36827                | 4050300517919     | LUMILUX T8 36/827   | 36 | 827   | G13 | 1200mm | 25               | 20  |
| L36827 <sup>12)</sup> | 4050300518114     | LUMILUX T8 36/8271  | 36 | 827   | G13 | 970mm  | 25               | 20  |
| L36830 <sup>12)</sup> | 4008321959058     | LUMILUX T8 36/8301  | 36 | 830   | G13 | 970mm  | 25               | 20  |
| L36830                | 4050300517896     | LUMILUX T8 36/830   | 36 | 830   | G13 | 1200mm | 25 <sup>3)</sup> | 20  |
| L36835                | 4050300447988     | LUMILUX T8 36/835   | 36 | 835   | G13 | 1200mm | 25               | 20  |
| L36840                | 4050300517872     | LUMILUX T8 36/840   | 36 | 840   | G13 | 1200mm | 25 <sup>3)</sup> | 20  |
| L36840 <sup>2)</sup>  | 4050300518091     | LUMILUX T8 36/8401  | 35 | 840   | G13 | 970mm  | 25               | 20  |
| L36865                | 4050300517858     | LUMILUX T8 36/865   | 36 | 865   | G13 | 1200mm | 25               | 20  |

Continued

Perfectly matched with QUICKTRONIC® electronic control gear


- 1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)
- 2) These lamps are not intended for general illumination. They are suitable for applications such as lighting for means of public transport
- 3) Also available in industrial packs for bulk packs. Contains 30 lamps

NEW!

All orders must be multiples of sales pack



## Fluorescent Tubes

**LUMILUX® T8 (Continued)**

| Product ID Code | EAN (Single Pack) | Product Description | W  | Color |     | I [mm] |                  | PPG |
|-----------------|-------------------|---------------------|----|-------|-----|--------|------------------|-----|
| L36880          | 4008321002976     | LUMILUX T8 36/880   | 36 | 880   | G13 | 1200mm | 25               | 20  |
| L38830          | 4050300518152     | LUMILUX T8 38/830   | 38 | 830   | G13 | 1047mm | 25               | 20  |
| L38840          | 4050300518138     | LUMILUX T8 38/840   | 38 | 840   | G13 | 1047mm | 25               | 20  |
| L38880          | 4008321072245     | LUMILUX T8 38/880   | 38 | 880   | G13 | 1047mm | 25               | 20  |
| L58827          | 4050300603049     | LUMILUX T8 58/827   | 58 | 827   | G13 | 1500mm | 25               | 20  |
| L58830          | 4050300517971     | LUMILUX T8 58/830   | 58 | 830   | G13 | 1500mm | 25 <sup>2)</sup> | 20  |
| L58835          | 4050300448008     | LUMILUX T8 58/835   | 58 | 835   | G13 | 1500mm | 25               | 20  |
| L58840          | 4050300517957     | LUMILUX T8 58/840   | 58 | 840   | G13 | 1500mm | 25 <sup>2)</sup> | 20  |
| L58865          | 4050300517933     | LUMILUX T8 58/865   | 58 | 865   | G13 | 1500mm | 25               | 20  |
| L58880          | 4008321002990     | LUMILUX T8 58/880   | 58 | 880   | G13 | 1500mm | 25               | 20  |
| L70835          | 4008321003911     | LUMILUX T8 70/835   | 70 | 835   | G13 | 1800mm | 25               | 20  |
| L70840          | 4008321003959     | LUMILUX T8 70/840   | 70 | 840   | G13 | 1800mm | 25               | 20  |

Perfectly matched with QUICKTRONIC® electronic control gear


- 1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)
- 2) Also available in industrial packs for bulk packs. Contains 30 lamps

All orders must be multiples of sales pack

## Fluorescent Tubes

**LUMILUX® T8 ENERGY SAVER**

- Triphosphor tube 26mm (1in) diameter
- To replace BASIC tubes operated only on CCG
- 10% energy saving compared to BASIC tubes
- Ideal for applications using CCG such as warehouses and corridors



| Product ID Code | EAN (Single Pack) | Product Description  | W  | COLOR |     | I [mm] |    | PPG |
|-----------------|-------------------|----------------------|----|-------|-----|--------|----|-----|
| L16830ES        | 4008321955791     | LUMILUX T8 ES 16/830 | 16 | 830   | G13 | 590mm  | 25 | 20  |
| L16840ES        | 4008321955777     | LUMILUX T8 ES 16/840 | 16 | 840   | G13 | 590mm  | 25 | 20  |
| L32830ES        | 4008321339652     | LUMILUX T8 ES 32/830 | 32 | 830   | G13 | 1200mm | 25 | 20  |
| L32840ES        | 4008321339676     | LUMILUX T8 ES 32/840 | 32 | 840   | G13 | 1200mm | 25 | 20  |
| L51830ES        | 4008321339713     | LUMILUX T8 ES 51/830 | 51 | 830   | G13 | 1500mm | 25 | 20  |
| L51840ES        | 4008321339690     | LUMILUX T8 ES 51/840 | 51 | 840   | G13 | 1500mm | 25 | 20  |

Perfectly matched with QUICKTRONIC® electronic control gear

NEW  
NEW  
NEW  
NEW  
NEW  
NEW

All orders must be multiples of sales pack




## Fluorescent Tubes

**LUMILUX® XT T8**

- Triphosphor tube 26mm (1in) diameter
- 50,000 hours average life and 42,000 hours extended service life with ECG
- Ideal for applications where relamping is expensive such as factories and warehouses

| Product ID Code | EAN (Single Pack) | Product Description  | W  | COLOR |     | I [mm] |    | PPG |
|-----------------|-------------------|----------------------|----|-------|-----|--------|----|-----|
| XT18830         | 4008321209085     | LUMILUX XT T8 18/830 | 18 | 830   | G13 | 590mm  | 25 | 20  |
| XT18840         | 4008321209108     | LUMILUX XT T8 18/840 | 18 | 840   | G13 | 590mm  | 25 | 20  |
| L18865XT        | 4008321209122     | LUMILUX XT T8 18/865 | 18 | 865   | G13 | 590mm  | 25 | 20  |
| XT36830         | 4008321209146     | LUMILUX XT T8 36/830 | 36 | 830   | G13 | 1200mm | 25 | 20  |
| XT36840         | 4008321209160     | LUMILUX XT T8 36/840 | 36 | 840   | G13 | 1200mm | 25 | 20  |
| L36865XT        | 4008321209221     | LUMILUX XT T8 36/865 | 36 | 865   | G13 | 1200mm | 25 | 20  |
| XT58830         | 4008321209344     | LUMILUX XT T8 58/830 | 58 | 830   | G13 | 1500mm | 25 | 20  |
| XT58840         | 4008321209320     | LUMILUX XT T8 50/840 | 58 | 840   | G13 | 1500mm | 25 | 20  |
| L58865XT        | 4008321923622     | LUMILUX XT T8 58/865 | 58 | 865   | G13 | 1500mm | 25 | 20  |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack


## Fluorescent Tubes



1)

**LUMILUX® XXT T8**

- Triphosphor tube 26mm (1in) diameter
- Extremely reliable and long service life
- 90,000 hours average life (ECG hot restart) and 75,000 hours service life with ECG
- Less maintenance and lower cost of ownership compared to LUMILUX® T8
- Ideal for applications where relamping is expensive such as factories and warehouses



| Product ID Code | EAN (Single Pack) | Product Description   | W  | Color | I [mm]     | PPG   |
|-----------------|-------------------|-----------------------|----|-------|------------|-------|
| L18830XXT       | 4008321923646     | LUMILUX XXT T8 18/830 | 18 | 830   | G13 590mm  | 25 20 |
| L18840XXT       | 4008321923660     | LUMILUX XXT T8 18/840 | 18 | 840   | G13 590mm  | 25 20 |
| L18865XXT*      | 4008321923684     | LUMILUX XXT T8 18/865 | 18 | 865   | G13 590mm  | 25 20 |
| L36830XXT       | 4008321923707     | LUMILUX XXT T8 36/830 | 36 | 830   | G13 1200mm | 25 20 |
| L36840XXT       | 4008321923721     | LUMILUX XXT T8 36/840 | 36 | 840   | G13 1200mm | 25 20 |
| L36865XXT*      | 4008321923745     | LUMILUX XXT T8 36/865 | 36 | 865   | G13 1200mm | 25 20 |
| L58830XXT       | 4008321923769     | LUMILUX XXT T8 58/830 | 58 | 830   | G13 1500mm | 25 20 |
| L58840XXT       | 4008321923783     | LUMILUX XXT T8 58/840 | 58 | 840   | G13 1500mm | 25 20 |
| L58865XXT*      | 4008321923806     | LUMILUX XXT T8 58/865 | 58 | 865   | G13 1500mm | 25 20 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

\* Available upon request

All orders must be multiples of sales pack




## Fluorescent Tubes

**LUMILUX® DE LUXE T8**

- Triphosphor tube 26mm (1in) diameter
- Deluxe triphosphor tube
- Superior colour rendering
- Ideal where colour rendition is important

| Product ID Code | EAN (Single Pack) | Product Description         | W  | Color | I [mm]     | PPG   |
|-----------------|-------------------|-----------------------------|----|-------|------------|-------|
| L15930          | 4050300014395     | LUMILUX DE LUXE T8 15/930   | 15 | 930   | G13 438mm  | 25 20 |
| L15954          | 4050300018249     | LUMILUX DE LUXE T8 15/954   | 15 | 954   | G13 438mm  | 25 20 |
| L16930          | 4050300242361     | LUMILUX DE LUXE T8 16/930   | 16 | 930   | G13 720mm  | 25 20 |
| L18930          | 4050300011264     | LUMILUX DE LUXE T8 18/930   | 18 | 930   | G13 590mm  | 25 20 |
| L18940          | 4050300011257     | LUMILUX DE LUXE T8 18/940   | 18 | 940   | G13 590mm  | 25 20 |
| L18954          | 4050300018256     | LUMILUX DE LUXE T8 18/954   | 18 | 954   | G13 590mm  | 25 20 |
| L18965          | 4008321111371     | LUMILUX DE LUXE T8 18/965   | 18 | 965   | G13 590mm  | 25 20 |
| L30930          | 4050300014432     | LUMILUX DE LUXE T8 30/930   | 30 | 930   | G13 895mm  | 25 20 |
| L36930          | 4050300011318     | LUMILUX DE LUXE T8 36/930   | 36 | 930   | G13 1200mm | 25 20 |
| L36940          | 4050300011301     | LUMILUX DE LUXE T8 36/940   | 36 | 940   | G13 1200mm | 25 20 |
| L36954          | 4050300018263     | LUMILUX DE LUXE T8 36/954   | 36 | 954   | G13 1200mm | 25 20 |
| L369541         | 4050300024196     | LUMILUX DE LUXE T8 36/954-1 | 36 | 954-1 | G13 970mm  | 25 20 |
| L36965          | 4008321111395     | LUMILUX DE LUXE T8 36/965   | 36 | 965   | G13 1200mm | 25 20 |
| L58930          | 4050300011363     | LUMILUX DE LUXE T8 58/930   | 58 | 930   | G13 1500mm | 25 20 |
| L58940          | 4050300011356     | LUMILUX DE LUXE T8 58/940   | 58 | 940   | G13 1500mm | 25 20 |
| L58954          | 4050300018270     | LUMILUX DE LUXE T8 58/954   | 58 | 954   | G13 1500mm | 25 20 |
| L58965          | 4008321090034     | LUMILUX DE LUXE T8 58/965   | 58 | 965   | G13 1500mm | 25 20 |

Perfectly matched with QUICKTRONIC® electronic control gear




All orders must be multiples of sales pack

## Fluorescent Tubes

**COLOR proof T8**

- Triphosphor tube 26mm (1in) diameter
- Deluxe triphosphor tube
- The best colour rendering
- Ideal for colour matching in reprographic workshops, photographic laboratories and dental laboratories



**NEW**  
**NEW**  
**NEW**

| Product ID Code | EAN (Single Pack) | Product Description | W  | COLOR |     | I [mm] |    | PPG |
|-----------------|-------------------|---------------------|----|-------|-----|--------|----|-----|
| L18950          | 4008321423023     | COLOR proof T8 18W  | 18 | 950   | G13 | 590mm  | 10 | 23  |
| L36950          | 4008321423047     | COLOR proof T8 36W  | 36 | 950   | G13 | 1200mm | 10 | 23  |
| L58950          | 4008321423061     | COLOR proof T8 58W  | 58 | 950   | G13 | 1500mm | 10 | 23  |

Perfectly matched with QUICKTRONIC® electronic control gear

**BIOLUX® T8**

- Triphosphor tube 26mm (1in) diameter
- Full spectrum tube with 6500K colour temperature
- Excellent colour rendering
- Ideal for work areas deficient of natural daylight where colour rendition is important

| Product ID Code | EAN (Single Pack) | Product Description | W  | COLOR |     | I [mm]     |    | PPG |
|-----------------|-------------------|---------------------|----|-------|-----|------------|----|-----|
| L18965BIO       | 4050300270807     | BIOLUX T8 18W       | 18 | 965   | G13 | 600mm/2ft  | 10 | 23  |
| L30965BIO       | 4050300302461     | BIOLUX T8 30W       | 30 | 965   | G13 | 900mm/3ft  | 10 | 23  |
| L36965BIO       | 4050300270821     | BIOLUX T8 36W       | 36 | 965   | G13 | 1200mm/4ft | 10 | 23  |
| L58965BIO       | 4050300370613     | BIOLUX T8 58W       | 58 | 965   | G13 | 1500mm/5ft | 10 | 23  |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack




## Fluorescent Tubes

**FLUORA® T8**

- Triphosphor tube 26mm (1in) diameter
- Ideal for stimulating healthy plant growth

| Product ID Code | EAN (Single Pack) | Product Description | W  | COLOR | I [mm]         | PPG   |
|-----------------|-------------------|---------------------|----|-------|----------------|-------|
| L1577           | 4050300003214     | FLUORA T8 15W       | 15 | 77    | G13 438mm      | 10 23 |
| L1877           | 4050300004235     | FLUORA T818W        | 18 | 77    | G13 600mm/2ft  | 10 23 |
| L3077           | 4050300003238     | FLUORA T8 30W       | 30 | 77    | G13 895mm      | 10 23 |
| L3677           | 4050300003184     | FLUORA T8 36W       | 36 | 77    | G13 1200mm/4ft | 10 23 |
| L5877           | 4050300004259     | FLUORA T8 58W       | 58 | 77    | G13 1500mm/5ft | 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

**Coloured T8**

- Triphosphor tube 26mm (1in) diameter
- Ideal for effect lighting

| Product ID Code | EAN (Single Pack) | Product Description | W  | COLOR     | I [mm]         | PPG   |
|-----------------|-------------------|---------------------|----|-----------|----------------|-------|
| L1860           | 4050300024219     | Coloured T8 18/R    | 18 | 60 Red    | G13 600mm/2ft  | 10 23 |
| L1862           | 4008321232700     | Coloured T8 18/Y    | 18 | 62 Yellow | G13 600mm/2ft  | 12 23 |
| L1866           | 4050300024226     | Coloured T8 18/G    | 18 | 66 Green  | G13 600mm/2ft  | 10 23 |
| L1867           | 4050300024233     | Coloured T8 18/BL   | 18 | 67 Blue   | G13 600mm/2ft  | 10 23 |
| L3067           | 4050300366920     | Coloured T8 30/BL   | 30 | 67 Blue   | G13 900mm/3ft  | 10 23 |
| L3660           | 4050300024240     | Coloured T8 36/R    | 36 | 60 Red    | G13 1200mm/4ft | 10 23 |
| L3662           | 4008321232724     | Coloured T8 36/Y    | 36 | 62 Yellow | G13 1200mm/4ft | 12 23 |
| L3666           | 4050300024257     | Coloured T8 66/G    | 36 | 66 Green  | G13 1200mm/4ft | 10 23 |
| L3667           | 4050300024264     | Coloured T8 36/BL   | 36 | 67 Blue   | G13 1200mm/4ft | 10 23 |
| L3862           | 4008321232984     | Coloured T8 38/Y    | 38 | 62 Yellow | G13 1047mm     | 12 23 |
| L5860           | 4050300024271     | Coloured T8 58/R    | 58 | 60 Red    | G13 1500mm/5ft | 10 23 |
| L5862           | 4008321232748     | Coloured T8 62/Y    | 58 | 62 Yellow | G13 1500mm/5ft | 12 23 |
| L5866           | 4050300024288     | Coloured T8 66/G    | 58 | 66 Green  | G13 1500mm/5ft | 10 23 |
| L5867           | 4050300024295     | Coloured T8 67/BL   | 58 | 67 Blue   | G13 1500mm/5ft | 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## Fluorescent Tubes




1)

**NATURA® T8**

- Triphosphor tube 26mm (1in) diameter
- Ideal for meat and delicatessen displays

| Product ID Code | EAN (Single Pack) | Product Description | W  | Color | I [mm]         | PPG   |
|-----------------|-------------------|---------------------|----|-------|----------------|-------|
| L1576           | 4050300018287     | NATURA T8 15/76     | 15 | 76    | G13 438mm      | 10 23 |
| L1876           | 4050300010519     | NATURA T8 18/76     | 18 | 76    | G13 600mm/2ft  | 10 23 |
| L3076           | 4050300010540     | NATURA T8 30/76     | 30 | 76    | G13 900mm/3ft  | 10 23 |
| L3676           | 4050300010526     | NATURA T8 36/76     | 36 | 76    | G13 1200mm/4ft | 10 23 |
| L36761          | 4050300010557     | NATURA T8 36/76-1   | 36 | 76-1  | G13 1600mm     | 10 23 |
| L5876           | 4050300010533     | NATURA T8 58/76     | 58 | 76    | G13 1500mm/5ft | 10 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

1)

**NATURA® SPLIT Control T8**

- Triphosphor tube 26mm (1in) diameter
- Integral protective sleeve
- Can be used in open luminaires within the food sector
- Ideal for meat and delicatessen displays

| Product ID Code | EAN (Single Pack) | Product Description           | W  | Color | I [mm]     | PPG   |
|-----------------|-------------------|-------------------------------|----|-------|------------|-------|
| L1876SPS        | 4008321232762     | NATURA SPLIT Control T8 18/76 | 18 | 76    | G13 590mm  | 12 23 |
| L3076SPS        | 4008321232786     | NATURA SPLIT Control T8 30/76 | 30 | 76    | G13 895mm  | 12 23 |
| L5876SPS        | 4008321232847     | NATURA SPLIT Control T8 58/76 | 58 | 76    | G13 1500mm | 12 23 |


Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack




## Fluorescent Tubes

**LUMILUX® SPLIT Control T8**

- Triphosphor tube 26mm (1in) diameter
- With plastic coating that retains splinters if the lamp is broken
- Ideal for food preparation areas and production lines

| Product ID Code | EAN (Single Pack) | Product Description             | W  | Color | I [mm]     | PPG   |
|-----------------|-------------------|---------------------------------|----|-------|------------|-------|
| L18840SPS       | 4008321232885     | LUMILUX SPLIT Control T8 18/840 | 18 | 840   | G13 590mm  | 12 23 |
| L36840SPS       | 4008321232823     | LUMILUX SPLIT Control T8 36/840 | 36 | 840   | G13 1200mm | 12 23 |
| L58840SPS       | 4008321232922     | LUMILUX SPLIT Control T8 58/840 | 58 | 840   | G13 1500mm | 12 23 |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)**LUMILUX® COLOR Control T8**

- Triphosphor tube 26mm (1in) diameter
- With neutral density UV filter
- Ideal light source for museums, offices and exhibitions

| Product ID Code | EAN (Single Pack) | Product Description             | W  | Color | I [mm]     | PPG   |
|-----------------|-------------------|---------------------------------|----|-------|------------|-------|
| L18940UVS       | 4008321050014     | LUMILUX COLOR Control T8 18/940 | 18 | 940   | G13 590mm  | 12 23 |
| L18954UVS       | 4008321120229     | LUMILUX COLOR Control T8 18/954 | 18 | 954   | G13 590mm  | 12 23 |
| L36940UVS       | 4008321050038     | LUMILUX COLOR Control T8 36/940 | 36 | 940   | G13 1200mm | 12 23 |
| L36954UVS       | 4008321120243     | LUMILUX COLOR Control T8 36/954 | 36 | 954   | G13 1200mm | 12 23 |
| L58940UVS       | 4008321050090     | LUMILUX COLOR Control T8 58/940 | 58 | 940   | G13 1500mm | 12 23 |
| L58954UVS       | 4008321049957     | LUMILUX COLOR Control T8 58/954 | 58 | 954   | G13 1500mm | 12 23 |

Perfectly matched with QUICKTRONIC® electronic control gear



All orders must be multiples of sales pack


## Fluorescent Tubes



1)


**LUMILUX® CHIP Control T8**

- Triphosphor tube 26mm (1in) diameter
- Yellow tube with neutral density UV and blue light filter
- With neutral density UV and blue light filter
- Ideal light source for microchip production and printing press applications



| Product ID Code | EAN (Single Pack) | Product Description          | W  | COLOR     |     | I [mm] |    | PPG |
|-----------------|-------------------|------------------------------|----|-----------|-----|--------|----|-----|
| L1862           | 4008321232700     | LUMILUX CHIP Control T8 18/Y | 18 | 62 Yellow | G13 | 590mm  | 12 | 23  |
| L3662           | 4008321232724     | LUMILUX CHIP Control T8 36/Y | 36 | 62 Yellow | G13 | 1200mm | 12 | 23  |
| L3862           | 4008321232984     | LUMILUX CHIP Control T8 38/Y | 38 | 62 Yellow | G13 | 1047mm | 12 | 23  |
| L5862           | 4008321232748     | LUMILUX CHIP Control T8 58/Y | 58 | 62 Yellow | G13 | 1500mm | 12 | 23  |

Perfectly matched with QUICKTRONIC® electronic control gear

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)**U-SHAPED**

- U-shaped tubes
- Ideal light source for square luminaires in modular sizes

| Product ID Code | EAN (Single Pack) | Product Description     | W  | COLOR |      | I [mm] |    | PPG |
|-----------------|-------------------|-------------------------|----|-------|------|--------|----|-----|
| L18830U         | 4008321959904     | U-Shaped T8 tube 18/830 | 18 | 830   | 2G13 | 310mm  | 24 | 23  |
| L18840U         | 4008321469168     | U-Shaped T8 tube 18/840 | 18 | 840   | 2G13 | 310mm  | 24 | 23  |
| L36830U         | 4008321959911     | U-Shaped T8 tube 36/830 | 36 | 830   | 2G13 | 607mm  | 12 | 23  |
| L36840U         | 4008321469182     | U-Shaped T8 tube 36/840 | 36 | 840   | 2G13 | 607mm  | 12 | 23  |
| L58830U         | 4008321959041     | U-Shaped T8 tube 58/830 | 58 | 830   | 2G13 | 765mm  | 12 | 23  |
| L58840U         | 4008321469205     | U-Shaped T8 tube 58/840 | 58 | 840   | 2G13 | 765mm  | 12 | 23  |


Perfectly matched with QUICKTRONIC® electronic control gear

NEW  
NEW  
NEW  
NEW  
NEW  
NEW

All orders must be multiples of sales pack




## Fluorescent Tubes

**LUMILUX® CIRCULAR**

- LUMILUX® Circular tubes with G10Q base
- Ideal for office lighting

| Product ID Code | EAN (Single Pack) | Product Description  | W  | COLOR |      | I [mm]     |    | PPG |
|-----------------|-------------------|----------------------|----|-------|------|------------|----|-----|
| L22840C         | 4008321581082     | Circular tube 22/840 | 22 | 840   | G10Q | 216mm dia. | 12 | 21  |
| L22865C         | 4008321581105     | Circular tube 22/865 | 22 | 865   | G10Q | 216mm dia. | 12 | 21  |
| L22827C         | 4008321581068     | Circular tube 22/827 | 22 | 827   | G10Q | 216mm dia. | 12 | 21  |
| L32865C         | 4008321581167     | Circular tube 32/865 | 32 | 865   | G10Q | 305mm dia. | 12 | 21  |
| L32827C         | 4008321581129     | Circular tube 32/827 | 32 | 827   | G10Q | 305mm dia. | 12 | 21  |
| L32840C         | 4008321581143     | Circular tube 32/840 | 32 | 840   | G10Q | 305mm dia. | 12 | 21  |
| L40865C         | 4008321960139     | Circular tube 40/865 | 40 | 865   | G10Q | 406mm dia. | 12 | 21  |
| L40840C         | 4050300014845     | Circular tube 40/840 | 40 | 840   | G10Q | 406mm dia. | 12 | 21  |

Perfectly matched with QUICKTRONIC® electronic control gear



All orders must be multiples of sales pack

## Fluorescent Tubes

**T2 FM® FLUORESCENT MINIATURE**

- 7mm diameter
- Ideal for slim luminaires for display lighting

| Product ID Code | EAN (Single Pack) | Product Description                | W  | COLOR |      | I [mm]  |    | PPG |
|-----------------|-------------------|------------------------------------|----|-------|------|---------|----|-----|
| FM6730          | 4008321157546     | T2 FM FLUORESCENT MINIATURE 6/730  | 6  | 730   | W4.3 | 218.3mm | 20 | 23  |
| FM6740          | 4008321157577     | T2 FM FLUORESCENT MINIATURE 6/740  | 6  | 740   | W4.3 | 218.3mm | 20 | 23  |
| FM6760          | 4008321157607     | T2 FM FLUORESCENT MINIATURE 6/760  | 6  | 760   | W4.3 | 218.3mm | 20 | 23  |
| FM8730          | 4008321157638     | T2 FM FLUORESCENT MINIATURE 8/730  | 8  | 730   | W4.3 | 319.9mm | 20 | 23  |
| FM8740          | 4008321157669     | T2 FM FLUORESCENT MINIATURE 8/740  | 8  | 740   | W4.3 | 319.9mm | 20 | 23  |
| FM8760          | 4008321157690     | T2 FM FLUORESCENT MINIATURE 8/760  | 8  | 760   | W4.3 | 319.9mm | 20 | 23  |
| FM11730         | 4008321157720     | T2 FM FLUORESCENT MINIATURE 11/730 | 11 | 730   | W4.3 | 421.5mm | 20 | 23  |
| FM11740         | 4008321157751     | T2 FM FLUORESCENT MINIATURE 11/740 | 11 | 740   | W4.3 | 421.5mm | 20 | 23  |
| FM11760         | 4008321157782     | T2 FM FLUORESCENT MINIATURE 11/760 | 11 | 760   | W4.3 | 421.5mm | 20 | 23  |
| FM13730         | 4008321157836     | T2 FM FLUORESCENT MINIATURE 13/730 | 13 | 730   | W4.3 | 523.1mm | 20 | 23  |
| FM13740         | 4008321157867     | T2 FM FLUORESCENT MINIATURE 13/740 | 13 | 740   | W4.3 | 523.1mm | 20 | 23  |
| FM13760         | 4008321157898     | T2 FM FLUORESCENT MINIATURE 13/760 | 13 | 760   | W4.3 | 523.1mm | 20 | 23  |

Perfectly matched with QUICKTRONIC® electronic control gear

All orders must be multiples of sales pack





## Fluorescent Tubes

**T12 FOR EXPLOSION PROOF LUMINAIRES SA TYPE**

- 38mm (1 1/2 in) diameter
- Ideal for normal and low ambient temperatures

| Product ID Code | EAN (Single Pack) | Product Description           |    |        |     |        |    |
|-----------------|-------------------|-------------------------------|----|--------|-----|--------|----|
| L20640SA        | 4050300018195     | T12 Explosion proof 20/640/SA | 20 | 20/640 | G13 | 590mm  | 25 |
| L40640SA        | 4050300018331     | T12 Explosion proof 40/640/SA | 40 | 20/640 | G13 | 1200mm | 25 |
| L65640SA        | 4050300018201     | T12 Explosion proof 65/640/SA | 65 | 20/640 | G13 | 1500mm | 25 |


**T12 FOR EXPLOSION PROOF LUMINAIRES XL TYPE**

- 38mm (1 1/2 in) diameter
- Single pin tube
- Ideal for volatile lighting applications especially oil rigs

| Product ID Code | EAN (Single Pack) | Product Description           |    |        |     |        |    |    |
|-----------------|-------------------|-------------------------------|----|--------|-----|--------|----|----|
| L20640X         | 4050300014630     | T12 Explosion proof 20/640/XL | 20 | 20/640 | Fa6 | 574mm  | 25 | 38 |
| L40640X         | 4050300014654     | T12 Explosion proof 40/640/XL | 40 | 20/640 | Fa6 | 1184mm | 25 | 38 |
| L65640X         | 4050300014616     | T12 Explosion proof 65/640/XL | 65 | 20/640 | Fa6 | 1484mm | 25 | 38 |

All orders must be multiples of sales pack

## Fluorescent Tubes

**FLUORESCENT STARTERS**

- For the reliable operation of fluorescent tubes

| Product ID Code     | EAN (Single Pack) | Product Description   | No. |        | PPG |
|---------------------|-------------------|---|-----|--------|-----|
| ST111               | 4050300854045     | 4W-80W single-tube 240V operation                                   | 1   | 25/400 | 28  |
| ST111SCH            | 4050300270166     | 4W-80W single-tube 240V operation bulk pack                         | 1   | 1200   | 28  |
| ST111HT             | 4050300854021     | 4W-80W single-tube 240V operation                                   | 1   | 400    | 28  |
| ST151               | 4050300854083     | 4W-22W series pair at 240V or single-tube operation 110V            | 2   | 400    | 28  |
| ST151SCH            | 4050300012803     | 4W-22W series pair at 240V or single-tube operation 110V, bulk pack | 2   | 1200   | 28  |
| <b>Twin blister</b> |                   |   |     |        |     |
| ST111BLI2           | 4050300064000     | 4W-80W single-tube 240V operation                                   | -   | 20     | 28  |
| ST151BLI2           | 4050300092638     | 4W-20W series pair at 240V or single-tube operation 110V            | -   | 20     | 28  |

**DEOS® FLUORESCENT STARTERS**

- Semi-electronic safety starters
- Superior advantages over conventional starters

| Product ID Code | EAN (Single Pack) | Product Description | No. |        | PPG |
|-----------------|-------------------|---------------------|-----|--------|-----|
| ST171           | 4050300854106     | ST171 DEOS 30-65W   | 1   | 25/200 | 28  |
| ST171SCH        | 4050300422855     | ST171SCH 38-80W     | 1   | 1200   | 28  |
| ST173           | 4050300854120     | ST173 DEOS 15-32W   | 3   | 25/200 | 28  |
| ST172           | 4050300854069     | ST172 DEOS 18-22W   | 2   | 25/200 | 28  |

All orders must be multiples of sales pack




Fluorescent Tubes

## Starter Application Guide

|  | Suitable for fluorescent tubes |     |     |     |     |     |     |     |      |      |     | Suitable for OSRAM DULUX® L&F |     |  |
|--|--------------------------------|-----|-----|-----|-----|-----|-----|-----|------|------|-----|-------------------------------|-----|--|
|  | 4W                             | 10W | 15W | 18W | 30W | 38W | 36W | 58W | 75W  | 70W  | 18W | 24W                           | 36W |  |
|  | 6W                             | 13W | 16W | 20W | 32W |     | 40W | 65W | 85W  | 100W |     |                               |     |  |
|  | 8W                             |     |     |     |     |     |     | 80W | 100W | 125W |     |                               |     |  |

### For single operation at 240V<sup>1)</sup>

|                     |   |   |   |   |   |   |   |   |  |  |   |   |   |
|---------------------|---|---|---|---|---|---|---|---|--|--|---|---|---|
| ST 111              | X | X | X | X | X | X | X | X |  |  | X | X | X |
| ST 171 <sup>2</sup> |   |   |   |   |   | X | X | X |  |  |   |   | X |
| ST173               |   |   | X | X | X |   |   |   |  |  | X | X |   |



### For series pair operation at 240V or single operation at 110V<sup>1)</sup>

|                     |   |  |   |   |  |   |   |   |  |  |   |   |   |
|---------------------|---|--|---|---|--|---|---|---|--|--|---|---|---|
| ST 151              | X |  | X | X |  |   |   |   |  |  | X | X |   |
| ST 171 <sup>2</sup> |   |  |   |   |  | X | X | X |  |  |   |   | X |

1) NOT suitable for OSRAM DULUX® S/E, D/E and T/E

2) Except 65W U-tube and 5ft 80W T12

All orders must be multiples of sales pack

## HIGH INTENSITY DISCHARGE LAMPS



# High Intensity Discharge Lamps

## Contents.

### CERAMIC METAL HALIDE LAMPS

|  |     |
|--|-----|
| POWERBALL® HQI® -T for enclosed luminaires                 | 122 |
| POWERBALL® HQI®-TM for enclosed luminaires                 | 123 |
| POWERBALL® HCI®-TC for enclosed luminaires                 | 124 |
| POWERBALL® HQI®-TF for enclosed luminaires                 | 124 |
| POWERBALL® HCI®-T and TC Shoplight for enclosed luminaires | 125 |
| POWERBALL® HQI®-TS for enclosed luminaires                 | 126 |
| POWERBALL® HQI®-TX/P for open luminaires                   | 126 |
| POWERBALL® HCI®-T/P for open and enclosed luminaires       | 127 |
| POWERBALL® HQI®-TT for enclosed luminaires                 | 127 |
| POWERBALL® HCI®-E/P for open and enclosed luminaires       | 128 |
| POWERBALL® HQI®-E for open and enclosed luminaires         | 129 |
| POWERBALL® HQI® 70W for enclosed luminaires                | 129 |
| POWERBALL® HCI®-R111 for open and enclosed luminaires      | 130 |
| POWERBALL® HCI®-PAR for open and enclosed luminaires       | 131 |

### QUARTZ METAL HALIDE LAMPS

|  |     |
|--|-----|
| POWERSTAR® HQI®-R for enclosed luminaires                      | 132 |
| POWERSTAR® HQI®-T for enclosed luminaires                      | 132 |
| POWERSTAR® HQI®-TS EXCELLENCE for enclosed luminaires          | 133 |
| POWERSTAR® HQI®-TS for enclosed luminaires                     | 134 |
| POWERSTAR® HQI®-TS High Wattage                                | 134 |
| POWERSTAR® HQI®-TS 2000W/D/S High Flux for enclosed luminaires | 135 |
| POWERSTAR® HQI®-TM for enclosed luminaires                     | 135 |
| POWERSTAR® HQI®-T for enclosed luminaires                      | 136 |
| POWERSTAR® HQI®-T NSI and NSI SUPER                            | 136 |
| POWERSTAR® HQI®-E for open and closed luminaires               | 137 |
| POWERSTAR® HQI®-E/P  | 138 |
| POWERSTAR® HQI®-E High Wattage                                 | 138 |
| POWERSTAR® HQI®-E NSI and NSI SUPER                            | 139 |

### HIGH PRESSURE SODIUM LAMPS

|  |     |
|--|-----|
| VIALOX® NAV®-E SUPER 4Y® (SON-E PLUS 4 YEAR)             | 140 |
| VIALOX® NAV®-E 4Y® (SON-E 4 YEAR)                        | 141 |
| VIALOX® NAV®-E (STANDARD SON-E) without internal igniter | 142 |
| VIALOX® NAV®-E 68W Plug-in (SON-E Plug-in)               | 142 |
| VIALOX® NAV®-E plug-in (SON-E plug-in)                   | 143 |
| VIALOX® NAV®-T SUPER 4Y® (SON-T PLUS 4 YEAR)             | 143 |
| VIALOX® NAV®-T 4Y® (SON-T 4 YEAR)                        | 144 |
| VIALOX® NAV®-T (STANDARD SON-T)                          | 144 |
| VIALOX® NAV®-TS SUPER 4Y® (SON-TS PLUS) and TS (SON-TS)  | 145 |
| PLANTASTAR®  | 146 |

### LOW PRESSURE SODIUM LAMPS

|                  |     |
|------------------|-----|
| SOX and SOX PLUS | 147 |
|------------------|-----|



### MERCURY VAPOUR LAMPS

|  |     |
|--|-----|
| HQL® SUPER DE LUXE (MBF SUPER DE LUXE) | 148 |
| HQL® DE LUXE (MBF DE LUXE)             | 148 |
| HQL® Standard (MBF)                    | 149 |
| HQL® R DE LUXE                         | 149 |





## HIGH INTENSITY DISCHARGE LAMPS – CERAMIC METAL HALIDE



### POWERBALL® HCl® -T for enclosed luminaires

- Compact single ended ceramic metal halide lamp
- Improved performance compared to conventional ceramic lamps
- Outstanding colour rendering and uniform distribution of light
- Ideal for showcasing merchandise and for indirect lighting

| Product ID Code | EAN (Single Pack) | Product Description            | W   | lm    | COLOR     |     | t [h]  | d [mm] | I [mm] | LCL a [mm] | Light No. | PPG   |
|-----------------|-------------------|--------------------------------|-----|-------|-----------|-----|--------|--------|--------|------------|-----------|-------|
| HCIT35WDLPB     | 4008321520258     | PB35W HCl-T 830                | 35  | 3600  | 830 - WDL | G12 | 12,000 | 19     | 100    | 56         | 1         | 12 29 |
| HCIT35NDLBP     | 4008321521026     | PB35N HCl-T 942                | 35  | 3500  | 942 - NDL | G12 | 12,000 | 19     | 100    | 56         | 1         | 12 29 |
| HCIT70WDLPB     | 4008321523402     | PB70W HCl-T 830                | 70  | 7300  | 830 - WDL | G12 | 12,000 | 19     | 100    | 56         | 1         | 12 29 |
| HCIT70NDLBP     | 4008321523488     | PB70N HCl-T 942                | 70  | 6800  | 942 - NDL | G12 | 12,000 | 19     | 100    | 56         | 1         | 12 29 |
| HCIT100830WDL   | 4008321523563     | PB100W HCl-T 830               | 100 | 9500  | 830 - WDL | G12 | 12,000 | 19     | 105    | 56         | 1         | 12 29 |
| HCIT100942NDL   | 4008321523587     | PB100N HCl-T 942               | 100 | 9300  | 942 - NDL | G12 | 12,000 | 19     | 105    | 56         | 1         | 12 29 |
| HCIT150WDLPB    | 4008321523600     | PB150W HCl-T 830               | 150 | 15000 | 830 - WDL | G12 | 12,000 | 25     | 105    | 56         | 1         | 12 29 |
| HCIT150NDLBP    | 4008321523648     | PB150N HCl-T 942               | 150 | 14500 | 942 - NDL | G12 | 12,000 | 25     | 105    | 56         | 1         | 12 29 |
| HCIT250WDLPB    | 4008321524225     | PB250W HCl-T 830 <sup>2)</sup> | 250 | 26000 | 830 - WDL | E40 | 12,000 | 46     | 226    | 150        | 2         | 12 29 |
| HCIT250NDLBP    | 4008321524249     | PB250N HCl-T 942 <sup>2)</sup> | 250 | 25000 | 942 - NDL | E40 | 12,000 | 46     | 226    | 150        | 2         | 12 29 |

Perfectly matched with POWERTRONIC® electronic control gear (PTi and PT FIT)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

2) Operate with NAV® control gear

NEW  
NEW


All orders must be multiples of sales pack



## High Intensity Discharge Lamps – Ceramic Metal Halide

**POWERBALL® HCI®-TM for enclosed luminaires**

- Compact single ended ceramic metal halide lamp
- Very high efficiency and improved performance compared to conventional ceramic lamps
- Outstanding colour rendering and uniform distribution of light
- G22 plug-in base for good positioning
- Hot re-strike available (HR version in GY22 base)
- Ideal for showcasing merchandise and for high power spotlights



**NEW**  
**NEW**  
**NEW**  
**NEW**  
**NEW**

| Product ID Code  | EAN (Single Pack) | Product Description                    | W   | lm    | Color   | t [h] | d [mm] | I [mm] | LCL A [mm] | PPG      |
|------------------|-------------------|--|-----|-------|---------|-------|--------|--------|------------|----------|
| HCITM250WDLPB    | 4008321524591     | PB250TMW HCI-TM 250W/930 <sup>1)</sup> | 250 | 26000 | 830-WDL | G22   | 12,000 | 28     | 175        | 90 10 29 |
| HCITM250WDLHR    | 4008321959423     | PBHCI-TM250W/930 HR <sup>2)</sup>      | 250 | 26000 | 830-WDL | GY22  | 12,000 | 28     | 175        | 90 10 29 |
| HCITM250NDLBPB   | 4008321524638     | PB250TMN HCI-TM 250W/942 <sup>1)</sup> | 250 | 25000 | 942-NDL | G22   | 12,000 | 28     | 175        | 90 10 29 |
| HCITM250NDLHR    | 4008321959430     | PBHCI-TM250W/942 HR <sup>2)</sup>      | 250 | 25000 | 942-NDL | GY22  | 12,000 | 28     | 175        | 90 10 29 |
| HCITM400930WDL   | 4008321524614     | PBHCI-TM 400W/930 <sup>1)</sup>        | 400 | 41000 | 930-WDL | G22   | 12,000 | 34     | 175        | 90 10 29 |
| HCITM400930WDLHR | 4008321959447     | PBHCI-TM400W/930 HR <sup>2)</sup>      | 400 | 41000 | 930-WDL | GY22  | 12,000 | 34     | 175        | 90 10 29 |
| HCITM400942NDL   | 4008321907691     | HCITM400942NDL 400W/942 <sup>1)</sup>  | 400 | 41000 | 942-NDL | G22   | 12,000 | 34     | 175        | 90 10 29 |
| HCITM400942NDL   | 4008321524577     | PB400TMN HCI-TM 400W/942 <sup>1)</sup> | 400 | 41000 | 942-NDL | G22   | 12,000 | -      | -          | 10 29    |
| HCITM400942NDLHR | 4008321959454     | PBHCI-TM400W/942 HR <sup>2)</sup>      | 400 | 41000 | 942-NDL | GY22  | 12,000 | 34     | 175        | 90 10 29 |

1) Operate with NAV® control gear

2) Operate with NAV® control gear/operate only with a suitable hot restart igniter with an ignition voltage of up to 25kV

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – Ceramic Metal Halide

**POWERBALL® HCI®-TC for enclosed luminaires**

- Extremely compact single ended ceramic metal halide lamp
- Excellent focus and directional light source for substituting halogen lighting
- New Secure Fix GU8.5 base ensures stable positioning
- Very high efficiency and improved performance compared to conventional ceramic lamps
- Outstanding colour rendering and uniform distribution of light
- Ideal for very small luminaires used in retail and hospitality lighting

| Product ID Code | EAN (Single Pack) | Product Description | W  | lm   | Color     |      | t [h]  |    | d [mm] |    | I [mm] |    | a [mm] | PPG |
|-----------------|-------------------|---------------------|----|------|-----------|------|--------|----|--------|----|--------|----|--------|-----|
| HCITC20WDLPB    | 4008321517647     | PB20TCW 830         | 20 | 1700 | 830 - WDL | G8.5 | 12,000 | 15 | 81     | 52 | 12     | 29 |        |     |
| HCITC35WDLPB    | 4008321517739     | PB35TCW 830         | 35 | 3500 | 830 - WDL | G8.5 | 12,000 | 15 | 81     | 52 | 12     | 29 |        |     |
| HCITC35NDLPB    | 4008321517784     | PB35TCN 942         | 35 | 3400 | 942 - NDL | G8.5 | 12,000 | 15 | 81     | 52 | 12     | 29 |        |     |
| HCITC70WDLPB    | 4008321521040     | PB70TCW 830         | 70 | 6900 | 830 - WDL | G8.5 | 12,000 | 15 | 81     | 52 | 12     | 29 |        |     |
| HCITC70NDLPB    | 4008321521866     | PB70TCN 942         | 70 | 6600 | 942 - NDL | G8.5 | 12,000 | 15 | 81     | 52 | 12     | 29 |        |     |

Perfectly matched with POWERTRONIC® electronic control gear (PTi and PT FIT)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)**POWERBALL® HCI®-TF for enclosed luminaires**

- The smallest compact single ended ceramic metal halide lamp from
- New twist and lock GU6.5 base ensures stable positioning
- Very high efficiency and improved performance compared to conventional ceramic lamps
- Outstanding colour rendering and distribution of light
- Operation only with ECG such as POWERTRONIC® PTi
- Ideal for very small luminaires used in shop, hotel, museum and exhibition lighting

| Product ID Code | EAN (Single Pack) | Product Description | W  | lm   | Color     |       | t [h]  |    | d [mm] |    | I [mm] |    | a [mm] | PPG |
|-----------------|-------------------|---------------------|----|------|-----------|-------|--------|----|--------|----|--------|----|--------|-----|
| HCITF20WDLPB    | 4008321517685     | PB20TFW 830         | 20 | 1700 | 830 - WDL | GU6.5 | 12,000 | 13 | 57     | 30 | 12     | 29 |        |     |
| HCITF35WDLPB    | 4008321964427     | PB35TFW 930         | 35 | 3400 | 930 - WDL | GU6.5 | 12,000 | 13 | 57     | 30 | 12     | 29 |        |     |

Perfectly matched with POWERTRONIC® electronic control gear (PTi)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

NEW

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – Ceramic Metal Halide




SHOPLIGHT

**POWERBALL® HCI®-T Shoplight for enclosed luminaires**

- Compact single ended ceramic metal halide lamp
- Specifically developed to meet the lighting requirements of shop interiors
- Exceptional natural colour rendering : Ra 95 especially red tones
- Perfect solution where colour rendering and colour matching are an important criteria
- Ideal for the optimum presentation of merchandise

| Product ID Code | EAN (Single Pack) | Product Description | W  | lm   | COLOR     |     | t [h]  |    |     | LCL a [mm] |    | PPG |
|-----------------|-------------------|---------------------|----|------|-----------|-----|--------|----|-----|------------|----|-----|
| HCIT35930WDLPB  | 4008321521002     | PB35WSL 930 SHOP    | 35 | 2800 | 930 - WDL | G12 | 12,000 | 19 | 100 | 56         | 12 | 29  |
| HCIT70930PB     | 4008321523440     | PB70WSL 930 SHOP    | 70 | 6300 | 930 - WDL | G12 | 12,000 | 19 | 100 | 56         | 12 | 29  |

Perfectly matched with POWERTRONIC® electronic control gear (PTI)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

SHOPLIGHT

**POWERBALL® HCI®-TC Shoplight for enclosed luminaires**

- Compact single ended ceramic metal halide lamp
- Specifically developed to meet the lighting requirements of shop interiors
- New Secure Fix GU8.5 base ensures stable positioning
- Exceptional natural colour rendering : Ra 95 especially red tones
- Perfect solution where colour rendering and colour matching are an important criteria
- Ideal for the optimum presentation of merchandise

| Product ID Code | EAN (Single Pack) | Product Description | W  | lm   | COLOR     |      | t [h]  |    |    | LCL a [mm] |    | PPG |
|-----------------|-------------------|---------------------|----|------|-----------|------|--------|----|----|------------|----|-----|
| HCITC35930PB    | 4008321517760     | PB35CWSL TC 35W/930 | 35 | 2800 | 930 - WDL | G8.5 | 12,000 | 15 | 81 | 52         | 12 | 29  |
| HCITC70930PB    | 4008321520968     | PB70CWSL TC 70W/930 | 70 | 6300 | 930 - WDL | G8.5 | 12,000 | 15 | 81 | 52         | 12 | 29  |

Perfectly matched with POWERTRONIC® electronic control gear (PTI)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## High Intensity Discharge Lamps – Ceramic Metal Halide

**POWERBALL® HCI®-TS for enclosed luminaires**

- Compact double ended ceramic metal halide lamp
- Suitable for hot restrike (70W, 150W)
- Very high efficiency and improved performance compared to conventional ceramic lamps
- Outstanding colour rendering and distribution of light
- Ideal for lighting shop interiors, reception areas, museums, exhibition halls, buildings and bridges

| Product ID Code   | EAN (Single Pack) | Product Description               | W   | lm    | Color   | t [h]   | d [mm] | I [mm] | LCL a [mm] | LED No. | PPG |
|-------------------|-------------------|-----------------------------------|-----|-------|---------|---------|--------|--------|------------|---------|-----|
| HCITS70WDLPB      | 4008321523525     | PB70SW -TS 70W/830 <sup>1)</sup>  | 70  | 6800  | 830-WDL | RX7s    | 12,000 | 20     | 120        | 60      | 2   |
| HCITS70NDLBP      | 4008321523549     | PB70SN -TS 70W/942 <sup>1)</sup>  | 70  | 6500  | 942-NDL | RX7s    | 12,000 | 20     | 120        | 60      | 2   |
| HCITS150WDLBP     | 4008321517814     | PB15SW -TS 150W/830 <sup>1)</sup> | 150 | 14500 | 830-WDL | RX7s-24 | 12,000 | 23     | 138        | 69      | 2   |
| HCITS150NDLBP     | 4008321517838     | PB15SN -TS 150W/942 <sup>1)</sup> | 150 | 14400 | 942-NDL | RX7s-24 | 12,000 | 23     | 138        | 69      | 2   |
| HCITS250WDLBP     | 4008321519672     | PB25SW -TS 250W/830 <sup>2)</sup> | 250 | 25000 | 830-WDL | Fc2     | 12,000 | 25     | 162        | 81      | 3   |
| HCITS250NNDLBP    | 4008321519696     | PB25SN -TS 250W/942 <sup>2)</sup> | 250 | 25000 | 942-NDL | Fc2     | 12,000 | 25     | 162        | 81      | 3   |
| HCITS250942NNDLBP | 4008321519696     | PB25SN -TS 250W/942 <sup>3)</sup> | 250 | 25000 | 942-NDL | Fc2     | 12,000 | 25     | 162        | 81      | 3   |
| HCITS250942NNDLBP | 4008321519696     | PB25SN -TS 250W/942 <sup>3)</sup> | 250 | 25000 | 942-NDL | Fc2     | 12,000 | 25     | 162        | 81      | 3   |

Perfectly matched with POWERTRONIC® electronic control gear (PTi and PTo)

- 1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)
- 2) Suitable for standard igniters with an ignition voltage of 3.6 to 5 kV
- 3) Operate on NAV® control gear/Suitable for standard igniters with an ignition voltage of 3.6 to 5 kV

**POWERBALL® HCI®-TX/P for open luminaires**

- New “protected” ceramic metal halide lamp
- Integrated arc tube protection offers maximum protection against shattering
- New GU8.5 “Twist & Lock” base
- Approved for use in open and closed luminaires
- Ideal for shop, office and hospitality lighting


| Product ID Code | EAN (Single Pack) | Product Description | W  | lm   | Color     | t [h] | PPG          |
|-----------------|-------------------|---------------------|----|------|-----------|-------|--------------|
| HCITXP35930     | 4008321539366     | PBHCI-TX/P 35W/930  | 35 | 3300 | 930 - WDL | GU8.5 | 12,000 12 29 |
| HCITXP35942     | 4008321539380     | PBHCI-TX/P 35W/942  | 35 | 3300 | 942 - NDL | GU8.5 | 12,000 12 29 |
| HCITXP70930     | 4008321539403     | PBHCI-TX/P 70W/930  | 70 | 7300 | 930 - WDL | GU8.5 | 12,000 12 29 |
| HCITXP70942     | 4008321539427     | PBHCI-TX/P 70W/942  | 70 | 7300 | 942 - NDL | GU8.5 | 12,000 12 29 |

NEW  
NEW  
NEW  
NEW

All orders must be multiples of sales pack




## High Intensity Discharge Lamps – Ceramic Metal Halide

**POWERBALL® HCI®-T/P for open and enclosed luminaires**


- Single ended tubular ceramic metal halide lamp
- Integrated arc tube protection offers maximum protection against shattering
- Outstanding colour rendering and distribution of light
- Very high efficiency and improved performance compared to conventional ceramic lamps
- Ideal for use in open luminaires without cover shields such as exhibitions, sports halls, rail stations and industrial installations



| Product ID Code  | EAN (Single Pack) | Product Description  | W   | lm    | Color     |        | t [h]  |    | d [mm] |    | I [mm] | LCL a [mm] |  | PPG |
|------------------|-------------------|----------------------|-----|-------|-----------|--------|--------|----|--------|----|--------|------------|--|-----|
| <b>Clear</b>     |                   |                      |     |       |           |        |        |    |        |    |        |            |  |     |
| HCITP70830WDLCL  | 4008321518828     | PB70PWC T/P 70W/830  | 70  | 7200  | 830 - WDL | ES/E27 | 12,000 | 34 | 128    | 89 | 12     | 29         |  |     |
| HCITP70942NDLCL  | 4008321518842     | PB70PNC T/P 70W/942  | 70  | 6700  | 942 - NDL | ES/E27 | 12,000 | 34 | 128    | 89 | 12     | 29         |  |     |
| HCITP100830WDLCL | 4008321518866     | PB10PWC T/P 100W/830 | 100 | 9000  | 830 - WDL | ES/E27 | 12,000 | 40 | 133    | 89 | 12     | 29         |  |     |
| HCITP100942NDLCL | 4008321518880     | PB10PNC T/P 100W/942 | 100 | 8800  | 942 - NDL | ES/E27 | 12,000 | 40 | 133    | 89 | 12     | 29         |  |     |
| HCITP150830WDLCL | 4008321518903     | PB15PWC T/P 150W/830 | 150 | 14500 | 830 - WDL | ES/E27 | 12,000 | 40 | 133    | 89 | 12     | 29         |  |     |
| HCITP150942NDLCL | 4008321518927     | PB15PNC T/P 150W/942 | 150 | 14500 | 942 - NDL | ES/E27 | 12,000 | 40 | 133    | 89 | 12     | 29         |  |     |



Perfectly matched with POWERTRONIC® electronic control gear (PTi)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)**POWERBALL® HCI®-TT for enclosed luminaires**

- Compact single ended ceramic metal halide lamp
- White light source similar to that of halogen shows surroundings in their natural colour
- Outstanding colour rendering and uniform distribution of light enhances safety
- Specifically developed for outdoor lighting and directly interchangeable with NAV® (SON) lamps
- Ideal for street and outdoor lighting applications



| Product ID Code | EAN (Single Pack) | Product Description | W   | lm    | Color     |         | t [h]  |    | d [mm] |     | I [mm] | LCL a [mm] |    | PPG |
|-----------------|-------------------|---------------------|-----|-------|-----------|---------|--------|----|--------|-----|--------|------------|----|-----|
| HCITT35830WDL   | 4008321533470     | PBHCI-TT 35W/830    | 35  | -     | 830 - WDL | ES/E27  | 12,000 | -  | -      | -   | -      | 12         | 29 |     |
| HCITT50830WDL   | 4008321959416*    | PBHCI-TT 50W/830    | 50  | 5000  | 830 - WDL | ES/E27  | 12,000 | 32 | 155    | 102 | 12     | 29         |    |     |
| HCITT70WDLPLB   | 4008321524263     | PB70-TT 70W/830     | 70  | 7000  | 830 - WDL | ES/E27  | 12,000 | 32 | 155    | 102 | 12     | 29         |    |     |
| HCITT100WDLPLB  | 4008321524287     | PBHCI-TT 100W/830   | 100 | 10000 | 830 - WDL | GES/E40 | 12,000 | 47 | 210    | 132 | 12     | 29         |    |     |
| HCITT150WDLPLB  | 4008321524300     | PB150-TT 150W/830   | 150 | 14500 | 830 - WDL | GES/E40 | 12,000 | 47 | 210    | 132 | 12     | 29         |    |     |
| HCITT250WDLPLB  | 4008321524324     | PBHCI-TT 250W/830   | 250 | 26000 | 830 - WDL | GES/E40 | 12,000 | 47 | 226    | 158 | 12     | 29         |    |     |


Perfectly matched with POWERTRONIC® electronic control gear (PTo)

\*In preparation at time of print. For further information please contact OSRAM

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## High Intensity Discharge Lamps – Ceramic Metal Halide

**POWERBALL® HCI®-E/P for open and enclosed luminaires**

- Single ended elliptical ceramic metal halide lamp
- Integrated arc tube protection offers maximum protection against shattering
- New 50W WDL Coated version is an ideal streetlight upgrade for HPS or retrofit for HPM lamps with new ballast and igniter
- Outstanding colour rendering and distribution of light
- Ideal for use in open luminaires without cover shields

| Product ID Code  | EAN (Single Pack) | Product Description         | W   | lm    | color     |        | t [h]  |    | I [mm] |    | PPG |
|------------------|-------------------|-----------------------------|-----|-------|-----------|--------|--------|----|--------|----|-----|
| <b>Coated</b>    |                   |                             |     |       |           |        |        |    |        |    |     |
| HCIEP35830WDLCO  | 4008321518408     | PB35EPW HCI-E/P 35W/830     | 35  | 3200  | 830 - WDL | ES/E27 | 12,000 | 54 | 138    | 12 | 29  |
| HCIEP35942NDLCO  | 4008321518446     | PB35EPN HCI-E/P 35W/942     | 35  | 3100  | 942 - NDL | ES/E27 | 12,000 | 54 | 138    | 12 | 29  |
| HCIEP50830WDL    | 4008321338488     | PB50EPW HCI-E/P 50W/830     | 50  | 4000  | 830 - WDL | ES/E27 | 12,000 | 54 | 138    | 12 | 29  |
| HCIEP70WDLPB     | 4008321518606     | PB70EPW HCI-E/P 70W/830     | 70  | 6700  | 830 - WDL | ES/E27 | 12,000 | 54 | 138    | 12 | 29  |
| HCIEP70942NDLCO  | 4008321518675     | PB70EPN HCI-E/P 70W/942     | 70  | 6300  | 942 - NDL | ES/E27 | 12,000 | 54 | 138    | 12 | 29  |
| HCIEP100WDLPB    | 4008321518804     | PB10EPW HCI-E/P 100W/830    | 100 | 8500  | 830 - WDL | ES/E27 | 12,000 | 54 | 138    | 12 | 29  |
| HCIEP100942CO    | 4008321518781     | PB10EPN HCI-E/P 100W/942    | 100 | 8300  | 942 - NDL | ES/E27 | 12,000 | 54 | 138    | 12 | 29  |
| HCIEP150830WDLCO | 4008321518743     | PB15EPW HCI-E/P 150W/830WDL | 150 | 13700 | 830 - WDL | ES/E27 | 12,000 | 54 | 138    | 12 | 29  |
| HCIEP150NDLBP    | 4008321518767     | PB15EPN HCI-E/P 150W/942NDL | 150 | 13700 | 942 - NDL | ES/E27 | 12,000 | 54 | 138    | 12 | 29  |

Perfectly matched with POWERTRONIC® electronic control gear (PTi and PTo)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

NEW


NEW

NEW

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – Ceramic Metal Halide

**POWERBALL® HCI®-E for open and enclosed luminaires**

- Single ended elliptical ceramic metal halide lamp
- Outstanding colour rendering and distribution of light
- Ideal for outdoor applications and also in areas with high ceilings such as factories, warehouses, exhibition halls, rail stations and industrial installations




| Product ID Code | EAN (Single Pack) | Product Description                 | W   | lm    | COLOR     |  | t [h]   |        | d [mm] |     | I [mm] |    | PPG |
|-----------------|-------------------|-------------------------------------|-----|-------|-----------|--|---------|--------|--------|-----|--------|----|-----|
| <b>Coated</b>   |                   |                                     |     |       |           |  |         |        |        |     |        |    |     |
| HCIE250WDLPB    | 4008321524188     | PB25EW HCI-E 250W/830 <sup>1)</sup> | 250 | 24500 | 830 - WDL |  | GES/E40 | 12,000 | 91     | 226 | 12     | 29 |     |
| HCIE250NDLPB    | 4008321524201     | PB25EN HCI-E 250W/942 <sup>1)</sup> | 250 | 22500 | 942 - NDL |  | GES/E40 | 12,000 | 91     | 226 | 12     | 29 |     |

1) Operate with NAV® Control gear

**POWERBALL HCI® 70W for enclosed luminaires**

- Direct replacement to HQL and NAV lamps
- Very good colour rendering
- Can be operated on NAV® control gear by replacing the igniter
- Ideal for white light solution for outdoor application



| Product ID Code | EAN (Single Pack) | Product Description | W  | lm   |  |  | t [h]  |    | d [mm] |    | I [mm] | LCL |  | PPG |
|-----------------|-------------------|---------------------|----|------|--|--|--------|----|--------|----|--------|-----|--|-----|
| HCIET70WDLPB    | 4008321549679     | PBHCI-ET 70W/WDL    | 70 | 6200 |  |  | 18,000 | 71 | 156    | 71 | 12     | 35  |  |     |

NEW!

All orders must be multiples of sales pack

## High Intensity Discharge Lamps – Ceramic Metal Halide

**POWERBALL® HCI®-R111 for open and enclosed luminaires**

- Ceramic metal halide lamp with integrated aluminium R111 metal reflector
- Integrated arc tube protection offering maximum protection against shattering
- A modern alternative to conventional halogen spotlights.
- Spot, flood and wide flood beam angles
- Outstanding colour rendering and uniform distribution of light
- New twist and lock GX8.5 base ensures stable positioning
- Ideal for spotlighting and floodlighting

| Product ID Code | EAN (Single Pack) | Product Description       | W  | COLOR     |     |  | t [h] |        | I [mm] |    | PPG |    |
|-----------------|-------------------|---------------------------|----|-----------|-----|--|-------|--------|--------|----|-----|----|
| HCIR1112083010D | 4008321519061     | PB20RW10 R111 20W/830 10D | 20 | 830 - WDL | 10° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1112083024D | 4008321519085     | PB20RW24 R111 20W/830 24D | 20 | 830 - WDL | 24° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1112083040D | 4008321519108     | PB20RW40 R111 20W/830 40D | 20 | 830 - WDL | 40° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1113583010D | 4008321519122     | PB35RW10 R111 35W/830 10D | 35 | 830 - WDL | 10° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1113583024D | 4008321519573     | PB35RW24 R111 35W/830 24D | 35 | 830 - WDL | 24° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1113583040D | 4008321519597     | PB35RW40 R111 35W/830 40D | 35 | 830 - WDL | 40° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1113594210D | 4008321519610     | PB35RN10 R111 35W/942 10D | 35 | 942 - NDL | 10° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1113594224D | 4008321519634     | PB35RN24 R111 35W/942 24D | 35 | 942 - NDL | 24° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1113594240D | 4008321519658     | PB35RN40 R111 35W/942 40D | 35 | 942 - NDL | 40° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1117083010D | 4008321518941     | PB70RW10 R111 70W/830 10D | 70 | 830 - WDL | 10° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1117083024D | 4008321518965     | PB70RW24 R111 70W/830 24D | 70 | 830 - WDL | 24° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1117083040D | 4008321518989     | PB70RW40 R111 70W/830 40D | 70 | 830 - WDL | 40° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1117042100  | 4008321519009     | PB70RN10 R111 70W/942 10D | 70 | 942 - NDL | 10° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1117094224D | 4008321519023     | PB70RN24 R111 70W/942 24D | 70 | 942 - NDL | 24° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |
| HCIR1117094240D | 4008321519047     | PB70RN40 R111 70W/942 40D | 70 | 942 - NDL | 40° |  | GX8.5 | 12,000 | 111    | 95 | 6   | 29 |


Perfectly matched with POWERTRONIC® electronic control gear (PTi and PT FIT)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)NEW  
NEW  
NEW


All orders must be multiples of sales pack



## High Intensity Discharge Lamps – Ceramic Metal Halide

**POWERBALL® HCI®-PAR for open and enclosed luminaires**

- Ceramic metal halide lamp with integrated glass reflector
- In PAR 20 and PAR 30 sizes and spot 10° and flood 30° beam angles
- Outstanding colour rendering and uniform distribution of light
- Ideal for spotlighting and floodlighting



| Product ID Code                  | EAN (Single Pack)       | Product Description    | [W]    | [COLOR] | [A] | [E] | [t [h]] | [d [mm]] | [l [mm]] | [PPG] |
|----------------------------------|-------------------------|------------------------|--------|---------|-----|-----|---------|----------|----------|-------|
| <b>PAR 20</b>                    |                         |                        |        |         |     |     |         |          |          |       |
| HCIPAR2035830WDLSP 4008321964502 | PB35SP20 PAR20 35W/830  | 35 830 - WDL Spot E27  | 12,000 | 65      | 95  | 12  | 29      |          |          |       |
| HCIPAR2035830WDLFL 4008321964519 | PB35FL20 PAR20 35W/830  | 35 830 - WDL Flood E27 | 12,000 | 65      | 95  | 12  | 29      |          |          |       |
| HCIPAR2035SP 4008321964526       | PB35SP20N PAR20 35W/942 | 35 942 - NDL Spot E27  | 12,000 | 65      | 95  | 12  | 29      |          |          |       |
| HCIPAR2035FL 4008321964533       | PB35FL20N PAR20 35W/942 | 35 942 - NDL Flood E27 | 12,000 | 65      | 95  | 12  | 29      |          |          |       |
| <b>PAR 30</b>                    |                         |                        |        |         |     |     |         |          |          |       |
| HCIPAR3035WDLPBSP 4008321964540  | PB35SP30 PAR30 35W/830  | 35 830 - WDL Spot E27  | 12,000 | 97      | 125 | 6   | 29      |          |          |       |
| HCIPAR3035WDLPBFL 4008321964557  | PB35FL30 PAR30 35W/830  | 35 830 - WDL Flood E27 | 12,000 | 97      | 125 | 6   | 29      |          |          |       |
| HCIPAR3035SP 4008321964564       | PB35SP30N PAR30 35W/942 | 35 942 - NDL Spot E27  | 12,000 | 97      | 125 | 6   | 29      |          |          |       |
| HCIPAR3035FL 4008321964571       | PB35FL30N PAR30 35W/942 | 35 942 - NDL Flood E27 | 12,000 | 97      | 125 | 6   | 29      |          |          |       |
| HCIPAR3070WDLPBSPU 4008321964588 | PB70SP30 PAR30 70W/830  | 70 830 - WDL Spot E27  | 12,000 | 97      | 125 | 6   | 29      |          |          |       |
| HCIPAR3070WDLFL 4008321964595    | PB70FL30 PAR30 70W/830  | 70 830 - WDL Flood E27 | 12,000 | 97      | 125 | 6   | 29      |          |          |       |
| HCIPAR3070SPDL40 4008321964601   | PB704030 PAR30 70W/830  | 70 830 - WDL 40° E27   | 12,000 | 97      | 125 | 6   | 29      |          |          |       |
| HCIPAR3070SP 4008321964618       | PB70SP30N PAR30 70W/942 | 70 942 - NDL Spot E27  | 12,000 | 97      | 125 | 6   | 29      |          |          |       |
| HCIPAR3070FL 4008321964625       | PB70FL30N PAR30 70W/942 | 70 942 - NDL Flood E27 | 12,000 | 97      | 125 | 6   | 29      |          |          |       |

Perfectly matched with POWERTRONIC® electronic control gear (PTi)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack




## HIGH INTENSITY DISCHARGE LAMPS – QUARTZ METAL HALIDE



### POWERSTAR® HQI®-R for enclosed luminaires

- Single ended elliptical quartz metal halide lamp
- With integral pre-focused dichroic reflector
- Ideal for light guide systems

| Product ID Code | EAN (Single Pack) | Product Description | W   | COLOR  |  | t [h] | d [mm] | I [mm] |    | PPG |
|-----------------|-------------------|---------------------|-----|--------|--|-------|--------|--------|----|-----|
| HQIR150NDL      | 4008321528070     | H150NR HQI-R        | 150 | NDL/F0 |  | 9.000 | 95     | 93     | 12 | 29  |



### POWERSTAR® HQI®-T for enclosed luminaires

- Compact single ended quartz metal halide lamp
- Amongst the shortest metal halide lamps in the world for general lighting
- Available in Warm White DE LUXE (WDL) and Neutral White DE LUXE (NDL)
- Ideal for high quality economical lighting

| Product ID Code | EAN (Single Pack) | Product Description | W   | Im    | COLOR |     | t [h] | d [mm] | I [mm] |    | PPG |
|-----------------|-------------------|---------------------|-----|-------|-------|-----|-------|--------|--------|----|-----|
| HQIT70NDL       | 4008321524799     | H70N HQI-T          | 70  | 5800  | NDL   | G12 | 9.000 | 84     | 56     | 12 | 29  |
| HQIT70WDL       | 4008321524775     | H70W HQI-T          | 70  | 5300  | WDL   | G12 | 9.000 | 84     | 56     | 12 | 29  |
| HQIT150NDLPRO   | 4008321524850     | H150N HQI-T         | 150 | 13000 | NDL   | G12 | 9.000 | 84     | 56     | 12 | 29  |
| HQIT150WDLPRO   | 4008321524836     | H150W HQI-T         | 150 | 13000 | WDL   | G12 | 9.000 | 84     | 56     | 12 | 29  |

Perfectly matched with POWERTRONIC® electronic control gear (PTi and PTo)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – Quartz Metal Halide

**POWERSTAR® HQI®-TS EXCELLENCE for enclosed luminaires**

- Long life double ended quartz metal halide lamps
- Increased efficiency, improved quality of light compared with conventional HQI®-TS lamps .
- High luminous efficacy (Up to 15% more light) and uniform distribution of light
- Up to 15% more light than standard HQI®-TS lamps
- Low thermal output
- Ideal for high quality economical lighting


| Product ID Code        | EAN (Single Pack) | Product Description | W                 | lm    | Color |         | t [h]   |          |         | PPG       |           |
|------------------------|-------------------|---------------------|-------------------|-------|-------|---------|---------|----------|---------|-----------|-----------|
| HQITS70WDLEXC          | 4008321964281     | HQITS70WDLEXC       | 70                | 6200  | WDL   |         | RX7s    | 12,000** | 19      | 117 12 30 |           |
| HQITS70NDLEXC          | 4008321964304     | HQITS70NDLEXC       | 70                | 6500  | NDL   |         | RX7s    | 12,000** | 19      | 117 12 30 |           |
| HQITS70DEXC            | 4008321964328     | HQITS70DEXC         | 70                | 6200  | D     |         | RX7s    | 12,000** | 19      | 117 12 30 |           |
| HQITS150WDLEXC         | 4008321964342     | HQITS150WDLEXC      | 150               | 12000 | WDL   |         | RX7s-24 | 12,000** | 23      | 135 12 30 |           |
| HQITS150NDLEXC         | 4008321964366     | HQITS150NDLEXC      | 150               | 12500 | NDL   |         | RX7s-24 | 12,000** | 23      | 135 12 30 |           |
| HQITS150DEXC           | 4008321964380     | HQITS150DEXC        | 150               | 13500 | D     |         | RX7s-24 | 12,000** | 23      | 135 12 30 |           |
| <b>Colour versions</b> |                   |                     |                   |       |       |         |         |          |         |           |           |
|                        | HQITS70BLEXC      | 4008321410115       | HQITS70W BL EXC   | 70    | –     | Blue    |         | RX7s-24  | 12000** | 19        | 117 12 30 |
|                        | HQITS150BLEXC     | 4008321410153       | HQITS150W BL EXC  | 150   | –     | Blue    |         | RX7s-24  | 12000** | 23        | 135 12 30 |
|                        | HQITS70GNEXC      | 4008321410139       | HQITS70W GR EXC   | 70    | –     | Green   |         | RX7s-24  | 12000** | 19        | 117 12 31 |
|                        | HQITS150GNEXC     | 4008321410177       | HQITS150W GR EXC  | 150   | –     | Green   |         | RX7s-24  | 12000** | 23        | 135 12 32 |
|                        | –                 | –                   | HQITS70W MA EXC*  | 70    | –     | Magenta |         | RX7s-24  | 12000** | 19        | 117 12 33 |
|                        | –                 | –                   | HQITS150W MA EXC* | 150   | –     | Magenta |         | RX7s-24  | 12000** | 23        | 135 12 34 |

Perfectly matched with POWERTRONIC® electronic control gear (PTi and PTo)

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)


\*In preparation at time of print. For further information please contact OSRAM

\*\*with CCG. ECG +30%



All orders must be multiples of sales pack

## High Intensity Discharge Lamps – Quartz Metal Halide



**POWERSTAR® HQI®-TS for enclosed luminaires**

- Compact double ended quartz metal halide lamp
- Ideal for high quality economical lighting

| Product ID Code | EAN (Single Pack) | Product Description             | W   | Im    | COLOR | t [h] | d [mm] | I [mm] | LCL a [mm] | Light No. | PPG     |
|-----------------|-------------------|---------------------------------|-----|-------|-------|-------|--------|--------|------------|-----------|---------|
| HQITS250WDL     | 4008321525130     | H250SW HQI-TS                   | 250 | 22000 | WDL   | FC2   | 12,000 | 25     | 162        | 82        | 1 12 29 |
| HQITS250NDL     | 4008321525178     | H25 SND HQI-TS                  | 250 | 20000 | NDL   | FC2   | 12,000 | 25     | 162        | 82        | 1 12 29 |
| HQITS250D       | 4008321525215     | H250SD HQI-TS                   | 250 | 20000 | D     | FC2   | 12,000 | 26     | 162        | 82        | 1 12 29 |
| HQITS400NDL     | 4008321525758     | H400SN HQI-TS <sup>1)</sup>     | 400 | 36000 | NDL   | FC2   | 12,000 | 33     | 206        | 103       | 2 12 29 |
| HQITS400D       | 4008321525734     | H400SD PRO HQI-TS <sup>2)</sup> | 400 | 37000 | D     | FC2   | 12,000 | 33     | 206        | 103       | 2 12 29 |

1) Operate only with NAV® control gear

2) Operate with NAV® control gear

**POWERSTAR® HQI®-TS High Wattage**

- Double ended quartz metal halide lamps
- Without outer bulb
- New 1000W PRO version with natural colour appearance and very good colour rendering
- Available with short or long arc
- Ideal for larger floodlighting applications

| Product ID Code  | EAN (Single Pack) | Product Description     | W    | Im     | COLOR | t [h]  | d [mm] | I [mm] | LCL a [mm] | Light No. | PPG     |
|------------------|-------------------|-------------------------|------|--------|-------|--------|--------|--------|------------|-----------|---------|
| <b>Short Arc</b> |                   |                         |      |        |       |        |        |        |            |           |         |
| HQITS1000NDSL    | 4050300349916     | H1KDSL HQI-TS 1000W/D/S | 1000 | 90000  | NDL   | Cables | 6,000  | 36     | 187        | 93        | 1 10 29 |
| HQITS1000DS      | 4050300300092     | H1KDS HQI-TS 1000W/D/S  | 1000 | 90000  | D     | Cables | 6,000  | 36     | 187        | 93        | 1 10 29 |
| HQITS1000DSPRO   | 4008321525475     | H1KDS PRO HQI-TS 1000W  | 1000 | 90000  | D     | Cables | 6,000  | 36     | 187        | 93        | 1 10 29 |
| HQITS2000NDSL    | 4008321525499     | H2KDSL PRO HQI-TS 2000W | 2000 | 215000 | NDL   | Cables | 6,000  | 36     | 187        | 93        | 1 10 29 |
| HQITS2000DS      | 4050300271682     | H2KDS 2000W/D/S         | 2000 | 200000 | D     | Cables | 6,000  | 36     | 187        | 93        | 2 10 29 |
| <b>Long Arc</b>  |                   |                         |      |        |       |        |        |        |            |           |         |
| HQITS2000NL      | 4050300607344     | H2KNL HQI-TS2000W/N     | 2150 | 230000 | N     | Cables | 6,000  | 32     | 274        | 137       | 3 10 29 |
| HQITS2000DL400   | 4008321931825     | H2KDL HQI-TS 2000W/D/LK | 2150 | 205000 | D     | Cables | 6,000  | 32     | 274        | 137       | 3 10 29 |


NEW

NEW

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – Quartz Metal Halide


**POWERSTAR® HQI®-TS 2000W/D/S High Flux for enclosed luminaires**

- Compact double ended quartz metal halide lamp
- Evolution of the HQI®-TS 2000W/D/S Short arc lamp with 10% more luminous flux
- Less total power consumption
- Suitable for hot restrike
- Ideal for professional sports lighting, TV broadcasting, large area lighting



| Product ID Code | EAN (Single Pack) | Product Description      | W    | lm     | Color | t [h] | d [mm] | I [mm] | LCL a [mm] | PPG      |
|-----------------|-------------------|--------------------------|------|--------|-------|-------|--------|--------|------------|----------|
| HQITS2000DSHF   | 4008321338310     | HQI-TS 2000W/D/S HF K12S | 2000 | 220000 | WDL   | Cable | 4,000  | 36     | 187        | 93 12 30 |

1) Operate only on a 12.2A control gear

**POWERSTAR® HQI®-TM for enclosed luminaires**

- Robust and very compact single ended quartz metal halide lamp
- Hot re-strike capability (GY22 base HR version only)
- Easy handling and optimum lamp positioning due to plug in bases
- Produce excellent directional light
- Ideal for large area lighting such as factories, airports, stadiums and industrial lighting


| Product ID Code | EAN (Single Pack) | Product Description                   | W    | lm    | Color  | t [h] | d [mm] | I [mm] | LCL a [mm] | PPG      |
|-----------------|-------------------|---------------------------------------|------|-------|--------|-------|--------|--------|------------|----------|
| HQITM600NDL     | 4008321959461*    | HQI-TM 600W/845 NDL <sup>1)</sup>     | 600  | 55000 | NDL    | G22   | 10,000 | 34     | 188        | 90 12 29 |
| HQITM600NDLHR   | 4008321959478*    | HQI-TM 600W/845 NDL HR <sup>2)</sup>  | 600  | 55000 | NDL HR | GY22  | 10,000 | 34     | 188        | 90 12 29 |
| HQITM600D       | 4008321959485*    | HQI-TM 600W/960 D <sup>1)</sup>       | 600  | 58000 | D      | G22   | 10,000 | 34     | 188        | 90 12 29 |
| HQITM600DHR     | 4008321959492*    | HQI-TM 600W/960 D HR <sup>2)</sup>    | 600  | 58000 | D HR   | GY22  | 10,000 | 34     | 188        | 90 12 29 |
| HQITM1000NDL    | 4008321959508*    | HQI-TM 1000W/845 NDL                  | 1000 | 92000 | NDL    | G22   | 10,000 | 38     | 188        | 90 12 29 |
| HQITM1000NDLHR  | 4008321959515*    | HQI-TM 1000W/845 NDL HR <sup>3)</sup> | 1000 | 92000 | NDL HR | GY22  | 10,000 | 38     | 188        | 90 12 29 |
| HQITM1000       | 4008321467553     | HQI-TM 1000W/960 D                    | 1000 | 97000 | D      | G22   | 10,000 | 38     | 188        | 90 12 29 |
| HQITM1000960DHR | 4008321959522*    | HQI-TM 1000W/960 D HR <sup>3)</sup>   | 1000 | 97000 | D HR   | GY22  | 10,000 | 38     | 188        | 90 12 29 |

\*In preparation at time of print. For further information please contact OSRAM

- 1) Operate with NAV® control gear
- 2) Operate only on suitable hot restart igniters with an ignition voltage of up to 25 kV/operate on NAV® control gear
- 3) Operate only on suitable hot restart igniters with an ignition voltage of up to 25 kV

All orders must be multiples of sales pack

## High Intensity Discharge Lamps – Quartz Metal Halide

**POWERSTAR® HQI®-T for enclosed luminaires**

- Single ended tubular quartz metal halide lamp
- Ideal for floodlighting buildings and sports facilities

| Product ID Code                                | EAN (Single Pack) | Product Description               | W    | lm     | Color   | t [h]   | $\phi$ d [mm] | I [mm] | LCL a [mm] | Light No. | PPG |
|--|-------------------|-----------------------------------|------|--------|---------|---------|---------------|--------|------------|-----------|-----|
| <b>Without igniter for enclosed luminaires</b> |                   |                                   |      |        |         |         |               |        |            |           |     |
| HQIT250D                                       | 4008321525710     | H250D T 250W/D PRO <sup>2)</sup>  | 250  | 20000  | D       | GES/E40 | 12,000        | 46     | 226        | 150       | 1   |
| HQIT400D                                       | 4008321525970     | H400D BT 400W/D PRO <sup>2)</sup> | 400  | 35000  | D       | GES/E40 | 12,000        | 62     | 285        | 175       | 4   |
| HQIT400N                                       | 4008321526786     | H400N T 400W/N                    | 400  | 42000  | N       | GES/E40 | 12,000        | 46     | 273        | 175       | 1   |
| HQIT1000N                                      | 4008321528285     | HQI-T 1000W/N                     | 1000 | 110000 | N       | GES/E40 | 12,000        | 76     | 345        | 220       | 3   |
| HQIT1000D                                      | 4008321527035     | H1KWD T 1000W/D                   | 1000 | 85000  | D       | GES/E40 | 12,000        | 76     | 345        | 220       | 3   |
| HQIT2000NESUPER                                | 4050300301860     | H2KNES T 2000W/N                  | 2000 | 240000 | N       | GES/E40 | 9,000         | 100    | 430        | 265       | 2   |
| HQIT2000D                                      | 4008321526809     | H2KWD T 2000W/D                   | 2000 | 180000 | D       | GES/E40 | 12,000        | 100    | 430        | 265       | 2   |
| <b>Coloured</b>                                |                   |                                   |      |        |         |         |               |        |            |           |     |
| HQIT400BLUE                                    | 4008321526861     | H400B HQI-T 400W BL <sup>3)</sup> | 400  | —      | BLUE    | GES/E40 | —             | 46     | 273        | 175       | 1   |
| HQIT400GREEN                                   | 4008321526847     | H400G HQI-T 400W GN <sup>3)</sup> | 400  | —      | GREEN   | GES/E40 | —             | 46     | 273        | 175       | 1   |
| HQIT400REDMAG                                  | 4008321526885     | H400M HQI-T 400W MA <sup>3)</sup> | 400  | —      | MAGENTA | GES/E40 | —             | 46     | 273        | 175       | 1   |
| <b>With igniter for enclosed luminaires</b>    |                   |                                   |      |        |         |         |               |        |            |           |     |
| HQIT2000N                                      | 4050300015347*    | 83330 T 2000W/N E40 <sup>1)</sup> | 2000 | 205000 | N       | GES/E40 | 9,000         | 100    | 430        | 265       | 2   |
| HQIT2000DI                                     | 4008321527011*    | H2KWD T 2000W/D/I <sup>1)</sup>   | 2000 | 180000 | D       | GES/E40 | —             | 100    | 430        | 265       | 2   |

\*In preparation at time of print. For further information please contact OSRAM

1) Operation without an external igniter

2) Operate with NAV® control gear

3) Operate with HQI® control gear

**POWERSTAR® HQI®-T NSI**

- Compact single ended quartz metal halide lamp
- Ideal for floodlighting buildings

| Product ID Code | EAN (Single Pack) | Product Description        | W   | lm    | Color | t [h]   | $\phi$ d [mm] | I [mm] | LCL a [mm] | PPG |    |
|-----------------|-------------------|----------------------------|-----|-------|-------|---------|---------------|--------|------------|-----|----|
| HQIT250NSI      | 4050300444604     | H25NSI HQI-T 250W/N/SI E40 | 250 | 20000 | N     | GES/E40 | 12,000        | 57     | 248        | 10  | 29 |
| HQIT400NSI      | 4050300376431     | H40NSI HQI-T 400W/N/SI E40 | 400 | 31000 | N     | GES/E40 | 12,000        | 57     | 248        | 10  | 29 |

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – Quartz Metal Halide

**POWERSTAR® HQI®-T NSI SUPER**




- Compact tubular single ended quartz metal halide lamp
- High lumen output and extra long life of 20,000 hours
- Ideal for industrial applications, trade shows, exhibition and sports halls and exterior floodlighting systems



| Product ID Code | EAN (Single Pack) | Product Description                     | W   | lm    | Color |  | t [h]   |        |    |           |
|-----------------|-------------------|---|-----|-------|-------|--|---------|--------|----|-----------|
| HQIT250NSISUPER | 4008321959584*    | HQI-T 250W/N/SI SUPER E40 <sup>1)</sup> | 250 | 19500 | N     |  | GES/E40 | 20,000 | 46 | 225 10 29 |
| HQIT400NSISUPER | 4008321959607*    | HQI-T 400W/N/SI SUPER E40 <sup>1)</sup> | 400 | 35000 | N     |  | GES/E40 | 20,000 | 46 | 275 10 29 |

\*In preparation at time of print. For further information please contact OSRAM

1) Operate with HQL® control gear



1

2

**POWERSTAR® HQI®-E for open and closed luminaires**

- Single ended elliptical quartz metal halide lamp
- Ideal for use in factories, offices, warehouses, rail stations and retail lighting




| Product ID Code | EAN (Single Pack) | Product Description                 | W   | lm    | Color |  | t [h]  |       |    |     |    |          |
|-----------------|-------------------|-------------------------------------|-----|-------|-------|--|--------|-------|----|-----|----|----------|
| <b>Clear</b>    |                   |                                     |     |       |       |  |        |       |    |     |    |          |
| HQIE70WDLCLEAR  | 4050300397788     | H70EWC HQI-E 70W/WDL                | 70  | 5200  | WDL   |  | ES/E27 | 9,000 | 55 | 141 | 89 | 1 20 29  |
| HQIE70NDLCLEAR  | 4050300397825     | H70ENC HQI-E 70W/NDL                | 70  | 5500  | WDL   |  | ES/E27 | 6,000 | 55 | 141 | 89 | 1 141 29 |
| HQIE100WDLCLEAR | 4050300351537     | H100EWC HQI-E 100W/WDL              | 100 | 8500  | WDL   |  | ES/E27 | 9,000 | 55 | 141 | 89 | 1 20 29  |
| HQIE100NDLCLEAR | 4050300345871     | H100ENC HQI-E 100W/NDL              | 100 | 8400  | NDL   |  | ES/E27 | 6,000 | 55 | 141 | 89 | 1 20 29  |
| HQIE150WDLCLEAR | 4050300433974     | H150EWC HQI-E 150W/WDL              | 150 | 12900 | WDL   |  | ES/E27 | 9,000 | 55 | 141 | 89 | 1 20 29  |
| HQIE150NDLCLEAR | 4050300434018     | H150ENC HQI-E 150W/NDL              | 150 | 12500 | NDL   |  | ES/E27 | 6,000 | 55 | 141 | 89 | 1 20 29  |
| <b>Coated</b>   |                   |                                     |     |       |       |  |        |       |    |     |    |          |
| HQIE70WDL       | 4050300397801     | H70EW HQI-E 70W/WDL                 | 70  | 4700  | WDL   |  | ES/E27 | 9,000 | 55 | 141 | –  | 2 20 29  |
| HQIE70NDL       | 4050300397849     | H70EN HQI-E 70W/NDL                 | 70  | 5100  | NDL   |  | ES/E27 | 6,000 | 55 | 141 | –  | 2 20 29  |
| HQIE100WDL      | 4050300351551     | H100EW HQI-E 100W/WDL               | 100 | 7900  | WDL   |  | ES/E27 | 9,000 | 55 | 141 | –  | 2 20 29  |
| HQIE100NDL      | 4050300345833     | H100EN HQI-E 100W/NDL               | 100 | 7700  | NDL   |  | ES/E27 | 6,000 | 55 | 141 | –  | 2 20 29  |
| HQIE150WDL      | 4050300433998     | H150EW HQI-E 150W/WDL <sup>1)</sup> | 150 | 11600 | WDL   |  | ES/E27 | 9,000 | 55 | 141 | –  | 2 20 29  |
| HQIE150NDL      | 4050300434032     | H150EN HQI-E 150W/NDL <sup>1)</sup> | 150 | 11500 | NDL   |  | ES/E27 | 6,000 | 55 | 141 | –  | 2 20 29  |

Perfectly matched with POWERTRONIC® electronic control gear (PTi, PT0, PT FIT)

1) Operate with NAV® control gear

All orders must be multiples of sales pack




## High Intensity Discharge Lamps – Quartz Metal Halide

**POWERSTAR® HQI®-E/P**

- Protected single ended elliptical quartz metal halide lamp
- Suitable for use in open luminaires without cover shields
- Ideal in factories, offices, warehouses, rail stations and retail lighting

| Product ID Code | EAN (Single Pack) | Product Description                 | W   | lm    | Color | t [h]   | d [mm] | I [mm] | LCL a [mm] | No. | PPG |
|-----------------|-------------------|-------------------------------------|-----|-------|-------|---------|--------|--------|------------|-----|-----|
| HQIEP250D       | 4008321525673     | H25EDP HQI-E/P 250W/D <sup>1)</sup> | 250 | 17000 | D     | GES/E40 | 6,000  | 90     | 226        | 12  | 29  |
| HQIEP400D       | 4008321525697     | H40EDP HQI-E/P 400W/D <sup>1)</sup> | 400 | 31000 | D     | GES/E40 | 12,000 | 120    | 290        | 12  | 29  |

1) Operate with NAV® control gear

**POWERSTAR® HQI®-E High Wattage**

- Single ended elliptical quartz metal halide lamp
- Ideal for enclosed luminaires in factories, offices and warehouses

| Product ID Code | EAN (Single Pack) | Product Description               | W    | lm     | Color | t [h]   | d [mm] | I [mm] | LCL a [mm] | No. | PPG |
|-----------------|-------------------|-----------------------------------|------|--------|-------|---------|--------|--------|------------|-----|-----|
| <b>Clear</b>    |                   |                                   |      |        |       |         |        |        |            |     |     |
| HQIE400NCLEAR   | 4008321526700     | H40ENC HQI-E 400W/N <sup>1)</sup> | 400  | 42000  | N     | GES/E40 | 12,000 | 120    | 285        | 198 | 1   |
| <b>Coated</b>   |                   |                                   |      |        |       |         |        |        |            |     |     |
| HQIE250D        | 4008321525659     | H25ED HQI-E 250W/D <sup>1)</sup>  | 250  | 19000  | D     | GES/E40 | 12,000 | 90     | 226        | –   | 2   |
| HQIE400D        | 4008321525512     | H40ED HQI-E 400W/D <sup>1)</sup>  | 400  | 34000  | D     | GES/E40 | 12,000 | 120    | 290        | –   | 2   |
| HQIE400N        | 4008321526724     | H400EN HQI-E 400W/N <sup>1)</sup> | 400  | 40000  | N     | GES/E40 | 12,000 | 120    | 285        | –   | 2   |
| HQIE1000N       | 4008321528261     | H1000EN HQI-E 1000W/N             | 1000 | 100000 | N     | GES/E40 | 12,000 | 165    | 380        | –   | 6   |

1) Operate with NAV® control gear

NEW


NEW

NEW

All orders must be multiples of sales pack





## High Intensity Discharge Lamps – Quartz Metal Halide

**POWERSTAR® HQI®-E NSI**

- Single ended elliptical quartz metal halide lamp
- Ideal for downlights in factories, offices and warehouses

| Product ID Code | EAN (Single Pack) | Product Description    | W   | lm    | Color | t [h]   | d [mm] | I [mm] | LCL a [mm] | PPG |   |    |
|-----------------|-------------------|------------------------|-----|-------|-------|---------|--------|--------|------------|-----|---|----|
| HQIE250NSI      | 405030044628      | H2ENSI HQI-E 250W/N/SI | 250 | 21500 | N     | GES/E40 | 9,000  | 89     | 216        | –   | 6 | 29 |
| HQIE400NSI      | 4008321302342     | H4ENS HQI-E 400W/N/SI  | 400 | 31000 | N     | GES/E40 | 9,000  | 37     | 297        | –   | 6 | 29 |

**POWERSTAR® HQI®-E NSI SUPER**

- Compact elliptical single ended quartz metal halide lamp
- High lumen output and extra long life of 20,000 hours
- Ideal for industrial applications, trade shows, exhibition and sports halls and exterior floodlighting systems

| Product ID Code | EAN (Single Pack) | Product Description                 | W   | lm    | Color | t [h]   | d [mm] | I [mm] | LCL a [mm] | PPG |    |
|-----------------|-------------------|-------------------------------------|-----|-------|-------|---------|--------|--------|------------|-----|----|
| HQIE250NSISUPER | 4008321959577*    | HQI-E 250W/N/SI SUPER <sup>1)</sup> | 250 | 19000 | N     | GES/E40 | 20,000 | 90     | 225        | 10  | 29 |
| HQIE400NSISUPER | 4008321959591*    | HQI-E 400W/N/SI SUPER <sup>1)</sup> | 400 | 34000 | N     | GES/E40 | 20,000 | 90     | 275        | 10  | 29 |

\*In preparation at time of print. For further information please contact OSRAM


1) Lamps ignite at an ignition voltage of 0.56 to 1 kVs; lamps must not be operated with an ignition voltage .1.5kVs/Operate on HQL® control gear

All orders must be multiples of sales pack



## HIGH INTENSITY DISCHARGE LAMPS – HIGH PRESSURE SODIUM LAMPS

**4 YEARS  
LONGLIFE**



### VIALOX® NAV®-E SUPER 4Y® (SON-E PLUS 4 YEAR)

- Elliptical diffuse high pressure sodium lamp
- Brightest and most economical high pressure SON lamps
- 4 year (4Y) relamping cycle
- 20% higher efficiency and direct replacement for NAV®-E Standard and 4Y
- Up to 25% longer life
- Without igniter
- Ideal for street lighting, floodlighting and indoor lighting in heavy industry



| Product ID Code | EAN (Single Pack) | Product Description                        | W   | lm    | Color | t [h]   | Ø d [mm] | I [mm] | PPG       |
|-----------------|-------------------|--|-----|-------|-------|---------|----------|--------|-----------|
| NAVE50S4Y       | 4008321356024     | S50P4 NAV-E 50W SUP 4Y E27                 | 50  | 3800  | 2000K | ES/E27  | 28,000   | 71     | 156 24 36 |
| NAVE70S4Y       | 4008321356048     | S70P4 NAV-E 70W SUP 4Y E27                 | 70  | 6300  | 2000K | ES/E27  | 28,000   | 71     | 156 24 36 |
| NAVE100S4Y      | 4050300015774     | S100P4 NAV-E 100W SUP 4Y E40 <sup>1)</sup> | 100 | 10200 | 2000K | GES/E40 | 28,000   | 76     | 183 12 36 |
| NAVE150S4Y      | 4050300024370     | S150P4 NAV-E 150W SUP 4Y E40 <sup>1)</sup> | 150 | 17000 | 2000K | GES/E40 | 28,000   | 91     | 226 12 36 |
| NAVE250S4Y      | 4050300024387     | S250P4 NAV-E 250W SUP 4Y E40 <sup>1)</sup> | 250 | 31100 | 2000K | GES/E40 | 28,000   | 91     | 226 12 36 |
| NAVE400S4Y      | 4050300024394     | S400P4 NAV-E 400W SUP 4Y E40 <sup>1)</sup> | 400 | 55500 | 2000K | GES/E40 | 28,000   | 122    | 290 12 36 |

Perfectly matched with POWERTRONIC® electronic control gear (up to 150W)


1) Important: Before replacing NAV® (SON) Standard lamps in existing installations, check that ignites are suitable

**NEW**  
**NEW**

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – High Pressure Sodium Lamps



1



2

4 YEARS  
LONGLIFE**VIALOX® NAV®-E 4Y® (SON-E 4 YEAR) ▲<sup>E</sup>**

- Elliptical diffuse high pressure sodium lamp
- 4 year (4Y) relamping cycle
- Up to 25% longer life
- Ideal for street lighting, floodlighting and indoor lighting in heavy industry

| Product ID Code | EAN (Single Pack) | Product Description | W | lm | color | t [h] | d [mm] | I [mm] | No. | PPG |
|-----------------|-------------------|---------------------|---|----|-------|-------|--------|--------|-----|-----|
|-----------------|-------------------|---------------------|---|----|-------|-------|--------|--------|-----|-----|

**Without internal igniter**

|                         |               |                      |     |       |       |         |        |     |     |   |    |    |
|-------------------------|---------------|----------------------|-----|-------|-------|---------|--------|-----|-----|---|----|----|
| NAVE50E4Y               | 4050300577678 | S504Y NAV-E 50W/E 4Y | 50  | 3500  | 2000K | ES/E27  | 28,000 | 71  | 156 | 1 | 24 | 34 |
| NAVE70E4Y               | 4050300577692 | S704Y NAV-E 70W/E 4Y | 70  | 5600  | 2000K | ES/E27  | 28,000 | 71  | 156 | 1 | 24 | 37 |
| NAVE1504Y <sup>2)</sup> | 4050300577555 | S1504Y NAV-E 150W 4Y | 150 | 14500 | 2000K | GES/E40 | 28,000 | 91  | 226 | 2 | 12 | 34 |
| NAVE2504Y <sup>2)</sup> | 4050300577579 | S2504Y NAV-E 250W 4Y | 250 | 27000 | 2000K | GES/E40 | 28,000 | 91  | 226 | 2 | 12 | 34 |
| NAVE4004Y <sup>2)</sup> | 4050300577593 | S4004Y NAV-E 400W 4Y | 400 | 48000 | 2000K | GES/E40 | 28,000 | 122 | 290 | 2 | 12 | 34 |

**With internal igniter**

|           |               |                              |    |      |       |        |        |    |     |   |    |    |
|-----------|---------------|------------------------------|----|------|-------|--------|--------|----|-----|---|----|----|
| NAVE50I4Y | 4050300606033 | NAV-E 50W/I 4Y <sup>1)</sup> | 50 | 3500 | 2000K | ES/E27 | 28,000 | 71 | 156 | 1 | 24 | 34 |
| NAVE70I4Y | 4050300606019 | NAV-E 70W/I 4Y <sup>1)</sup> | 70 | 5600 | 2000K | ES/E27 | 28,000 | 71 | 156 | 1 | 24 | 34 |

Perfectly matched with POWERTRONIC® PTo electronic control gear (up to 150W)

1) Operate only with NAV® control gear/No igniter required

2) Banned from 1.4.2012



All orders must be multiples of sales pack



## High Intensity Discharge Lamps – High Pressure Sodium Lamps



1

2

**VIALOX® NAV®-E (STANDARD SON-E) without internal igniter**


- Elliptical diffuse high pressure sodium lamp
- Ideal for economical street lighting and floodlighting

| Product ID Code                 | EAN (Single Pack) | Product Description            | W    | lm     | Color |         | t [h]  |     | d [mm] |   | I [mm] |    | No. |  | PPG |
|---------------------------------|-------------------|--------------------------------|------|--------|-------|---------|--------|-----|--------|---|--------|----|-----|--|-----|
| <b>Without internal igniter</b> |                   |                                |      |        |       |         |        |     |        |   |        |    |     |  |     |
| NAVE50E <sup>2)</sup>           | 4050300015750     | S50 NAV-E 50W/E                | 50   | 3500   | 2000K | ES/E27  | 18,000 | 71  | 156    | 1 | 24     | 34 |     |  |     |
| NAVE70E <sup>2)</sup>           | 4050300015767     | S70 NAV-E 70W/E                | 70   | 5600   | 2000K | ES/E27  | 18,000 | 71  | 156    | 1 | 24     | 37 |     |  |     |
| NAVE100 <sup>2)</sup>           | 4008321087300     | S100 NAV-E 100W                | 100  | 8500   | 2000K | GES/E40 | 18,000 | 76  | 183    | 2 | 12     | 34 |     |  |     |
| NAVE150 <sup>2)</sup>           | 4050300015613     | S150 NAV-E 150W                | 150  | 14500  | 2000K | GES/E40 | 18,000 | 91  | 226    | 2 | 12     | 34 |     |  |     |
| NAVE250 <sup>2)</sup>           | 4050300015620     | S250 NAV-E 250W                | 250  | 27000  | 2000K | GES/E40 | 18,000 | 91  | 226    | 2 | 12     | 34 |     |  |     |
| NAVE400 <sup>2)</sup>           | 4050300015637     | S400 NAV-E 400W                | 400  | 48000  | 2000K | GES/E40 | 18,000 | 122 | 290    | 2 | 12     | 34 |     |  |     |
| NAVE1000 <sup>2)</sup>          | 4050300015644     | S1000 NAV-E 1000W              | 1000 | 128000 | 2000K | GES/E40 | 18,000 | 165 | 370    | 2 | 6      | 34 |     |  |     |
| <b>With internal igniter</b>    |                   |                                |      |        |       |         |        |     |        |   |        |    |     |  |     |
| NAVE50I <sup>2)</sup>           | 4050300015583     | S50I NAV-E 50W/I <sup>1)</sup> | 50   | 3500   | 2000K | ES/E27  | 16,000 | 71  | 156    | 1 | 24     | 35 |     |  |     |
| NAVE70I <sup>2)</sup>           | 4050300015590     | S70I NAV-E 70W/I <sup>1)</sup> | 70   | 5600   | 2000K | ES/E27  | 16,000 | 71  | 156    | 1 | 24     | 35 |     |  |     |

Perfectly matched with POWERTRONIC® PTo electronic control gear (up to 150W)

1) Operate only with NAV® control gear/No igniter required

2) Banned from 1.4.2012

**VIALOX® NAV®-E 68W Plug-in (SON-E plug-in)**

- Direct replacement for HQL® 80W
- Up to 15% energy savings and 42% higher lumen output than HQL® 80W
- Ideal for outdoor and industrial floodlighting applications

| Product ID Code | EAN (Single Pack) | Product Description | W  | lm   | Color |        | t [h]  |    | d [mm] |    | I [mm] |  | No. |  | PPG |
|-----------------|-------------------|---------------------|----|------|-------|--------|--------|----|--------|----|--------|--|-----|--|-----|
| NAVE68          | 4008321345462     | NAV-E 68W PLUGIN    | 68 | 5400 | 2000K | ES/E27 | 14,000 | 71 | 152    | 12 | 35     |  |     |  |     |


Perfectly matched with POWERTRONIC® electronic control gear (PTo)

NEW

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – High Pressure Sodium Lamps

**VIALOX® NAV®-E plug-in (SON-E plug-in)** 

- Replacement (retrofit) high pressure sodium lamps for mercury vapour lamp
- No external igniter required
- Ideal for outdoor and industrial floodlighting applications




| Product ID Code       | EAN (Single Pack) | Product Description | W    | lm    | Color |         | t [h]  |     | d [mm] |    | I [mm] |  |
|-----------------------|-------------------|---------------------|------|-------|-------|---------|--------|-----|--------|----|--------|--|
| NAVE110               | 4050300024318     | S110I NAV-E 110W    | 110W | 8000  | 2000K | ES/E27  | 14,000 | 76  | 170    | 40 | 35     |  |
| NAVE210 <sup>1)</sup> | 4050300015576     | S210I NAV-E 210W    | 210W | 18000 | 2000K | GES/E40 | 14,000 | 91  | 226    | 12 | 35     |  |
| NAVE350 <sup>1)</sup> | 4050300015651     | S350I NAV-E 350W    | 350W | 34000 | 2000K | GES/E40 | 14,000 | 122 | 285    | 12 | 35     |  |

Perfectly matched with POWERTRONIC® PTo electronic control gear (up to 150W)

1) Banned from 1.4.2015 as per EU phase-out plan

**VIALOX® NAV®-T SUPER 4Y® (SON-T PLUS 4 YEAR)** 

- Tubular clear high pressure sodium lamp
- One of the brightest and most economical SON lamps
- 4 year (4Y) relamping cycle
- 20% higher efficiency and direct replacement for NAV®-E Standard and 4Y versions
- Up to 25% longer life
- Without igniter
- Ideal for street lighting, floodlighting and indoor lighting in heavy industry



| Product ID Code | EAN (Single Pack) | Product Description                    | W   | lm    | Color |         | t [h]  |    | d [mm] |   | I [mm] |    |
|-----------------|-------------------|--|-----|-------|-------|---------|--------|----|--------|---|--------|----|
| NAVT50S         | 4050300024325     | S50PT4 NAV-T 50W SUP4Y <sup>1)</sup>   | 50  | 4400  | 2000K | ES/E27  | 28,000 | 38 | 156    | 1 | 12     | 36 |
| NAVT70S         | 4050300015736     | S70PT4 NAV-T 70W SUP4Y <sup>1)</sup>   | 70  | 6600  | 2000K | ES/E27  | 28,000 | 38 | 156    | 1 | 12     | 36 |
| NAVT100S4Y      | 4050300015743     | S100PT4 NAV-T 100W SUP4Y <sup>1)</sup> | 100 | 10700 | 2000K | GES/E40 | 28,000 | 47 | 210    | 2 | 12     | 36 |
| NAVT150S4Y      | 4050300024400     | S150PT4 NAV-T 150W SUP4Y <sup>1)</sup> | 150 | 17500 | 2000K | GES/E40 | 28,000 | 47 | 210    | 2 | 12     | 36 |
| NAVT250S4Y      | 4050300024417     | S250PT4 NAV-T 250W SUP4Y <sup>1)</sup> | 250 | 33200 | 2000K | GES/E40 | 28,000 | 47 | 257    | 2 | 12     | 36 |
| NAVT400S4Y      | 4050300281179     | S400PT4 NAV-T 400W SUP4Y <sup>1)</sup> | 400 | 56500 | 2000K | GES/E40 | 28,000 | 47 | 285    | 2 | 12     | 36 |
| NAVT600S4Y      | 4050300275772     | S600PT4 NAV-T 600W SUP4Y <sup>1)</sup> | 600 | 90000 | 2000K | GES/E40 | 28,000 | 47 | 285    | 2 | 12     | 36 |

Perfectly matched with POWERTRONIC® PTo electronic control gear (up to 150W)

1) Important: Before replacing NAV® (SON) standard lamps in existing installations, check that igniters are suitable

All orders must be multiples of sales pack

## High Intensity Discharge Lamps – High Pressure Sodium Lamps

4 YEARS  
LONGLIFE

1



2

**VIALOX® NAV®-T 4Y® (SON-T 4 YEAR)** 

- Tubular clear high pressure sodium lamp
- 4 year (4Y) relamping cycle
- Up to 25% longer life
- Without igniter
- Ideal for street lighting, floodlighting and indoor lighting in heavy industry

| Product ID Code         | EAN (Single Pack) | Product Description  | W   | lm    | Color         | t [h]  | d [mm] | I [mm] | LCL a [mm] | Light No. | PPG   |
|-------------------------|-------------------|----------------------|-----|-------|---------------|--------|--------|--------|------------|-----------|-------|
| NAVT704Y <sup>1)</sup>  | 4050300579061     | S70T4Y NAV-T 70W 4Y  | 70  | 6000  | 2000K ES/E27  | 28,000 | 38     | 156    | 104        | 1         | 12 34 |
| NAVT1504Y <sup>1)</sup> | 4050300577616     | S15T4Y NAV-T 150W 4Y | 150 | 15000 | 2000K GES/E40 | 28,000 | 47     | 210    | 132        | 2         | 12 34 |
| NAVT2504Y <sup>1)</sup> | 4050300577630     | S25T4Y NAV-T 250W 4Y | 250 | 28000 | 2000K GES/E40 | 28,000 | 47     | 257    | 158        | 2         | 12 34 |
| NAVT4004Y <sup>1)</sup> | 4050300577654     | S40T4Y NAV-T 400W 4Y | 400 | 48000 | 2000K GES/E40 | 28,000 | 47     | 285    | 175        | 2         | 12 34 |

Perfectly matched with POWERTRONIC® PTo electronic control gear (up to 150W)

1) Banned from 1.4.2012 as per EU phase-out plan



1



2

**VIALOX® NAV®-T (STANDARD SON-T)**

- Tubular clear high pressure sodium lamp
- Ideal for economical street lighting and floodlighting

| Product ID Code        | EAN (Single Pack) | Product Description    | W    | lm     | Color         | t [h]  | d [mm] | I [mm] | LCL a [mm] | Light No. | PPG   |
|------------------------|-------------------|------------------------|------|--------|---------------|--------|--------|--------|------------|-----------|-------|
| <b>Without igniter</b> |                   |                        |      |        |               |        |        |        |            |           |       |
| NAVT50                 | 4008321337986     | S 50T NAV-T 50W        | 50   | 3700   | 2000K ES/E27  | 18,000 | 38     | 156    | 104        | 1         | 12 34 |
| NAVT70 <sup>1)</sup>   | 4050300255590     | S70T NAV-T 70W         | 70   | 6000   | 2000K ES/E27  | 18,000 | 38     | 156    | 104        | 1         | 12 34 |
| NAVT100 <sup>1)</sup>  | 4008321087287     | S 100T NAV-T 100W      | 100  | 9000   | 2000K GES/E40 | 18,000 | 47     | 210    | 132        | 2         | 12 34 |
| NAVT150 <sup>1)</sup>  | 4050300015668     | S150T NAV-T 150W       | 150  | 15000  | 2000K GES/E40 | 18,000 | 47     | 210    | 132        | 2         | 12 34 |
| NAVT250 <sup>1)</sup>  | 4050300015675     | S250T NAV-T 250W       | 250  | 28000  | 2000K GES/E40 | 18,000 | 47     | 257    | 158        | 2         | 12 34 |
| NAVT400 <sup>1)</sup>  | 4050300015682     | S400T NAV-T 400W       | 400  | 48000  | 2000K GES/E40 | 18,000 | 47     | 285    | 175        | 2         | 12 34 |
| NAVT1000 <sup>1)</sup> | 4050300251417     | S1KWT NAV-T 1000W 230V | 1000 | 130000 | 2000K GES/E40 | 18,000 | 66     | 360    | 240        | 2         | 10 34 |

NEW

**With igniter**

|                         |               |                           |      |        |               |        |    |     |     |   |       |
|-------------------------|---------------|---------------------------|------|--------|---------------|--------|----|-----|-----|---|-------|
| NAVT1000I <sup>1)</sup> | 4050300287171 | S1KWTI NAV-T 1000W 400V/I | 1000 | 130000 | 2000K GES/E40 | 18,000 | 66 | 360 | 240 | - | 12 35 |
|-------------------------|---------------|---------------------------|------|--------|---------------|--------|----|-----|-----|---|-------|

Perfectly matched with POWERTRONIC® PTo electronic control gear (up to 150W)

1) Banned from 1.4.2012

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – High Pressure Sodium Lamps

**VIALOX® NAV®-TS SUPER 4Y® (SON-TS PLUS) **

- Double ended high pressure sodium lamp
- One of the brightest and most economical SON lamps
- 4 year (4Y) relamping cycle
- Without igniter 
- Ideal for smaller floodlighting applications



| Product ID Code | EAN (Single Pack) | Product Description       | W   | lm    | Color | t [h]   |  d [mm] |  l [mm] | LCL  | a [mm] | PPG |    |
|-----------------|-------------------|---------------------------|-----|-------|-------|---------|--|--|---|--------|-----|----|
| NAVTS70S        | 4050300024301     | S70TS NAV-TS 70W SUP 4Y   | 70  | 6800  | 2000K | Rx7s    | 24,000   | 20   | 120   | 57     | 12  | 35 |
| NAVTS150S       | 4050300281667     | S150TS NAV-TS 150W SUP 4Y | 150 | 15000 | 2000K | Rx7s-24 | 24,000   | 23   | 138   | 66     | 12  | 35 |

Perfectly matched with POWERTRONIC® electronic control gear (PTo)

**VIALOX® NAV®-TS (STANDARD SON-TS) **


- Double ended high pressure sodium lamp
- Instant hot restart is possible with a special igniter
- Without igniter 
- Ideal for lighting bridges, tunnels and railway lines



| Product ID Code | EAN (Single Pack) | Product Description | W   | lm    | Color | t [h] |  d [mm] |  l [mm] | LCL  | a [mm] | PPG |    |
|-----------------|-------------------|---------------------|-----|-------|-------|-------|--|--|---|--------|-----|----|
| NAVTS250        | 4050300015705     | S250TS NAV-TS 250W  | 250 | 25500 | 2000K | FC2   | 24,000   | 23   | 206   | 103    | 12  | 35 |
| NAVTS400        | 4050300015712     | S400TS NAV-TS 400W  | 400 | 48000 | 2000K | FC2   | 24,000   | 23   | 206   | 103    | 12  | 35 |

All orders must be multiples of sales pack

## High Intensity Discharge Lamps – High Pressure Sodium Lamps


**PLANTASTAR®**

- Tubular clear high pressure sodium lamp
- Without igniter
- Ideal for use in professional horticulture

| Product<br>ID Code | EAN<br>(Single Pack) | Product<br>Description               | W   | Im    |         | d [mm] | I   | LCL<br>[mm] | a [mm] | PPG |
|--------------------|----------------------|--------------------------------------|-----|-------|---------|--------|-----|-------------|--------|-----|
| PLANTASTARINTER250 | 4008321240620        | PS 250T PLANTASTAR 400W              | 250 | 33200 | GES/E40 | 47     | 257 | 158         | 12     | 35  |
| PLANTASTAR400      | 4050300620084        | PS400T PLANTASTAR 400W <sup>1)</sup> | 400 | 56500 | GES/E40 | 47     | 285 | 175         | 12     | 35  |
| PLANTASTAR600      | 4050300620107        | PS600T PLANTASTAR 600W <sup>1)</sup> | 600 | 89000 | GES/E40 | 47     | 285 | 175         | 12     | 35  |
| PLANTASTAR600CG    | 4008321284303        | PS600CGT PLANTASTAR 600W             | 600 | 87000 | GES/E40 | 47     | 285 | 175         | 12     | 35  |

1) Lamps require igniters with an ignition voltage of 4 to 5 kVs


NEW



All orders must be multiples of sales pack




## HIGH INTENSITY DISCHARGE LAMPS – LOW PRESSURE SODIUM LAMPS



### SOX

- Standard low pressure sodium lamp
- Ideal for streetlighting, amenity and security lighting

| Product ID Code | EAN (Single Pack) | Product Description | W   | lm    |       | t [h]  | d [mm] | $\frac{l}{d}$ [mm] | PPG |    |
|-----------------|-------------------|---------------------|-----|-------|-------|--------|--------|--------------------|-----|----|
| SOX18           | 4050300015569     | SX18 SOX 18W        | 18  | 1800  | BY22d | 16,000 | 54     | 216                | 12  | 33 |
| SOX180          | 4050300015552     | SX180 SOX 180W      | 180 | 32000 | BY22d | 16,000 | 68     | 1120               | 6   | 33 |



### SOX PLUS

- Low pressure sodium lamp
- 12,000 hour guarantee
- Ideal for streetlighting, amenity and security lighting

| Product ID Code | EAN (Single Pack) | Product Description  | W   |       | PPG   |
|-----------------|-------------------|----------------------|-----|-------|-------|
| SOX35PLUS       | 4050300614311     | SXP35 SOX PLUS 35W   | 35  | BY22d | 12 33 |
| SOX55PLUS       | 4050300614335     | SXP55 SOX PLUS 55W   | 55  | BY22d | 12 33 |
| SOX90PLUS       | 4050300614359     | SXP90 SOX PLUS 90W   | 90  | BY22d | 12 33 |
| SOX135PLUS      | 4050300614373     | SXP135 SOX PLUS 135W | 135 | BY22d | 12 33 |

All orders must be multiples of sales pack



## HIGH INTENSITY DISCHARGE LAMPS – MERCURY VAPOUR LAMPS




### HQL® SUPER DE LUXE (MBF SUPER DE LUXE)

- Elliptical high pressure mercury lamp
- With golden brown filter
- Incandescent-like colour appearance
- Ideal for versatile indoor and outdoor lighting applications

| Product ID Code         | EAN (Single Pack) | Product Description      | W   | lm   | Color  | t [h]  | d [mm] | I [mm] | PPG |    |
|-------------------------|-------------------|--------------------------|-----|------|--------|--------|--------|--------|-----|----|
| HQL50SDL <sup>1)</sup>  | 4050300015217     | HQ50SD HQL 50W SUPER DL  | 50  | 1600 | ES/E27 | 20,000 | 56     | 130    | 40  | 32 |
| HQL80SDL <sup>1)</sup>  | 4050300015224     | HQ80SD HQL 80W SUPER DL  | 80  | 3400 | ES/E27 | 20,000 | 71     | 155    | 40  | 32 |
| HQL125SDL <sup>1)</sup> | 4050300018515     | HQ125D HQL 125W SUPER DL | 125 | 5700 | ES/E27 | 20,000 | 76     | 168    | 40  | 32 |

1) Banned from 1.4.2015 as per EU phase-out plan



1

2

### HQL® DE LUXE (MBF DE LUXE)

- Elliptical high pressure mercury lamp
- Warmer appearance
- Emits more light than a standard HQL®
- Suitable for 4 years of operation in street lighting
- Ideal for versatile indoor and outdoor lighting applications

| Product ID Code        | EAN (Single Pack) | Product Description     | W   | lm    | Color | t [h]   | d [mm] | I [mm] | PPG |    |    |
|------------------------|-------------------|-------------------------|-----|-------|-------|---------|--------|--------|-----|----|----|
| HQL50DL <sup>1)</sup>  | 4050300015132     | HQ50D HQL 50W DE LUXE   | 50  | 2000  | 3600K | ES/E27  | 20,000 | 56     | 130 | 40 | 32 |
| HQL80DL <sup>1)</sup>  | 4050300015149     | HQ80D HQL 80W DE LUXE   | 80  | 4000  | 3400K | ES/E27  | 20,000 | 71     | 155 | 40 | 32 |
| HQL125DL <sup>1)</sup> | 4050300015156     | HQ125D HQL 125W DE LUXE | 125 | 6800  | 3400K | ES/E27  | 20,000 | 76     | 168 | 40 | 32 |
| HQL250DL <sup>1)</sup> | 4050300015163     | HQ250D HQL 250W DELUXE  | 250 | 14000 | 3400K | GES/E40 | 20,000 | 91     | 226 | 12 | 32 |
| HQL400DL <sup>1)</sup> | 4050300015170     | HQ400D HQL 400W DELUXE  | 400 | 24000 | 3800K | GES/E40 | 20,000 | 122    | 285 | 12 | 32 |

1) Banned from 1.4.2015 as per EU phase-out plan

All orders must be multiples of sales pack



## High Intensity Discharge Lamps – Mercury Vapour Lamps



1




2

**HQL® Standard (MBF)**

- Elliptical high pressure mercury lamp
- Yttrium vanadate phosphor coating
- Neutral white light colour
- Ideal for traffic and factory lighting applications

| Product ID Code       | EAN (Single Pack) | Product Description | W    | lm    | COLOR |         | t [h]  |     | d [mm] | I [mm] |    |    | PPG |
|-----------------------|-------------------|---------------------|------|-------|-------|---------|--------|-----|--------|--------|----|----|-----|
| HQL50 <sup>1)</sup>   | 4050300015040     | MB50 HQL            | 50   | 1800  | 4200K | ES/E27  | 20,000 | 56  | 130    | 1      | 40 | 31 |     |
| HQL80 <sup>1)</sup>   | 4050300012360     | MB80 HQL            | 80   | 3800  | 4200K | ES/E27  | 20,000 | 71  | 155    | 1      | 40 | 31 |     |
| HQL125 <sup>1)</sup>  | 4050300012377     | MB125 HQL           | 125  | 6300  | 4200K | ES/E27  | 20,000 | 76  | 168    | 1      | 40 | 31 |     |
| HQL250 <sup>1)</sup>  | 4050300015064     | MB250 HQL           | 250  | 13000 | 4000K | GES/E40 | 20,000 | 91  | 226    | 2      | 12 | 31 |     |
| HQL400 <sup>1)</sup>  | 4050300015071     | MB400 HQL           | 400  | 22000 | 4000K | GES/E40 | 20,000 | 122 | 285    | 2      | 12 | 31 |     |
| HQL700 <sup>1)</sup>  | 4050300015088     | MB700 HQL           | 700  | 40000 | 4000K | GES/E40 | 15,000 | 141 | 325    | 2      | 6  | 31 |     |
| HQL1000 <sup>1)</sup> | 4050300015095     | MB1KLV HQL          | 1000 | 57000 | 4000K | GES/E40 | 15,000 | 165 | 355    | 2      | 6  | 31 |     |

1) Banned from 1.4.2015 as per EU phase-out plan

**HQL® R DE LUXE**


- Mushroom shaped high pressure mercury lamp with reflector
- Yttrium vanadate phosphor coating
- Provides a warm white light colour
- Ideal for decorative lighting, plant lighting, aquariums

| Product ID Code       | EAN (Single Pack) | Product Description | W  | lm   | COLOR |        | t [h]  |     | d [mm] | I [mm] |    |  | PPG |
|-----------------------|-------------------|---------------------|----|------|-------|--------|--------|-----|--------|--------|----|--|-----|
| HQL80DL <sup>1)</sup> | 405030003290      | HQLR80WDELUXE       | 80 | 3000 | 3400K | ES/E27 | 20,000 | 125 | 168    | 6      | 31 |  |     |

1) Banned from 1.4.2015 as per EU phase-out plan

All orders must be multiples of sales pack

## LED MODULES




# LED Modules

## Contents.

|  |     |
|--|-----|
| STREETlight Module Advanced                            | 152 |
| STREETlight Protect Module                             | 152 |
| PrevalED™ Core   | 153 |
| COINlight® Advanced                                    | 154 |
| COINlight-OSTAR® Heatsink                              | 154 |
| LINEARlight-DRAGON®                                    | 155 |
| CONNECTsystem for LINEARlight-DRAGON®                  | 155 |
| LINEARlight Dragon Slim                                | 156 |
| LINEARlight POWER Flex                                 | 157 |
| CONNECTsystem for Flex modules                         | 157 |
| LINEARlight Flex/Eco                                   | 158 |
| LINEARlight Flex                                       | 159 |
| LINEARlight  | 160 |
| CONNECTsystem for LINEARlight and EFFECTlight          | 160 |
| LINEARlight Optics                                     | 161 |
| DRAGONeye®   | 161 |
| DRAGONpuck®  | 162 |
| DRAGONtape®  | 162 |
| DRAGONtape® Optics                                     | 163 |
| DRAGON-X Plus  | 163 |
| DRAGON-X   | 164 |
| COINlight®   | 164 |
| LINEARlight DRAGON® Colormix                           | 165 |
| CONNECTsystem for LINEARlight DRAGON Colormix          | 165 |
| DRAGONchain® Colormix                                  | 166 |
| LINEARlight Colormix Flex                              | 166 |
| CONNECTsystem for LINEARlight Colormix Flex modules    | 167 |
| LINEARlight Colormix                                   | 167 |
| CONNECTsystem for LINEARlight Colormix                 | 167 |
| COINlight® Colormix                                    | 168 |
| BACKlight Protect                                      | 168 |
| BACKlight POWER  | 169 |
| BACKlight BL02   | 169 |
| Installation aid for BACKlight BL02 and BACKlight BL04 | 170 |
| DRAGONchain®   | 170 |
| LEDs DECO® FLEX  | 171 |
| LINEARlight Track                                      | 171 |



## LED Modules




### STREETlight Module Advanced

- Robust street light LED module
- LED illumination of highways and byways
- Optical lens reflector concept using 3 multichip LEDs
- Viewing angle 80° x 140° with 50,000 hours lifetime
- LED replacement without tools

| Product ID Code | EAN (Single Pack) | Product Description                                     | W  | V/mA | No. | PPG   |
|-----------------|-------------------|---|----|------|-----|-------|
| SLA1L123742     | 4008321965967     | STREETlight Module Advanced 4200K (93,6 x 72,0 x 44,8)  | 29 | 24   | 1   | 20 38 |
| SLA1L143760     | 4008321958853     | STREETlight Module Advanced 6000K (93,6 x 72,0 x 44,8)  | 29 | 24   | 1   | 20 38 |
| SLA1L105830     | 4008321958877     | STREETlight Module Advanced 3000K 93,6 x 72,0 x 44,8    | 29 | 24   | 1   | 20 38 |
| SLA1SL123742    | 4008321965981     | STREETlight Module Advanced 4200K (98,0 x 72,0 x 50,8)  | 29 | 24   | 2   | 20 38 |
| SLA1SL143760    | 4008321960061     | STREETlight Module Advanced 6000K 98,0 x 72,0 x 50,8    | 29 | 24   | 2   | 20 38 |
| SLA1SL105830    | 4008321960085     | STREETlight Module Advanced 3000K 98,0 x 72,0 x 50,8    | 29 | 24   | 2   | 20 38 |
| SLA1SOCKET      | 4008321958891     | STREETlight Module Advanced Socket (96,7 x 72,0 x 20,3) | —  | —    | 3   | 20 38 |

Perfectly matched with OPTOTRONIC® OT 75 E

NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW



### STREETlight Protect Module

- Robust street light LED module
- Modular solution with 15 high power LEDs
- Integrated heat sink and IP 66 protection

| Product ID Code | EAN (Single Pack) | Product Description     | W  | V/mA | No. | PPG |
|-----------------|-------------------|-------------------------|----|------|-----|-----|
| SLP1W4F765      | 4008321964755     | SLP1 W4F 765 (L75x 130) | 23 | 24   | 4   | 38  |
| SLP1W4F854      | 4008321964748     | SLP1 W4F 854 (L75x 130) | 23 | 24   | 4   | 38  |
| SLP1W4F840      | 4008321964731     | SLP1 W4F 840 (L75x 130) | 23 | 24   | 4   | 38  |
| SLP1W4F830      | 4008321964724     | SLP1 W4F 830 (L75x 130) | 23 | 24   | 4   | 38  |


Perfectly matched with OPTOTRONIC® OT 75 E

NEW  
NEW  
NEW  
NEW

All orders must be multiples of sales pack



## LED Modules

**PrevalLED™ Core**

- Up to 3000 lm out of 50mm Ø package, height of 9mm
- Beam angle of 140° for optimum coupling of reflectors
- Flexible module design based on PCB, LED array and protective cover



| Product ID Code | EAN (Single Pack) | Product Description | W  | lm   |    | PPG |
|-----------------|-------------------|---------------------|----|------|----|-----|
| LEP3000930HDC   | 4008321966070     | LEP-3000-930-HD-C   | 43 | 3000 | 20 | 38  |
| LEP3000840HDC   | 4008321966094     | LEP-3000-840-HD-C   | 43 | 3000 | 20 | 38  |
| LEP2100930HDC   | 4008321963352     | LEP-2100-930-HD-C   | 28 | 2100 | 20 | 38  |
| LEP2100840HDC   | 4008321963369     | LEP-2100-840-HD-C   | 28 | 2100 | 20 | 38  |
| LEP2100830C     | 4008321963376     | LEP-2100-930-C      | 38 | 2100 | 20 | 38  |
| LEP2100840C     | 4008321963383     | LEP-2100-840-C      | 35 | 2100 | 20 | 38  |
| LEP800930HDC    | 4008321963390     | LEP-800-930-HD-C    | 11 | 800  | 20 | 38  |
| LEP800840HDC    | 4008321963406     | LEP-800-840-HD-C    | 11 | 800  | 20 | 38  |

Perfectly matched with OPTOTRONIC® OTp 24V Range



All orders must be multiples of sales pack

## LED Modules




### COINlight® Advanced

- Powered by 3 Golden DRAGON® Plus LEDs
- Integrated 36° optics for wide flood lighting
- Heatsink available for improved lifetime of 80,000 hours
- Ideal for replacing halogen lamps

| Product ID Code | EAN (Single Pack) | Product Description    | W   | V/mA |    | PPG |
|-----------------|-------------------|------------------------|-----|------|----|-----|
| CA50051L36854   | 4008321958952     | CA50-051-854-L36 CO AD | 7.5 | 24   | 25 | 38  |
| CA50051L36840   | 4008321958938     | CA50-051-840-L36 CO AD | 7.5 | 24   | 25 | 38  |
| CA50051L36830   | 4008321958914     | CA50-051-830-L36 CO AD | 7.5 | 24   | 25 | 38  |

Perfectly matched with OPTOTRONIC® OT 24V Range




### COINlight-OSTAR® Heatsink

- Accessory for optimised heat dissipation of COINlight-OSTAR®
- Improves life time of the module
- Easy mounting by screwing the heat sink on the module

| Product ID Code | EAN (Single Pack) | Product Description               |    | PPG |
|-----------------|-------------------|-----------------------------------|----|-----|
| COHS50          | 4008321299246     | COHS-50 HEAT SINK COINlight-OSTAR | 20 | 38  |

All orders must be multiples of sales pack

## LED Modules

**LINEARlight-DRAGON®**


- Six high power Golden DRAGON® LED on a metal core board
- Complete module includes optics and designer heat sink
- Low profile design
- Plug & Play using CONNECTsystem
- FineWHITE for best colour uniformity
- Ideal for recessed lighting applications and wall washing

| Product ID Code          | EAN (Single Pack) | Product Description  | W  | V/mA | No. | PPG |
|--------------------------|-------------------|--|----|------|-----|-----|
| <b>Individual boards</b> |                   |  |    |      |     |     |
| LD06AW3F827LL            | 4008321940452     | LD06-W3F-827 LINEARlight DRAGON FineWHITE 24V 12W 2700K      | 12 | 24   | 1   | 38  |
| -                        | 4008321385757*    | LD06B-W4F-830 LINEARlight DRAGON FineWHITE 24V 12W 3000K     | 12 | 24   | 1   | 38  |
| LD06BW4F840LL            | 4008321395870     | LD06B-W4F-840 LINEARlight DRAGON FineWHITE 24V 12W 4000K     | 12 | 24   | 1   | 38  |
| LD06BW4F854LL            | 4008321395993     | LD06B-W4F-854 LINEARlight DRAGON FineWHITE 24V 12W 5400K     | 12 | 24   | 1   | 38  |
| <b>Complete modules</b>  |                   |  |    |      |     |     |
| LD06A3F827L30LL          | 4008321940476     | LD06 A W3F-827 L30 LINEARlight DRAGON 24V 12W White 2700K    | 12 | 24   | 2   | 38  |
| LD06AW3F854L30LL8        | 4008321940438     | LD06 A W3F-854-L30 LINEARlight DRAGON 24V 8W White 5400K     | 8  | 24   | 2   | 38  |
| -                        | 4008371395290*    | LD06B-W4F-854-L30 LINEARLIGHT DRAGON 24V 12W FineWHITE 5400K | 12 | 24   | 2   | 38  |
| LD06BW4F830L30           | 4008321394491     | LD06B-W4F-830-L30 LINEARLIGHT DRAGON 24V 12W FineWHITE 3000K | 12 | 24   | 2   | 38  |
| LD06BW4F840L30           | 4008321394613     | LD06B-W4F-840-L30 LINEARLIGHT DRAGON 24V 12W FineWHITE 4000K | 12 | 24   | 2   | 38  |

Perfectly matched with OPTOTRONIC® OT 24V Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

\*In preparation at time of print. For further information please contact OSRAM


**CONNECTsystem for LINEARlight-DRAGON®**

- Plug and play CONNECTsystem (feeder and connector) enables easy connection of LINEARlight DRAGON®

| Product ID Code                              | EAN (Single Pack) | Product Description   | W | V/mA | No. | PPG |
|--|-------------------|---|---|------|-----|-----|
| LD2CONN100                                   | 4008321182883     | LD-2CONN-100mm  | 1 | 10   | 38  |     |
| LD2CONN40                                    | 4008321182869     | LD-2CONN-40mm   | 2 | 10   | 38  |     |
| LD2PIN                                       | 4008321182845     | LD-2PIN feeder  | 3 | 10   | 38  |     |
| <b>LINEARlight DRAGON – Mounting Bracket</b> |                   |   |   |      |     |     |
| LDMB   | 4008321225672     | LD-MB LINEARlight DRAGON mounting bracket LxWxH 32.5x22x6.6 | 4 | 12   | 38  |     |

All orders must be multiples of sales pack

## LED Modules



### LINEARlight Dragon Slim

- High Power LED profile
- Contains 6 Hi-flux Golden DRAGON® LED with Thinfilm technology
- Easy plug and play connection
- Ideal for display, cabinet, fridge lighting


| Product ID Code | EAN (Single Pack) | Product Description                   | W | V/mA | PPG  |
|-----------------|-------------------|---------------------------------------|---|------|------|
| LD06SW4F830     | 4008321953308     | LD06S-W4F-830 LINEARlight DRAGON Slim | 7 | 24   | 6 38 |
| LD06SW4F840     | 4008321953322     | LD06S-W4F-840 LINEARlight DRAGON Slim | 7 | 24   | 6 38 |

Perfectly matched with OPTOTRONIC® OT 24V Range

NEW  
NEW

All orders must be multiples of sales pack

## LED Modules


**LINEARlight POWER Flex**

- High output linear LED module on a flexible circuit board
- 3m reel
- FineWHITE for best colour uniformity
- Ideal for edge lighting, cove lighting and linear illumination

| Product ID Code | EAN (Single Pack) | Product Description                                  | W  | V/mA |   | PPG |
|-----------------|-------------------|--|----|------|---|-----|
| LF06PW4F854     | 4008321966032     | LM06P W4F 854 LINEARlight POWER Flex FineWHITE 5400K | 72 | 24   | 8 | 38  |
| LF06PW4F840     | 4008321966025     | LM06P W4F 840 LINEARlight POWER Flex FineWHITE 4000K | 72 | 24   | 8 | 38  |
| LF06PW4F830     | 4008321960528     | LM06P W4F 830 LINEARlight POWER Flex FineWHITE 3000K | 72 | 24   | 8 | 38  |
| LF06PW4F827     | 4008321966001     | LM06P W4F 827 LINEARlight POWER Flex FineWHITE 2700K | 72 | 24   | 8 | 38  |
| LM10PW3F854     | 4008321215482     | LM10P W3F 854 LINEARlight POWER Flex FineWHITE 5400K | 48 | 24   | 8 | 38  |
| LM10PW4F854     | 4008321310798     | LM10P W4F 854 LINEARlight POWER Flex FineWHITE 5400K | 72 | 24   | 8 | 38  |
| OSLM10PW3F827   | 4008321940537     | LM10P W3F 827 LINEARlight POWER Flex FineWHITE 2700K | 72 | 24   | 8 | 38  |
| LM10PW3F830     | 4008321350565     | LM10P W3F 830 LINEARlight POWER Flex 72W 24V         | 72 | 24   | 8 | 38  |
| LM10PW3F840     | 4008321350886     | LM10P W3F 840 LINEARlight POWER Flex 72W 24V         | 72 | 24   | 8 | 38  |

Perfectly matched with OPTOTRONIC® OT 24V Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)


**CONNECTsystem for Flex modules**

- For each attaching and interconnecting of LINEARlight POWER Flex

| Product ID Code | EAN (Single Pack) | Product Description                   | V/mA | No. |       | PPG |
|-----------------|-------------------|---------------------------------------|------|-----|-------|-----|
| LMCONN10FLEX    | 4008321916259     | LM-CONN 10 Flex                       | 25   | 1   | 20x10 | 38  |
| LMCONN150FLEX   | 4008321931375     | LM-CONN 150 Flex connect system 10x10 | 25   | 2   | 10x10 | 38  |
| LM2PINFLEX      | 4008321916211     | LM-2PIN Flex connect system           | 25   | 3   | 10x10 | 38  |
| LMCONN10FLEX    | 4008321916259     | LM-4PIN Flex connect system           | 25   | 4   | 10x10 | 38  |

All orders must be multiples of sales pack

## LED Modules



### LINEARlight Flex/Eco

- NEW Generation of linear LED module on a flexible circuit board
- Up to 9.9m long and can be split into units of 5 LEDs
- Adhesive tape on reverse provides easy mounting
- Ideal for lighting complex contours


| Product ID Code                       | EAN (Single Pack) | Product Description                                 | W    | V/mA |       | PPG |
|---------------------------------------|-------------------|---|------|------|-------|-----|
| <b>9900mm (L) x 8mm (W) x 3mm (H)</b> |                   |   |      |      |       |     |
| LF05AW3F827                           | 4008321546906     | LF05A-W3F-827 LINEARlight Flex/ Eco FineWHITE 2700K | 72   | 24   | 8     | 38  |
| OSLF05AW3F830                         | 4008321955371     | LF05A-W3F-830 LINEARlight Flex/ Eco FineWHITE 3000K | 72   | 24   | 8     | 38  |
| OSLF05AW3F840                         | 4008321955364     | LF05A-W3F-840 LINEARlight Flex/ Eco FineWHITE 4000K | 72   | 24   | 8     | 38  |
| OSLF5AB3                              | 4008321955388     | LF05A-B3 LINEARlight Flex/ Eco Blue                 | 72   | 24   | 8     | 38  |
| <b>6000mm (L) x 8mm (W) x 3mm (H)</b> |                   |   |      |      |       |     |
| OSLF05EW2F830                         | 4008321955401     | LF05E-W2F-830 LINEARlight Flex/ Eco FineWHITE 3000K | 24.5 | 24   | 8     | 38  |
| OSLF05EW2F840                         | 4008321955395     | LF05E-W2F-840 LINEARlight Flex/ Eco FineWHITE 4000K | 24.5 | 24   | 8     | 38  |
| OSLF05EB2                             | 4008321955425     | LF05E-B2 LINEARlight Flex/ Eco Blue                 | 24.5 | 24   | 8     | 38  |
| OSLF5ER1                              | 4008321955418     | LF05E-R1 LINEARlight Flex/ Eco Red                  | 36   | 24   | 8     | 38  |
| OSLF5EY2                              | 4008321955449     | LF05E-T2 LINEARlight Flex/ Eco Green                | 24.5 | 24   | 8     | 38  |
| OSLF05EY1                             | 4008321955432     | LF05E-Y1 LINEARlight Flex/ Eco Yellow               | 36   | 24   | 8     | 38  |
| <b>CONNECTsystem for 8mm modules</b>  |                   |   |      |      |       |     |
| LF2PINFLEX                            | 4008321955326     | LF-2PIN 25V 3A                                      | -    | -    | 10X10 | 38  |
| LFCCONN10FLEX                         | 4008321955333     | LF-CONN-10 25V 3A                                   | -    | -    | 20X10 | 38  |
| LFCCONN150FLEX                        | 4008321955340     | LF-CONN-150 25V 3A                                  | -    | -    | 10X10 | 38  |
| LF2TERMFLEX                           | 4008321955357     | LF-2TERM  | -    | -    | 20X10 | 38  |

Perfectly matched with OPTOTRONIC® OT 24V Range



All orders must be multiples of sales pack

## LED Modules

**LINEARlight Flex**

- Linear LED module on a flexible circuit board
- TOPLED® version is 8.4m long and can be split into units of 10 LEDs
- SIDELED® version is 4.2m long and can be split into units of 4 LEDs
- Adhesive tape on reverse provides easy installation
- Ideal for lighting complex contours


| Product ID Code         | EAN (Single Pack) | Product Description                               | W    | V/mA | No. | PPG  |
|-------------------------|-------------------|---|------|------|-----|------|
| <b>600 LED TOPLED®</b>  |                   |   |      |      |     |      |
| OSLM10AW3F827           | 4008321940490     | LM10A-W3F-827 LINEARlight Flex White              | 72   | 24   | 1   | 8 38 |
| OSLM10AW3F830           | 4008321342874     | LM10A-W3F-830 LINEARlight Flex White              | 72   | 24   | 1   | 8 38 |
| OSLM10AW3F835           | 4008321938350     | LM10A-W3F-835 LINEARlight Flex White              | 72   | 24   | 1   | 8 38 |
| OSLM10A2                | 4008321341990     | LM10A-A2 LINEARlight Flex Red                     | 72   | 24   | 1   | 8 38 |
| OSLM10B2                | 4008321168818     | LM10A-B2 LINEARlight Flex Blue                    | 72   | 24   | 1   | 8 38 |
| OSLM10AY1               | 4050300946030     | LM10A-Y1 LINEARlight Flex Yellow                  | 72   | 24   | 1   | 8 38 |
| <b>300 LED SIDELED®</b> |                   |   |      |      |     |      |
| OSLM11AW3847            | 4008321187161     | LM11A-W3-847 LINEARlight Flex SIDELED White 4700K | 30   | 10   | 2   | 8 38 |
| OSLM11AW3854            | 4008321187185     | LM11A-W3-854 LINEARlight Flex SIDELED White 5400K | 30   | 10   | 2   | 8 38 |
| OSLM11AW3865            | 4008321187208     | LM11A-W3-865 LINEARlight Flex SIDELED White 6500K | 30   | 10   | 2   | 8 38 |
| OSLM11AA                | 4008321086952     | LM11A-A LINEARlight Flex SIDELED Red              | 15   | 10   | 2   | 8 38 |
| OSLM11AB                | 4008321086976     | LM11A-B LINEARlight Flex SIDELED Blue             | 30   | 10   | 2   | 8 38 |
| OSLM11AT                | 4008321086990     | LM11A-T LINEARlight Flex SIDELED Green            | 30   | 10   | 2   | 8 38 |
| OSLM11AY1               | 4050300946016     | LM11A-Y1 LINEARlight Flex SIDELED Yellow          | 22.5 | 10   | 2   | 8 38 |

Perfectly matched with OPTOTRONIC® OT 10V Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## LED Modules



### LINEARlight


- Linear LED module on a rigid circuit board with 32 LEDs
- 448mm long and can be split into units of 4 LEDs
- Ideal for edge, signage and directional lighting

| Product ID Code | EAN (Single Pack) | Product Description                       | W | V/mA | No. | PPG |
|-----------------|-------------------|---|---|------|-----|-----|
| OSLM01AA1       | 4050300887128     | LM01A-A1 LINEARlight Red                  | 4 | 10   | 10  | 38  |
| OSLM01AS1       | 4050300888002     | LM01A-S1 LINEARlight Super Red            | 4 | 10   | 10  | 38  |
| OSLM01AO1       | 4050300888040     | LM01A-O1 LINEARlight Orange               | 4 | 10   | 10  | 38  |
| OSLM01AB2       | 4008321313652     | LM01A-B2 LINEARlight Blue                 | 4 | 10   | 10  | 38  |
| OSLM01AT2       | 4050300887845     | LM01A-T2 LINEARlight Green                | 4 | 10   | 10  | 38  |
| OSLM01AY1       | 4008321015969     | LM01A-Y1 LINEARlight Yellow               | 4 | 10   | 10  | 38  |
| OSLM01AW3F854   | 4008321387950     | LM01A-W3F-854 LINEARlight FineWHITE 5400K | 4 | 10   | 10  | 38  |
| OSLM01AW3F827   | 4008321372390     | LM01A-W3F-827 LINEARlight FineWHITE 2700K | 4 | 10   | 10  | 38  |
| OSLM01AW3F830   | 4008321342997     | LM01A-W3F 830 LINEARlight FineWHITE 3000K | 4 | 10   | 10  | 38  |
| OSLM1AW3F835    | 4008321938336     | LM01A-W3F 835 LINEARlight FineWHITE 3500K | 4 | 10   | 10  | 38  |
| OSLM01AW3F840   | 4008321343413     | LM01A-W3F 840 LINEARlight FineWHITE 4000K | 4 | 10   | 10  | 38  |

Perfectly matched with OPTOTRONIC® OT 10V Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

NEW  
NEW  
NEW  
NEW  
NEW  
NEW




### CONNECTsystem for LINEARlight and EFFECTlight

- Enables simple connection of LED modules (not suitable for LINEARlight flex)

| Product ID Code | EAN (Single Pack) | Product Description   | V/mA | No. | PPG      |
|-----------------|-------------------|---|------|-----|----------|
| OSLM2CONN       | 4008321908643     | LM-2CONN connector for 2nd gen. single colour               | 11   | 1   | 50X10 38 |
| OSLM2CONN50     | 4008321908667     | LM-2CONN-50mm flexible connector for 2nd gen. single colour | 11   | 2   | 50X10 38 |
| OSLM2PINP10     | 4008321908629     | LM-2PIN power feed for 2nd gen. single colour               | 11   | 3   | 50X10 38 |


All orders must be multiples of sales pack

## LED Modules

**LINEARlight Optics**

- Snap-on optical lens for LINEARlight
- Reduces viewing angle

| Product ID Code | EAN (Single Pack) | Product Description                                      |    |    |
|-----------------|-------------------|--|----|----|
| OP420           | 4008321908704     | 20° optics for LINEARlight module, 26° for white modules | 80 | 38 |

**DRAGOneye®**

- One high power Golden DRAGON® LED in an IP65 housing
- FineWHITE for best colour uniformity
- 22mm diameter, with M10 x 1.5mm thread
- Excellent LED efficiency 42lm/W (White version)
- 200mm pre-wired cables for simple connection
- Ideal for compact LED luminaires




| Product ID Code | EAN (Single Pack) | Product Description                        |     |       |     |    |
|-----------------|-------------------|--|-----|-------|-----|----|
| DE1W4F854       | 4008321364999     | DE1-W4F-854 DRAGONEYE 1.2W FineWHITE 5400K | 1.2 | 350mA | 264 | 38 |
| DE1W3F830       | 4008321365361     | DE1-W3F-830 DRAGONEYE 1.2W FineWHITE 3000K | 1.2 | 350mA | 264 | 38 |
| DE1A2           | 4008321909732     | DE1-A2 DRAGONEYE 0.8W Red                  | 0.8 | 350mA | 264 | 38 |
| DE1T2           | 4008321909763     | DE1-T2 DRAGONEYE 1.2W Green                | 1.2 | 350mA | 264 | 38 |
| DE1Y2           | 4008321909756     | DE1-Y2 DRAGONEYE 0.8W Yellow               | 0.8 | 350mA | 264 | 38 |

**NEW**  
**NEW**

Perfectly matched with OPTOTRONIC® OT 350mA Range  
1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## LED Modules





### DRAGONpuck®

- Three high power Golden DRAGON® LED with a highly efficient optical system
- 35mm diameter
- Only 12mm high
- 200mm pre-wired cables
- Ideal for new LED solutions where a focused light is needed

| Product ID Code | EAN (Single Pack) | Product Description                               | W   | V/mA  | PPG   |
|-----------------|-------------------|---|-----|-------|-------|
| OSDP3W3F827     | 4008321940377     | DP3-W3F-827 DRAGONpuck 3.6w 350mA FineWHITE       | 3.6 | 350mA | 16 38 |
| OSDP3W4F854     | 4008321940551     | DP3-W4F-854 DRAGONpuck 3.6w 350mA FineWHITE 5400K | 3.6 | 350mA | 16 38 |
| OSDP3A2         | 4008321149534     | DP3-A2 DRAGONpuck 2.3W 350mA Red                  | 2.3 | 350mA | 16 38 |
| OSDP3T2         | 4008321149510     | DP3-T2 DRAGONpuck 3.4W 350mA True Green           | 3.4 | 350mA | 16 38 |

Perfectly matched with OPTOTRONIC® OT 350mA Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



### DRAGONtape®

- Six series connected high power Golden DRAGON® LEDs on a flexible substrate
- Can be split into units of 1 to 6 LEDs
- Self adhesive backing
- Ideal for shop and furniture luminaires, small signals, effect lighting and industrial applications

| Product ID Code | EAN (Single Pack) | Product Description                    | W   | V/mA  | PPG   |
|-----------------|-------------------|--|-----|-------|-------|
| OSDT6B3         | 4008321365224     | DT6-W4F-854 DRAGONtape FineWHITE 5400K | 7.2 | 350mA | 25 38 |
| OSDT6B3GB       | 4008321368461     | DT6-W4F-827 DRAGONtape FineWHITE 2700K | 7.2 | 350mA | 25 38 |
| OSDT6A1         | 4008321015747     | DT6-A1 DRAGONtape 4.6w Red             | 4.8 | 350mA | 25 38 |
| OSDT6A2         | 4008321150141     | DT6-A2 DRAGONtape 4.6w Amber           | 4.8 | 350mA | 25 38 |
| OSDT6B3         | 4008321277398     | DT6-B3 DRAGONtape 4.6w Blue            | 7.2 | 350mA | 25 38 |


NEW  
NEW

Perfectly matched with OPTOTRONIC® OT 350mA Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)


All orders must be multiples of sales pack

## LED Modules

**DRAGONTape® Optics**

- Optical lens for DRAGONTape®
- 10°, 30° symmetric and 14°x22° asymmetric angles
- Ideal for focussing light from DRAGONTape®

| Product ID Code | EAN (Single Pack) | Product Description                                      |  |  |
|-----------------|-------------------|--|---|---|
| OP1110          | 4008321909893     | 10° Optics for DRAGONTape and LINEARlight DRAGON PCB     | 150   | 38  |
| OP1130          | 4008321909770     | 30° Optics for DRAGONTape and LINEARlight DRAGON PCB     | 150   | 38  |
| OP1114          | 4008321909787     | 14°x22° Optics for DRAGONTape and LINEARlight DRAGON PCB | 150   | 38  |

**DRAGON-X® Plus**

- Metal core PCB
- 170° viewing angle with optional holder/ lens clip


| Product ID Code | EAN (Single Pack) | Product Description        |  |  |  |  |
|-----------------|-------------------|----------------------------|--|--|--|---|
| DX01W4F854      | 4008321960047     | DRAGON X PLUS DX01-W4F-854 | 1.2  | 350mA  | 60   | 38  |
| DX01W4F830      | 4008321960023     | DRAGON X PLUS DX01-W4F-830 | 1.2  | 350mA  | 60   | 38  |

Perfectly matched with OPTOTRONIC® OT 350mA Range



All orders must be multiples of sales pack

## LED Modules




### DRAGON-X®

- One high power Golden DRAGON® LED on a hexagonal metal core board
- Integrated 10°, 30° and 60° optics or 120° without optics
- Without soldering cables
- Ideal for portable, compact, architectural, shop and interior luminaires

| Product ID Code | EAN (Single Pack) | Product Description   | W   | V/mA  |    | PPG |
|-----------------|-------------------|---|-----|-------|----|-----|
| DX1W3733L30     | 4008321166272     | DX1-W3-733-L30 DRAGON X 1.2w White 3300K 30° without cable  | 1.2 | 350mA | 10 | 38  |
| DX1W3733L60     | 4008321166296     | DX1-W3-733-L60 DRAGON X 1.2w White 5400K 60° without cable  | 1.2 | 350mA | 10 | 38  |
| DX1W3854W       | 4008321166234     | DX1-W3-854-W DRAGON X 1.2w White 5400K 120° without cable   | 1.2 | 350mA | 10 | 38  |
| DX1W3854L12     | 4008321166173     | DX1-W3-854-L12W DRAGON X 1.2w White 5400K 12° without cable | 1.2 | 350mA | 10 | 38  |
| DX1W3865W       | 4008321166159     | DX1-W3-865-W DRAGON X White 6500K 120° without cable        | 1.2 | 350mA | 10 | 38  |
| DX1W3865L12     | 4008321166098     | DX1-W3-865-L12W DRAGON X 1.2w White 6500K 12° without cable | 1.2 | 350mA | 10 | 38  |
| DX1W3865L30     | 4008321166111     | DX1-W3-865-L30W DRAGON X 1.2w White 6500K 30° without cable | 1.2 | 350mA | 10 | 38  |

Perfectly matched with OPTOTRONIC® OT 350mA Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



### COINlight®

- Compact round LED module with nine LED
- Ideal for path lighting, recessed wall and floor lighting

| Product ID Code | EAN (Single Pack) | Product Description           | W   | V/mA |    | PPG |
|-----------------|-------------------|-------------------------------|-----|------|----|-----|
| OSCM01EW3       | 4008321397041     | CMM01E-W3-854 COINlight White | 1.2 | 24   | 25 | 38  |


Perfectly matched with OPTOTRONIC® OT 24V Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

NEW!

All orders must be multiples of sales pack

## LED Modules



**LINEARlight DRAGON® Colormix**

- Linear high flux RGB module
- Contains 8x high power Golden DRAGON® LEDs, lens holder and heat sink
- 640 lumens of intensive mixed light consuming just 24V of electrical power
- Two versions: an integrated system including heatsink, feeder and optics (LD18A-14X22) and a single board (LD18A)
- Connection via LINEARlight DRAGON® CONNECTsystem
- Up to two modules can be connected in series
- Ideal for creating intensive colour effect and mood lighting

| Product ID Code | EAN (Single Pack) | Product Description  | W  | V/mA | PPG  |
|-----------------|-------------------|--|----|------|------|
| LD18ARGB1422    | 4008321251787     | LD18A-RGB 14x22 LINEARlight-DRAGON Colormix System with feeder | 23 | 24   | 6 38 |
| LD18ARGB        | 4008321248572     | LD18A-RGB LINEARlight-DRAGON Colormix Board with feeder        | 23 | 24   | 6 38 |

Perfectly matched with OPTOTRONIC® OT 24V Range


1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**CONNECTsystem for LINEARlight DRAGON® Colormix**

| Product ID Code | EAN (Single Pack) | Product Description  | V/mA      | PPG   |
|-----------------|-------------------|--|-----------|-------|
| LD4PIN          | 4008321931337     | LD-4PIN power feed for LINEARlight DRAGON Colormix 10mm feeder     | 25v/2.5mA | 10 38 |
| LD4CONN100      | 4008321931351     | LD-4CONN-100mm flexible connector for 2nd gen. single colour 100mm | 25v/2.5mA | 10 38 |

All orders must be multiples of sales pack

## LED Modules




### DRAGONchain® Colormix

- IPx5 LED RGB LED chain suitable for outdoor use
- Consists of 6 metal core boards with 4 high power Golden DRAGON® Argus LEDs
- 2 versions: Basic module:- PCB board; Overall module:- with housing and heatsink
- Ideal for dynamic coloured backlighting, floor mounting, mood lighting large areas

| Product ID Code | EAN (Single Pack) | Product Description                         | W  | V/mA |   | PPG |
|-----------------|-------------------|---|----|------|---|-----|
| OSDC24ARGBD     | 4008321251831     | DC24A-RGB DRAGON CHAIN Colormix             | 23 | 24   | 6 | 38  |
| OSDC24ARGBH     | 4008321254658     | DC24A-RGB-H D CHAIN Colormix Housed version | 23 | 24   | 6 | 38  |

Perfectly matched with OPTOTRONIC® OT 24V Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



### LINEARlight Colormix Flex

- Red, green and blue flexible colour mixing linear LED module
- 4m long and can be split into units of 10 LEDs
- Ideal for dynamic effect lighting


| Product ID Code  | EAN (Single Pack) | Product Description                     | W  | V/mA |   | PPG |
|------------------|-------------------|---|----|------|---|-----|
| OSLF05CERGB1     | 4008321593375     | LF05CE-RGB LINEARlight Colormix Flex    | 39 | 24   | 8 | 38  |
| OSLM10LRGB2B6    | 4008321288714     | LM10L RGB2 B6 LINEARlight Colormix Flex | 41 | 24   | 8 | 38  |
| OSLM10LRGB2B7MIX | 4008321285317     | LM10L RGB2 B7 LINEARlight Colormix Flex | 41 | 24   | 8 | 38  |
| OSLM10LRGBB7     | 4008321008824     | LM10L RGB B7 LINEARlight Colormix Flex  | 55 | 24   | 8 | 38  |
| OSLF05CARGB3     | 4008321592644     | LF05CA-RGB3 LINEARlight Colormix Flex   | 72 | 24   | 8 | 38  |

Perfectly matched with OPTOTRONIC® OT 24V Range


1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## LED Modules

**CONNECTsystem for LINEARlight Colormix Flex modules**



| Product ID Code | EAN (Single Pack) | Product Description                   | V/mA | W No. | PPG      |
|-----------------|-------------------|---------------------------------------|------|-------|----------|
| LMCONN10FLEX    | 4008321916259     | LM-CONN 10 Flex                       | 25   | 1     | 20x10 38 |
| LMCONN150FLEX   | 4008321931375     | LM-CONN 150 Flex connect system 10x10 | 25   | 2     | 10x10 38 |
| LM2PINFLEX      | 4008321916211     | LM-2PIN Flex connect system           | 25   | 4     | 10x10 38 |
| LM4PINFLEX      | 4008321916235     | LM-4PIN Flex connect system           | 25   | 3     | 10x10 38 |

**LINEARlight Colormix**

- Red, green and blue colour mixing linear LED module on a rigid circuit board
- 450mm long and can be split into units of 10 LEDs
- Ideal for dynamic effect lighting

| Product ID Code | EAN (Single Pack) | Product Description               | W   | V/mA | PPG   |
|-----------------|-------------------|-----------------------------------|-----|------|-------|
| OSLM01MRGBB7    | 4050300820873     | LM01M-RGB-B7 LINEARlight Colormix | 8.3 | 24   | 10 38 |

Perfectly matched with OPTOTRONIC® OT 24V Range


1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)**CONNECTsystem for LINEARlight Colormix**

- Enables simple connection of LED modules (not suitable for LINEARlight flex)

| Product ID Code | EAN (Single Pack) | Product Description                                       | PPG   |
|-----------------|-------------------|---|-------|
| OSLM4CONN45     | 4008321116277     | LM-4CONN-45 flexible connector for 2nd gen. single colour | 10 38 |
| OSLM4PIN        | 4008321908681     | LM-4PIN power feed for colormix                           | 10 38 |

All orders must be multiples of sales pack

## LED Modules




### COINlight® Colormix

- Compact round RGB LED module with 5 MultiLED units
- Ideal for backlighting, accent lighting, recessed wall and floor lighting

| Product ID Code | EAN (Single Pack) | Product Description              | W   | V/mA | PPG  |
|-----------------|-------------------|----------------------------------|-----|------|------|
| OSCL05ARGB      | 4008321208262     | CL05A-RGB COINlight RGB Colormix | 1.2 | 24   | 1 38 |

Perfectly matched with OPTOTRONIC® OT 24V Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



### BACKlight Protect

- NEW: special encapsulation of the LED boards providing maximum robustness
- NEW: Ingress protection IP66 for outdoor application
- Two long, flexible LED chains per module (up to 7.2m)
- New W4F-765 provides double brightness compared to W3F-865
- FineWhite for best colour uniformity
- Long lifetime and maximum reliability
- Ideal for illuminated signs and channel letters


| Product ID Code | EAN (Single Pack) | Product Description                         | W  | V/mA | PPG    |
|-----------------|-------------------|---|----|------|--------|
| BL04LPW4F       | 4008321375650     | BL04LP-W4F-765 BACKlight PROTECT FineWHITE  | 44 | 10   | 1 5 38 |
| BL02LPW4F       | 4008321375414     | BL02LP-W4F-765 BACKlight PROTECT FineWHITE  | 44 | 10   | 2 5 38 |
| BL02LPW3F       | 4008321375537     | BL02LP-W3F-830 BACKlight PROTECT Warm White | 44 | 10   | 2 5 38 |
| OSBL02LP02      | 4008321403599     | BL02LP-02-HE BACKlight PROTECT Orange       | 22 | 10   | 2 5 38 |
| OSBL02LPR2      | 4008321403575     | BL02LP-R2-HE BACKlight PROTECT Red          | 22 | 10   | 2 5 38 |
| OSBL02LPB2      | 4008321403537     | BL02LP-B2-HE BACKlight PROTECT Blue         | 22 | 10   | 2 5 38 |
| OSBL02LPT2      | 4008321403551     | BL02LP-T2-HE BACKlight PROTECT Green        | 22 | 10   | 2 5 38 |

Perfectly matched with OPTOTRONIC® OT 10V Range

NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW  
NEW

All orders must be multiples of sales pack

## LED Modules

**BACKLight POWER**

- High power LED Module for signage backlighting
- Module efficacy of 60 lm/W with 135° viewing angle

| Product ID Code | EAN (Single Pack) | Product Description | V/mA | PPG |
|-----------------|-------------------|---------------------|------|-----|
| BACKLPOW34      | 4008321534729     | BP02A-W4F-765 6500K | 24   | 38  |

Perfectly matched with OPTOTRONIC® OT 24V Range

**BACKLight BL02**

- 60 linked circuit boards each holding 2 LED
- Can be operated from one OPTOTRONIC® power supply
- S version is 2 x 4.8m long with 80mm light centre
- L version is 2 x 7.2m long with 120mm light centre
- FineWHITE for best colour uniformity
- Ideal for installation in narrow letter signage


| Product ID Code | EAN (Single Pack) | Product Description         | W  | V/mA | PPG  |
|-----------------|-------------------|-----------------------------|----|------|------|
| BACKLIGHT44W    | 4008321372277     | BL02L-W4F-765               | 44 | 10   | 5 38 |
| OSBL02SA1       | 4008321083715     | BL02S-A1 BACKlight 2G Amber | 38 | 10   | 5 38 |
| OSBL02SA2       | 4008321174932     | BL02S-A2 BACKlight 2G Amber | 38 | 10   | 5 38 |

Perfectly matched with OPTOTRONIC® OT 10V Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack


## LED Modules



### Installation aid for BACKlight BL02 and BACKlight BL04

- Self adhesive installation aid

| Product ID Code | EAN (Single Pack) | Product Description                                     |    |    |  |
|-----------------|-------------------|---|----|----|--|
| OSBLT           | 4008321161284     | BL-T 5X 60 Installation aid for BACKlight BL02 and BL04 | 60 | 38 |  |



### DRAGONchain®

- Module comprising LED Chain of 18 metal boards each with two OSRAM Golden DRAGON® LEDs
- Two modules can be operated on one OT75E OPTOTRONIC® ECG
- Efficient alternative to white neon tubes
- Very long life time - up to 60,000 hours
- FineWHITE for best colour uniformity
- Ideal for signage, illuminated advertising and corporate lighting, backlighting of complex and deep structures

| Product ID Code | EAN (Single Pack) | Product Description            |    |    |   |
|-----------------|-------------------|--------------------------------|----|----|---|
| OSDC02BW4F765   | 4008321338013     | DC02B-W4F-765 FineWHITE 6500K  | 36 | 24 | 1 |
| OSDC02CW4F765   | 4008321410757     | DC02C-W4F- 765 FineWHITE 6500K | 36 | 24 | 6 |
| OSDC02CW4F830   | 4008321410962     | DC02C-W4F- 830 FineWHITE 3000K | 36 | 24 | 6 |

Perfectly matched with OPTOTRONIC® OT 24V Range

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## LED Modules


**LEDs DECO® FLEX**

- Plug & Play flexible light strip for easy home decoration\*
- 3 x Flexible LED strips with connectors and controller
- Ideal for edge and decorative lighting

| Product ID Code | EAN (Single Pack) | Product Description       | W  | V/mA |   | PPG |
|-----------------|-------------------|---------------------------|----|------|---|-----|
| LEDDECOCBASE    | 4008321524348     | LEDS DECO FLEX BASE KIT   | 36 | 12   | 3 | 38  |
| LEDDECORG       | 4008321524409     | LEDS DECO FLEX ADD ON KIT | -  | -    | 5 | 38  |

\*Base kit with European Plug

**NEW**  
**NEW**

**LINEARlight Track**


- Lightweight aluminium track system for flexible or rigid OSRAM LINEARlight modules
- Two versions: Prismatic version for indirect lighting and diffused version for direct light
- Easy mounting and installation of flexible and rigid LED modules, either individually or as a light strip
- Rails come into two different lengths and can be shortened or extended to desired length
- Brackets and metal pins included
- Provides optimum cooling of the LED modules for long life and maximum reliability



| Product ID Code | EAN (Single Pack) | Product Description  |   |    | PPG |
|-----------------|-------------------|--|---|----|-----|
| LTH047S         | 4008321256805     | LT-H074-S DIFFS TRACK 464 x 35.5 x 37.5mm LINEARlight track  | 2 | 10 | 38  |
| LTH143S         | 4008321256829     | LT-H143-S DIFFS TRACK 1424 x 35.5 x 37.5mm LINEARlight track | 2 | 6  | 38  |
| LTH047P         | 4008321239563     | LT-H047-P PRISM TRACK 464 x 35.5 x 26.5mm LINEARlight track  | 1 | 10 | 38  |
| LTH143P         | 4008321239587     | LT-H143-P PRISM TRACK 1424 x 35.5 x 26.5mm LINEARlight track | 1 | 6  | 38  |

All orders must be multiples of sales pack

AUTOMOTIVE LAMPS



# Automotive Lamps

## Contents.

### PREMIUM UPGRADE HEADLAMPS


|                            |     |
|----------------------------|-----|
| NIGHT BREAKER® PLUS        | 174 |
| SILVERSTAR®                | 175 |
| COOL BLUE®                 | 176 |
| ULTRA LIFE®                | 177 |
| TRUCKSTAR®                 | 178 |
| XENARC®                    | 179 |
| XENARC® COOL BLUE® INTENSE | 180 |
| NIGHT RACER®               | 180 |
| X-RACER®                   | 181 |

### ORIGINAL 12V AND 24V BULBS


|   |     |
|---|-----|
| Original 12V and 24V halogen headlight bulbs                    | 182 |
| Original 12V and 24V headlight bulbs                            | 183 |
| Original Stop, tail and directional 12V and 24V auxiliary bulbs | 183 |
| Original Parking and interior 12V and 24V auxiliary bulbs       | 184 |
| Original Festoon 12V and 24V auxiliary bulbs                    | 184 |
| Original Wedge base 12V and 24V auxiliary bulbs                 | 185 |
| MINIWATT®   | 186 |
| MINI EUROBOX kits   | 187 |




## AUTOMOTIVE – PREMIUM UPGRADE HEADLAMPS



1



2



3

### NIGHT BREAKER® PLUS

- Up to 50% longer lifetime compared to first generation
- Up to 90% more light on the road and a 10% whiter light
- Twin retail DUOPACKS




| Product ID Code | EAN (Single Pack) | Product Description                | ECE Ref | W     | V  |        |   | No.  |    | PPG |
|-----------------|-------------------|------------------------------------|---------|-------|----|--------|---|------|----|-----|
| 64150NBP        | 4008321544582     | H1 Halogen NIGHT BREAKER PLUS +90% | H1      | 55    | 12 | P14.5s | 1 | 10x2 | 38 |     |
| 64193NBP        | 4008321550798     | H4 Halogen NIGHT BREAKER PLUS +90% | H4      | 60/55 | 12 | P43t   | 2 | 10x2 | 38 |     |
| 64210NBP        | 4008321548290     | H7 Halogen NIGHT BREAKER PLUS +90% | H7      | 55    | 12 | PX26d  | 3 | 10x2 | 38 |     |

Also available in single blister H1, H3, H4, H7 and H11




Also available in twin blister H1, H4, and H7

NEW  
NEW  
NEW



All orders must be multiples of sales pack

## Automotive – Premium Upgrade Headlamps

**NIGHT BREAKER®**




- Up to 90% more light on the road and a 10% whiter light
- Twin retail DUOPACKS



| Product ID Code | EAN (Single Pack) | Product Description           | ECE Ref | W     | V  |        | No. |      | PPG |
|-----------------|-------------------|-------------------------------|---------|-------|----|--------|-----|------|-----|
| 64150NBR        | 4008321226747     | H1 Halogen NIGHT BREAKER +90% | H1      | 55    | 12 | P14.5s | 1   | 10x2 | 38  |
| 64193NBR        | 4008321227096     | H4 Halogen NIGHT BREAKER +90% | H4      | 60/55 | 12 | P43t   | 2   | 10x2 | 38  |
| 64210NBR        | 4008321227201     | H7 Halogen NIGHT BREAKER +90% | H7      | 55    | 12 | PX26d  | 3   | 10x2 | 38  |

Also available in single blister H1, H3, H4, H7 and H11

Also available in twin blister H1, H4, H7

**SILVERSTAR®**


- Up to 50% more light on the road
- Twin retail DUOPACKS



| Product ID Code | EAN (Single Pack) | Product Description        | ECE Ref | W     | V  |        | No. |      | PPG |
|-----------------|-------------------|----------------------------|---------|-------|----|--------|-----|------|-----|
| 64150SVS        | 4008321144614     | H1 Halogen SILVERSTAR +50% | H1      | 55    | 12 | P14.5s | 1   | 10x2 | 38  |
| 64193SVS        | 4008321144737     | H4 Halogen SILVERSTAR +50% | H4      | 60/55 | 12 | P43t   | 2   | 10x2 | 38  |
| 64210SVS        | 4008321144751     | H7 Halogen SILVERSTAR +50% | H7      | 55    | 12 | PX26d  | 3   | 10x2 | 38  |


Also available in single blister H1, H4 and H7

Also available in twin blister H1, H4 and H7



All orders must be multiples of sales pack

## Automotive – Premium Upgrade Headlamps

**COOL BLUE®**

- Distinctive, crisp bluish-white light
- Up to 20% more light on the road

| Product ID Code | EAN (Single Pack) | Product Description | ECE Ref | W | V |  |  |  |
|-----------------|-------------------|---------------------|---------|---|---|--|--|--|
|-----------------|-------------------|---------------------|---------|---|---|--|--|--|

**Headlight Bulbs**

- Twin retail DUOPACKS

|         |               |                       |     |       |    |        |   |         |
|---------|---------------|-----------------------|-----|-------|----|--------|---|---------|
| 64150CB | 4008321144775 | H1 Halogen COOL BLUE  | H1  | 55    | 12 | P14.5s | 1 | 10x2 38 |
| 64193CB | 4008321144799 | H4 Halogen COOL BLUE  | H4  | 60/55 | 12 | P43t   | 2 | 10x2 38 |
| 64210CB | 4008321144812 | H7 Halogen COOL BLUE  | H7  | 55    | 12 | PX26d  | 3 | 10x2 38 |
| 9005CB  | 4008321164490 | HB3 Halogen COOL BLUE | HB3 | 60    | 12 | P20d   | 4 | 10x2 38 |
| 9006CB  | 4008321164513 | HB4 Halogen COOL BLUE | HB4 | 60    | 12 | P22d   | 4 | 10x2 38 |

Also available in single blister H1, H4 and H7

Also available in twin blister H1, H4 and H7


**Parking and sidelight bulbs**

- Twin blister retail packs

|            |               |                       |     |   |    |           |   |       |
|------------|---------------|-----------------------|-----|---|----|-----------|---|-------|
| 64132CB02B | 4050300925820 | H6W Halogen COOL BLUE | H6W | 6 | 12 | BAX9s     | 7 | 20 38 |
| 2825HCB02B | 4050300925707 | W5W Halogen COOL BLUE | W5W | 5 | 12 | W2.1x9.5d | 5 | 20 38 |
| 2825CB02B  | 4050300925721 | W5W COOL BLUE         | W5W | 5 | 12 | W2.1x9.5d | 5 | 20 38 |
| 3893CB02B  | 4050300925660 | T4W COOL BLUE         | T4W | 4 | 12 | BA9s      | 6 | 20 38 |

All orders must be multiples of sales pack

## Automotive – Premium Upgrade Headlamps

**ULTRA LIFE®**

- Extra longlife bulbs with a 3 year guarantee<sup>1)</sup>
- Up to 3 times longer lifetime than standard bulbs
- Designed for day and night operation



| Product ID Code | EAN (Single Pack) | Product Description | ECE Ref | W | V |  | No. |  | PPG |
|-----------------|-------------------|---------------------|---------|---|---|--|-----|--|-----|
|-----------------|-------------------|---------------------|---------|---|---|--|-----|--|-----|

**Headlight Bulbs**

- Twin retail DUOPACKS

|   |          |               |               |    |       |    |        |   |         |
|---|----------|---------------|---------------|----|-------|----|--------|---|---------|
| ■ | 64150ULT | 4008321416162 | H1 ULTRA LIFE | H1 | 55    | 12 | P14,5s | 1 | 10x2 38 |
| ■ | 64150D   | 4008321144836 | H1 LIGHT@DAY  | H1 | 55    | 12 | P14,5s | 1 | 10x2 38 |
| ■ | 64193ULT | 4008321416186 | H4 ULTRA LIFE | H4 | 60/55 | 12 | P43t   | 2 | 10x2 38 |
| ■ | 64210ULT | 4008321416148 | H7 ULTRA LIFE | H7 | 55    | 12 | PX26d  | 3 | 10x2 38 |

Also available in single blister H1, H4 and H7

Also available in twin blister H1, H4, and H7

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**Tail and sidelight bulbs**


- Longlife tail and sidelight bulbs
- Twin blister retail packs
- Also available in garage packaging

|   |             |               |                   |        |      |    |           |    |       |
|---|-------------|---------------|-------------------|--------|------|----|-----------|----|-------|
| ■ | 5007ULT02B  | 4008321415202 | R5W ULTRA LIFE    | R5W    | 5    | 12 | BA15s     | 5  | 20 38 |
| ■ | 5007D02B    | 4050300925585 | R5W LIGHT@DAY     | R5W    | 5    | 12 | BA15s     | 5  | 20 38 |
| ■ | 6418ULT02B  | 4008321415240 | C5W ULTRA LIFE    | C5W    | 5    | 12 | SV8.5-8   | 6  | 20 38 |
| ■ | 6418D02B    | 4050300773674 | C5W LIGHT@DAY     | C5W    | 5    | 12 | SV8.5-8   | 6  | 20 38 |
| ■ | 2825ULT02B  | 4008321415189 | W5W ULTRA LIFE    | W5W    | 5    | 12 | W2.1x9.5d | 7  | 20 38 |
| ■ | 2825D02B    | 4050300772936 | W5W LIGHT@DAY     | W5W    | 5    | 12 | W2.1x9.5d | 7  | 20 38 |
| ■ | 64132ULT02B | 4008321415325 | H6W ULTRA LIFE    | H6W    | 6    | 12 | BAX9S     | 8  | 20 38 |
| ■ | 64132D02B   | 4050300773339 | H6W LIGHT@DAY     | H6W    | 6    | 12 | BAX9s     | 8  | 20 38 |
| ■ | 5008ULT02B  | 4008321415226 | R10W ULTRA LIFE   | R10W   | 10   | 12 | BA15s     | 5  | 20 38 |
| ■ | 5008D02B    | 4050300773490 | R10W LIGHT@DAY    | R10W   | 10   | 12 | BA15s     | 5  | 20 38 |
| ■ | 7528ULT02B  | 4008321415288 | P21/5W ULTRA LIFE | P21/5W | 21/5 | 12 | BAY15d    | 9  | 20 38 |
| ■ | 7528D02B    | 4050300773384 | P21/5W LIGHT@DAY  | P21/5W | 21/5 | 12 | BAY15d    | 9  | 20 38 |
| ■ | 7506ULT02B  | 4008321415141 | P21W ULTRA LIFE   | P21W   | 21   | 12 | BA15s     | 10 | 20 38 |
| ■ | 7507ULT02B  | 4008321415165 | PY21W ULTRA LIFE  | PY21W  | 21   | 12 | BAU15s    | 11 | 20 38 |



All orders must be multiples of sales pack

## Automotive – Premium Upgrade Headlamps

**TRUCKSTAR®**

- Up to 100% more life and up to 100% more light on the road
- Ideal headlamp upgrade for commercial vehicles

| Product ID Code | EAN (Single Pack) | Product Description | ECE Ref | W | V | PPG | No. | Box |
|-----------------|-------------------|---------------------|---------|---|---|-----|-----|-----|
|-----------------|-------------------|---------------------|---------|---|---|-----|-----|-----|

**Headlight Bulbs****Twin retail DUOPACKS**

|          |               |              |    |       |    |        |   |      |    |
|----------|---------------|--------------|----|-------|----|--------|---|------|----|
| 64155LTS | 4008321161062 | H1 TRUCKSTAR | H1 | 70    | 24 | P14.5s | 1 | 10x2 | 38 |
| 64196LTS | 4008321161260 | H4 TRUCKSTAR | H4 | 70/75 | 24 | P43t   | 3 | 10x2 | 38 |
| 64215LTS | 4008321161246 | H7 TRUCKSTAR | H7 | 70    | 24 | PX26d  | 4 | 10x2 | 38 |

**Single blister retail packs**

|             |               |              |    |       |    |        |   |    |    |
|-------------|---------------|--------------|----|-------|----|--------|---|----|----|
| 64155LTS01B | 4008321040596 | H1 TRUCKSTAR | H1 | 70    | 24 | P14.5s | 1 | 10 | 38 |
| 64156LTS01B | 4008321040572 | H3 TRUCKSTAR | H3 | 70    | 24 | PK22s  | 2 | 10 | 38 |
| 64196LTS01B | 4008321155535 | H4 TRUCKSTAR | H4 | 70/75 | 24 | P43t   | 3 | 10 | 38 |
| 64215LTS01B | 4008321040619 | H7 TRUCKSTAR | H7 | 70    | 24 | PX26d  | 4 | 10 | 38 |

**Single box carton packs**

|          |               |              |    |       |    |        |   |     |    |
|----------|---------------|--------------|----|-------|----|--------|---|-----|----|
| 64155LTS | 4008321004093 | H1 TRUCKSTAR | H1 | 70    | 24 | P14.5s | 1 | 100 | 38 |
| 64156LTS | 4008321004123 | H3 TRUCKSTAR | H3 | 70    | 24 | PK22s  | 2 | 100 | 38 |
| 64196LTS | 4008321133571 | H4 TRUCKSTAR | H4 | 70/75 | 24 | P43t   | 3 | 100 | 38 |
| 64215LTS | 4008321004246 | H7 TRUCKSTAR | H7 | 70    | 24 | PX26d  | 4 | 100 | 38 |


**Stop, tail and directional indicator bulbs**

- Previously known as GIGANT® HEAVY DUTY
- Twin blister retail packs
- Also available in carton packs

|            |               |                 |       |    |    |              |   |    |    |
|------------|---------------|-----------------|-------|----|----|--------------|---|----|----|
| 3930LTS02B | 4008321174055 | T4W TRUCKSTAR   | T4W   | 4  | 24 | BA9s         | – | 20 | 38 |
| 5627LTS02B | 4008321174017 | R5W TRUCKSTAR   | R5W   | 5  | 24 | BA15s        | – | 20 | 38 |
| 5637LTS02B | 4008321174031 | R10W TRUCKSTAR  | R10W  | 10 | 24 | BA15s        | – | 20 | 38 |
| 7511LTS02B | 4008321173973 | P21W TRUCKSTAR  | P21W  | 21 | 24 | BA15s        | – | 20 | 38 |
| 7510LTS02B | 4008321173997 | PY21W TRUCKSTAR | PY21W | 21 | 24 | BAU15s Amber | – | 20 | 38 |

All orders must be multiples of sales pack

## Automotive – Premium Upgrade Headlamps


**XENARC®**

- Electronic Gas Discharge Headlight Bulbs
- Produces up to 100% more light output than standard halogen headlight bulbs
- Ideal for vehicles with existing gas discharge headlight systems only



| Product ID Code | EAN (Single Pack) | Product Description | ECE Ref | W  |         |   | No. |    | PPG |
|-----------------|-------------------|---------------------|---------|----|---------|---|-----|----|-----|
| 66142           | 4050300893259     | D1S XENARC**        | D1S     | 35 | PK32d-2 | 1 | 10  | 38 |     |
| 66152           | 4008321902719     | D1R XENARC**        | D1R     | 35 | PK32d-3 | 2 | 10  | 38 |     |
| 66040           | 4050300357393     | D2S XENARC**        | D2S     | 35 | P32d-2  | 3 | 10  | 38 |     |
| 66050           | 4050300433486     | D2R XENARC**        | D2R     | 35 | P32d-3  | 4 | 10  | 38 |     |
| 66144           | 4008321184474     | D1S XENARC**        | D1S     | 35 | PK32d-2 | 1 | 10  | 38 |     |
| 66154           | 4008321184511     | D1R XENARC**        | D1R     | 35 | PK32d-3 | 2 | 10  | 38 |     |
| 66240           | 4008321184573     | D2S XENARC**        | D2S     | 35 | P32d-2  | 3 | 10  | 38 |     |
| 66250           | 4008321184634     | D2R XENARC**        | D2R     | 35 | P32d-3  | 4 | 10  | 38 |     |
| 66340           | 4008321379627     | D3S XENARC**        | D3S     | 35 | PK32d-5 | 5 | 10  | 38 |     |
| 66350           | 4008321129857     | D3R XENARC**        | D3R     | 35 | PK32d-6 | 6 | 10  | 38 |     |
| 66440           | 4008321349392     | D4S XENARC**        | D4S     | 35 | P32d-5  | 7 | 10  | 38 |     |
| 66450           | 4008321349576     | D4R XENARC**        | D4R     | 35 | P32d-6  | 8 | 10  | 38 |     |

\*\*For use with XENAELECTRON® electronic control gear – available on request


**XENARC® D2 COOL BLUE®**

- Extra blue xenon light with razor sharp contrast

| Product ID Code | EAN (Single Pack) | Product Description  | ECE Ref | W  |        |   | No. |    | PPG |
|-----------------|-------------------|----------------------|---------|----|--------|---|-----|----|-----|
| 66240CB         | 4008321213518     | D2S XENARC COOL BLUE | D2S     | 35 | P32d-2 | 1 | 10  | 38 |     |
| 66250CB         | 4008321213532     | D2R XENARC COOL BLUE | D2R     | 35 | P32d-3 | 2 | 10  | 38 |     |

All orders must be multiples of sales pack

## Automotive – Premium Upgrade Headlamps


**XENARC® COOL BLUE® INTENSE**

- The new extra blue intense xenon light with razor sharp contrast
- up to 20% more light – 5000 Kelvin



| Product ID Code | EAN (Single Pack) | Product Description          | ECE Ref | W  | V       |   |      | No. |  | PPG |
|-----------------|-------------------|------------------------------|---------|----|---------|---|------|-----|--|-----|
| 66144CBI        | 4008321401472     | D1S XENARC COOL BLUE INTENSE | D1S     | 35 | PK32d-2 | 1 | 10   | 38  |  |     |
| 66154CBI        | 4008321401373     | D1R XENARC COOL BLUE INTENSE | D1R     | 35 | PK32d-3 | 2 | 10   | 38  |  |     |
| 66240CBI        | 4008321401359     | D2S XENARC COOL BLUE INTENSE | D2S     | 35 | P32d-2  | 3 | 10   | 38  |  |     |
| 66250CBI        | 4008321401533     | D2R XENARC COOL BLUE INTENSE | D2R     | 35 | P32d-3  | 4 | 10   | 38  |  |     |
| 66240CBI        | 4008321588883     | D2S XENARC COOL BLUE INTENSE | D2S     | 35 | P32d-2  | 3 | 10X2 | 38  |  |     |

NEW  
NEW  
NEW  
NEW

**NIGHT RACER®**

- Up to 90% more light on the road
- 10% whiter light
- See and be seen - for safer riding




| Product ID Code | EAN (Single Pack) | Product Description | ECE Ref | W | V |  |  | No. |  | PPG |
|-----------------|-------------------|---------------------|---------|---|---|--|--|-----|--|-----|
|-----------------|-------------------|---------------------|---------|---|---|--|--|-----|--|-----|

**Headlight Bulbs****Twin Blister Packs with a special helmet shaped box**

|            |               |                |    |       |    |       |   |    |    |  |
|------------|---------------|----------------|----|-------|----|-------|---|----|----|--|
| 64193NR02B | 4008321395672 | H4 NIGHT RACER | H4 | 60/55 | 12 | P43t  | 1 | 20 | 38 |  |
| 64210NR02B | 4008321395658 | H7 NIGHT RACER | H7 | 55    | 12 | PX26d | 2 | 20 | 38 |  |

All orders must be multiples of sales pack

## Automotive – Premium Upgrade Headlamps



1 2

**X-RACER®**

- XTRA Blue light for that look of Xenon
- Up to 4000 Kelvin
- See and be seen – for style concious riders




| Product ID Code | EAN (Single Pack) | Product Description | ECE Ref | W | V |  | No. |  | PPG |
|-----------------|-------------------|---------------------|---------|---|---|--|-----|--|-----|
|-----------------|-------------------|---------------------|---------|---|---|--|-----|--|-----|

**Headlight Bulbs****Twin Blister Packs with a special helmet shaped box**

|            |               |            |    |       |    |       |   |    |    |
|------------|---------------|------------|----|-------|----|-------|---|----|----|
| 64193XR02B | 4008321395719 | H4 X-RACER | H4 | 60/55 | 12 | P43t  | 1 | 20 | 38 |
| 64210XR02B | 4008321395696 | H7 X-RACER | H7 | 55    | 12 | PX26d | 2 | 20 | 38 |



All orders must be multiples of sales pack


**AUTOMOTIVE – ORIGINAL 12V AND 24V****Original 12V and 24V halogen headlight bulbs****ORIGINAL SPARE PART**

| Product ID Code                    | EAN (Single Pack) | Product Description          | ECE Ref | W      | V  | Ref.     | No. | PPG    |
|------------------------------------|-------------------|------------------------------|---------|--------|----|----------|-----|--------|
| <b>12V halogen headlight bulbs</b> |                   |                              |         |        |    |          |     |        |
| 64150                              | 405030001487      | H1 Halogen                   | H1      | 55     | 12 | P14.5s   | 1   | 100 38 |
| 64175                              | 4050300218900     | H2 Halogen                   | H2      | 70     | 24 | X511     | 2   | 100 38 |
| 64152                              | 4050300222738     | H1 High Performance Halogen* | H1      | 100    | 12 | PX14.5s  | –   | 100 38 |
| 64151                              | 4050300001494     | H3 Halogen                   | H3      | 55     | 12 | PK22s    | 3   | 100 38 |
| 64153                              | 4050300222837     | H3 High Performance Halogen* | H3      | 100    | 12 | PKY22s   | –   | 100 38 |
| 64193                              | 4050300001470     | H4 Halogen                   | H4      | 60/55  | 12 | P43t     | 9   | 100 38 |
| 64194                              | 4050300225852     | H4 High Performance Halogen* | H4      | 100/80 | 12 | PU43t    | –   | 100 38 |
| 64210                              | 4050300332185     | H7 Halogen                   | H7      | 55     | 12 | PX26d    | 4   | 100 38 |
| 64217                              | 4050300524399     | H7 High Performance Halogen* | H7      | 65     | 12 | PX26d    | –   | 100 38 |
| 64218                              | 4050300526188     | H7 Halogen                   | H7      | 65     | 12 | PX26d    | –   | 100 38 |
| 64212                              | 4050300498751     | H8 Halogen                   | H8      | 35     | 12 | PGJ19-1  | 5   | 100 38 |
| 64242                              | 4008321055422     | H8B Halogen                  | H8B     | 35     | 12 | PGJY19-1 | –   | 100 38 |
| 64213                              | 4050300524368     | H9 Halogen                   | H9      | 65     | 12 | PGJ19-5  | 6   | 100 38 |
| 64243                              | 4008321055477     | H9B Halogen                  | H9B     | 65     | 12 | PGJY19-5 | –   | 100 38 |
| 9145                               | 4050300186320     | H10 Halogen                  | H10     | 42     | 12 | PY20d    | 7   | 100 38 |
| 64211                              | 4050300524313     | H11 Halogen                  | H11     | 55     | 12 | PGH19-2  | 8   | 100 38 |
| 64241                              | 4008321054654     | H11B Halogen                 | H11B    | 55     | 12 | PGJY19-2 | –   | 100 38 |
| 9008                               | 4008321939401     | H13 Halogen                  | H13     | 60/55  | 12 | P26.4t   | –   | 100 38 |
| 64176                              | 4008321218391     | H15 Halogen                  | H15     | 15/55  | 12 | PGJ23t-1 | –   | 100 38 |
| 9003L                              | 4050300308975     | HB2 Halogen                  | HB2     | 60/55  | 12 | P43t     | 9   | 100 38 |
| 9005                               | 4050300137193     | HB3 Halogen                  | HB3     | 60     | 12 | P20d     | 11  | 100 38 |
| 9005XS                             | 0046135320408     | HB3A Halogen                 | HB3A    | 60     | 12 | P20d     | 12  | 100 38 |
| 9006                               | 4050300012650     | HB4 Halogen                  | HB4     | 51     | 12 | P22d     | 13  | 100 38 |
| 9006XS                             | 4050300532400     | HB4A Halogen                 | HB4A    | 51     | 12 | P22d     | –   | 100 38 |
| 64183                              | 4050300350554     | R2 Halogen                   | R2      | 45/40  | 12 | P45t     | 10  | 100 38 |
| 64185                              | 4050300439969     | HS1 Halogen                  | HS1     | 35/55  | 12 | Px43t    | 9   | 100 38 |
| <b>24V halogen headlight bulbs</b> |                   |                              |         |        |    |          |     |        |
| 64155                              | 4050300016498     | H1 Halogen                   | H1      | 70     | 24 | P14.5s   | 1   | 100 38 |
| 64175                              | 4050300218900     | H2 Halogen                   | H2      | 70     | 24 | X511     | 2   | 100 38 |
| 64156                              | 4050300016535     | H3 Halogen                   | H3      | 70     | 24 | PK22s    | 3   | 100 38 |
| 64196                              | 4050300016542     | H4 Halogen                   | H4      | 75/70  | 24 | P43t     | 9   | 100 38 |
| 64215                              | 4050300386522     | H7 Halogen                   | H7      | 70     | 24 | PX26d    | 4   | 100 38 |


\*For off road use only. These products are not ECE approved and are not for use on public roads.

All orders must be multiples of sales pack

## Automotive Lamps – Original 12V and 24V








1



2

## Original 12V and 24V headlight bulbs

| Product ID Code | EAN (Single Pack) | Product Description | ECE Ref | W     | V  |       | No. | PPG |    |
|-----------------|-------------------|---------------------|---------|-------|----|-------|-----|-----|----|
| 7951            | 4050300001500     | R2 12V              | R2      | 45/40 | 12 | P45t  | 1   | 100 | 38 |
| 7952            | 4050300016405     | R2 24V              | R2      | 55/50 | 24 | P45t  | 1   | 100 | 38 |
| 7326            | 4050300271248     | S1 12V              | S1      | 25/25 | 12 | BA20d | 2   | 100 | 38 |
| 7327            | 4050300016375     | S2 12V              | S2      | 35/35 | 12 | BA20d | 2   | 100 | 38 |



9

## Original stop, tail &amp; directional 12V and 24V auxiliary bulbs

| Product ID Code | EAN (Single Pack) | ECE Ref     | W    | V  |        | No. | PPG |    |
|-----------------|-------------------|-------------|------|----|--------|-----|-----|----|
| 5627            | 4050300838335     | R5W         | 5    | 24 | BA15s  | 1   | 50  | 38 |
| 5626            | 4008321095336     | –           | 5    | 24 | BA15d  | 2   | 50  | 38 |
| 5007            | 4050300838427     | R5W         | 5    | 12 | BA15s  | 1   | 50  | 38 |
| 3893            | 4050300838489     | T4W         | 4    | 12 | BA9s   | 4   | 50  | 38 |
| 64132           | 4008321094896     | H6W         | 6    | 12 | BAX9s  | –   | 50  | 38 |
| 64136           | 4008321095190     | H21W        | 21   | 12 | BAY9s  | 8   | 50  | 38 |
| 64138           | 4008321094988     | H21W        | 21   | 24 | BAY9s  | 8   | 50  | 38 |
| 7511            | 4050300838090     | P21W        | 21   | 24 | BA15s  | 5   | 50  | 38 |
| 5008            | 4050300838212     | R10W        | 10   | 12 | BA15s  | 1   | 50  | 38 |
| 5009            | 4008321095442     | RY10W       | 10   | 12 | BAU15s | 3   | 50  | 38 |
| 5637            | 4050300831459     | R10W        | 10   | 24 | BA15s  | 1   | 50  | 38 |
| 3930            | 4050300838366     | T4W         | 4    | 24 | BA9s   | 6   | 50  | 38 |
| 7528            | 4050300838069     | P21/5W      | 21/5 | 12 | BAY15d | 7   | 50  | 38 |
| 7537            | 4050300838038     | P21/5W      | 21/5 | 24 | BAY15d | 7   | 50  | 38 |
| 7506            | 4050300838120     | P21W        | 21   | 12 | BA15s  | 5   | 50  | 38 |
| 7225            | 4050300891514     | P21/4W      | 21/5 | 12 | BAZ15d | 7   | 50  | 38 |
| 7507            | 4050300891477     | PY21W AMBER | 21   | 12 | BAU15s | 9   | 50  | 38 |

All orders must be multiples of sales pack

## Automotive Lamps – Original 12V and 24V



1



2



3

## Original Parking &amp; Interior 12V and 24V auxiliary bulbs


| Product ID Code | EAN (Single Pack) | W | V  |      |   |    | PPG |
|-----------------|-------------------|---|----|------|---|----|-----|
| 3796            | 4050300891309     | 2 | 12 | BA9s | 1 | 50 | 38  |
| 3797            | 4050300891668     | 2 | 24 | BA9s | 2 | 50 | 38  |
| 3860            | 4008321095756     | 5 | 12 | BA9s | 3 | 50 | 38  |
| 3894            | 4008321095725     | 3 | 12 | BA9s | 1 | 50 | 38  |



1



2



3




4

## Original Festoon 12V and 24V auxiliary bulbs

| Product ID Code | EAN (Single Pack) | ECE Ref | W  | V  |         |   |    | PPG |
|-----------------|-------------------|---------|----|----|---------|---|----|-----|
| 6418            | 4050300838397     | C5W     | 5  | 12 | SV8.5-8 | 1 | 50 | 38  |
| 6423            | 4050300831435     | C5W     | 5  | 24 | SV8.5-8 | 1 | 50 | 38  |
| 6428            | 4008321094384     | C3W     | 3  | 12 | SV7-8   | 3 | 50 | 38  |
| 6430            | 4008321094414     | –       | 3  | 24 | SV7-8   | 3 | 50 | 38  |
| 6411            | 4050300891354     | –       | 10 | 12 | SV8.5-8 | 2 | 50 | 38  |
| 6413            | 4050300891439     | –       | 5  | 12 | SV8.5-8 | 2 | 50 | 38  |
| 6421            | 4008321090768     | –       | 3  | 24 | SV8.5-8 | 4 | 50 | 38  |
| 6424            | 4050300891712     | –       | 5  | 24 | SV8.5-8 | 4 | 50 | 38  |
| 6438            | 4008321094353     | –       | 10 | 12 | SV8.5-8 | 1 | 50 | 38  |
| 6461            | 4008321094261     | –       | 10 | 12 | SV8.5-8 | 1 | 50 | 38  |
| 6429            | 4008321090836     | –       | 10 | 24 | SV8.5-8 | 4 | 50 | 38  |
| 6453            | 4008321094544     | –       | 15 | 24 | SV8.5-8 | 4 | 50 | 38  |
| 6475            | 4008321090874     | –       | 18 | 12 | SV8.5-8 | 4 | 50 | 38  |
| 6480            | 4008321090935     | –       | 18 | 24 | SV8.5-8 | 4 | 50 | 38  |
| 6476            | 4008321090904     | C21W    | 21 | 12 | SV8.5-8 | 4 | 50 | 38  |

All orders must be multiples of sales pack

## Automotive Lamps – Original 12V and 24V


**Original Wedge base 12V and 24V auxiliary bulbs**

| Product ID Code | EAN (Single Pack) | ECE Ref | W    | V  |                 | Wash No. |    | PPG |
|-----------------|-------------------|---------|------|----|-----------------|----------|----|-----|
| 2721            | 4050300838540     | –       | 1.2  | 12 | W2x4.6d         | 1        | 50 | 38  |
| 2825            | 4050300838632     | W5W     | 5    | 12 | W2.1x9.5d       | 2        | 50 | 38  |
| 2821            | 4050300838663     | W3W     | 3    | 12 | W2.1x9.5d       | 3        | 50 | 38  |
| 2840            | 4008321094698     | –       | 2    | 24 | W2.1x9.5d       | 4        | 50 | 38  |
| 2841            | 4008321094728     | W3W     | 3    | 24 | W2.1x9.5d       | 5        | 50 | 38  |
| 2845            | 4050300891552     | W5W     | 5    | 24 | W2.1x9.5d       | 6        | 50 | 38  |
| 2827            | 4050300891200     | WY5W    | 5    | 12 | W2.1x9.5d AMBER | 7        | 50 | 38  |
| 2741            | 4050300838519     | –       | 1.2  | 24 | W2x4.6d         | 8        | 50 | 38  |
| 921             | 4008321100948     | W16W    | 16   | 12 | W2.1x9.5d       | 9        | 50 | 38  |
| 3156            | 4008321090621     | P27W    | 27   | 12 | W2.5x16d        | 10       | 50 | 38  |
| 3157            | 4008321090683     | P27/7W  | 27/7 | 12 | W2.5x16q        | 11       | 50 | 38  |
| 7505            | 4008321090652     | W21W    | 21   | 12 | W3x16d          | 12       | 50 | 38  |
| 7515            | 4008321090713     | W21/5W  | 21/5 | 12 | W3x16q          | 13       | 50 | 38  |



All orders must be multiples of sales pack

## Automotive Lamps – Original 12V and 24V

**MINIWATT®**

- Colour-coded tacho bulbs
- Sizes available to fit varying printed circuit boards
- Ideal for dashboard lighting

| Product ID Code               | EAN (Single Pack) | Product Description | W   | V  |        |   |    | PPG |
|-------------------------------|-------------------|---------------------|-----|----|--------|---|----|-----|
| <b>Suitable for 1.5mm PCB</b> |                   |                     |     |    |        |   |    |     |
| 2351MF6                       | 4008321096852     | Jet black           | 1.2 | 12 | BX8.4d | 1 | 50 | 38  |
| 2352MF6                       | 4008321097149     | Pale green          | 2   | 12 | BX8.4d | 1 | 50 | 38  |
| 2452MF6                       | 4008321097118     | Beige               | 1.5 | 12 | BX8.4d | 1 | 50 | 38  |
| 2473MF6                       | 4008321096821     | Pastel orange       | 1.1 | 12 | BX8.4d | 1 | 50 | 38  |
| <b>Suitable for 2.0mm PCB</b> |                   |                     |     |    |        |   |    |     |
| 2721MF                        | 4050300891255     | Jet black           | 1.2 | 12 | B8.5d  | 2 | 50 | 38  |
| 2722MF                        | 4008321096791     | Lime green          | 2   | 12 | B8.5d  | 2 | 50 | 38  |
| 2752MF                        | 4008321096760     | Beige               | 1.5 | 12 | B8.5d  | 2 | 50 | 38  |
| 2741MF                        | 4050300891606     | Slate grey          | 1.2 | 24 | B8.5d  | 2 | 50 | 38  |
| 64122MF                       | 4008321095107     | Copper brown        | 3   | 12 | B10d   | 4 | 50 | 38  |
| 64124MF                       | 4008321101471     | Jet black           | 5   | 12 | B10d   | 4 | 50 | 38  |
| 2721MF8                       | 4008321096388     | Jet black           | 1.2 | 12 | B8.3d  | 3 | 50 | 38  |
| 2741MF8                       | 4008321097170     | Slate grey          | 1.2 | 24 | B8.3d  | 3 | 50 | 38  |
| 2722MF8                       | 4008321096418     | White               | 2   | 12 | B8.3d  | 3 | 50 | 38  |



All orders must be multiples of sales pack

## Automotive Lamps – Original 12V and 24V

**MINI EUROBOX Kits**

- Compact spare bulb kit
- Covers all major car types and manufacturers
- Essential for foreign motoring
- Ideal for all road users

| Product ID Code | EAN (Single Pack) | Product Description                   | 12 | 10 | 38 |
|-----------------|-------------------|---------------------------------------|----|----|----|
| CLKM H1         | 4050300875217     | H1 Mini Eurobox car spare bulb kit    | 12 | 10 | 38 |
| CLKM H4         | 4050300873398     | H4 Mini Eurobox car spare bulb kit    | 12 | 10 | 38 |
| CLKM H7         | 4050300876375     | H7 Mini Eurobox car spare bulb kit    | 12 | 10 | 38 |
| CLKM H7/H1      | 4050300873411     | H1/H7 Mini Eurobox car spare bulb kit | 12 | 10 | 38 |



All orders must be multiples of sales pack

DISPLAY/OPTIC LAMPS



# Display/Optic Lamps

## Contents.


|  |     |
|--|-----|
| HMI® single ended metal halide   | 191 |
| HMI® double ended metal halide   | 192 |
| HTI® single ended metal halide   | 193 |
| HTI® double ended metal halide   | 193 |
| Baby SharXS® HTI® double ended metal halide                              | 194 |
| SharXS® HTI® double ended metal halide                                   | 195 |
| Maxi SharXS® HTI® double ended metal halide                              | 195 |
| HTI® metal halide with dichroic reflector                                | 196 |
| HSR® metal halide  | 196 |
| 4ARXS HSD™ metal halide  | 197 |
| Lok-it!® metal halide lamps  | 197 |
| EMH™ metal halide lamps (Classic Line)                                   | 198 |
| Lampholders  | 199 |
| Low voltage halogen without reflector (HLX)                              | 200 |
| Low voltage halogen without reflector (Krypton)                          | 201 |
| Halogen reflector lamps – MR11 35mm diameter                             | 202 |
| Halogen reflector lamps – MR16 51mm diameter 8-20V                       | 202 |
| Halogen reflector lamps – MR16 51mm diameter 21-120V                     | 203 |
| Halogen lamps, medium/high voltage single-ended 150-360W                 | 203 |
| Halogen lamps, medium/high voltage single-ended 400-1000W                | 204 |
| Halogen studio lamps, single ended 300-650W                              | 205 |
| Halogen studio lamps, single ended 750-1000W                             | 206 |
| Halogen studio lamps, single ended 1200-2000W                            | 207 |
| Halogen lamps – double ended   | 208 |
| HPL® high performance single ended halogen lamps with special bases      | 209 |
| STUDIOLINE   | 209 |
| DOT-it Backstage Blue for entertainment                                  | 210 |
| aluPAR® 56 halogen lamps   | 210 |
| aluPAR® 64 halogen lamps   | 211 |
| Halogen lamps current controlled – single ended                          | 212 |
| Halogen lamps current controlled with PK30d base                         | 213 |
| Halogen reflector current controlled halogen lamps with dichroic coating | 214 |
| Halogen lamps current controlled – double ended                          | 215 |
| Electronic control gear for medical applications                         | 216 |
| XBO® Xenon short arc lamps with reflector 75-300W                        | 217 |
| XBO® Xenon short arc lamps with reflector 450-1000W                      | 218 |
| XBO® Classic Line for cinema projection                                  | 219 |
| XBO® Xtreme Life for cinema projection                                   | 220 |
| XBO® lamps for digital cinema projection                                 | 221 |
| XSTAGE® Xenon short arc lamps for entertainment                          | 222 |
| HBO® Mercury short arc lamps 50-200W                                     | 222 |

## CONTENTS

|  |     |
|--|-----|
| Special lamps for IR applications              | 223 |
| XERADEX® lamps                                 | 223 |
| XIS XERADEX® irradiation system                | 224 |
| DBD electronic control gear for XERADEX® lamps | 224 |
| Microlithography lamps for i-line systems      | 225 |
| Microlithography lamps for LCD systems         | 226 |
| Other Microlithography lamps up to 1000W       | 226 |
| HXP® long life mercury short-arc lamps         | 227 |
| Lamps without Halogen, low voltage             | 227 |
| SPECTRAL lamps                                 | 228 |
| Lamps for scientific purposes                  | 228 |
| HALOTHERM® Infra-red Halogen lamps             | 229 |
| RUBYSTARS® Halogen infra-red lamps             | 230 |
| SICCATHERM® Infra-red lamps                    | 230 |
| THERATHERM® INFRA-RED HEAT LAMPS               | 231 |
| Fluorescent tubes with black glass bulbs       | 232 |
| OSRAM DULUX® BLUE AND BLUE UVA                 | 232 |
| HNS® germicidal lamps producing no ozone       | 233 |



## Display/Optic Lamps

**HMI® single ended metal halide**

- 6000K – daylight colour temperature
- Excellent colour rendering
- Hot restart
- Dimmable
- Ideal for location, stage, studio and TV lighting

| Product ID Code | EAN (Single Pack) | Product Description    | W     | V   | lm      |        |   | No. |  | PPG |
|-----------------|-------------------|------------------------|-------|-----|---------|--------|---|-----|--|-----|
| HMI200SE        | 4008321299444     | HMI 200W/SE            | 200   | 70  | 16000   | GZY9.5 | 1 | 10  |  | 38  |
| HMI250SE        | 4050300239064     | HMI 250 W/SE           | 270   | 50  | 16200   | FaX1.5 | 2 | 1   |  | 38  |
| HMI400SE        | 4008321299468     | HMI 400 W/ SE          | 400   | 70  | 33000   | GZZ9.5 | 3 | 10  |  | 38  |
| HMI575SEL       | 4050300603100     | HMI 575 W/SEL XS       | 575   | 95  | 49000   | G22    | 4 | 10  |  | 38  |
| HMI700SEXS      | 4008321191601     | HMI 700 W/SE XS        | 700   | 100 | 56000   | G22    | 4 | 10  |  | 38  |
| HMI1200SEL      | 4008321062109     | HMI 1200 W/SE XS       | 1200  | 100 | 110000  | G38    | 5 | 1   |  | 38  |
| HMI1800SEXS     | 4008321378453     | HMI 1800W/SE XS        | 1800  | 140 | 165000  | G38    | 6 | 1   |  | 39  |
| HMI2500SE       | 4050300284293     | HMI 2500 W/SE XS       | 2500  | 115 | 240000  | G38    | 7 | 1   |  | 38  |
| HMI4000SE       | 4008321244314     | HMI 4000 W/SE XS       | 4000  | 200 | 380000  | G38    | 7 | 1   |  | 38  |
| HMI6000SE       | 4050300564067     | HMI 6000 W/SE XS       | 6000  | 123 | 600000  | GX38   | 6 | 1   |  | 38  |
| HMI12000SE      | 4050300650418     | HMI 12000 W/SE XS      | 12000 | 160 | 1150000 | GX38   | 6 | 1   |  | 38  |
| HMI18000SEGX51  | 4008321098955     | HMI 18000 W/SE/GX51 XS | 18000 | 225 | 1600000 | GX51   | 6 | 1   |  | 38  |

W = Watts

SE = Single ended



XS = eXtreme Seal (max. permissible foil temperature 450° C)



All orders must be multiples of sales pack

## Display/Optic Lamps



1



3



2



4

**HMI® double ended metal halide**

- 6000K – daylight colour temperature
- Excellent colour rendering
- Hot restart
- Dimmable
- Ideal for location, stage, studio and TV lighting


| Product ID Code | EAN (Single Pack) | Product Description | W     | V   | Im      | A    |         | No. |   | PPG |
|-----------------|-------------------|---------------------|-------|-----|---------|------|---------|-----|---|-----|
| HMI575DXS       | 4008321285102     | HMI 575 W/DXS       | 575   | 95  | 49000   | 7    | SFc10   | 1   | 1 | 38  |
| HMI1200DXS      | 4008321931153     | HMI 1200 W/DXS      | 1200  | 100 | 110000  | 13.8 | SFc15.5 | 2   | 1 | 38  |
| HMI2500S        | 4050300025780     | HMI 2500 W/S XS     | 2500  | 115 | 240000  | 25.6 | SFa21   | 3   | 1 | 38  |
| HMI2500DXS      | 4008321182197     | HMI 2500 W/DXS      | 2500  | 115 | 240000  | 25.6 | SFa21   | 3   | 1 | 38  |
| HMI4000DXS      | 4008321210203     | HMI 4000 W/DXS      | 4000  | 200 | 380000  | 24   | SFa21   | 3   | 1 | 38  |
| HMI6000DXS      | 4008321210210     | HMI 6000 W/DXS      | 6000  | 123 | 570000  | 55   | S25.5   | 4   | 1 | 38  |
| HMI12000DXS     | 4008321210227     | HMI 12000 W/DXS     | 12000 | 160 | 1150000 | 84   | S30     | 4   | 1 | 38  |
| HMI18000DXS     | 4008321210234     | HMI 18000 W/DXS     | 18000 | 225 | 1700000 | 88   | S30     | 4   | 1 | 38  |
| HMI24000DXS     | 4008321355805     | HMI 24000W/DXS      | 24000 | 280 | 2300000 | 86   | S30     | 4   | 1 | 38  |

W = Watts  
 S = Short  
 XS = exTreme Seal (max. permissible foil temperature 450° C)



All orders must be multiples of sales pack

## Display/Optic Lamps


**HTI® single ended metal halide**

- Metal halide lamp similar to HMI
- Short arc technology
- Ideal for fibre optic applications, effect spot lights and slide projectors

| Product ID Code | EAN (Single Pack) | Product Description | W    | V   | Im     | A    |             | No. |    | PPG |
|-----------------|-------------------|---------------------|------|-----|--------|------|-------------|-----|----|-----|
| HTIS35          | 4050300503578     | HTI S 35/12         | 35   | 85  | 3200   | 2.2  | P32d-2      | 1   | 10 | 38  |
| HTI150          | 4050300301402     | HTI 150 W           | 150  | 90  | 10000  | 1.8  | GY9.5       | 2   | 12 | 38  |
| HTI152          | 4050300461519     | HTI 152 W           | 150  | 95  | 10000  | 1.8  | GY9.5       | 3   | 12 | 38  |
| HTI700SE        | 4008321061096     | HTI 700 W/SE/75 XS  | 700  | 70  | 59000  | 10   | GY9.5       | 4   | 1  | 38  |
| HTI705SE        | 4050300618074     | HTI 705 W/SE XS     | 700  | 70  | 59000  | 10   | GY9.5       | 5   | 1  | 38  |
| HTI1200SE       | 4050300371153     | HTI 1200 W/SE XS    | 1200 | 100 | 105000 | 13.8 | GY22        | 6   | 1  | 38  |
| HTI2500SE       | 4050300371146     | HTI 2500 W/SE XS    | 2500 | 115 | 240000 | 25.6 | GY22 +cable | 7   | 1  | 38  |



JL = Square-wave AC current  
XS = eXtreme Seal (max. permissible foil temperature 450° C)

**HTI® double ended metal halide**

- Metal halide lamp similar to HMI
- Short arc technology
- Ideal for fibre optic applications, effect spot lights and slide projectors

| Product ID Code | EAN (Single Pack) | Product Description | W    | V   | Im     | A  |         | No. |   | PPG |
|-----------------|-------------------|---------------------|------|-----|--------|----|---------|-----|---|-----|
| HTI2500DEL      | 4050300596709     | HTI 2500 W/DEL      | 2500 | 115 | 270000 | 26 | Special | 1   | 1 | 38  |
| HTI4000DE       | 4050300519845     | HTI 4000 W/DE       | 4000 | 115 | 360000 | 40 | S25.5   | 2   | 1 | 38  |




~ = Sine wave AC current  
XS = eXtreme Seal (max. permissible foil temperature 450° C)



All orders must be multiples of sales pack

## Display/Optic Lamps

**Baby SharXS® HTI® double ended metal halide**

- 5600K, 5700K, 6000K, 6500K, 7500K & 8000K colour temperature
- Short arc technology
- Excellent colour rendering
- Modular design
- Ideal for location, stage, studio and TV lighting

| Product ID Code | EAN (Single Pack) | Product Description         | W   | V   | lm    | A   |         |   | PPG |
|-----------------|-------------------|-----------------------------|-----|-----|-------|-----|---------|---|-----|
| BSXHTI250D580   | 4008321129161     | Baby SharXS HTI 250 W/D5/80 | 250 | 90  | 19000 | 3.2 | SFc10-4 | 1 | 38  |
| BSXHTI300D557   | 4008321129185     | Baby SharXS HTI 300 W/D5/57 | 300 | 80  | 20000 | 4.4 | SFc10-4 | 1 | 38  |
| BSXHTI300D565   | 4008321129208     | Baby SharXS HTI 300 W/D5/65 | 300 | 100 | 22000 | 3.6 | SFc10-4 | 1 | 38  |
| BSXHTI575D556   | 4008321129345     | Baby SharXS HTI 575 W/D5/56 | 575 | 97  | 43000 | 6.9 | SFc10-4 | 1 | 38  |



XS = eXtreme Seal (max. permissible foil temperature 450° C)



All orders must be multiples of sales pack



## Display/Optic Lamps

**SharXS® HTI® double ended metal halide**

- 6000K, 7000K & 7500K colour temperature
- Short arc technology
- Excellent colour rendering
- Modular design
- Ideal for location, stage, studio and TV lighting

| Product ID Code | EAN (Single Pack) | Product Description     | W    | V   | Im     | A    |         |   | PPG |
|-----------------|-------------------|-------------------------|------|-----|--------|------|---------|---|-----|
| SXHTI400D375    | 4008321285157     | SharXS HTI 400 W/D3/75  | 400  | 49  | 26000  | 8.5  | SFc10-4 | 1 | 38  |
| SXHTI575D475    | 4008321285195     | SharXS HTI 575 W/D4/75  | 575  | 64  | 44000  | 9    | SFc10-4 | 1 | 38  |
| SXHTI700D460    | 4008321285218     | SharXS HTI 700 W/D4/60  | 700  | 70  | 59000  | 10   | SFc10-4 | 1 | 38  |
| SXHTI700D475    | 4008321285232     | SharXS HTI 700 W/D4/75  | 700  | 70  | 59000  | 10   | SFc10-4 | 1 | 38  |
| SXHTI1200D760   | 4008321285256     | SharXS HTI 1200 W/D7/60 | 1200 | 95  | 110000 | 12.7 | SFc10-4 | 1 | 38  |
| SXHTI1200D775   | 4008321285270     | SharXS HTI 1200 W/D7/75 | 1200 | 95  | 110000 | 12.7 | SFc10-4 | 1 | 38  |
| SXHTI1500D7601  | 4008321285294     | SharXS HTI 1200 W/D7/76 | 1500 | 110 | 165000 | 13.6 | SFc10-4 | 1 | 38  |



XS = eXtreme Seal (max. permissible foil temperature 450° C)

**Maxi SharXS® HTI® double ended metal halide**

- A new addition to the SharXS® family
- 6000K colour temperature
- Short arc technology
- Excellent colour rendering
- Modular design
- Ideal for location, stage, studio and TV lighting



| Product ID Code | EAN (Single Pack) | Product Description           | W    | V   | Im     | A  |         |   | PPG |
|-----------------|-------------------|-------------------------------|------|-----|--------|----|---------|---|-----|
| MSXHTI2000D1060 | 4008321334947     | Maxi SharXS HTI 2000 W/D10/60 | 2000 | 105 | 200000 | 19 | SFc15.5 | 1 | 38  |




XS = eXtreme Seal (max. permissible foil temperature 450° C)

All orders must be multiples of sales pack




## Display/Optic Lamps



### HTI® metal halide with dichroic reflector

- HTI lamp with dichroic prefocussed reflectors
- Ideal for medical applications and entertainment lighting

| Product ID Code | EAN (Single Pack) | Product Description              | W   | V  | A   |   | No. |    | PPG |
|-----------------|-------------------|----------------------------------|-----|----|-----|---|-----|----|-----|
| HTI25022        | 4050300367781     | HTI 250 W/22                     | 270 | 45 | 6   | 1 | 2   | 38 |     |
| HTI25032        | 4050300226576     | HTI 250 W/32                     | 270 | 45 | 6   | 1 | 2   | 38 |     |
| HTI40024        | 4050300228327     | HTI 400 W/24 (with plug & cable) | 400 | 55 | 7.3 | 2 | 2   | 38 |     |
| HTI40324        | 4050300386331     | HTI 403 W/24 (with plug & cable) | 400 | 55 | 7.3 | 2 | 2   | 38 |     |



### HSR® metal halide




- Single ended metal halide lamp similar to HTI lamp
- Fitted with an outer bulb for ease of handling
- Ideal for "architainment" applications

| Product ID Code | EAN (Single Pack) | Product Description | W    | V    | lm     | A    |  | No. |    | PPG |
|-----------------|-------------------|---------------------|------|------|--------|------|--|-----|----|-----|
| HSR400          | 4050300315942     | HSR 400/60          | 400  | 67   | 33000  | 6.9  |  | 1   | 10 | 38  |
| HSR57560        | 4050300941776     | HSR 575/60          | 575  | 97.5 | 49000  | 7    |  | 1   | 10 | 38  |
| HSR57572        | 4050300651187     | HSR 575/72          | 575  | 97.5 | 49000  | 7    |  | 1   | 10 | 38  |
| HSR120060       | 4050300526836     | HSR 1200/60         | 1200 | 100  | 110000 | 13.8 |  | 2   | 20 | 38  |

All orders must be multiples of sales pack



## Display/Optic Lamps



1




2

3

**4ArXS HSD™ metal halide**

- Long life HSR lamp
- Ideal for commercial and architectural applications

| Product ID Code | EAN (Single Pack) | Product Description   | W   | V  | Im    | A   |       | No. |    | PPG |
|-----------------|-------------------|-----------------------|-----|----|-------|-----|-------|-----|----|-----|
| HSD15070        | 4008321202147     | 4ArXS HSD 150W/70     | 150 | 97 | 12000 | 1.8 | G12   | 1   | 10 | 38  |
| HSD150UL75      | 4008321202116     | 4ArXS HSD 150W/UL/75) | 150 | 97 | 11000 | 1.8 | G12   | 1   | 10 | 38  |
| HSD200          | 4050300424682     | 4ArXS HSD 200W/60     | 200 | 70 | 13000 | 3.3 | GY9.5 | 2   | 10 | 38  |
| HSD25060        | 4050300501925     | 4ArXS HSD 250W/60     | 250 | 90 | 17000 | 3.3 | GY9.5 | 2   | 10 | 38  |
| HSD25080        | 4050300808635     | 4ArXS HSD 250W/80     | 250 | 95 | 17000 | 3.3 | GY9.5 | 2   | 10 | 38  |
| HSD250UL75      | 4008321083586     | 4ArXS HSD 250W/UL/75  | 250 | 90 | 15000 | 3.3 | GY9.5 | 2   | 10 | 38  |
| HSD575          | 4050300593937     | 4ArXS HSD 575W/72     | 575 | 88 | 45000 | 7.4 | GX9.5 | 3   | 10 | 38  |



1

2

3

**Lok-it!® metal halide lamps**


- Lamp system with bayonet cap
- Lampholder ensures secure hold during transportation and has a bayonet lock for rapid installation and removal



| Product ID Code  | EAN (Single Pack) | Product Description        | W    | V   | Im     | A      |   | No. |    | PPG |
|--|-------------------|----------------------------|------|-----|--------|--------|---|-----|----|-----|
| <span style="background-color: yellow; color: black; padding: 2px;">NEW</span> HSDLOKIT30080     | 4008321493989     | Lok-it! HSD 300W/80/P28    | 300  | 95  | 27000  | PGSx28 | 1 | 1   | 38 |     |
| <span style="background-color: yellow; color: black; padding: 2px;">NEW</span> HTILOKIT700P50    | 4008321485205     | Lok-it! HTI 700W/75/P50    | 700  | 100 | 50000  | PGSx50 | 2 | 1   | 38 |     |
| <span style="background-color: yellow; color: black; padding: 2px;">NEW</span> HTILOKIT700P28    | 4008321510549     | Lok-it! HTI 700W/75/P28    | 700  | 100 | 50000  | PGSx28 | 3 | 1   | 38 |     |
| <span style="background-color: yellow; color: black; padding: 2px;">NEW</span> HTILOKIT1500      | 4008321344410     | Lok-it! HTI 1500W/60/P50   | 1500 | 100 | 135000 | PGSx50 | 2 | 1   | 38 |     |
| <span style="background-color: yellow; color: black; padding: 2px;">NEW</span> LPHOLDLOCKTOGJX50 | 4008321404725     | Lamp holder Lok-it! PGJX50 | 1500 | 250 | —      | —      | — | 1   | 38 |     |
| <span style="background-color: yellow; color: black; padding: 2px;">NEW</span> LOKITPGJX28       | 4008321512079     | Lamp holder Lok-it! PGJX28 | 700  | 250 | —      | —      | — | 20  | 38 |     |

All orders must be multiples of sales pack

## Display/Optic Lamps

**EMH™ metal halide lamps (Classic Line)**

- Economy Metal Halide short arc lamps
- Economical versions of the most popular metal halide lamps
- For use in enclosed luminaires only
- Ideal for use in clubs, shops and small stages

| Product ID Code | EAN (Single Pack) | Product Description | W    | V   | lm    |         |   |    | PPG |
|-----------------|-------------------|---------------------|------|-----|-------|---------|---|----|-----|
| EMH150SE70      | 4008321345004     | EMH 150W/SE/70      | 150  | 90  | 8000  | GY9.5   | 1 | 10 | 38  |
| -               | 4008321412294*    | EMH 250W/SE/80      | 250  | 94  | 15000 | GY9.5   | 2 | 30 | 38  |
| -               | 4008321412317*    | EMH 575W/DE/60      | 575  | 95  | 42000 | SFc10-4 | 3 | 30 | 38  |
| EMH575DE75      | 4008321345066     | EMH 575W/DE/75      | 575  | 95  | 42000 | SFc10-4 | 3 | 10 | 38  |
| EMH575SE75      | 4008321345080     | EMH 575W/SE/75      | 575  | 95  | 42000 | GX9.5   | 4 | 10 | 38  |
| -               | 4008321412379*    | EMH 1200W/DE/60     | 1200 | 100 | 95000 | SFc15.5 | 3 | 30 | 38  |

\* In preparation at time of print. For further information please contact OSRAM.



All orders must be multiples of sales pack



## Display/Optic Lamps

**Lampholders**

OSRAM lampholders for halogen and discharge lamps

Optimum quality lampholders from the same source as the relevant lamps

| Product ID Code  | EAN (Single Pack) | Product Description      | W    | V    |    | PPG |
|------------------|-------------------|--------------------------|------|------|----|-----|
| LAMPHOLDERSHARXS | 4008321189042     | Lampholder SharXs SFc1-4 | 1200 | 1000 | 1  | 38  |
| LPHOLDTP22PAR    | 4008321335265     | Lampholder TP22-H/CE PAR | 1000 | 250  | 10 | 38  |
| LPHOLDTP22S4     | 4008321335241     | Lampholder TP22-H/CE     | 1000 | 250  | 10 | 38  |
| LPHOLDPAR1       | 4008321355928     | Lampholder PAR1          | 1000 | 250  | 10 | 38  |
| LPHOLDG12        | 4008321355942     | Lampholder G12           | 150  | 1000 | 4  | 38  |
| LPHOLDG22        | 4008321355966     | Lampholder G22           | 1200 | 1000 | 2  | 38  |
| LPHOLDG38        | 4008321355980     | Lampholder G38           | 5000 | 1000 | 1  | 38  |
| LPHOLDGY9        | 4008321356000     | Lampholder GY9.5         | 500  | 1000 | 2  | 38  |
| LPHOLDS26        | 4008321388636     | Lampholder S26           | 3000 | 600  | 20 | 38  |
| LPHOLDS26A       | 4008321388674     | Lampholder S26A          | 3000 | 600  | 20 | 38  |
| LPHOLDTP22XL     | 4008321388735     | Lampholder TP22-XL       | 1000 | 250  | 10 | 38  |
| LPHOLDTP23H      | 4008321388711     | Lampholder TP23-H        | 1200 | 250  | 20 | 38  |
| LPHOLDTP61       | 4008321388698     | Lampholder TP61          | 750  | 250  | 25 | 38  |



All orders must be multiples of sales pack

## Display/Optic Lamps



1



2



3



4

### Low voltage halogen without reflector (HLX)

- XENOPHOT® (HLX) lamps have a Xenon gas filling
- Up to 10% greater luminous flux than a Krypton gas filled version
- Ideal for stage and studio lighting

| Product ID Code    | EAN (Single Pack) | ANSI | LIF   | W   | V  | Im    |        | No. |    | PPG |
|--------------------|-------------------|------|-------|-----|----|-------|--------|-----|----|-----|
| <b>6V version</b>  |                   |      |       |     |    |       |        |     |    |     |
| HLX64250           | 4050300012407     | ESB  | M30   | 20  | 6  | 460   | G4     | 2   | 40 | 38  |
| HLX64251           | 4050300338316     | —    | —     | 20  | 6  | 500   | PG22   | 1   | 30 | 38  |
| HLX64265           | 4008321107053     | —    | —     | 30  | 6  | 765   | G4     | 2   | 40 | 38  |
| <b>12V version</b> |                   |      |       |     |    |       |        |     |    |     |
| HLX64610           | 4050300006697     | BRL  | A1220 | 50  | 12 | 1600  | G6.35  | 2   | 40 | 38  |
| HLX64611           | 4008321107091     | —    | —     | 50  | 12 | 1350  | G6.35  | 2   | 40 | 38  |
| HLX62138           | 4050300242958     | —    | —     | 100 | 12 | 2800  | G6.35  | 3   | 40 | 38  |
| HLX64621           | 4050300535531     | —    | —     | 100 | 12 | 2750  | PG22   | 1   | 30 | 38  |
| HLX64623           | 4050300012018     | EVA  | M28   | 100 | 12 | 2800  | GY6.35 | 2   | 40 | 38  |
| HLX64625           | 4050300006703     | FCR  | A1215 | 100 | 12 | 3600  | GY6.35 | 2   | 40 | 38  |
| <b>15V Version</b> |                   |      |       |     |    |       |        |     |    |     |
| HLX64633           | 4050300006710     | BRJ  | A1234 | 150 | 15 | 5600  | G6.35  | 2   | 40 | 38  |
| <b>24V Version</b> |                   |      |       |     |    |       |        |     |    |     |
| HLX64638           | 4050300283050     | —    | —     | 100 | 24 | 2900  | G6.35  | 2   | 40 | 38  |
| HLX64640           | 4050300006727     | FCS  | A1216 | 150 | 24 | 6000  | G6.35  | 2   | 40 | 38  |
| HLX64641           | 4050300048260     | —    | —     | 150 | 24 | 2700  | G6.35  | 2   | 40 | 38  |
| HLX64642           | 4050300012025     | FDV  | M184  | 150 | 24 | 5000  | G6.35  | 2   | 40 | 38  |
| HLX64654           | 4008321241399     | —    | —     | 250 | 24 | 9000  | GY9.5  | 4   | 12 | 38  |
| HLX64655           | 4050300006734     | EHJ  | A1223 | 250 | 24 | 10000 | G6.35  | 2   | 40 | 38  |
| HLX64657           | 4050300012001     | EVC  | M33   | 250 | 24 | 9000  | G6.35  | 2   | 40 | 38  |
| HLX64656           | 4050300023120     | FNT  | —     | 275 | 24 | 10000 | G6.35  | 2   | 40 | 38  |
| <b>36V Version</b> |                   |      |       |     |    |       |        |     |    |     |
| HLX64663           | 4050300006741     | EVD  | A1239 | 400 | 36 | 16000 | G6.35  | 2   | 40 | 38  |
| HLX64664           | 4008321241474     | —    | —     | 400 | 36 | 14500 | G6.35  | 2   | 40 | 38  |
| HLX64665           | 4008321099761     | —    | —     | 400 | 36 | 12200 | G6.35  | 2   | 12 | 38  |

All orders must be multiples of sales pack

## Display/Optic Lamps



1

2

3

4

5

**Low voltage tungsten halogen without reflector (Krypton)**

- Krypton gas filling
- Clear finish
- Ideal for stage and studio lighting and industrial applications



| Product ID Code      | EAN (Single Pack) | ANSI | LIF   | W   | V    | Im   |       | No. |    | PPG |
|----------------------|-------------------|------|-------|-----|------|------|-------|-----|----|-----|
| <b>6V version</b>    |                   |      |       |     |      |      |       |     |    |     |
| 64222                | 4050300327273     | —    | —     | 10  | 6    | 150  | PG22  | 1   | 30 | 38  |
| 64223                | 4008321107039     | —    | M43   | 10  | 6    | 150  | G4    | 2   | 40 | 38  |
| 64225                | 4050300006758     | ESA  | M29   | 10  | 6    | 200  | G4    | 2   | 40 | 38  |
| 64275                | 4050300258690     | —    | M137  | 35  | 6    | 760  | G4    | 3   | 40 | 38  |
| <b>12V version</b>   |                   |      |       |     |      |      |       |     |    |     |
| 64258                | 4050300285153     | —    | —     | 20  | 12   | 350  | G4    | 2   | 40 | 38  |
| 64259                | 4008321352569     | —    | —     | 20  | 12   | 400  | G4    | 2   | 40 | 38  |
| 64260                | 4050300099798     | —    | M185  | 30  | 12   | 800  | PG22  | 1   | 30 | 38  |
| 64261                | 4050300220529     | —    | M130  | 30  | 12   | 750  | G6.35 | 2   | 40 | 38  |
| 64602                | 4008321107077     | —    | M134  | 50  | 12   | 1000 | G6.35 | 2   | 40 | 38  |
| 64628                | 4008321099549     | FDT  | A1261 | 100 | 12   | 3000 | GY9.5 | 4   | 12 | 38  |
| <b>22.8V version</b> |                   |      |       |     |      |      |       |     |    |     |
| 64291                | 4008321330550     | —    | —     | 40  | 22.8 | 1200 | G6.35 | 5   | 40 | 38  |
| 64650                | 4008321107138     | —    | —     | 50  | 22.8 | 1150 | G6.35 | 3   | 40 | 38  |
| 64668                | 4008321331182     | —    | —     | 80  | 22.8 | 3050 | G6.35 | 5   | 40 | 38  |
| 64292XIR             | 4008321330598     | —    | —     | 150 | 22.8 | 6000 | G6.35 | 5   | 40 | 38  |
| <b>24V version</b>   |                   |      |       |     |      |      |       |     |    |     |
| 64647                | 4008321107114     | —    | —     | 100 | 24   | 3600 | G6.35 | 3   | 40 | 38  |
| 64643                | 4008321099648     | FDS  | A1262 | 150 | 24   | 5000 | GY9.5 | 4   | 12 | 38  |


Some lamp models are available as XENOPHOT® versions (type HLX®).

With xenon instead of krypton as the filler gas, a luminous flux up to 10 % higher is achieved with the same electrical lamp data for details refer to page 200



All orders must be multiples of sales pack

## Display/Optic Lamps



### Halogen reflector lamps – MR11 35mm diameter

- Compact design
- With prefocussed reflector
- Ideal for theatre, film and TV lighting

| Product ID Code | EAN (Single Pack) | W   | V  | GZ       | No. | PPG |    |
|-----------------|-------------------|-----|----|----------|-----|-----|----|
| 64255           | 4050300006833     | 20  | 8  | GZX4     | 1   | 20  | 38 |
| 64613           | 4050300241012     | 75  | 12 | G5.3-4.8 | 2   | 20  | 38 |
| 64617           | 4050300231211     | 75  | 12 | G5.3-4.8 | 2   | 20  | 38 |
| 64617S          | 4050300461106     | 75  | 12 | G5.3-4.8 | 2   | 20  | 38 |
| 64624           | 4050300013916     | 100 | 12 | G5.3-4.8 | 2   | 20  | 38 |



### Halogen reflector lamps – MR16 51mm diameter 8-20V

- Compact design
- With prefocused reflector
- Ideal for theatre, film and TV lighting




| Product ID Code     | EAN (Single Pack) | ANSI  | LIF   | W   | V    | GZ     | No. | PPG |
|---------------------|-------------------|-------|-------|-----|------|--------|-----|-----|
| 64607               | 4050300006789     | EFM   | A1229 | 50  | 8    | GZ6.35 | 20  | 38  |
| HLX64615            | 4050300006796     | EFN   | A1230 | 75  | 12   | GZ6.35 | 20  | 38  |
| HLX64627            | 4050300006802     | EFP   | A1231 | 100 | 12   | GZ6.35 | 20  | 38  |
| 64629               | 4050300943169     | –     | –     | 100 | 12   | GZ6.35 | 20  | 38  |
| 64637               | 4008321352071     | –     | A1271 | 100 | 12   | GZ6.35 | 20  | 38  |
| 64619 <sup>1)</sup> | 4050300017273     | EPX   | –     | 90  | 14.5 | GX5.3  | 50  | 38  |
| 64620               | 4050300797397     | EFR-5 | –     | 150 | 15   | GZ6.35 | 20  | 38  |
| HLX64634            | 4050300006819     | EFR   | A1232 | 150 | 15   | GZ6.35 | 20  | 38  |
| HLX64635            | 4050300238807     | –     | –     | 150 | 15   | GZ6.35 | 20  | 38  |

1) Available on request. For further information please contact OSRAM

All orders must be multiples of sales pack

## Display/Optic Lamps


**Halogen reflector lamps – MR16 51mm diameter 21-120V**

- Compact design
- With prefocused reflector
- Ideal for theatre, film and TV lighting

| Product ID Code | EAN (Single Pack) | ANSI   | W   | V   |       |    | PPG |
|-----------------|-------------------|--------|-----|-----|-------|----|-----|
| 93637           | 4050300350097     | EJV    | 150 | 21  | GX5.3 | 24 | 38  |
| 93638           | 4050300456843     | EKE    | 150 | 21  | GX5.3 | 24 | 38  |
| HLX64653        | 4008321540423     | ELC    | 250 | 24  | GX5.3 | 20 | 38  |
| 64659           | 4008321540188     | ELC-10 | 250 | 24  | GX5.3 | 20 | 38  |
| 93653           | 4050300636450     | ELC-3  | 250 | 24  | GX5.3 | 24 | 38  |
| 93506           | 4050300349930     | ENH    | 250 | 120 | GY5.3 | 24 | 38  |



1



2



3

**Halogen lamps, medium/high voltage single-ended 150-360W**


- Maximum luminous efficacy
- Suitable where colour temperature is required for 3400K sensitised material
- Ideal for TV, video and film studios



| Product ID Code | EAN (Single Pack) | ANSI | LIF  | W   | V   |        | No. |    | PPG |
|-----------------|-------------------|------|------|-----|-----|--------|-----|----|-----|
| 64501           | 4050300279237     | –    | –    | 150 | 120 | GX6.35 | 1   | 25 | 38  |
| 64502           | 4050300289977     | –    | –    | 150 | 230 | GX6.35 | 1   | 25 | 38  |
| 64505           | 4008321098436     | –    | –    | 200 | 230 | GX6.35 | 2   | 12 | 38  |
| 24064505        | 4008321098610     | –    | –    | 200 | 240 | GX6.35 | 2   | 12 | 38  |
| 64512           | 4008321098634     | FNS  | –    | 300 | 120 | GX6.35 | 2   | 12 | 38  |
| 64514           | 4008321098672     | –    | CP96 | 300 | 120 | GX6.35 | 2   | 12 | 38  |
| 64515           | 4008321098696     | –    | –    | 300 | 230 | GX6.35 | 2   | 12 | 38  |
| 24064515        | 4008321098719     | –    | –    | 300 | 240 | GX6.35 | 2   | 12 | 38  |
| 64516           | 4008321098733     | –    | –    | 300 | 230 | GX6.35 | 2   | 12 | 38  |
| 24064516        | 4008321098757     | –    | CP97 | 300 | 240 | GX6.35 | 2   | 12 | 38  |
| 64662           | 4008321097873     | –    | M38  | 300 | 230 | GY9.5  | 3   | 12 | 38  |

All orders must be multiples of sales pack

## Display/Optic Lamps

**Halogen lamps, medium/high voltage single-ended 400-1000W**


- Maximum luminous efficacy
- Enhanced filament design
- Ideal for theatre, film and TV lighting

| Product ID Code | EAN (Single Pack) | ANSI | LIF    | W    | V   |        | No. |    | PPG |
|-----------------|-------------------|------|--------|------|-----|--------|-----|----|-----|
| 24093591        | 4050300481555     | FSY  | -      | 400  | 240 | GY9.5  | 1   | 24 | 38  |
| 93592           | 4050300481531     | FSX  | -      | 400  | 230 | GY9.5  | 1   | 24 | 38  |
| 64672           | 4008321098559     | -    | M/40   | 500  | 230 | GY9.5  | 2   | 12 | 38  |
| 24064672        | 4008321098535     | -    | M/40   | 500  | 240 | GY9.5  | 2   | 12 | 38  |
| 64680           | 4008321098573     | -    | A1/244 | 500  | 230 | GY9.5  | 3   | 12 | 38  |
| 24064680        | 4008321098597     | -    | A1/244 | 500  | 240 | GY9.5  | 3   | 12 | 38  |
| 64540           | 4008321098818     | BVM  | P1/13  | 650  | 230 | GX6.35 | 2   | 12 | 38  |
| 24064540        | 4008321098795     | BVM  | P1/13  | 650  | 240 | GX6.35 | 2   | 12 | 38  |
| 64686           | 4008321098498     | DYR  | A1/233 | 650  | 230 | GY9.5  | 4   | 12 | 38  |
| 24064686        | 4008321098511     | DRY  | A1/233 | 650  | 240 | GY9.5  | 4   | 12 | 38  |
| 64573           | 4008321098832     | -    | -      | 1000 | 120 | GX6.35 | 2   | 12 | 38  |
| 64575           | 4008321098856     | EGY  | P115   | 1000 | 230 | GX6.35 | 2   | 12 | 38  |
| 24064575        | 4008321098450     | EGY  | P115   | 1000 | 240 | GX6.35 | 2   | 12 | 38  |



All orders must be multiples of sales pack

## Display/Optic Lamps

**Halogen studio lamps, single ended 300-650W**


- Maximum luminous efficacy
- Suitable where colour temperature is required for 3200K sensitised material
- Ideal for professional film and TV recordings

| Product ID Code | EAN (Single Pack) | ANSI | LIF  | W   | V   | Im    |       |   |    | PPG |
|-----------------|-------------------|------|------|-----|-----|-------|-------|---|----|-----|
| 64673           | 4008321099785     | –    | CP81 | 300 | 230 | 7500  | GY9.5 | 1 | 12 | 38  |
| 24064673        | 4008321099808     | –    | CP81 | 300 | 230 | 7500  | GY9.5 | 1 | 12 | 38  |
| 64670           | 4050300022536     | –    | T25  | 500 | 230 | 11000 | GY9.5 | 6 | 25 | 38  |
| 64674           | 4008321099822     | –    | CP82 | 500 | 230 | 13500 | GY9.5 | 1 | 12 | 38  |
| 24064674        | 4008321099846     | –    | CP82 | 500 | 240 | 13500 | GY9.5 | 1 | 25 | 38  |
| 64716           | 4050300506494     | GKV  | –    | 600 | 230 | 14000 | G9.5  | 2 | 25 | 38  |
| 24064716        | 4050300506517     | GKV  | –    | 600 | 240 | 14000 | G9.5  | 2 | 25 | 38  |
| 64717           | 4050300296692     | FRK  | CP89 | 650 | 230 | 16250 | GY9.5 | 3 | 25 | 38  |
| 24064717        | 4050300304953     | FRK  | CP89 | 650 | 240 | 16250 | GY9.5 | 3 | 25 | 38  |
| 64718           | 4050300022543     | GCT  | T27  | 650 | 230 | 14500 | GY9.5 | 3 | 25 | 38  |
| 24064718        | 4050300283463     | GCT  | T27  | 650 | 240 | 14500 | GY9.5 | 3 | 25 | 38  |
| 64719           | 4050300019154     | –    | T12  | 650 | 230 | 12000 | GX9.5 | 4 | 20 | 38  |
| 64720           | 4050300017716     | –    | CP23 | 650 | 230 | 16800 | GX9.5 | 4 | 20 | 38  |
| 64721           | 4050300217970     | FKH  | CP39 | 650 | 230 | 16800 | G22   | 5 | 20 | 38  |



All orders must be multiples of sales pack

## Display/Optic Lamps


**Halogen studio lamps, single ended 750-1000W**

- Maximum luminous efficacy
- Suitable where colour temperature is required for 3200K sensitised material
- Ideal for professional film and TV recordings

| Product ID Code | EAN (Single Pack) | ANSI | LIF  | W    | V   |        | No. |    | PPG |
|-----------------|-------------------|------|------|------|-----|--------|-----|----|-----|
| 64678           | 4050300609102     | —    | —    | 800  | 230 | G9.5   | 1   | 25 | 38  |
| 64576           | 4008321099860     | —    | P217 | 1000 | 230 | GX6.35 | 2   | 12 | 38  |
| 64743           | 4008321225702     | FEL  | CP77 | 1000 | 120 | G9.5   | 3   | 20 | 38  |
| 64744           | 4050300017723     | FWP  | T19  | 1000 | 230 | GX9.5  | 4   | 20 | 38  |
| 24064744        | 4050300283333     | FWP  | T19  | 1000 | 240 | GX9.5  | 4   | 20 | 38  |
| 64745           | 4050300213262     | FVA  | CP70 | 1000 | 230 | GX9.5  | 5   | 20 | 38  |
| 24064745        | 4050300283234     | FVA  | CP70 | 1000 | 240 | GX9.5  | 5   | 20 | 38  |
| 24064747        | 4050300283999     | FKJ  | CP71 | 1000 | 240 | G22    | 6   | 20 | 38  |
| 64748XS         | 4008321218483     | —    | —    | 1000 | 230 | GY9.5  | 5   | 25 | 38  |
| 24064748XS      | 4008321218506     | —    | —    | 1000 | 240 | GY9.5  | 5   | 25 | 38  |
| 93734           | 4050300350073     | FEL  | CP77 | 1000 | 240 | G9.5   | 3   | 12 | 38  |




XS = eXtreme Seal (max. permissible foil temperature 450° C)



All orders must be multiples of sales pack

## Display/Optic Lamps

**Halogen studio lamps, single ended 1200-20000W**


- Maximum luminous efficacy
- Suitable where colour temperature is required for 3200K sensitised material
- Ideal for professional film and TV recordings

| Product ID Code | EAN (Single Pack) | ANSI | LIF    | W     | V   | Im     |       | No. |    | PPG |
|-----------------|-------------------|------|--------|-------|-----|--------|-------|-----|----|-----|
| 93723           | 4008321370594     | –    | CP/110 | 1200  | 80  | 37500  | 2PIN  | 1   | 12 | 38  |
| 64752           | 4050300296616     | FWS  | T29    | 1200  | 230 | 28600  | GX9.5 | 2   | 20 | 38  |
| 24064752        | 4050300305011     | FWS  | T29    | 1200  | 240 | 28600  | GX9.5 | 2   | 20 | 38  |
| 64754           | 4050300296746     | –    | CP90   | 1200  | 230 | 30000  | GX9.5 | 3   | 20 | 38  |
| 64756           | 4050300296722     | –    | CP93   | 1200  | 230 | 30000  | G22   | 1   | 20 | 38  |
| 64777           | 4050300367682     | –    | CP92   | 2000  | 230 | 52000  | G22   | 1   | 20 | 38  |
| 64787           | 4050300246154     | –    | CP75   | 2000  | 230 | 52000  | G22   | 1   | 20 | 38  |
| 64788           | 4050300213286     | FTM  | CP72   | 2000  | 230 | 52000  | GY16  | 4   | 20 | 38  |
| 24064788        | 4050300283258     | FTM  | CP72   | 2000  | 240 | 52000  | GY16  | 4   | 20 | 38  |
| 64789           | 4050300219103     | FKK  | CP73   | 2000  | 220 | 52000  | G38   | 5   | 1  | 38  |
| 24064789        | 4050300283371     | FKK  | CP73   | 2000  | 240 | 52000  | G38   | 5   | 1  | 38  |
| 64796           | 4050300406428     | –    | CP91   | 2500  | 230 | 65000  | G22   | 1   | 20 | 38  |
| 64805           | 4050300212609     | –    | CP85   | 5000  | 230 | 135000 | G38   | 6   | 1  | 38  |
| 24064805        | 4050300283401     | –    | CP85   | 5000  | 240 | 135000 | G38   | 6   | 1  | 38  |
| 64815           | 4050300780696     | ECR  | CP83   | 10000 | 230 | 285000 | G38   | 7   | 1  | 38  |
| 64818           | 4050300782713     | BCM  | CP99   | 20000 | 230 | 580000 | G38   | 8   | 1  | 38  |



All orders must be multiples of sales pack

## Display/Optic Lamps



### Halogen lamps – double ended


- Maximum luminous efficacy
- Suitable where colour temperature is required for 3200K sensitised material
- Ideal for professional film and TV recordings

| Product ID Code | EAN (Single Pack) | ANSI | LIF   | W    | V   | Im    |      | No. |    | PPG |
|-----------------|-------------------|------|-------|------|-----|-------|------|-----|----|-----|
| 64571           | 4050300014180     | DXX  | P213  | 800  | 230 | 21000 | R7s  | 1   | 50 | 38  |
| 24064571        | 4050300283388     | DXX  | P213  | 800  | 240 | 21000 | R7s  | 1   | 50 | 38  |
| 64572           | 4008321325181     | –    | P2/35 | 1000 | 230 | 25000 | R7s  | 2   | 50 | 38  |
| 64579           | 4050300014104     | FDG  | –     | 1000 | 120 | 33000 | R7s  | 2   | 12 | 38  |
| 64580           | 4050300068888     | –    | P112  | 1000 | 230 | 35000 | R7s  | 2   | 15 | 38  |
| 24064580        | 4050300283173     | –    | P112  | 1000 | 240 | 35000 | R7s  | 2   | 15 | 38  |
| 64583           | 4050300249094     | –    | P220  | 1000 | 230 | 27000 | R7s  | 2   | 12 | 38  |
| 24064583        | 4050300411477     | –    | P220  | 1000 | 240 | 27000 | R7s  | 2   | 12 | 38  |
| 64741           | 4050300209333     | EKM  | P27   | 1000 | 230 | 25000 | R7s  | 2   | 12 | 38  |
| 64751           | 4050300214641     | ELN  | P212  | 1250 | 230 | 33500 | R7s  | 2   | 12 | 38  |
| 24064751        | 4050300283357     | ELN  | P212  | 1250 | 240 | 33500 | R7s  | 2   | 12 | 38  |
| 64781           | 4050300229997     | FEX  | P227  | 2000 | 230 | 50000 | RX7s | 2   | 12 | 38  |
| 24064781        | 4050300283500     | FEX  | P227  | 2000 | 240 | 50000 | RX7s | 2   | 12 | 38  |




All orders must be multiples of sales pack

## Display/Optic Lamps



1



2

**HPL® high performance single ended halogen lamps with special bases**

- Extended lamp life
- Light output equal to 1000W lamp
- The QXL® halogen lamp with the special bayonet base can be changed without tools and without opening the spotlight
- Ideal for entertainment and architectural applications

| Product ID Code | EAN (Single Pack) | W   | V   | lm    |         | No. |    | PPG |
|-----------------|-------------------|-----|-----|-------|---------|-----|----|-----|
| 93728           | 4050300461816     | 575 | 230 | 14900 | 2PIN    | 1   | 12 | 38  |
| 24093728        | 4050300461830     | 575 | 240 | 14900 | 2PIN    | 1   | 12 | 38  |
| 93728LL         | 4008321090102     | 575 | 240 | 11780 | 2PIN    | 1   | 12 | 38  |
| 24093728LL      | 4008321174444     | 575 | 230 | 11780 | 2PIN    | 1   | 12 | 38  |
| 93729           | 4050300654201     | 750 | 230 | 19750 | 2PIN    | 1   | 12 | 38  |
| 24093729        | 4050300654225     | 750 | 240 | 19750 | 2PIN    | 1   | 12 | 38  |
| 93729LL         | 4008321090324     | 750 | 250 | 15600 | 2PIN    | 1   | 12 | 38  |
| 24093729LL      | 4008321174468     | 750 | 240 | 15600 | 2PIN    | 1   | 12 | 38  |
| 93721           | 4008321090195     | 750 | 77  | 22950 | Bayonet | 2   | 12 | 38  |



XS = eXtreme Seal (max. permissible foil temperature 450° C)


**STUDIOLINE**

- Compact fluorescent lamp
- 3200K or 5600K colour temperature
- Ideal for film and TV lighting

| Product ID Code   | EAN (Single Pack) | W  | lm   |     |    | PPG |
|-------------------|-------------------|----|------|-----|----|-----|
| STUDIOLINE55/3200 | 4050300575292     | 55 | 3800 | G11 | 10 | 38  |
| STUDIOLINE55/5600 | 4050300575278     | 55 | 3800 | G11 | 10 | 38  |

All orders must be multiples of sales pack


## Display/Optic Lamps



### DOT-it Backstage Blue for entertainment

- Portable LED luminaire with bright blue LEDs
- A mobile light source providing light where its needed
- Ideal for film and TV lighting

| Product ID Code | EAN (Single Pack) | Product Description   | W    | V   |   | PPG |
|-----------------|-------------------|-----------------------|------|-----|---|-----|
| DOTITBACKSTAG   | 4008321411426     | DOT-IT Backstage blue | 0.23 | 4.5 | 6 | 38  |



### aluPAR® 56 halogen lamps


- Lightweight aluminium reflector
- Ideal for stage lighting

| Product ID Code | EAN (Single Pack) | Product Description | W   | V   |       | PPG  |
|-----------------|-------------------|---------------------|-----|-----|-------|------|
| 120ALUPAR56NSP  | 4008321369550     | aluPAR 56 NSP       | 300 | 120 | GX16d | 6 38 |
| 120ALUPAR56MFL  | 4008321369574     | aluPAR 56 MFL       | 300 | 120 | GX16d | 6 38 |
| 120ALUPAR56WFL  | 4008321369598     | aluPAR 56 WFL       | 300 | 120 | GX16d | 6 38 |
| 230ALUPAR56NSP  | 4008321209788     | aluPAR 56 NSP       | 300 | 230 | GX16d | 6 38 |
| 230ALUPAR56MFL  | 4008321209863     | aluPAR 56 MFL       | 300 | 230 | GX16d | 6 38 |
| 230ALUPAR56WFL  | 4008321209801     | aluPAR 56 WFL       | 300 | 230 | GX16d | 6 38 |
| 240ALUPAR300NSP | 4008321107947     | aluPAR 56 NSP       | 300 | 240 | GX16d | 6 38 |
| 240ALUPAR300MFL | 4008321107985     | aluPAR 56 MFL       | 300 | 240 | GX16d | 6 38 |
| 240ALUPAR56WFL  | 4008321209887     | aluPAR 56 WFL       | 300 | 240 | GX16d | 6 38 |



All orders must be multiples of sales pack

## Display/Optic Lamps

**aluPAR® 64 halogen lamps**


- Lightweight aluminium reflector

| Product ID Code     | EAN (Single Pack) | Product Description | ANSI | LIF  | W    | V   |       | PPG |    |
|---------------------|-------------------|---------------------|------|------|------|-----|-------|-----|----|
| ALUPAR64500VNNSPCP8 | 4008321341259     | aluPAR 64 VNSP      | —    | CP86 | 500  | 230 | GX16d | 6   | 38 |
| ALUPAR64500NSPCP87  | 4008321341273     | aluPAR 64 NSP       | —    | CP87 | 500  | 230 | GX16d | 6   | 38 |
| ALUPAR64500MFLCP88  | 4008321341327     | aluPAR 64 MFL       | —    | CP88 | 500  | 230 | GX16d | 6   | 38 |
| 240ALUPAR64500VNSP  | 4008321341365     | aluPAR 64 VNSP      | —    | CP86 | 500  | 240 | GX16d | 6   | 38 |
| 240ALUPAR64500NSPC  | 4008321341389     | aluPAR 64 NSP       | —    | CP87 | 500  | 240 | GX16d | 6   | 38 |
| 240ALUPAR64500MFLC  | 4008321341402     | aluPAR 64 MFL       | —    | CP88 | 500  | 240 | GX16d | 6   | 38 |
| ALUPAR64VNSP        | 4008321205773     | aluPAR 64 VNSP      | EXC  | —    | 1000 | 230 | GX16d | 6   | 38 |
| ALUPAR64NSP         | 4008321205797     | aluPAR 64 NSP       | EXD  | CP60 | 1000 | 230 | GX16d | 6   | 38 |
| ALUPAR64MFL         | 4008321205858     | aluPAR 64 MFL       | EXE  | CP61 | 1000 | 230 | GX16d | 6   | 38 |
| ALUPAR641000WFL     | 4008321341921     | aluPAR 64 WFL       | EXG  | CP62 | 1000 | 230 | GX16d | 6   | 38 |
| 240ALUPAR64VNSP     | 4008321205872     | aluPAR 64 VNSP      | EXC  | —    | 1000 | 240 | GX16d | 6   | 38 |
| 240ALUPAR64NSP      | 4008321205896     | aluPAR 64 NSP       | EXD  | —    | 1000 | 240 | GX16d | 6   | 38 |
| 240ALUPAR64MFL      | 4008321205919     | aluPAR 64 MFL       | EXE  | —    | 1000 | 240 | GX16d | 6   | 38 |
| 240ALUPAR641000WFL  | 4008321341945     | aluPAR 64 WFL       | EXG  | —    | 1000 | 240 | GX16d | 6   | 38 |



All orders must be multiples of sales pack

## Display/Optic Lamps



### Halogen lamps, current controlled – single ended


- To be used in series connected systems
- Emits bright, visual light
- Ideal for airfield lighting

| Product ID Code | EAN (Single Pack) | ANSI | LIF  | W   | A    | Im   |       | Light No. | PPG   |
|-----------------|-------------------|------|------|-----|------|------|-------|-----------|-------|
| 64322           | 4008321100146     | EXL  | –    | 30  | 6.6A | 430  | GY9.5 | 1         | 12 38 |
| 64311UK         | 4008321106346     | –    | J159 | 36  | 6.6A | 600  | G6.35 | 2         | 40 38 |
| 64321           | 4008321106360     | –    | J157 | 45  | 6.6A | 900  | G6.35 | 2         | 40 38 |
| 64320           | 4008321100122     | EXM  | –    | 45  | 6.6A | 900  | GZ9.5 | 1         | 12 38 |
| 64346           | 4008321106384     | –    | J158 | 100 | 6.6A | 2300 | G6.35 | 3         | 40 38 |
| 64386           | 4008321106407     | –    | J139 | 200 | 6.6A | 4700 | G6.35 | 3         | 40 38 |
| 58750           | 4008321100160     | EZL  | –    | 200 | 6.6A | 5200 | GY9.5 | 1         | 12 38 |



All orders must be multiples of sales pack

## Display/Optic Lamps

**Halogen lamps, current controlled with PK30d base**


- To be used in series connected systems
- Emits bright, visual light
- Ideal for airfield lighting

| Product ID Code | EAN (Single Pack) | Product Description  | L     | I   | F     | W    | A      | Im |     |    | No. |  | PPG |
|-----------------|-------------------|----------------------|-------|-----|-------|------|--------|----|-----|----|-----|--|-----|
| 64323C          | 4008321391582     | 64323 C 30-15        | –     | 30  | PK30d | 300  | PKX30d | 1  | 100 | 38 |     |  |     |
| 64317C          | 4008321345493     | 64317 C 45-15        | J1/76 | 45  | PK30d | 800  | PKX30d | 1  | 100 | 38 |     |  |     |
| 64317IRC        | 4008321340139     | 64317 IRC-C 45-30    | J1/76 | 45  | PK30d | 900  | PKX30d | 2  | 100 | 38 |     |  |     |
| 64318A          | 4008321345516     | 64318 A 45-15        | J1/77 | 45  | PK30d | 800  | PKX30d | 1  | 100 | 38 |     |  |     |
| 64319Z          | 4008321345578     | 64319 Z/C 45-15      | –     | 45  | PK30d | 800  | PKX30d | 1  | 100 | 38 |     |  |     |
| 64319IRCA       | 4008321340153     | 64319 IRC-A 45-30    | –     | 45  | PK30d | 900  | PKX30d | 2  | 100 | 38 |     |  |     |
| HLX64328A       | 4008321345592     | 64328 HLX-A 65-15    | –     | 65  | PK30d | 1450 | PKX30d | 3  | 100 | 38 |     |  |     |
| HLX64328Z       | 4008321345615     | 64328 HLX-Z/C 65-15  | –     | 65  | PK30d | 1450 | PKX30d | 3  | 100 | 38 |     |  |     |
| HLX64341A       | 4008321345639     | 64341 HLX-A 100-15   | J1/79 | 100 | PK30d | 2700 | PKX30d | 3  | 100 | 38 |     |  |     |
| HLX64341Z       | 4008321345653     | 64341 HLX-Z/C 100-15 | J1/79 | 100 | PK30d | 2700 | PKX30d | 3  | 100 | 38 |     |  |     |
| HLX64342        | 4008321345677     | 64342 HLX-C 100-15   | J1/80 | 100 | PK30d | 2700 | PKX30d | 3  | 100 | 38 |     |  |     |
| HLX64361A       | 4008321345691     | 64361 HLX-A 150-15   | J1/83 | 150 | PK30d | 3600 | PKX30d | 3  | 100 | 38 |     |  |     |
| HLX64361Z       | 4008321345714     | 64361 HLX-Z/C 150-15 | J1/83 | 150 | PK30d | 3600 | PKX30d | 3  | 100 | 38 |     |  |     |
| HLX64382A       | 4008321345738     | 64382 HLX-A 200-15   | J1/84 | 200 | PK30d | 4800 | PKX30d | 3  | 100 | 38 |     |  |     |
| HLX64382        | 4008321345752     | 64382 HLX-C 200-15   | J1/84 | 200 | PK30d | 4800 | PKX30d | 3  | 100 | 38 |     |  |     |



All orders must be multiples of sales pack

## Display/Optic Lamps



### Halogen lamps, current controlled with reflector

- To be used in series connected systems
- With dichroic coating for cooler heat projection
- Ideal for airfield lighting

| Product ID Code | EAN (Single Pack) | Product Description | W   | A    |        | No. |    | PPG |
|-----------------|-------------------|---------------------|-----|------|--------|-----|----|-----|
| 64331SPA        | 4008321102560     | 64331 SP-A 30-10    | 30  | 6.6A | Cables | 1   | 20 | 38  |
| 64333A          | 4008321166340     | 64333 A-40-15       | 40  | 6.6A | Cables | 1   | 20 | 38  |
| 64333B          | 4008321104731     | 64333 B             | 40  | 6.6A | Cables | 1   | 20 | 38  |
| 64333CUK        | 4008321104885     | 64333 C             | 40  | 6.6A | Cables | 1   | 20 | 38  |
| 64337A          | 4008321102515     | 64337A45-15         | 45  | 6.6A | Cables | 1   | 20 | 38  |
| 64337B45        | 4008321104700     | 64337B45-15         | 45  | 6.6A | Cables | 1   | 20 | 38  |
| 64337A          | 4008321102737     | 64337A48-15         | 48  | 6.6A | Cables | 1   | 20 | 38  |
| 64337B48        | 4008321105226     | 64337 IRC-LL-B      | 48  | 6.6A | Cables | 1   | 20 | 38  |
| 64337C48        | 4008321105240     | 64337C IRC-LL-C     | 48  | 6.6A | Cables | 1   | 20 | 38  |
| 64337IRC-C      | 4008321102492     | 64337 IRC-C 48-30   | 48  | 6.6A | Cables | 2   | 20 | 38  |
| 64338A          | 4008321105301     | 64338 A 48-10       | 48  | 6.6A | Cables | 1   | 20 | 38  |
| 64337IRC-A      | 4008321341174     | 64337 IRC-A 48-30   | 48  | 6.6A | Cables | 2   | 20 | 38  |
| 64336A          | 4008321186713     | 64336 A 62-15       | 62  | 6.6A | Cables | 3   | 20 | 38  |
| 64339A          | 4008321101600     | 64339-A 105-10      | 105 | 6.6A | Cables | 4   | 20 | 38  |
| 64339           | 4008321105424     | 64339-AC 105-10     | 105 | 6.6A | Cables | 4   | 20 | 38  |
| 64339B          | 4008321105462     | 64339-B 105-10      | 105 | 6.6A | Cables | 4   | 20 | 38  |
| 64339C          | 4008321105486     | 64339-C 105-10      | 105 | 6.6A | Cables | 4   | 20 | 38  |




All orders must be multiples of sales pack

## Display/Optic Lamps



1



2

**Halogen lamps, current controlled – double ended**

- To be used in series connected systems
- Emits bright, visual light
- Ideal for airfield lighting

| Product ID Code | EAN (Single Pack) | LIF   | W   | A    |        |   |    | PPG |
|-----------------|-------------------|-------|-----|------|--------|---|----|-----|
| 64315           | 4050300206844     | J1/78 | 45  | 6.6A | R7s-15 | 1 | 25 | 38  |
| 64340           | 4050300017266     | J182  | 100 | 6.6A | R7s-15 | 2 | 25 | 38  |
| 64380           | 4050300209944     | J140  | 200 | 6.6A | R7s-18 | 2 | 25 | 38  |



All orders must be multiples of sales pack

## Display/Optic Lamps

**Electronic control gear for medical applications**

- Various lamp types (eg HXP® lamps) are designed exclusively for operation with series PT-VIP ECG
- These ECGs operate the lamps in special patented operating modes which benefit lamp life and efficacy


| Product ID Code | EAN (Single Pack) | Product Description                              | W   | [mm] | [mm] | [mm] |    | PPG |
|-----------------|-------------------|--|-----|------|------|------|----|-----|
| PTVIP01XB075    | 4008321502650     | PT-VIP 01 Mega & PT HVI 16kV 5.5A for XBO 75W/AC | 75  | 150  | 60   | 30   | 25 | 38  |
| PTVIP2AC01DIM   | 4008321040855     | PT-VIP 2AC/380 01 DIM 120                        | 120 | 150  | 60   | 32   | 25 | 38  |
| PTVIP4AC03DIM   | 4008321337276     | PT-VIP 4AC/380 03 DIM 206                        | 200 | 135  | 50   | 30   | 50 | 38  |



All orders must be multiples of sales pack



## Display/Optic Lamps

**XBO® Xenon short arc lamps (75-300W)**


- Double ended short arc xenon lamp
- Very high luminance, high colour rendering, dimmable long life lamps
- Ideal for cinema projection

| Product ID Code          | EAN (Single Pack) | Product Description     | W   | V    |   | No. |    | PPG |
|--------------------------|-------------------|-------------------------|-----|------|---|-----|----|-----|
| <b>Without reflector</b> |                   |                         |     |      |   |     |    |     |
| XB0752                   | 4050300508801     | XBO 75 W/2 DC           | 75  | 14   | 1 | 10  | 38 |     |
| XB07520FR                | 4050300508825     | XBO 75W/2 OFR DC        | 75  | 14   | 1 | 10  | 38 |     |
| XB01000FR                | 4008321386328     | XBO 100 W/OFR DC        | 100 | 14   | 2 | 10  | 38 |     |
| XB0150CROFR              | 4050300508788     | XBO 150 W/CR DC         | 150 | 16.5 | 3 | 10  | 38 |     |
| XB01501                  | 4050300508344     | XBO 150 W/1 DC          | 150 | 25   | 3 | 10  | 38 |     |
| XB015010FR               | 4050300508368     | XBO 150W/1 OFR DC       | 150 | 25   | 3 | 10  | 38 |     |
| XB01504                  | 4050300508382     | XBO 150W/4 DC           | 150 | 25   | 3 | 10  | 38 |     |
| <b>With reflector</b>    |                   |                         |     |      |   |     |    |     |
| XB075RAC                 | 4008321964816     | XBO R 75W/AC 34.5       | 75  | —    | 4 | 2   | 38 |     |
| XB0R10045C               | 4050300367767     | XBO R 100W/45 C DC      | 100 | —    | 5 | 2   | 38 |     |
| XB0R100450FR             | 4050300317205     | XBO R 100W/45 OFR DC    | 100 | —    | 6 | 2   | 38 |     |
| XB0R10145C               | 4050300388458     | XBO R 101W/45 C OFR DC  | 101 | —    | 7 | 2   | 38 |     |
| XB0R18045                | 4050300432175     | XBO R 180W/45 DC        | 180 | —    | 6 | 2   | 38 |     |
| XB0R18045C               | 4050300432199     | XBO R 180W/ 45 C OFR DC | 180 | —    | 5 | 2   | 38 |     |
| XB0R18145C               | 4050300450872     | XBO R 180W/45 C OFR DC  | 180 | —    | 7 | 2   | 38 |     |
| XB0R300                  | 4008321137722     | XBO R 181W/45 C DC      | 181 | —    | 4 | 2   | 38 |     |



All orders must be multiples of sales pack

## Display/Optic Lamps

**XBO® Xenon short arc lamps with reflector (450-10000W)**

- Double ended short arc xenon lamp
- Very high luminance, high colour rendering, dimmable long life lamps
- Ideal for cinema projection



| Product ID Code | EAN (Single Pack) | Product Description | W    | V  | No. |   | PPG |
|-----------------|-------------------|---------------------|------|----|-----|---|-----|
| XBO4500FR       | 4008321082633     | XBO 450 W OFR       | 450  | 17 | 1   | 1 | 38  |
| XBO450          | 4008321082640     | XBO 450W            | 450  | 17 | 2   | 1 | 38  |
| XBO4501         | 4008321082510     | XBO 450 W/1         | 450  | 17 | 2   | 1 | 38  |
| XBO4502         | 4008321082626     | XBO 450 W/2 OFR     | 450  | 17 | 1   | 1 | 38  |
| XBO4504         | 4006584412990     | XBO 450 W/4         | 450  | 17 | 3   | 1 | 38  |
| XBO500HOFR      | 4008321082503     | XBO 500 W/H OFR     | 500  | 17 | 4   | 1 | 38  |
| XBO9000FR       | 4008321081346     | XBO 900 W OFR       | 900  | 19 | 5   | 1 | 38  |
| XBO1000HSOFR    | 4008321082114     | XBO 1000 W/HS OFR   | 1000 | 19 | 6   | 1 | 38  |
| XBO1000HSCOFR   | 4008321082107     | XBO 1000 W/HSC OFR  | 1000 | 19 | 7   | 1 | 38  |
| XBO1000HTPOFR   | 4008321081353     | XBO 1000 W/HTP OFR  | 1000 | 21 | 4   | 1 | 38  |
| XBO1600CAOFR    | 4008321064738     | XBO 1600 W/CA OFR   | 1600 | 24 | 6   | 1 | 38  |
| XBO2000HSOFR    | 4008321081360     | XBO 2000 W/HS OFR   | 2000 | 24 | 10  | 1 | 38  |
| XBO2000HTTOFR   | 4008321064769     | XBO 2000 W/HTT OFR  | 2000 | 24 | 8   | 1 | 38  |
| XBO2000SHSCOFR  | 4008321082077     | XBO 2000 W/SHSC OFR | 2000 | 27 | 1   | 1 | 38  |
| XBO2000HCCOFR   | 4008321117250     | XBO 2000 W/HCC OFR  | 2000 | 28 | 9   | 1 | 38  |
| XBO25000FR      | 4008321064783     | XBO 2500 W OFR      | 2500 | 29 | 10  | 1 | 38  |
| XBO30000HTCOFR  | 4008321064820     | XBO 3000 W/HTC OFR  | 3000 | 29 | 2   | 1 | 38  |
| XBO40000HSAOFR  | 4008321337030     | XBO 4000 W/HAS OFR  | 4000 | 29 | 9   | 1 | 38  |
| XBO42000CAOFR   | 4008321337047     | XBO 4200 W/CA OFR   | 4200 | 29 | 2   | 1 | 38  |
| XBO8000HSOFR    | 4008321552310     | XBO 8000 W/HS OFR   | 8000 | 45 | 1   | 1 | 38  |



All orders must be multiples of sales pack



## Display/Optic Lamps

**XBO® Classic Line for cinema projection**


- Double ended short arc xenon lamp
- Very high luminance, high colour rendering, dimmable long life lamps
- Ideal for cinema projection

| Product ID Code   | EAN (Single Pack) | Product Description    | W    | V  | No. | PPG |    |
|-------------------|-------------------|------------------------|------|----|-----|-----|----|
| XB01600CLOFR      | 4008321318022     | XBO 1600 W CL OFR      | 1600 | 24 | 1   | 1   | 38 |
| XB01600HSCLOFR    | 4008321317940     | XBO 1600 W/HS CL OFR   | 1550 | 23 | 2   | 1   | 38 |
| XB01600HSCCLOFR   | 4008321317957     | XBO 1600 W/HSC CL OFR  | 1550 | 23 | 3   | 1   | 38 |
| XB02000HCLOFR     | 4008321209566     | XBO 2000W/H CL OFR     | 2000 | 28 | 4   | 1   | 38 |
| XB02000HSCLOFR    | 4008321288653     | XBO 2000 W/HS CL OFR   | 2000 | 24 | 6   | 1   | 38 |
| XB02000HTPCL      | 4008321288646     | XBO 2000 W/HTP CL OFR  | 2000 | 27 | 5   | 1   | 38 |
| XB02000SHSCCLOFR  | 4008321317933     | XBO 2000 W/ShSC CL OFR | 2000 | 27 | 3   | 1   | 38 |
| XB02500HSCLOFR    | 4008321288660     | XBO 2500 W/HS CL OFR   | 2500 | 28 | 6   | 1   | 38 |
| XB03000HCLOFR     | 4008321209573     | XBO 3000 W/H CL OFR    | 3000 | 29 | 6   | 1   | 38 |
| XB03000HSCLOFR    | 4008321210265     | XBO 3000 W/HS CL OFR   | 3000 | 29 | 7   | 1   | 38 |
| XB03000HTPCL      | 4008321288677     | XBO 3000 W/HTP CL OFR  | 3000 | 29 | 6   | 1   | 38 |
| XB04000HSCLOFR    | 4008321210272     | XBO 4000 W/HS CL OFR   | 4000 | 28 | 6   | 1   | 38 |
| XB04000HTPCL      | 4008321288684     | XBO 4000 W/HTP CL OFR  | 4000 | 30 | 5   | 1   | 38 |
| XB05000HCLOFR     | 4008321317988     | XBO 5000 W/H CL OFR    | 5000 | 35 | 6   | 1   | 38 |
| XB05000HBMCLCLOFR | 4008321317995     | XBO 5000 W/HBM CL OFR  | 5000 | 34 | 6   | 1   | 38 |
| XB06000HSCLOFR    | 4008321318008     | XBO 6000 W/HS CL OFR   | 6000 | 37 | 6   | 1   | 38 |
| XB07000HSCLOFR    | 4008321318015     | XBO 7000 W/HS CL OFR   | 7000 | 42 | 6   | 1   | 38 |



All orders must be multiples of sales pack

## Display/Optic Lamps

**XBO® Xtreme Life for cinema projection**


- Double ended short arc xenon lamp
- Very high luminance, high colour rendering, dimmable long life lamps
- Ideal for cinema projection

| Product ID Code | EAN (Single Pack) | Product Description   | W    | V  | No. | PPG |    |
|-----------------|-------------------|-----------------------|------|----|-----|-----|----|
| XBO1600XL0FR    | 4008321299918     | XBO 1600W XL OFR      | 1600 | 24 | 1   | 1   | 38 |
| XBO1600HSXL0FR  | 4008321299925     | XBO 1600W/HS XL OFR   | 1550 | 23 | 2   | 1   | 38 |
| XBO1600HSCXL0FR | 4008321299932     | XBO 1600W/HSC XL OFR  | 1550 | 23 | 3   | 1   | 38 |
| XBO2000HXL0FR   | 4008321211781     | XBO 2000W/HXL OFR     | 2000 | 27 | 4   | 1   | 38 |
| XBO2000HTPXL    | 4008321244031     | XBO 2000W/HTP XL OFR  | 2000 | 28 | 5   | 1   | 38 |
| XBO2500XL0FR    | 4008321372789     | XBO 2500W XL OFR      | 2500 | 29 | 6   | 1   | 38 |
| XBO2500HSXL0FR  | 4008321299963     | XBO 2500W/HS XL OFR   | 2500 | 28 | 7   | 1   | 38 |
| XBO3000HXL0FR   | 4008321226174     | XBO 3000W/H XL OFR    | 3000 | 29 | 8   | 1   | 38 |
| XBO3000HSXL0FR  | 4008321330031     | XBO 3000W/HS XL OFR   | 3000 | 29 | 5   | 1   | 38 |
| XBO3000HTPXL    | 4008321244017     | XBO 3000 W/HTP XL OFR | 3000 | 29 | 5   | 1   | 38 |
| XBO4000HS0FR    | 4008321412812     | XBO 4000W/HS XL OFR   | 4000 | 30 | 9   | 1   | 38 |
| XBO4000HTPXL    | 4008321244024     | XBO 4000 W/HTP XL OFR | 4000 | 30 | 5   | 1   | 38 |
| XBO6000HSXL0FR  | 4008321299987     | XBO 6000 W/HS XL OFR  | 6000 | 37 | 5   | 1   | 38 |
| XBO6000HTPXL0FR | 4008321334923     | XBO 6000 W/HTP XL OFR | 6000 | 37 | 5   | 1   | 38 |
| XBO7000HSXL0FR  | 4008321299970     | XBO 7000 W/HS XL OFR  | 7000 | 42 | 5   | 1   | 38 |
| XBO4500HS0FR    | 4008321412881     | XBO 4500W/HS XL OFR   | 4500 | 32 | 5   | 1   | 38 |
| XBO5000H0FR     | 4008321412829     | XBO 5000W/H XL OFR    | 5000 | 35 | 8   | 1   | 38 |
| XBO5000HBM0FR   | 4008321412836     | XBO 5000W/HBM XL OFR  | 5000 | 34 | -   | 1   | 38 |
| XBO4500HTP0FR   | 4008321412898     | XBO 4500W/HTP XL OFR  | 4500 | 32 | -   | 1   | 38 |



All orders must be multiples of sales pack

## Display/Optic Lamps

**XBO® lamps for digital cinema projection**


- Double ended short arc xenon lamp
- Very high luminance, high colour rendering, dimmable long life lamps
- Ideal for cinema projection

| Product ID Code | EAN (Single Pack) | Product Description  | W    | V  |   | No. |    | PPG |
|-----------------|-------------------|----------------------|------|----|---|-----|----|-----|
| <b>DHP</b>      |                   |                      |      |    |   |     |    |     |
| XB01200DHP0FR   | 4008321396433     | XBO 1200W/DHP OFR    | 1200 | 20 | 1 | 1   | 38 |     |
| XB02000DHP0FR   | 4008321244048     | XBO 2000W/DHP OFR    | 2000 | 25 | 1 | 1   | 38 |     |
| XB03000DHP0FR   | 4008321330048     | XBO 3000W/DHP OFR    | 3000 | 30 | 1 | 1   | 38 |     |
| XB03000DHPCLOFR | 4008321309532     | XBO 3000W/DHP XL OFR | 3000 | 30 | 1 | 1   | 38 |     |
| XB03000DHSOFR   | 4008321330017     | XBO 3000W/DHS OFR    | 3000 | 29 | 1 | 1   | 38 |     |
| XB04000DHPCLOFR | 4008321309686     | XBO 4000W/DHP XL OFR | 4000 | 34 | 1 | 1   | 38 |     |
| XB04500DHP0FR   | 4008321372727     | XBO 4500W/DHP OFR    | 4500 | 30 | 1 | 1   | 38 |     |
| XB06000DHP0FR   | 4008321549693     | XBO 6000W/DHP OFR    | 6000 | 35 | 1 | 1   | 38 |     |
| XB06500DHP0FR   | 4008321549723     | XBO 6500W/DHP OFR    | 6500 | 37 | 1 | 1   | 38 |     |
| XB04000DHP0FR   | 4008321546272     | XBO 4000W/DHP OFR    | 4000 | 33 | 1 | 1   | 38 |     |
| XB03000DHSOFR   | 4008321199065     | XBO 3000W/DHS OFR    | 3000 | 29 | 1 | 1   | 38 |     |
| <b>DTP</b>      |                   |                      |      |    |   |     |    |     |
| XB02000DTP0FR   | 4008321191533     | XBO 2000W/DTP OFR    | 2000 | 25 | 2 | 1   | 38 |     |
| XB03000DTP0FR   | 4008321191540     | XBO 3000W/DTP OFR    | 3000 | 27 | 2 | 1   | 38 |     |
| XB04500DTP0FR   | 4008321372734     | XBO 4500W/DTP OFR    | 4500 | 32 | 2 | 1   | 38 |     |
| <b>HPS</b>      |                   |                      |      |    |   |     |    |     |
| XB02000HPS0FR   | 4008321330000     | XBO 2000W/HPS OFR    | 2000 | 25 | 3 | 1   | 38 |     |
| XB03000HPS0FR   | 4008321330062     | XBO 3000W/HPS OFR    | 3000 | 29 | 3 | 1   | 38 |     |
| XB04200HPS0FR   | 4008321330086     | XBO 4200W/HPS OFR    | 4200 | 35 | 3 | 1   | 38 |     |
| <b>HSLA</b>     |                   |                      |      |    |   |     |    |     |
| XB03000HSLA0FR  | 4008321330079     | XBO 3000W/HSLA OFR1) | 3000 | 29 | 4 | 1   | 38 |     |
| XB04500HSLA0FR  | 4008321372710     | XBO 4500W/HSLA OFR1) | 4500 | 30 | 4 | 1   | 38 |     |
| XB06000HSLA0FR  | 4008321549716     | XBO 6000W/HSLA OFR   | 6000 | 35 | 4 | 1   | 38 |     |
| XB06500HSLA0FR  | 4008321549730     | XBO 6500W/HSLA OFR   | 6500 | 38 | 4 | 1   | 38 |     |
| XB08000HSLA0FR  | 4008321549747     | XBO 8000W/HSLA OFR   | 8000 | 43 | 4 | 1   | 38 |     |



All orders must be multiples of sales pack

## Display/Optic Lamps




1

2

**XSTAGE® Xenon short arc lamps for entertainment**

- Short arc xenon lamp
- Optimised for outdoor use
- Ideal for event and architectural lighting and large scale floodlighting

| Product ID Code | EAN (Single Pack) | Product Description | W    | V  |   | No. |    | PPG |
|-----------------|-------------------|---------------------|------|----|---|-----|----|-----|
| XSTAGE2000      | 4008321288820     | Xstage 2000W OFR    | 2000 | 23 | 1 | 1   | 38 |     |
| XSTAGE3000      | 4008321199690     | Xstage 3000W OFR    | 3000 | 30 | 1 | 1   | 38 |     |
| XSTAGE4000      | 4008321199706     | Xstage 4000W OFR    | 4000 | 30 | 1 | 1   | 38 |     |
| XSTAGE7000      | 4008321199713     | Xstage 7000W OFR    | 7000 | 40 | 2 | 1   | 38 |     |



1

3

5

2

4

6

**HBO® Mercury short arc lamps 50-200W**

- Short arc Mercury lamp
- Ideal for UV generation in scientific and technical applications

| Product ID Code          | EAN (Single Pack) | Product Description  | W   |   | No. |    | PPG |
|--------------------------|-------------------|----------------------|-----|---|-----|----|-----|
| <b>Without reflector</b> |                   |                      |     |   |     |    |     |
| HBO50ACL2                | 4050300507118     | HBO 50 W/AC L2       | 50  | 1 | 1   | 38 |     |
| HBO50ACL1                | 4050300507132     | HBO 50 W/AC L1       | 50  | 1 | 1   | 38 |     |
| HBO503                   | 4050300506692     | HBO 50 W/3 DC        | 50  | 2 | 1   | 38 |     |
| HBO1002                  | 4050300507095     | HBO 100 W/2 DC       | 100 | 3 | 1   | 38 |     |
| HBO1032                  | 4050300382128     | HBO 103 W/2 DC       | 103 | 3 | 1   | 38 |     |
| HBO2004                  | 4050300506715     | HBO 200 W/4 AC       | 200 | 4 | 1   | 38 |     |
| HBO2024                  | 4050300507156     | HBO 202 W/4 AC       | 202 | 4 | 1   | 38 |     |
| HBO2002L2                | 4050300508283     | HBO 200 W/2 L2 AC/DC | 200 | 5 | 1   | 38 |     |
| HBO2002L1                | 4050300508153     | HBO 200 W/2 L1 AC/DC | 200 | 5 | 1   | 38 |     |
| HBO200DC                 | 4050300506791     | HBO 200 W/DC         | 200 | 5 | 1   | 38 |     |
| HBO200DCTM               | 4008321137623     | HBO 200 W/DC TM      | 200 | 5 | 1   | 38 |     |
| <b>With reflector</b>    |                   |                      |     |   |     |    |     |
| HBOR10345                | 4050300405957     | HBO R 103 W/45 DC    | 103 | 6 | 1   | 38 |     |




All orders must be multiples of sales pack



## Display/Optic Lamps



1



2

**Special lamps for IR applications**

- Short wave halogen infrared lamp developed specifically for fast heating processes

| Product ID Code | EAN (Single Pack) | Product Description | ANSI | W    | V    |      | No. |    | PPG |
|-----------------|-------------------|---------------------|------|------|------|------|-----|----|-----|
| 54555           | 4008321216304     | 54555               | –    | 1000 | 120  | G9.5 | 1   | 12 | 38  |
| 64743HT         | 4050300506531     | 64743 HT            | FEL  | 1000 | 120  | G9.5 | 2   | 12 | 38  |
| VIPR120P24I     | 4050300563084     | HXP R120W/ 17C      | –    | 120  | 82.5 | –    | –   | 1  | 38  |
| HXPR20045MP2    | 4008321180087     | HXP R200W/ 45M      | –    | 200  | 78   | –    | –   | 1  | 38  |



1



2



3

**XERADEX® lamps**


- Xenon excimer lamps

| Product ID Code     | EAN (Single Pack) | Product Description            |     | No. |   | PPG |
|---------------------|-------------------|--------------------------------|-----|-----|---|-----|
| <b>Single ended</b> |                   |                                |     |     |   |     |
| XERADEX120SB4685    | 4008321190994     | XERADEX L40/120/SB-S46/85      | 20  | 1   | 1 | 38  |
| XERADEX120SBKF50    | 4008321191014     | XERADEX L40/120/SB-SX48/KF50   | 20  | 2   | 1 | 38  |
| XERADEX120SBKF50HV  | 400832121125      | XERADEX L40/120/SB-SX48/KF50HV | 20  | 2   | 1 | 38  |
| XERADEX175SB4595    | 4008321191052     | XERADEX L40/175/SB-S45/95      | 20  | 1   | 1 | 38  |
| XERADEX175SB4685    | 4008321191038     | XERADEX L40/175/SB-S46/85      | 20  | 1   | 1 | 38  |
| XERADEX175SBKF50HV  | 4008321243713     | XERADEX L40/175/SB-SX48/KF50HV | 20  | 2   | 1 | 38  |
| <b>Double ended</b> |                   |                                |     |     |   |     |
| XERADEX375DB        | 4008321939289     | XERADEX L40/375/DB-AZ48/90     | 60  | 3   | 1 | 38  |
| XERADEX620DB        | 4008321939296     | XERADEX L40/620/DB-AZ48/90     | 100 | 3   | 1 | 38  |



All orders must be multiples of sales pack

## Display/Optic Lamps

**XIS XERADEX® irradiation system**

- Complete systems that can be used as stand alone units or integrated as part of an installation
- The system comprises XERADEX® 20W lamps, DBD 20 electronic control gear, special VUC compatible reflectors and a quartz front panel

| Product ID Code | EAN (Single Pack) | Product Description  |     |     |    |   |   | PPG |
|-----------------|-------------------|----------------------|-----|-----|----|---|---|-----|
| XTU70           | 4008321216328     | XTU 70 30W 110-240V  | 180 | 94  | 56 | 1 | 1 | 38  |
| XIS170S         | 4008321158253     | XIS 170 60W 110-240V | 320 | 230 | 75 | 2 | 1 | 38  |

**DBD electronic control gear for XERADEX® lamps**

- DBD electronic control gear designed exclusively for operating XERADEX® lamps


| Product ID Code | EAN (Single Pack) | Product Description |         |     |     |     |   | PPG |
|-----------------|-------------------|---------------------|---------|-----|-----|-----|---|-----|
| DBD20           | 4050300939469     | DBD 20/110-240      | 110-240 | 240 | 17  | 95  | 1 | 38  |
| DBD300DIM       | 4008321939357     | DBD 300/100-240 DIM | 110-240 | 250 | 166 | 125 | 1 | 38  |



All orders must be multiples of sales pack



## Display/Optic Lamps



## Microlithography lamps for i-line systems


| Product ID Code                 | EAN (Single Pack) | Product Description | W    | V    | No. | PPG |    |
|---------------------------------|-------------------|---------------------|------|------|-----|-----|----|
| <b>For ASML i-line systems</b>  |                   |                     |      |      |     |     |    |
| HBO1003PIL                      | 4050300461380     | HBO 1003W/PIL DC    | 700  | 27.1 | 1   | 8   | 38 |
| HBO1500PIL                      | 4050300461465     | HBO 1500W/PIL DC    | 1500 | 23   | 2   | 6   | 38 |
| HBO2100PIL                      | 4050300800431     | HBO 2100W/PIL DC    | 2100 | 24   | 2   | 6   | 38 |
| HBO2500PIL                      | 4050300947396     | HBO 2500W/PIL DC    | 2500 | 28   | 3   | 1   | 38 |
| HBO3500PIL                      | 4008321355843     | HBO 3500W/PIL DC    | 3400 | 23   | 4   | 4   | 38 |
| <b>For Canon i-line systems</b> |                   |                     |      |      |     |     |    |
| HBO1000CEL                      | 4050300412627     | HBO 1000W/CEL       | 750  | 47   | 5   | 1   | 38 |
| HBO1002CEL                      | 4050300412634     | HBO 1002W/CEL       | 750  | 47   | 6   | 1   | 38 |
| HBO1500CIEL                     | 4050300624037     | HBO 1500W/CIEL      | 1500 | 23   | 7   | 6   | 38 |
| HBO1500CIEL                     | 4050300538204     | HBO 1500W/CIEL      | 1500 | 23   | 7   | 1   | 38 |
| HBO2001CIEL                     | 4050300972121     | HBO 2001W/CIEL      | 2000 | 26   | 8   | 4   | 38 |
| HBO2001CIELX                    | 4008321122735     | HBO 2001W/CIELX     | 2000 | 24   | 8   | 4   | 38 |
| HBO2001CIL                      | 4050300947235     | HBO 2001W/CIL       | 2000 | 26   | 8   | 4   | 38 |
| HBO2700CIL                      | 4050300896588     | HBO 2700W/CIL       | 2700 | 26   | 9   | 1   | 38 |
| <b>For Nikon i-line systems</b> |                   |                     |      |      |     |     |    |
| HBO1002NIL                      | 4050300461403     | HBO 1002W/NIL       | 750  | 25.8 | 10  | 8   | 38 |
| HBO2000NIL                      | 4050300490212     | HBO 2000W/NIL       | 1750 | 26   | 11  | 1   | 38 |
| HBO2001NIEL                     | 4050300538211     | HBO 2001W/NIEL      | 1750 | 26   | 12  | 1   | 38 |
| HBO2001NIL                      | 4050300461489     | HBO 2001W/NIL       | 1750 | 26   | 12  | 6   | 38 |
| HBO2002NIL                      | 4050300772714     | HBO 2002W/NIL       | 1750 | 26   | 13  | 1   | 38 |
| HBO2011NIL                      | 4050300652641     | HBO 2011W/NIL       | 2000 | 25   | 13  | 6   | 38 |
| HBO2011NILH                     | 4050300991665     | HBO 2011W/NILH      | 2000 | 25   | 13  | 6   | 38 |
| HBO2501NIL                      | 4050300628288     | HBO 2501W/NIL       | 2500 | 23   | 14  | 4   | 38 |
| HBO2510NIL                      | 4050300628400     | HBO 2510W/NIL       | 2500 | 23   | 15  | 4   | 38 |

All orders must be multiples of sales pack






## Display/Optic Lamps




1




2

**Microlithography lamps for LCD systems**


| Product ID Code              | EAN (Single Pack) | Product Description | W    | V  | Q No. | PPG |
|------------------------------|-------------------|---------------------|------|----|-------|-----|
| <b>For Canon LCD systems</b> |                   |                     |      |    |       |     |
| HBO8000C                     | 4008321352323     | HBO 8000W/C         | 8000 | 81 | 1     | 4   |
| HBO8000CHL                   | 4008321280282     | HBO 8000W/CHL       | 8000 | 81 | 1     | 38  |
| <b>For Nikon LCD systems</b> |                   |                     |      |    |       |     |
| HBO4300NHLVS11               | 4008321281159     | HBO 4300W/NHL       | 4300 | 54 | 2     | 4   |
| HBO4300NHL                   | 4008321281142     | HBO 4300W/NHL       | 4300 | 54 | 2     | 1   |




1



3



2



4

**Other Microlithography lamps up to 1000W**



| Product ID Code | EAN (Single Pack) | Product Description | W    | V    | Q No. | PPG |
|-----------------|-------------------|---------------------|------|------|-------|-----|
| HBO250BY        | 4050300803432     | HBO 250W/BY DC      | 250  | 40   | 1     | 1   |
| HBO250LS        | 4008321336668     | HBO 250W/LS DC      | 250  | 39   | 2     | 1   |
| HBO350          | 4050300351599     | HBO 350W DC         | 350  | 67.5 | 3     | 1   |
| HBO350S         | 4050300258041     | HBO 350W/S DC       | 350  | 68   | 3     | 1   |
| HBO1000D        | 4050300288857     | HBO 1000W/D         | 1000 | 37.7 | 4     | 38  |



All orders must be multiples of sales pack



## Display/Optic Lamps

**HXP® long life mercury short-arc lamps**

- Pico 9 base
- Gas filled incandescent lamp
- Ideal for scientific applications

| Product ID Code | EAN (Single Pack) | Product Description   | W   | V | No. | PPG |
|-----------------|-------------------|-----------------------|-----|---|-----|-----|
| HXPR12017CP50   | 4050300786476     | HXP R 120W/17C AC     | 120 | 1 | 1   | 38  |
| HXPR12045CVIS   | 4050300882772     | HXP R 120W/45C VIS AC | 120 | 2 | 1   | 38  |
| HXPR12045CUV    | 4050300666525     | HXP R 120W/45C UV AC  | 120 | 2 | 1   | 38  |
| HXPR20045M      | 4008321180070     | HXP R 200W/45M AC     | 200 | 2 | 1   | 38  |

**Lamps without Halogen, low voltage**

- For optical and photo-electronic purposes

| Product ID Code | EAN (Single Pack) | W  | V  | No.     | PPG      |
|-----------------|-------------------|----|----|---------|----------|
| 8013            | 4050300206356     | 10 | 6  | BA15d   | 1 100 38 |
| 8014            | 4050300206370     | 10 | 6  | BA15s   | 1 100 38 |
| 8017            | 4050300017327     | 15 | 6  | B15d    | 2 100 38 |
| 8018            | 4050300206417     | 15 | 6  | B15d    | 2 100 38 |
| 8022            | 4050300206677     | 50 | 12 | BA20d   | 3 100 38 |
| 8024            | 4050300013817     | 40 | 12 | BA20d   | 4 100 38 |
| 8100            | 4050300342122     | 5A | 6  | E14/SES | 5 100 38 |



All orders must be multiples of sales pack

## Display/Optic Lamps



1



2



3




4


**SPECTRAL lamps**

- Pico 9 base
- Gas filled incandescent lamp
- Ideal for scientific applications


| Product ID Code | EAN (Single Pack) | AC / DC | Lamp Type        | W  | Light Bulb No. | Boxed | PPG |
|-----------------|-------------------|---------|------------------|----|----------------|-------|-----|
| CD10            | 4050300210353     | AC      | Cadmium          | 15 | 1              | 1     | 38  |
| CS10            | 4050300213842     | AC      | Caesium          | 10 | 1              | 1     | 38  |
| HE10            | 4050300212258     | AC      | Helium           | 55 | 1              | 1     | 38  |
| K10             | 4050300212197     | AC      | Potassium        | 10 | 1              | 1     | 38  |
| NA10            | 4008321417800     | AC      | Sodium           | 15 | 1              | 1     | 38  |
| NE10            | 4050300212210     | AC      | Neon             | 30 | 1              | 1     | 38  |
| HG100           | 4050300231310     | AC/DC   | Mercury          | 22 | 2              | 1     | 38  |
| HGCD10          | 4050300211459     | AC      | Mercury/ Cadmium | 25 | 1              | 1     | 38  |
| RB10            | 4050300213866     | AC      | Rubidium         | 10 | 1              | 1     | 38  |
| TL10            | 4050300211435     | AC      | Thallium         | 15 | 1              | 1     | 38  |
| ZN10            | 4050300212234     | AC      | Zinc             | 15 | 1              | 1     | 38  |




1a



1b



2



3


**Lamps for scientific purposes**

- Used mainly for scientific purposes as comparison standards and calibration lamps
- Ideal for photometry, colorimetry and physics

| Product ID Code | EAN (Single Pack) | Product Description  | V  | Boxed     | Light Bulb No. | Boxed | PPG |
|-----------------|-------------------|----------------------|----|-----------|----------------|-------|-----|
| WI17G           | 4050300209104     | WI 17/G 9V 16A       | 9  | E27/51X39 | 1              | 1     | 38  |
| WI40G           | 4050300206783     | WI 40/G 31V 6A 2856K | 31 | E27/51X39 | 2              | 1     | 38  |
| WI41G           | 4050300206806     | WI 41/G 31V 6A 2856K | 31 | E27/51X39 | 3              | 1     | 38  |


All orders must be multiples of sales pack

## Display/Optic and Special Lamps

**HALOTHERM® Infra-red halogen lamps**


- Ideal for plastics, paper and printing industries, for drying paint and restaurant food areas

| Product ID Code        | EAN (Single Pack) | Product Description              | W    | V   | COLOR           |          | No. |    | PPG |
|------------------------|-------------------|----------------------------------|------|-----|-----------------|----------|-----|----|-----|
| <b>Quartz Clear</b>    |                   |                                  |      |     |                 |          |     |    |     |
| ITT200                 | 4008321203472     | HALO ITT 200/235-0170            | 200  | 235 | Quartz Clear    | R7s      | 1   | 12 | 38  |
| ITT350                 | 4008321204219     | HALO ITT 350/235-0170            | 350  | 235 | Quartz Clear    | R7s      | 1   | 12 | 38  |
| ITT500CL               | 4008321203519     | HALO ITT 500/235-0170            | 500  | 235 | Quartz Clear    | R7s      | 1   | 12 | 38  |
| ITT500                 | 4008321206701     | HALO ITT 500/235-0170 K          | 500  | 235 | Quartz Clear    | R7s      | 1   | 12 | 38  |
| ITT700                 | 4008321203533     | HALO ITT 700/235-0170            | 700  | 235 | Quartz Clear    | R7s      | 1   | 12 | 38  |
| ITT1000                | 4008321203557     | HALO ITT 1000/235-0170           | 1000 | 235 | Quartz Clear    | R7s      | 1   | 12 | 38  |
| ITT100001ROL1          | 4008321555076     | HALO ITT 1000/235-01X0           | 1000 | 235 | Quartz Clear    | X        | 2   | 12 | 38  |
| ITT2000ROL1            | 4008321555137     | HALO ITT 2000/235-01Y0 K         | 2000 | 235 | Quartz Clear    | Y        | 3   | 12 | 38  |
| ITT2000                | 4008321555151     | HALO ITT 2000/235-0103 K         | 2000 | 235 | Quartz Clear    | —        | 4   | 12 | 38  |
| ITT2200                | 4008321555175     | HALO ITT 2300/235-0102           | 2200 | 235 | Quartz Clear    | —        | 4   | 12 | 38  |
| ITT3000UNV1            | 4008321387127     | HALO ITT 3000/235-0102 K         | 3000 | 235 | Quartz Clear    | —        | 4   | 60 | 38  |
| 400ITT3000             | 4008321507174     | HALO ITT 3000/400-0102 K         | 3000 | 400 | Quartz Clear    | —        | 4   | 60 | 38  |
| ITT3000ROL1            | 4008321555199     | HALO ITT 3000/235-01Y0 K         | 3000 | 235 | Quartz Clear    | Y        | 3   | 12 | 38  |
| ITT3000                | 4008321206725     | HALO ITT 3000/235-01Y0 Z/K       | 3000 | 235 | Quartz Clear    | Y/Z      | 5   | 30 | 38  |
| <b>White reflector</b> |                   |                                  |      |     |                 |          |     |    |     |
| ITT5000870             | 4008321206299     | HALO ITT 500/235-0870            | 500  | 235 | White reflector | R7s      | 1   | 12 | 38  |
| ITT50008               | 4008321555090     | HALO ITT 500/235-08X0            | 500  | 235 | White reflector | X        | 2   | 12 | 38  |
| ITT100008ROL1          | 4008321555113     | HALO ITT 1000/235-08X0           | 1000 | 235 | White reflector | X        | 2   | 12 | 38  |
| ITT1000S               | 4008321206275     | HALO ITT 1000/235-0826 /S        | 1000 | 235 | White reflector | K9x15/21 | 6   | 12 | 38  |
| ITT1000CL              | 4008321259738     | HALO ITT 1000/235-0826 /S 600CL  | 1000 | 235 | White reflector | K9x15/21 | 6   | 60 | 38  |
| ITT2000                | 4008321206350     | HALO ITT 2000/235-0826 K/S       | 2000 | 235 | White reflector | K9x15/21 | 6   | 12 | 38  |
| ITT2000CL              | 4008321259790     | HALO ITT 2000/235-0826 K/S 600CL | 2000 | 235 | White reflector | K9x15/21 | 6   | 60 | 38  |
| ITP2500                | 4008321252944     | HALO ITP 2500/235-0826 K/S       | 2500 | 235 | White reflector | K9x15/21 | 6   | 12 | 38  |
| ITT2500                | 4008321206336     | HALO ITT 2500/400-0826 K         | 2500 | 400 | White reflector | K9x15/21 | 6   | 12 | 38  |
| ITT3000CL              | 4008321206312     | HALO ITT 3000/400-0826 K         | 3000 | 400 | White reflector | K9x15/21 | 6   | 12 | 38  |



All orders must be multiples of sales pack



## Display/Optic and Special Lamps



### RUBYSTAR® Halogen Infra-red lamps

- Rubied quartz Infra-red halogen lamp
- Ideal for applications in which visible light would be a distraction

| Product ID Code | EAN (Single Pack) | Product Description       | W    | V   | COLOR         |          |   |    | PPG |
|-----------------|-------------------|---------------------------|------|-----|---------------|----------|---|----|-----|
| RUBYST120026    | 4008321204233     | RUBYSTAR 1200/235-0026 PH | 1200 | 235 | Rubied quartz | K9x15/21 | 1 | 12 | 38  |
| RUBYST130070    | 4008321203618     | RUBYSTAR 1300/235-0070    | 1300 | 235 | Rubied quartz | R7s      | 2 | 12 | 38  |
| RUBYST150028    | 4008321196804     | RUBYSTAR 1500/235-0028    | 1500 | 235 | Rubied quartz | K9x15/21 | 1 | 12 | 38  |
| RUBYST200023    | 4008321196620     | RUBYSTAR 1500/235-0023    | 2000 | 235 | Rubied quartz | K9x15/21 | 1 | 12 | 38  |



1

2



### SICCATHERM® Infra-red lamps

- Infra-red heat lamp
- Ideal for in food processing for pasteurising and drying and keeping food warm

| Product ID Code | EAN (Single Pack) | Product Description       | W   | V   | COLOR      |     |   |    | PPG |
|-----------------|-------------------|---------------------------|-----|-----|------------|-----|---|----|-----|
| 240SICCA100LR   | 4008321392145     | SICCATHERM PAR38 Red 100W | 100 | 240 | Red filter | E27 | 2 | 12 | 38  |
| 240SICCA150LR   | 4008321502094     | SICCATHERM R125 Red 150W  | 150 | 240 | Red filter | E27 | 1 | 12 | 38  |
| 240SICCA175LR   | 4008321392190     | SICCATHERM PAR38 Red 175W | 175 | 240 | Red filter | E27 | 2 | 12 | 38  |
| 240SICCA250CL   | 4008321507051     | SICCATHERM R125 CL 250W   | 250 | 240 | Clear      | E27 | 1 | 12 | 38  |
| 240SICCA250FR   | 4008321507037     | SICCATHERM R125 FR 250W   | 250 | 240 | Frosted    | E27 | 1 | 12 | 38  |
| 240SICCA250LR   | 4008321507013     | SICCATHERM R125 Red 250W  | 250 | 240 | Red filter | E27 | 1 | 12 | 38  |
| 240SICCA275CL   | 4008321507075     | SICCATHERM R125 CL 275W   | 275 | 240 | Clear      | E27 | 1 | 12 | 38  |
| SICCA375        | 4050300206912     | SICCATHERM R125 CL 375W   | 375 | 230 | Clear      | E27 | 1 | 12 | 38  |

All orders must be multiples of sales pack

## Display/Optic and Special Lamps


**THERATHERM® Infra-red heat lamps**

- Infra-red heat lamp
- Ideal for use in the cosmetic industry and as heat sources in saunas, swimming pools

| Product ID Code | EAN (Single Pack) | Product Description      | W   | V   | COLOR      |  |  | No. |  | PPG |
|-----------------|-------------------|--------------------------|-----|-----|------------|--|--|-----|--|-----|
| THERA150DL      | 4008321392213     | THERA PAR 38 Red DL 150W | 150 | 240 | Red filter |  |  | 2   |  | 38  |
| THERA250        | 4008321507099     | THERA R125 Red 250W      | 250 | 240 | Red filter |  |  | 1   |  | 38  |

All orders must be multiples of sales pack

## Display/Optic and Special Lamps

**Fluorescent tubes with black glass bulbs**

- Fluorescent tube that emits long wave UV radiation
- Ideal for all applications involving fluorescence analysis such as criminal investigation, Food and textiles industry and effect lighting

| Product ID Code | EAN (Single Pack) | Product Description | W  | G   | I [mm] | No. | PPG |
|-----------------|-------------------|---------------------|----|-----|--------|-----|-----|
| L1873           | 4008321054685     | L 18/73             | 18 | G13 | 590    | 25  | 38  |
| L3673           | 4008321054715     | L 36/73             | 36 | G13 | 1200   | 20  | 38  |




1

2

**OSRAM DULUX® BLUE AND BLUE UVA**

- DULUX® Blue: Compact fluorescent lamp approved for use in medical applications
- DULUX® Blue UVA: Compact fluorescent lamp used mainly for curing plastics, dentistry, circuit board manufacture and scientific investigation


| Product ID Code | EAN (Single Pack) | Product Description | W  | G    | I [mm] | No. | PPG |    |
|-----------------|-------------------|---------------------|----|------|--------|-----|-----|----|
| DS971           | 4008321198860     | DULUX S BLUE        | 9  | G23  | 167mm  | 2   | 50  | 38 |
| DL1871          | 4008321198884     | DULUX L BLUE        | 18 | 2G11 | 217mm  | 1   | 10  | 38 |
| DS778           | 4008321198907     | DULUX S BLUE UVA    | 7  | G23  | 137mm  | 2   | 50  | 38 |
| DS978           | 4008321198938     | DULUX S BLUE UVA    | 9  | G23  | 167mm  | 2   | 50  | 38 |
| DL1878          | 4008321198990     | DULUX L BLUE UVA    | 18 | 2G11 | 217mm  | 1   | 10  | 38 |



All orders must be multiples of sales pack




## Display/Optic and Special Lamps

**HNS® germicidal lamps producing no ozone**

- Germicidal lamps producing no ozone
- Ideal for disinfecting water, air and surfaces, water purification in applications such as swimming pools, water treatment systems, drinking water

| Product ID Code | EAN (Single Pack) | Product Description | W  | G5   | I [mm] | 1 | No. | PPG |
|-----------------|-------------------|---------------------|----|------|--------|---|-----|-----|
| HNS4            | 4008321378316     | HNS 4W G5           | 4  | G5   | 136    | 1 | 25  | 38  |
| HNS60FR         | 4008321378330     | HNS 6W G5           | 6  | G5   | 212    | 1 | 25  | 38  |
| HNS80FR         | 4008321378385     | HNS 8W G5           | 8  | G5   | 288    | 1 | 25  | 38  |
| HNS11G5         | 4008321468796     | HNS 11W G5          | 11 | G5   | 212    | 1 | 25  | 38  |
| HNS15G13        | 4008321398826     | HNS 15W G13         | 15 | G13  | 438    | 1 | 20  | 38  |
| HNS25G13        | 4008321398857     | HNS 25W G13         | 25 | G13  | 438    | 1 | 20  | 38  |
| HNS300FR        | 4008321398888     | HNS 30W G13         | 30 | G13  | 895    | 1 | 10  | 38  |
| HNS55G13        | 4008321398918     | HNS 55W G13         | 55 | G13  | 895    | 1 | 10  | 38  |
| HNSL18          | 4008321220431     | HNS L 18W 2G11      | 18 | 2G11 | 214    | 2 | 10  | 38  |
| HNSL24          | 4008321220561     | HNS L 24W 2G11      | 24 | 2G11 | 314    | 2 | 10  | 38  |
| HNSL36          | 4008321220684     | HNS L 36W 2G11      | 36 | 2G11 | 408    | 2 | 10  | 38  |
| HNS50FR         | 4008321229946     | HNS S 5W G23        | 5  | G23  | 108    | 3 | 10  | 38  |
| HNS70FR         | 4050300941202     | HNS S 7W G23        | 7  | G23  | 136    | 3 | 10  | 38  |
| HNS90FR         | 4050300941226     | HNS S 9W G23        | 9  | G23  | 166    | 3 | 10  | 38  |
| HNS110FR        | 4050300941240     | HNS S 11W G23       | 11 | G23  | 236    | 3 | 10  | 38  |
| HNSSE7          | 4008321383891     | HNS S/E 7W 2G7      | 7  | 2G7  | 112    | 4 | 10  | 38  |
| HNSSE9          | 4008321384911     | HNS S/E 9W 2G7      | 9  | 2G7  | 142    | 4 | 10  | 38  |
| HNSSE11         | 4008321384935     | HNS S/E 11W 2G7     | 11 | 2G7  | 212    | 4 | 10  | 38  |



All orders must be multiples of sales pack

## ELECTRONIC CONTROL GEAR



# Electronic Control Gear Contents.



## ECG FOR FLUORESCENT AND/OR COMPACT FLUORESCENT LAMPS

|  |     |
|--|-----|
| QUICKTRONIC® INTELLIGENT QTi DALI® DIM for T5 fluorescent tubes        | 237 |
| QUICKTRONIC® INTELLIGENT QTi DALI® DIM for T8 fluorescent tubes        | 238 |
| QUICKTRONIC® INTELLIGENT QTi DALI® DIM for CFL OSRAM DULUX® D/E,T/E    | 238 |
| QUICKTRONIC® QT DALI® DIM for CFL OSRAM DULUX® T/E HE                  | 239 |
| QUICKTRONIC® INTELLIGENT QTi DIM (1-10V) for T5 fluorescent tubes      | 239 |
| QUICKTRONIC® DE LUXE HF DIM (1-10V) for T8 fluorescent tubes           | 240 |
| QUICKTRONIC® INTELLIGENT QTi DIM (1-10V) for T8 fluorescent tubes      | 240 |
| QUICKTRONIC® INTELLIGENT QTi DIM (1-10V) for CFL OSRAM DULUX® D/E, T/E | 241 |
| QUICKTRONIC® INTELLIGENT QTi for T5 fluorescent tubes                  | 241 |
| QUICKTRONIC® PROFESSIONAL QTP5 for T5 HE fluorescent tubes             | 242 |
| QUICKTRONIC® PROFESSIONAL for T5 HO fluorescent tubes                  | 242 |
| QUICKTRONIC® QT for T5 circular fluorescent tubes                      | 243 |
| QUICKTRONIC® PROFESSIONAL for T5 FC and DL lamps                       | 243 |
| QUICKTRONIC® PROFESSIONAL QTP8 for T8 fluorescent tubes                | 244 |
| QUICKTRONIC® FIT QT-FIT8 for T8 fluorescent tubes                      | 245 |
| QUICKTRONIC® INSTANT START ECONOMIC QTIS E for T8 fluorescent tubes    | 246 |
| QUICKTRONIC® ECO QT-ECO for CFL OSRAM DULUX® D/E, T/E, FM lamps        | 247 |
| QUICKTRONIC® PROFESSIONAL QTP-DL for CFL OSRAM DULUX L® and F lamps    | 248 |
| QUICKTRONIC® PROFESSIONAL for compact fluorescent lamps                | 249 |
| QUICKTRONIC® QT-TE for CFL OSRAM DULUX® T/E HE                         | 249 |
| DULUXTRONIC®   | 250 |
| QUICKTRONIC® QT-FM for T2 fluorescent tubes                            | 251 |
| QUICKTRONIC® ECONOMIC QT-ECO for T2 fluorescent tubes                  | 251 |
| QUICKTRONIC® for OSRAM ENDURA®   | 252 |
| ECG accessories – Protective Casing OUTKIT®                            | 252 |
| ECG accessories – QT Cable Clamp                                       | 252 |

## ECG FOR HID LAMPS

|   |     |
|---|-----|
| POWERTRONIC® OUTDOOR PTo for HID lamps                            | 253 |
| POWERTRONIC® INTELLIGENT PTi S for HID lamp (without cable clamp) | 254 |
| POWERTRONIC® INTELLIGENT PTi for HID lamps (with cable clamp)     | 255 |
| POWERTRONIC® INTELLIGENT SNAP for HID lamps (with cable clamp)    | 256 |
| POWERTRONIC® FIT PT-FIT for HID lamps                             | 256 |
| POWERTRONIC® GREENHOUSE   | 257 |
| EBN-OS Inrush current limiter for POWERTRONIC®                    | 257 |

## ECG FOR LOW VOLTAGE HALOGEN LAMPS

|  |     |
|--|-----|
| HALOTRONIC® DALI® for Low Voltage Halogen lamps      | 258 |
| HALOTRONIC® LONG (HTL) for Low Voltage Halogen lamps | 258 |
| HALOTRONIC® HTM MOUSE® for Low Voltage Halogen lamps | 259 |
| HALOTRONIC® NANO for Low Voltage Halogen lamps       | 259 |
| ET-PARROT®   | 260 |
| Dimming modules for HALOTRONIC®                      | 260 |

## CONTENTS

### ECG FOR LED MODULES

|   |     |
|---|-----|
| 10V OPTOTRONIC® units for LED modules   | 261 |
| 24V OPTOTRONIC® units for LED modules   | 261 |
| 350mA OPTOTRONIC® units for LED modules | 262 |
| 700mA OPTOTRONIC® units for LED modules | 262 |
| OPTOTRONIC® Dimmers                     | 263 |
| OPTOTRONIC® Units with DALI interfaces  | 263 |
| OPTOTRONIC® for PrevaLED™               | 264 |




# Systematic quality – from a single source

## The multi-level system guarantee from OSRAM


OSRAM introduced the System<sup>+</sup> Guarantee for lamp and ECG from a single source more than 6 years ago. The System<sup>+</sup> Guarantee is popular with system operators as it provides additional security for using modern energy-efficient systems, especially dimming systems. More than 10 million ECGs throughout the world have already been registered, ranging from industrial facilities and shopping centers to the smallest lighting systems. The System<sup>+</sup> Guarantee is in high demand among users particularly for dimming systems and high-intensity discharge lamps.

OSRAM is the only ECG supplier to replace **any** ECG that fails as a result of a material or manufacturing defect.



To meet market requirements and demands due to the increasing use of lighting control components OSRAM now offers in addition to a guarantee on lamps and ECGs a System<sup>+</sup> Guarantee in connection with OSRAM lighting control components.


**For more information go to**  
[www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**ELECTRONIC CONTROL GEAR****ECG FOR FLUORESCENT AND/OR COMPACT FLUORESCENT LAMPS****QUICKTRONIC® INTELLIGENT QTi DALI® DIM for T5 fluorescent tubes**

- Digital dimmable ECG for T5 HE & HO fluorescent lamps, OSRAM DULUX® L CONSTANT, OSRAM DULUX® T/E IN PLUS
- Intelligent lamp detection and superior dimming from 1 to 100%

| Product ID Code               | EAN (Single Pack) | Product Description             | PPG   |
|-------------------------------|-------------------|---------------------------------|-------|
| <b>Single</b>                 |                   |                                 |       |
| QTIDALI114-24DIM              | 4050300870380     | QTi DALI 1x14/24/220-240 DIM    | 20 39 |
| QTIDALI121-39DIM              | 4050300870366     | QTi DALI 1x21/39/220-240 DIM    | 20 39 |
| QTIDALI128-54DIM              | 4050300870809     | QTi DALI 1x28/54/220-240 DIM    | 20 39 |
| QTIDALI135-80DIM              | 4050300870342     | QTi DALI 1x35/49/80/220-240 DIM | 20 39 |
| <b>Twin</b>                   |                   |                                 |       |
| QTIDALI214-24DIM              | 4050300870861     | QTi DALI 2x14/24/220-240 DIM    | 20 39 |
| QTIDALI221-39DIM              | 4050300870489     | QTi DALI 2x21/39/220-240 DIM    | 20 39 |
| QTIDALI228-54DIM              | 4050300870502     | QTi DALI 2x28/54/220-240 DIM    | 20 39 |
| QTIDALI235-49DIM              | 4050300870465     | QTi DALI 2x35/49/220-240 DIM    | 20 39 |
| QTIDALI280DIM                 | 4050300870441     | QTi DALI 2x80/220-240 DIM       | 20 39 |
| <b>Three &amp; four lamps</b> |                   |                                 |       |
| QTIDALI314-24DIM              | 4008321069955     | QTi DALI 3x14/24/220-240 DIM    | 20 39 |
| QTIDALI414-24DIM              | 4008321070036     | QTi DALI 4x14/24/220-240 DIM    | 20 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® INTELLIGENT QTi DALI® DIM for T8 fluorescent tubes**

- Digital dimmable ECG for T8 fluorescent lamps
- Intelligent lamp detection and superior dimming from 1 to 100%

| Product ID Code               | EAN (Single Pack) | Product Description       |    | PPG |
|-------------------------------|-------------------|---------------------------|----|-----|
| <b>Single</b>                 |                   |                           |    |     |
| QTIDALI118DIM                 | 4050300870403     | QTi DALI 1x18/220-240 DIM | 20 | 39  |
| QTIDALI136DIM                 | 4050300870427     | QTi DALI 1x36/220-240 DIM | 20 | 39  |
| QTIDALI158DIM                 | 4050300870823     | QTi DALI 1x58/220-240 DIM | 20 | 39  |
| <b>Twin</b>                   |                   |                           |    |     |
| QTIDALI218DIM                 | 4050300870526     | QTi DALI 2x18/220-240 DIM | 20 | 39  |
| QTIDALI236DIM                 | 4050300870885     | QTi DALI 2x36/220-240 DIM | 20 | 39  |
| QTIDALI258DIM                 | 4050300870847     | QTi DALI 2x58/220-240 DIM | 20 | 39  |
| <b>Three &amp; four lamps</b> |                   |                           |    |     |
| QTIDALI318DIM                 | 4008321069979     | QTi DALI 3x18/220-240 DIM | 20 | 39  |
| QTIDALI418DIM                 | 4008321070050     | QTi DALI 4x18/220-240 DIM | 20 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**QUICKTRONIC® INTELLIGENT QTi DALI® DIM for CFL OSRAM DULUX® D/E,T/E**


- Intelligent digital dimmable ECG for OSRAM DULUX® D/E and T/E compact fluorescent lamps
- With DALI or 1-10V dimming interface

| Product ID Code    | EAN (Single Pack) | Product Description      |    | PPG |
|--------------------|-------------------|--------------------------|----|-----|
| <b>Single</b>      |                   |                          |    |     |
| QTIDALITE118-57DIM | 4008321060808     | QTi DALI-T/E 1x18-57 DIM | 20 | 39  |
| <b>Twin</b>        |                   |                          |    |     |
| QTIDALITE218-42DIM | 4008321060822     | QTi DALI-T/E 2x18-42 DIM | 20 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)


All orders must be multiples of sales pack

## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® QT DALI® DIM for CFL OSRAM DULUX® T/E HE**

- New QT (DALI) T/E 14-17 HE for operating OSRAM DULUX® T/E HE Lamps

| Product ID Code   | EAN (Single Pack) | Product Description         |    | PPG |
|-------------------|-------------------|-----------------------------|----|-----|
| QTDALITE114-17DIM | 4008321327383     | QT DALI T/E 1x14-17 HE DIM  | 12 | 39  |
| QTDALITE214-17DIM | 4008321327406     | QTP DALI T/E 2x14-17 HE DIM | 12 | 39  |

**NEW****QUICKTRONIC® INTELLIGENT QTi DIM (1-10V) for T5 fluorescent tubes**


- 1...10V intelligent dimmable ECG for T5 HO and HE fluorescent lamps
- Dimming range 1 to 100%

| Product ID Code               | EAN (Single Pack) | Product Description        |    | PPG |
|-------------------------------|-------------------|----------------------------|----|-----|
| <b>Single</b>                 |                   |                            |    |     |
| QT1114-24DIM                  | 4050300870922     | QTi 1x14/24/220-240 DIM    | 20 | 39  |
| QT1121-39DIM                  | 4050300870564     | QTi 1x21/39/220-240 DIM    | 20 | 39  |
| QT1128-54DIM                  | 4050300870588     | QTi 1x28/54/220-240 DIM    | 20 | 39  |
| QT1135-80DIM                  | 4050300870540     | QTi 1x35/49/80/220-240 DIM | 20 | 39  |
| <b>Twin</b>                   |                   |                            |    |     |
| QT1214-24DIM                  | 4050300870946     | QTi 2x14/24/220-240 DIM    | 20 | 39  |
| QT1221-39DIM                  | 4050300870694     | QTi 2x21/39/220-240 DIM    | 20 | 39  |
| QT1228-54DIM                  | 4050300870717     | QTi 2x28/54/220-240 DIM    | 20 | 39  |
| QT1235-49DIM                  | 4050300870670     | QTi 2x35/49/220-240 DIM    | 20 | 39  |
| QT1235DIM                     | 4050300870984     | QTi 2x80/220-240 DIM       | 20 | 39  |
| <b>Three &amp; four lamps</b> |                   |                            |    |     |
| QT1314-24DIM                  | 4008321069719     | QTi 3x14/24/220-240 DIM    | 20 | 39  |
| QT1414-24DIM                  | 4008321069993     | QTi 4x14/24/220-240 DIM    | 20 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® DE LUXE HF DIM (1-10V) for T8 fluorescent tubes**

- 1...10V dimming ECG for T8 fluorescent lamps
- Dimming range 1 to 100% (three & four lamp 3 to 100%)

| Product ID Code | EAN (Single Pack) | Product Description |    |    |
|-----------------|-------------------|---------------------|----|----|
| <b>Single</b>   |                   |                     |    |    |
| HF118DIM        | 4050300319254     | HF 1x18/230-240 DIM | 20 | 39 |
| HF136DIM        | 4050300297705     | HF 1x36/230-240 DIM | 20 | 39 |
| HF158DIM        | 4050300297729     | HF 1x58/230-240 DIM | 20 | 39 |
| <b>Twin</b>     |                   |                     |    |    |
| HF218DIM        | 4050300350950     | HF 2x18/230-240 DIM | 20 | 39 |
| HF236DIM        | 4050300350974     | HF 2x36/230-240 DIM | 20 | 39 |
| HF258DIM        | 4050300350998     | HF 2x58/230-240 DIM | 20 | 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**QUICKTRONIC® INTELLIGENT QTi DIM (1-10V) for T8 fluorescent tubes**

- 1...10V intelligent dimmable ECG for T8 fluorescent lamps
- Dimming range 1 to 100%

| Product ID Code               | EAN (Single Pack) | Product Description  |    |    |
|-------------------------------|-------------------|----------------------|----|----|
| <b>Single</b>                 |                   |                      |    |    |
| QT1118DIM                     | 4050300870601     | QTi 1x18/220-240 DIM | 20 | 39 |
| QT1136DIM                     | 4050300870625     | QTi 1x36/220-240 DIM | 20 | 39 |
| QT1158DIM                     | 4050300870908     | QTi 1x58/220-240 DIM | 20 | 39 |
| <b>Twin</b>                   |                   |                      |    |    |
| QT1218DIM                     | 4050300870960     | QTi 2x18/220-240 DIM | 20 | 39 |
| QT1236DIM                     | 4050300870755     | QTi 2x36/220-240 DIM | 20 | 39 |
| QT1258DIM                     | 4050300870731     | QTi 2x58/220-240 DIM | 20 | 39 |
| <b>Three &amp; four lamps</b> |                   |                      |    |    |
| QT1318DIM                     | 4008321069931     | QTi 3x18/220-240 DIM | 20 | 39 |
| QT1418DIM                     | 4008321070012     | QTi 4x18/220-240 DIM | 20 | 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® INTELLIGENT QTi DIM (1-10V) for CFL OSRAM DULUX® D/E, T/E**

- 1...10V intelligent dimmable ECG for OSRAM DULUX® D/E and T/E compact fluorescent lamps

| Product ID Code | EAN (Single Pack) | Product Description           |    | PPG |
|-----------------|-------------------|-------------------------------|----|-----|
| QTITE118-57DIM  | 4008321060860     | QTi-T/E 1x18-57/ 220-240 DIM  | 20 | 39  |
| Twin            |                   |                               |    |     |
| QTITE218-42DIM  | 4008321060846     | QTi-T/E 2x18-42 / 220-240 DIM | 20 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**QUICKTRONIC® INTELLIGENT QTi for T5 fluorescent tubes**

- Intelligent ECG for T5 HO and HE fluorescent lamps
- Higher efficiency, shorter cases

| Product ID Code | EAN (Single Pack) | Product Description   |    | PPG |
|-----------------|-------------------|-----------------------|----|-----|
| <b>Single</b>   |                   |                       |    |     |
| QT1114          | 4050300796871     | QTi 1x14/24/21/39     | 20 | 39  |
| QT1114GII       | 4008321383334     | QTi 1x14/24/21/39 GII | 20 | 39  |
| QT1128          | 4050300796857     | QTi 1x28/54           | 20 | 39  |
| QT1128GII       | 4008321383358     | QTi 1x28/54/35/49 GII | 20 | 39  |
| QT1135          | 4050300796833     | QTi 1x35/49/80        | 20 | 39  |
| QT1135GII       | 4008321383372     | QTi 1x35/49/80 GII    | 20 | 39  |
| <b>Twin</b>     |                   |                       |    |     |
| QT1214          | 4050300797090     | QTi 2x14/24/21/39     | 20 | 39  |
| QT1214GII       | 4008321383396     | QTi 2x14/24/21/39 GII | 20 | 39  |
| QT1228          | 4050300797076     | QTi 2x28/54           | 20 | 39  |
| QT1228GII       | 4008321383419     | QTi 2x28/54/35/49 GII | 20 | 39  |
| QT1235          | 4050300796895     | QTi 2x35/49           | 20 | 39  |
| QT1235-80       | 4008321174291     | QTi 2x35/49/80        | 20 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® PROFESSIONAL QTP5 for T5 HE fluorescent tubes**

- ECG for T5 HE fluorescent lamps including NEW Longlife XT HO T5 tube and DULUX® L 28W HE lamps
- New 2nd generation family offer product life of up to 100,000 hours, suitable for protection class I & II luminaires and are shorter in dimension

| Product ID Code | EAN (Single Pack) | Product Description         |    |    |
|-----------------|-------------------|-----------------------------|----|----|
| <b>Single</b>   |                   |                             |    |    |
| QTP511435       | 4008321329035     | QTP5 1x14-35 2nd generation | 20 | 39 |
| <b>Twin</b>     |                   |                             |    |    |
| QTP521435       | 4008321329073     | QTP5 2x14-35 2nd generation | 20 | 39 |
| <b>Triple</b>   |                   |                             |    |    |
| QTP5314         | 4008321484598     | QTP5 3x14, 4x14             | 20 | 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**QUICKTRONIC® PROFESSIONAL for T5 HO fluorescent tubes**


- ECG for T5 HO fluorescent tubes and DULUX® L 55W-80W
- New 2nd generation family offer product life of up to 100,000 hours, suitable for protection class I & II luminaires and are shorter in dimension

| Product ID Code | EAN (Single Pack) | Product Description          |    |    |
|-----------------|-------------------|------------------------------|----|----|
| <b>Single</b>   |                   |                              |    |    |
| QTP512439       | 4008321329110     | QTP5 1x24-39 2nd generation  | 20 | 39 |
| QTP5149         | 4008321329370     | QTP5 1x49 2nd generation     | 20 | 39 |
| QTP5154         | 4008321329394     | QTP5 1x54 2nd generation     | 20 | 39 |
| QTP5180         | 4008321329059     | QTP5 1x80 2nd generation     | 20 | 39 |
| <b>Twin</b>     |                   |                              |    |    |
| QTP522439       | 4008321329417     | QTP5 2 X24-39 2nd generation | 20 | 39 |
| QTP5249         | 4008321329431     | QTP5 2x49 2nd generation     | 20 | 39 |
| QTP5254         | 4008321329097     | QTP5 2x54 2nd generation     | 20 | 39 |
| QTFQ280CW       | 4050300825564     | QTP5 2x80 2nd generation     | 20 | 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® QT for T5 circular fluorescent tubes**

- ECG for T5 circular fluorescent lamps

| Product ID Code | EAN (Single Pack) | Product Description                           | Light No. | PPG   |
|-----------------|-------------------|---|-----------|-------|
| <b>Single</b>   |                   |   |           |       |
| QTM126-42SE     | 4050300817699     | QT-M 1x26-42/220-240 SE OUTDOOR USE MULTIWATT | 1         | 20 39 |
| QTCFC155        | 4050300526096     | QT-FC 1x55/230-240                            | 2         | 20 39 |
| <b>Twin</b>     |                   |   |           |       |
| QTM226-32       | 4050300624969     | QT-M 2x26-32/230-240 MULTIWATT                | 3         | 20 39 |
| QTM226-42       | 4008321110022     | QT-M 2x26-42/220-240 MULTIWATT                | 3         | 20 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**QUICKTRONIC® PROFESSIONAL for T5 FC and DL lamps**


- Suitable for 1xFC 55 and 1xDL 55W lamps
- K2 case (103 x 67 x 31 mm)
- Suitable for optional K2 cable clamp for independent installation
- 50,000 hours lifetime

| Product ID Code | EAN (Single Pack) | Product Description            | PPG   |
|-----------------|-------------------|--------------------------------|-------|
| QTPFC155        | 4008321537041*    | QTP-FC - 1x FC 55 and 1x DL 55 | 20 39 |

NEW!

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

\*In preparation at time of print. For further information please contact OSRAM



All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® PROFESSIONAL QTP8 for T8 fluorescent tubes**

- ECG for T8 fluorescent lamps including the new OSRAM LUMILUX® XXT tube


| Product ID Code               | EAN (Single Pack) | Product Description     |    | PPG |
|-------------------------------|-------------------|-------------------------|----|-----|
| <b>Single</b>                 |                   |                         |    |     |
| QTP8118                       | 4008321131584     | QTP8 1x18/230-240       | 20 | 39  |
| QTP8136                       | 4008321131621     | QTP8 1x36/230-240       | 20 | 39  |
| QTP8158                       | 4008321131669     | QTP8 1x58/230-240       | 20 | 39  |
| <b>Twin</b>                   |                   |                         |    |     |
| QTP8218                       | 4008321131607     | QTP8 2x18/230-240       | 20 | 39  |
| QTP8236                       | 4008321131645     | QTP8 2x36/230-240       | 20 | 39  |
| QTP8258                       | 4008321131683     | QTP8 2x58/230-240       | 20 | 39  |
| <b>Three &amp; four lamps</b> |                   |                         |    |     |
| QTP8318                       | 4008321131706     | QTP8 3x18, 4x18/230-240 | 20 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



All orders must be multiples of sales pack

## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps


**QUICKTRONIC® FIT QT-FIT8 for T8 fluorescent tubes**

- T8 standard pre-heat ECG for T8 fluorescent tubes
- Up to 25% energy saving and 80% higher lamp life compared to magnetic ballast
- Automatic shutdown at lamp failure and automatic restart after lamp replacement
- High energy efficiency (EEI=A2)
- Long ECG lifetime (50,000 hours) suitable for use with motion sensors

| Product ID Code               | EAN (Single Pack) | Product Description | PPG   |
|-------------------------------|-------------------|---------------------|-------|
| <b>Single</b>                 |                   |                     |       |
| QTFIT8118                     | 4008321294180     | QT-FIT8 1X18        | 20 39 |
| QTFIT8136                     | 4008321294203     | QT-FIT8 1X36        | 20 39 |
| QTFIT8158                     | 4008321294227     | QT-FIT8 1X58-70     | 20 39 |
| <b>Twin</b>                   |                   |                     |       |
| QTFIT8218                     | 4008321294241     | QT-FIT8 2X18        | 20 39 |
| QTFIT8236                     | 4008321294265     | QT-FIT8 2X36        | 20 39 |
| QTFIT8258                     | 4008321294289     | QT-FIT8 2X58-70     | 20 39 |
| <b>Three &amp; four lamps</b> |                   |                     |       |
| QTFIT8318                     | 4008321294302     | QT-FIT8 3X, 4X18    | 20 39 |
| QTFIT8336                     | 4008321512055     | QT-FIT8 3X36        | 20 39 |


1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

NEW



All orders must be multiples of sales pack

## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps


**QUICKTRONIC® INSTANT START ECONOMIC QTIS E for T8 fluorescent tubes**

- Economical ECG for T8 fluorescent lamps

| Product ID Code               | EAN (Single Pack) | Product Description       |    |    |
|-------------------------------|-------------------|---------------------------|----|----|
| <b>Single</b>                 |                   |                           |    |    |
| QTISE118                      | 4050300775388     | QTIS e 1x18/220-240       | 20 | 39 |
| QTISE136                      | 4050300940649     | QTIS e 1x36/220-240       | 20 | 39 |
| QTISE158                      | 4050300940625     | QTIS e 1x58/220-240       | 20 | 39 |
| <b>Twin</b>                   |                   |                           |    |    |
| QTISE218                      | 4050300775401     | QTIS e 2x18/220-240       | 20 | 39 |
| QTISE236                      | 4050300940663     | QTIS e 2x36/220-240       | 20 | 39 |
| QTISE258                      | 4050300940618     | QTIS e 2x58/220-240       | 20 | 39 |
| <b>Three &amp; four lamps</b> |                   |                           |    |    |
| QTISE418                      | 4050300940670     | QTIS e 3x18, 4x18/220-240 | 20 | 39 |
| QTISE336CW                    | 4008321104687     | QTIS e 3x36/220-240       | 20 | 39 |


Will be replaced by QT-FIT8. Please refer to page 246 for further information

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® ECO QT-ECO for CFL OSRAM DULUX® D/E, T/E, FM lamps**

- ECG with typical dimensions of CCG
- Suitable for compact fluorescent lamps

| Product ID Code | EAN (Single Pack) | Product Description              |    |    |
|-----------------|-------------------|----------------------------------|----|----|
| <b>Single</b>   |                   |                                  |    |    |
| QTEC014-16      | 4050300638584     | QT-ECO 1x4-16/220-240 S square   | 20 | 39 |
| QTEC014-16L     | 4050300660370     | QT-ECO 1x4-16/220-240 L long     | 20 | 39 |
| QTEC0118-21     | 4050300794907     | QT-ECO 1x18-21/220-240 S square  | 20 | 39 |
| QTEC0118-24     | 4050300638560     | QT-ECO 1x18-24/220-240 S square  | 20 | 39 |
| QTEC0118-24L    | 4050300660417     | QT-ECO 1x18-24/220-240 L long    | 20 | 39 |
| QTEC0126        | 4008321065971     | QT-ECO 1x26/220-240 S square     | 20 | 39 |
| <b>Twin</b>     |                   |                                  |    |    |
| QTEC025-11      | 4050300821504     | QT-ECO 2x5-11/220-240 S square   | 20 | 39 |
| QTECOTE218      | 4050300803982     | QT-ECO/T/E 2x18/220-240 S square | 20 | 39 |
| QTECOTE226      | 4050300804002     | QT-ECO T/E 2x26/220-240 S square | 20 | 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps


**QUICKTRONIC® PROFESSIONAL QTP-DL for CFL OSRAM DULUX® L and F lamps**

- ECG for OSRAM DULUX® L and F compact fluorescent lamps
- 2nd generation version with shorter cases


| Product ID Code | EAN (Single Pack) | Product Description                      | No. | PPG   |
|-----------------|-------------------|--|-----|-------|
| <b>Single</b>   |                   |  |     |       |
| QTPDL11824      | 4008321117861     | QTP-DL 1x18-24/220-240                   | 1   | 20 39 |
| QTPDL13640      | 4008321117908     | QTP-DL 1x36-40/220-240                   | 1   | 20 39 |
| QTPDL155        | 4008321117946     | QTP-DL 1x55/220-240                      | 1   | 20 39 |
| QTPDL155GII     | 4008321390158     | QTP-DL 1x55/220-240 GII (2nd Generation) | 1   | 20 39 |
| <b>Twin</b>     |                   |  |     |       |
| QTPDL21824      | 4008321117885     | QTP-DL 2x18-24/220-240                   | 2   | 20 39 |
| QTPDL23640      | 4008321117922     | QTP-DL 2x36-40/220-240                   | 2   | 20 39 |
| QTPDL255        | 4008321117960     | QTP-DL 2x55/220-240                      | 2   | 20 39 |
| QTPDL255GII     | 4008321390172     | QTP-DL 2x55/220-240 GII (2nd Generation) | 2   | 20 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



All orders must be multiples of sales pack

## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® PROFESSIONAL for Compact Fluorescent lamps**


- ECG for 4-pin compact fluorescent lamps
- Suitable for OSRAM DULUX® D/E and T/E lamps
- New QTP Multiwatt version suitable for OSRAM DULUX® D/E, T/E, DL, DF and LUMILUX® FC, HO & T8 lamps

| Product ID Code | EAN (Single Pack) | Product Description                           | PPG   |
|-----------------|-------------------|---|-------|
| <b>Single</b>   |                   |   |       |
| QTPDE110        | 4008321181572     | QTP-D/E 1x10-13/220-240                       | 20 39 |
| QTPTE118        | 4008321181701     | QTP-T/E 1x18-13/220-240                       | 20 39 |
| QTM126-42SE     | 4050300817699     | QT-M 1x26-42/220-240 SE OUTDOOR USE MULTIWATT | 20 39 |
| QTPM126-42      | 4008321329134     | QTP-M 1x 26-42/220-240                        | 20 39 |
| <b>Twin</b>     |                   |   |       |
| QTPDE21013      | 4008321181596     | QTP-D/E 2x10-13/220-240                       | 20 39 |
| QTPTE218        | 4008321181619     | QTP-T/E 2x18/220-240                          | 20 39 |
| QTM226-32       | 4050300624969     | QT-M 2x26-32/230-240 MULTIWATT                | 20 39 |
| QTM226-42       | 4008321110022     | QT-M 2x26-42/220-240 MULTIWATT                | 20 39 |
| QTPM226-32      | 4008321329158     | QTP-M 2x 26-32/220-240                        | 20 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

NEW

NEW

**QUICKTRONIC® QT-TE and QT-T/E HE for CFL OSRAM DULUX® T/E and T/E HE**


|            |               |                       |       |
|------------|---------------|-----------------------|-------|
| QTTE114-17 | 4008321327345 | QT-T/E 1x14-17 HE     | 12 39 |
| QTTE214-17 | 4008321327369 | QT-T/E 2x14-17 HE     | 12 39 |
| QTPTE1218  | 4008321537065 | QTP-T/E 1x18, 2x18    | 20 39 |
| QTPTE1226  | 4008321537089 | QTP-T/E 1x26-42, 2x26 | 20 39 |

NEW

NEW


All orders must be multiples of sales pack

## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**DULUXTRONIC®**


- ECG with integral lampholder for pin base compact fluorescent
- Suitable for OSRAM DULUX® S/E, D/E and T/E

| Product ID Code  | EAN (Single Pack) | Product Description    | No. | PPG   |
|------------------|-------------------|------------------------|-----|-------|
| <b>S version</b> |                   |                        |     |       |
| DTSE511S         | 4008321181459     | DT-S/E 5-11/230-240 S  | 1   | 20 39 |
| <b>C version</b> |                   |                        |     |       |
| DTDE1013C        | 4008321181510     | DT-D/E 10-13/230-240 C | 2   | 20 39 |
| DTTE18C          | 4050300421384     | DT-T/E 18/230-240 C    | 2   | 20 39 |
| <b>P version</b> |                   |                        |     |       |
| DTDE1013P        | 4008321181534     | DT-D/E 10-13/230-240 P | 3   | 20 39 |
| DTTE18P          | 4050300421421     | DT-T/E 18/230-240 P    | 3   | 20 39 |
| <b>L version</b> |                   |                        |     |       |
| DTSE511L         | 4008321181473     | DT-S/E 5-11/230-240 L  | 4   | 20 39 |
| DTDE1013L        | 4008321181497     | DT-D/E 10-13/230-240 L | 5   | 20 39 |
| DTTE18L          | 4050300406404     | DT-T/E 18/230-240 L    | 5   | 20 39 |



All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® QT-FM for T2 fluorescent tubes**

- ECG for FM T2 miniature fluorescent lamps

| Product ID Code        | EAN (Single Pack) | Product Description   | No. | PPG   |
|------------------------|-------------------|-----------------------|-----|-------|
| <b>With housing</b>    |                   |                       |     |       |
| QTFM16                 | 4050300511139     | QT-FM 1x6/230-240 L   | 1   | 20 39 |
| QTFM18                 | 4050300511153     | QT-FM 1x8/230-240 L   | 1   | 20 39 |
| QTFM111                | 4050300511177     | QT-FM 1x11/230-240 L  | 1   | 20 39 |
| QTFM113                | 4050300511191     | QT-FM 1x13/230-240 L  | 1   | 20 39 |
| <b>Without housing</b> |                   |                       |     |       |
| QTFM18LB               | 4050300363523     | QT-FM 1x8/230-240 LB  | 2   | 20 39 |
| QTFM111LB              | 4050300363547     | QT-FM 1x11/230-240 LB | 2   | 20 39 |
| QTFM113LB              | 4050300363561     | QT-FM 1x13/230-240 LB | 2   | 20 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**QUICKTRONIC® ECONOMIC QT-ECO for T2 fluorescent tubes**


- ECG for FM T2 miniature fluorescent lamps

| Product ID Code | EAN (Single Pack) | Product Description       | PPG   |
|-----------------|-------------------|---------------------------|-------|
| QTECOFM16-8     | 4050300797502     | QT-ECO FM 1x6-8/220-240   | 50 39 |
| QTECOFM11-13    | 4050300799780     | QT-ECO FM 1x11-13/220-240 | 20 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## Electronic Control Gear – ECG for Fluorescent and/or Compact Fluorescent Lamps

**QUICKTRONIC® for OSRAM ENDURA®**

- Electronic control gear for OSRAM ENDURA® lamp




| Product ID Code | EAN (Single Pack) | Product Description         |   |    |
|-----------------|-------------------|-----------------------------|---|----|
| QTENDURA70      | 4050300804668     | QT ENDURA 70-100/120-240 S  | 1 | 39 |
| QTENDURA100SUK  | 4050300662589     | QT ENDURA 100-150/120-240 S | 1 | 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**ECG accessories – Protective Casing OUTKIT®**

- IP67 rated ECG housing

| Product ID Code | EAN (Single Pack) | Product Description                        |    |    |
|-----------------|-------------------|--|----|----|
| OUTKIT30S       | 4008321159533     | Short – for ECG dimensions 360 x 30 x 30mm | 20 | 39 |
| OUTKIT21S       | 4008321159571     | Short – for ECG dimensions 360 x 30 x 21mm | 20 | 39 |
| OUTKIT30L       | 4008321159557     | Long – for ECG dimensions 423 x 30 x 30mm  | 20 | 39 |
| OUTKIT21L       | 4008321159595     | Long – for ECG dimensions 423 x 30 x 21mm  | 20 | 39 |

**ECG accessories – QT Cable Clamp**


| Product ID Code | EAN (Single Pack) | Product Description |    |    |
|-----------------|-------------------|---------------------|----|----|
| –               | 4008321907727*    | QT CABLE CLAMP K2   | 10 | 39 |
| QTCABLECLAMPK3  | 4008321190741     | QT CABLE CLAMP K3   | 10 | 39 |

\*In preparation at time of print. For further information please contact OSRAM

All orders must be multiples of sales pack

## ELECTRONIC CONTROL GEAR

### ECG FOR HID LAMPS




#### POWERTRONIC® OUTDOOR PTo for HID lamps

- ECG for metal halide lamps
- New PTo DALI intelligent version for street and outdoor lighting
- PTo 3DIM has 3 dim options
  - 1) DALI control – continual dimming range between 60% and 100% lamp output
  - 2) Step DIM – Two step switching
  - 3) Astro DIM – Two step dimming with an integrated timer control
- Complies with new EMI Standards acc to EN 55015

| Product ID Code | EAN (Single Pack) | Product Description   | PPG   |
|-----------------|-------------------|-----------------------|-------|
| PT035           | 4008321956323     | PTo 35/220-240        | 20 39 |
| PT050DIM3       | 4008321956347     | PTo 50/220-240 3 DIM  | 20 39 |
| PT070DIM3       | 4008321959355     | PTo 70/220-240 3 DIM  | 20 39 |
| -               | 4008321956361*    | PTo 100/220-240 3 DIM | 20 39 |
| -               | 4008321956385*    | PTo 150/220-240 3 DIM | 20 39 |


1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

\*In preparation at time of print. For further information please contact OSRAM



All orders must be multiples of sales pack


## Electronic Control Gear – ECG for HID Lamps

**POWERTRONIC® INTELLIGENT PTi S for HID lamp (without cable clamp)**

- New intelligent versions (PTi) available for single and twin lamps
- PCB version for 20W HID high systems
- Compact dimensions and light designed for small luminaire designs
- Excellent thermal behaviour for very high limit temperatures
- Without cable clamp


| Product ID Code | EAN (Single Pack) | Product Description                    | No. | PPG   |
|-----------------|-------------------|--|-----|-------|
| <b>Single</b>   |                   |  |     |       |
| PTI205          | 4008321353290     | PTi 20/220-240 S without cable clamp   | 1   | 20 39 |
| PTI20B          | 4008321391490     | PTi 20/220-240 B (PCB)                 | –   | 20 39 |
| PTI35SMINI      | 4008321955906     | PTi 35/220-240 S Mini                  | –   | 20 39 |
| PTI35BMINI      | 4008321955913     | PTi 35/220-240 B Mini                  | –   | 20 39 |
| PTI35S          | 4008321073112     | PTi 35/220-240 S without cable clamp   | 2   | 20 39 |
| PTI235S         | 4008321372642     | PTi 2x35/220-240 S without cable clamp | 2   | 20 39 |
| PTI70S          | 4008321049629     | PTi 70/220-240 S without cable clamp   | 2   | 20 39 |
| PTI100S         | 4008321926630     | PTi 100/220-240 S without cable clamp  | 2   | 20 39 |
| PTI150S         | 4008321188090     | PTi 150/220-240 S without cable clamp  | 2   | 20 39 |
| <b>Twin</b>     |                   |  |     |       |
| PTI270S         | 4008321910028     | PTi 2x70/220-240 S without cable clamp | 2   | 20 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



All orders must be multiples of sales pack

## Electronic Control Gear – ECG for HID Lamps

**POWERTRONIC® INTELLIGENT PTi for HID lamps (with cable clamp)**

- New intelligent versions (PTi) available for single and twin lamps
- Extended terminal section enables mains looping
- Screw down cable clamps for reliable strain relief
- Screwless plug in terminals for rapid and accurate cabling


| Product ID Code  | EAN (Single Pack) | Product Description   | No. | PPG   |
|------------------|-------------------|---|-----|-------|
| <b>Single</b>    |                   |   |     |       |
| PTI20I           | 4008321404763     | PTi 20/220-240 I  | 1   | 20 39 |
| PTI35I           | 4008321099488     | PTi 35/220-240 I with cable clamp                               | 2   | 20 39 |
| PTI70I           | 4008321099501     | PTi 70/220-240 I with cable clamp                               | 2   | 20 39 |
| PTI100I          | 4008321926654     | PTi 100/220-240 I with cable clamp                              | 2   | 20 39 |
| PTI150I          | 4008321915535     | PTi 150/220-240 I with cable clamp                              | 2   | 20 39 |
| <b>Twin</b>      |                   |   |     |       |
| PTI270I          | 4008321910042     | PTi 2x70/220-240 I with cable clamp                             | 2   | 20 39 |
| PTI35IP          | 4008321290458     | PTi 35/220-240 I ST 18 cap with cable clamp and prewired cable  | 2   | 20 39 |
| PTI70IP          | 4008321290472     | PTi 70/220-240 I ST 18 cap with cable clamp and prewired cable  | 2   | 20 39 |
| PTODALI70DIM     | 4008321940612     | PTo DALI 70 20/220-240 DIM                                      | 2   | 20 39 |
| PTI150IP         | 4008321318152     | PTi 150/220-240 I ST 18 cap with cable clamp and prewired cable | 2   | 20 39 |
| PTI35IP          | 4008321543462     | PTi 35/220-240 I GST 18 cap with cable clamp and prewired cable | 2   | 20 39 |
| PTI70IP          | 4008321543943     | PTi 70/220-240 I GST 18 cap with cable clamp and prewired cable | 2   | 20 39 |
| <b>Twin lamp</b> |                   |   |     |       |
| PTI235S          | 4008321122247     | PTi 2x35/220-240 I with cable clamp                             | 2   | 20 39 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

NEW


NEW

NEW



All orders must be multiples of sales pack

## Electronic Control Gear – ECG for HID Lamps

**POWERTRONIC® INTELLIGENT SNAP for HID lamps (with cable clamp)**


- ECG with integrated socket for easy installation
- For all 35W and 70W HID lamps (HQI® and HCI®)
- Luminaire side equipped with ST 18 universal female plug
- Mains side equipped with GST 18 plug
- 40,000 hours ECG lifetime

| Product ID Code | EAN (Single Pack) | Product Description   | 1  | PPG |
|-----------------|-------------------|-----------------------|----|-----|
| PTI35SNAP       | 4008321955920     | PTi 35/220 - 240 SNAP | 20 | 39  |
| PTI70SNAP       | 4008321955937     | PTi 70/220 - 240 SNAP | 20 | 39  |


1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



1



2

**POWERTRONIC® FIT PT-FIT for HID lamps**

- ECG suitable for standard track and spot lightning fixtures

| Product ID Code            | EAN (Single Pack) | Product Description  | 1 | No. | PPG |
|----------------------------|-------------------|----------------------|---|-----|-----|
| <b>Without Cable Clamp</b> |                   |                      |   |     |     |
| PTFIT35S                   | 4008321386625     | PT-FIT 35/220-240 S  | 1 | 20  | 39  |
| PTFIT35                    | 4008321498731     | PT-FIT 35/220-240 B  | 1 | 20  | 39  |
| PTFIT70S                   | 4008321386649     | PT-FIT 70/ 220-240 S | 1 | 20  | 39  |
| PTFIT70                    | 4008321498717     | PT-FIT 70/ 220-240 B | 1 | 20  | 39  |
| <b>With Cable Clamp</b>    |                   |                      |   |     |     |
| PTFIT35I                   | 4008321377661     | PT-FIT 35/220-240 I  | 2 | 20  | 39  |
| PTFIT70I                   | 4008321377685     | PT-FIT 70/ 220-240 I | 2 | 20  | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack

## Electronic Control Gear – ECG for HID Lamps

**POWERTRONIC® GREENHOUSE**


- PTg – ECG for greenhouse lighting
- Ideal in systems with PLANTASTER®

| Product ID Code | EAN (Single Pack) | Product Description |   | PPG |
|-----------------|-------------------|---------------------|---|-----|
| PTG1000         | 4008321956408     | PTg 100/400         | 1 | 39  |

**EBN-OS Inrush current limiter for POWERTRONIC®**

- Inrush limiter for PTi and QTi installations
- Enables refurbishment of CCG installations without changing electrical infrastructure
- Ideal for all POWERTRONIC® ECG


| Product ID Code | EAN (Single Pack) | Product Description |     | PPG |
|-----------------|-------------------|---------------------|-----|-----|
| EBNOS           | 4006584548019     | EBN-OS              | 100 | 39  |



All orders must be multiples of sales pack

## ELECTRONIC CONTROL GEAR

### ECG FOR LOW VOLTAGE HALOGEN LAMPS




#### HALOTRONIC® DALI® for Low Voltage Halogen lamps

- Low voltage electronic transformers
- Long casing L 140mm x H 34mm x D 44mm
- Fully controllable with DALI® or Touch DIM/ Touch DIM Sensor
- Suitable for 12V halogen lamps

| Product ID Code                                       | EAN (Single Pack) | Product Description                                     |    | PPG |
|---|-------------------|---|----|-----|
| HTI105DALI  | 4008321420633     | HTI DALI 105/220-240 DIM                                | 10 | 39  |
| <b>Dimmer module for controlling HALOTRONIC® DALI</b> |                   |   |    |     |
| HTIDALI150DIM   | 4050300807782     | HTI DALI 150/220-240 DIM                                | 10 | 39  |
| HTIDALI315DIM   | 4008321957344     | HTI DALI 315 DIM dimming module for controlling HTIDALI | 10 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



#### HALOTRONIC® LONG (HTL) for Low Voltage Halogen lamps


- Low voltage electronic transformers
- Long casing L 140mm x H 34mm x D 44mm
- Fully dimmable with trailing and leading edge phase dimmer
- Suitable for 12V halogen lamps

| Product ID Code | EAN (Single Pack) | Product Description |    | PPG |
|-----------------|-------------------|---------------------|----|-----|
| HTL105          | 4008321927019     | HTL 105/230-240     | 10 | 39  |
| HTL225          | 4008321927026     | HTL 225/230-240     | 10 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack


## Electronic Control Gear – ECG for Low Voltage Halogen Lamps

**HALOTRONIC® HTM MOUSE® for Low Voltage Halogen lamps**

- Low voltage compact electronic transformers
- Fully dimmable with trailing and leading edge phase dimmer
- Suitable for 12V halogen lamps

| Product ID Code     | EAN (Single Pack) | Product Description | No. | P  | PPG |
|---------------------|-------------------|---------------------|-----|----|-----|
| <b>With housing</b> |                   |                     |     |    |     |
| HTM70               | 4050300442310     | HTM 70/230-240      | 1   | 20 | 39  |
| HTM105              | 4050300442334     | HTM 105/230-240     | 1   | 20 | 39  |
| HTM150              | 4050300581415     | HTM 150/230-240     | 2   | 10 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**HALOTRONIC® NANO for Low Voltage Halogen lamps**

- Low voltage electronic transformers
- Extremely compact
- Fully dimmable (trailing edge)
- Ideal partner for MINISTAR® low voltage lamps

| Product ID Code | EAN (Single Pack) | Product Description | P  | PPG |
|-----------------|-------------------|---------------------|----|-----|
| HTN75I          | 4008321073037     | HTN 75/230-240 I    | 20 | 39  |
| HTN75S          | 4008321909329     | HTN 75/230-240 S    | 20 | 39  |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)


All orders must be multiples of sales pack

## Electronic Control Gear – ECG for Low Voltage Halogen Lamps

**ET-PARROT®**

- Low voltage compact electronic transformers
- Fully dimmable with trailing and leading edge phase dimmer
- Suitable for 12V halogen lamps

| Product ID Code | EAN (Single Pack) | Product Description     |    |    |
|-----------------|-------------------|-------------------------|----|----|
| ET70            | 4008321111593     | ET-PARROT 70/220-240 I  | 50 | 39 |
| ET105           | 4008321111579     | ET-PARROT 105/220-240 I | 50 | 39 |


**Dimming modules for HALOTRONIC®**

- For controlling HALOTRONIC® LVTH transformers

| Product ID Code | EAN (Single Pack) | Product Description   |    |    |
|-----------------|-------------------|---|----|----|
| HT110DIM        | 4050300451350     | HT 1-10 DIM for controlling HALOTRONIC in 1...10V dimming systems | 10 | 39 |

All orders must be multiples of sales pack

## ELECTRONIC CONTROL GEAR ECG FOR LED MODULES




### 10V OPTOTRONIC® units for LED modules

- Electronic control gear for 10V LED modules
- Ideal for obtaining the optimum performance from LED modules

| Product ID Code | EAN (Single Pack) | Product Description  | No. | PPG   |
|-----------------|-------------------|----------------------|-----|-------|
| OT6/240CE       | 4008321113306     | OT 6/200-240/10V CE  | 1   | 20 38 |
| OT12LE          | 4008321174253     | OT 12/200-240/10V LE | 2   | 20 38 |
| OT15            | 4008321391544     | OT 15/220-240/10     | 3   | 20 38 |
| OT50            | 4050300817491     | OT 50/220-240/10V    | 4   | 10 38 |
| OT50E           | 4008321362452     | OT 50/220-240/10V E  | 5   | 10 38 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



### 24V OPTOTRONIC® units for LED modules


- Electronic control gear for 24V LED modules
- Ideal for obtaining the optimum performance from LED modules

| Product ID Code | EAN (Single Pack) | Product Description       | No. | PPG   |
|-----------------|-------------------|---------------------------|-----|-------|
| OT6/240/24CE    | 4008321113269     | OT 6/200-240/24V CE       | 1   | 20 38 |
| OT6/120/24CE    | 4008321129130     | OT 6/100-120/24V CE       | -   | 20 38 |
| OT8             | 4008321040169     | OT 8/200-240/24V          | 5   | 50 38 |
| OT20S           | 4050300662626     | OT 20/120-240/24V S       | 2   | 10 38 |
| OT20            | 4050300618111     | OT 20/230-240/24V         | 4   | 30 38 |
| OTEASY60        | 4008321187796     | OT EASY 60/220-240/24 RGB | -   | 10 38 |
| OT75            | 4050300817477     | OT 75/220-240/24V         | 3   | 10 38 |
| OT7SE           | 4008321362476     | OT 75/220-240/24V E       | 6   | 10 38 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack


## Electronic Control Gear – ECG for LED Modules

**350mA OPTOTRONIC® units for LED modules**

- Electronic control gear for 350mA LED modules
- Ideal for obtaining the optimum performance from LED modules

| Product ID Code | EAN (Single Pack) | Product Description    | No. | PPG   |
|-----------------|-------------------|------------------------|-----|-------|
| OT091024350DIM  | 4050300888897     | OT 9/10-24/350mA DIM   | 1   | 50 38 |
| OT9/120         | 4050300888835     | OT 9/100-120/350mA E   | 1   | 50 38 |
| OT9/350         | 4050300888262     | OT 9/200-240/350mA     | 1   | 50 38 |
| OT09350DIM      | 4008321187321     | OT 9/200-240/350mA DIM | 2   | 20 38 |
| OT42            | 4008321421678     | OT 42/220-240/350 E    | 3   | 20 38 |


1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

**700mA OPTOTRONIC® units for LED modules**

- Electronic control gear for 700mA LED modules
- Ideal for obtaining the optimum performance from LED modules


| Product ID Code | EAN (Single Pack) | Product Description     | No. | PPG   |
|-----------------|-------------------|-------------------------|-----|-------|
| OT18DIM         | 4008321139320     | OT 18/200-240/700mA DIM | 1   | 20 38 |
| OT35            | 4008321169365     | OT 35/200-240/700mA     | 2   | 24 38 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



All orders must be multiples of sales pack

## Electronic Control Gear – ECG for LED Modules




### OPTOTRONIC® Dimmers

- Connect to secondary side of power supplies for dimming
- Dynamic control of LED
- Opens up new applications for LEDs

| Product ID Code | EAN (Single Pack) | Product Description                      | No. | PPG   |
|-----------------|-------------------|--|-----|-------|
| OTDIM           | 4050300943459     | OT DIM 1...10V (10V & 24V modules)       | 1   | 20 38 |
| OTRGBDIM        | 4050300793108     | OT RGB 3-Channel DIM (10V & 24V modules) | 1   | 20 38 |
| OTRGB           | 4050300792460     | OT RGB Sequencer (10V & 24V modules)     | 1   | 20 38 |
| OTDMXRGB1024DIM | 4008321160829     | OT RGB DMX DIM                           | 1   | 20 38 |
| OTDMX3X1RGMDIM  | 4008321279835     | OT RGB DMX DIM 3 X 1                     | 2   | 10 38 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



### OPTOTRONIC® Units with DALI interfaces

- DALI control via DALI Interface
- Integrated Touch DIM function for QTi DALI 75 and QTi DALI DIM
- 3 DIM version ideal for STREETlight Advance and STREETlight Protect modules

| Product ID Code | EAN (Single Pack) | Product Description                     | No. | PPG   |
|-----------------|-------------------|---|-----|-------|
| OTDALI75        | 4008321371560     | OTi DALI 75/220-240/24V 1-4             | -   | 10 38 |
| OTIDALIDIM      | 4008321061195     | OTi DALI DIM (10V & 24V modules)        | 1   | 20 38 |
| OT65243DIM      | 4008321964403     | OT 65 220-240/24 3 DIM E                | -   | 20 38 |
| OTDALI25        | 4050300829463     | OT DALI 25/220-240/24 RGB (24V modules) | 2   | 20 38 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

NEW

NEW

All orders must be multiples of sales pack


## Electronic Control Gear – ECG for LED Modules

**OPTOTRONIC® for PrevalED™**

- Electronic control gear for PrevalED™ LED modules and accessories

| Product ID Code                     | EAN (Single Pack) | Product Description                      |   |    |
|-------------------------------------|-------------------|--|---|----|
| OTP45HD<br><small>NEW</small>       | 4008321966117     | OTp 45/220-240/700 HD                    | 1 | 38 |
| OTP35HD<br><small>NEW</small>       | 4008321963413     | OTp DALI 35/220-240/700 HD               | 1 | 38 |
| OTP35HD<br><small>NEW</small>       | 4008321963420     | OTp 35/220-240/700 HD                    | 1 | 38 |
| OTP35<br><small>NEW</small>         | 4008321962218     | OTp 35/220-240/700                       | 1 | 38 |
| OTP15HD<br><small>NEW</small>       | 4008321962225     | OTp 15/220-240/700 HD                    | 1 | 38 |
| OTPCABLE<br><small>NEW</small>      | 4008321966131     | Cable, 40 cm                             | 1 | 38 |
| OTPCABLE80<br><small>NEW</small>    | 4008321590565     | Cable, 80 cm                             | 1 | 38 |
| OTPCABLECLAMP<br><small>NEW</small> | 4008321966155     | Cable clamp for OTp 45, OTp DALI, OTp 35 | 1 | 38 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)



All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS



# Light Management Systems

## Contents.

|                                    |     |
|------------------------------------|-----|
| <b>ENERGY SAVING</b>               |     |
| <b>Mains Switching Sensors</b>     |     |
| SOLAR                              | 270 |
| Switch RC                          | 270 |
| HIGH BAY motion sensor             | 271 |
| VISION motion sensor               | 271 |
| DUO daylight and presence detector | 272 |
| Wall Switch                        | 272 |
| OUTDOOR                            | 273 |
| <b>1-10V Sensors</b>               |     |
| DIM PICO                           | 274 |
| DIM MICO                           | 274 |
| DIM MULTI                          | 275 |
| <b>Touch DIM® System</b>           |     |
| Touch DIM® WCU                     | 277 |
| Touch DIM® RMC                     | 277 |
| Touch DIM® RC                      | 277 |
| Touch DIM® LS/PD LI                | 278 |
| Touch DIM® LS LI                   | 278 |
| <b>MULTIeco and MULTI 3</b>        |     |
| LS/PD MULTI 3                      | 280 |
| LS/PD MULTI 3 FL                   | 280 |
| LS/PD MULTI 3 B                    | 281 |
| LS/PD MULTI 3 CI                   | 281 |
| DALI MULTIEco                      | 281 |
| DIM MULTIeco                       | 282 |
| MULTIEco                           | 282 |
| DALI MULTI 3                       | 283 |
| DIM MULTI 3                        | 283 |
| <b>AMBIENCE</b>                    |     |
| <b>EASY COLOR control</b>          |     |
| EASY RMC                           | 285 |
| EASY Hybrid Remote                 | 285 |
| EASY Color Drive                   | 286 |
| EASY Touch Panel                   | 286 |
| EASY IR CI                         | 287 |
| EASY IR                            | 287 |
| EASY RC                            | 287 |
| EASY PB Coupler                    | 288 |
| EASY PC Kit                        | 288 |
| EASY SYS CP                        | 288 |
| OT EASY 60 II                      | 289 |
| <b>DALI EASY III</b>               | 289 |
| EASY DMX 16x4 SO                   | 289 |
| EASY DMX 32x4 SO                   | 290 |
| EASY DMX 64x4 SO                   | 290 |
| OT EASY 32                         | 290 |
| <b>OT DMX</b>                      |     |
| LED Dimmer OT DMX                  | 291 |
| <b>SCENES</b>                      |     |
| <b>DALI®/1-10V Manual dimmers</b>  |     |
| DALI MCU                           | 293 |
| DIM MCU                            | 293 |
| <b>DALI® BASIC System</b>          |     |
| DALI WCU 5 BASIC                   | 295 |
| DALI LS/PD BASIC                   | 295 |
| DALI LS/PD BASIC LI                | 295 |
| DALI RC BASIC SO                   | 296 |
| <b>DALI® PROFESSIONAL System</b>   |     |
| DALI PRO Touch Panel               | 298 |
| Glass touch 6                      | 298 |
| Glass touch 12                     | 299 |
| Glass touch 6 JW                   | 299 |
| E:BUS DALI Gateway                 | 299 |
| DALI PRO PB Coupler                | 300 |
| DALI PRO Sensor Coupler            | 300 |
| DALI PRO CONT-4                    | 301 |
| <b>COMPONENTS</b>                  |     |
| <b>Interfaces and amplifiers</b>   |     |
| DALI REPEATER LI                   | 303 |
| DALI REPEATER SO                   | 303 |
| DALI CON 1...10 LI                 | 304 |
| DALI CON 1...10 SO                 | 304 |
| DIM SA                             | 304 |
| LMS DMX CON DALI SO                | 305 |
| <b>Accessories</b>                 |     |
| Y-CONNECTOR                        | 306 |
| Y-CONNECTOR SCREW                  | 306 |
| Mounting Adapter                   | 306 |
| SENSOR KIT                         | 307 |
| ECO CI KIT                         | 307 |
| LMS CI BOX                         | 307 |

## Light Management Systems



### OSRAM – the perfect partner for LMS

Light management products from OSRAM provide the ideal basis for innovative tailor-made lighting concepts – from an individual luminaire to more complex systems. Due to OSRAM's many years of experience and in-depth technical know-how, our wide-ranging product portfolio meets the requirements of an impressive array of applications:

- Energy saving with daylight-dependent and presence-dependent lighting
- Atmospheric and dynamic RGB lighting
- Multifunctional management of lighting groups and lighting scenes

**This is possible through manual or remote control, with a high degree of flexibility.**

**OSRAM lighting management systems can be easily tailored to the specific requirements of the application:**

#### Energy saving



- Light management systems for daylight-dependent and presence-dependent lighting
- Light management systems with maintenance-free EnOcean radio technology
- Sensors for non-system-specific use

#### Ambience



- Light management systems for dynamic RGB lighting
- Light management systems for daylight simulation


#### Scenes



- Light management systems for multifunctional management of lighting groups and lighting scenes
- Simple manual dimming solutions




#### Components



- Non-system-specific components for expanding, connecting or installing light management products


1) Lighting systems which are entitled to receive a System+ Guarantee and are controlled or operated by components of Light Management Systems (LMS components), are also entitled to an additional 5-year guarantee on LMS components from OSRAM. For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

## LIGHT MANAGEMENT SYSTEMS – ENERGY SAVING



All orders must be multiples of sales pack


## LIGHT MANAGEMENT SYSTEMS – ENERGY SAVING Mains Switching Sensors



### SOLAR

- Daylight and presence sensor with transmitter combining EnOcean wireless technology
- Solar powered, wireless, maintenance free
- Energy saving potential up to 45%
- Range up to 30m (up to 5 walls) or 100m (no walls)
- Ideal for new installations or as a retrofit solution for existing lighting systems

| Product ID Code | EAN (Single Pack) | Product Description          |    | PPG |
|-----------------|-------------------|------------------------------|----|-----|
| SOLARSENSOR     | 4008321385628     | Daylight and presence sensor | 20 | 39  |




### Switch RC

- Radio receiver for OSRAM control elements
- Choice of 5 operating modes
- Up to 8 sensors and 8 wall mounted/ hand held transmitters can be trained on one Switch RC
- Up to 14 ECGs can be connected with adjustable switch off delay 1 to 20 mins

| Product ID Code  | EAN (Single Pack) | Product Description |    | PPG |
|------------------|-------------------|---------------------|----|-----|
| SWITCHRCRECEIVER | 4008321385642     | Radio receiver      | 20 | 39  |



All orders must be multiples of sales pack

Light Management Systems  
Energy Saving – Mains Switching Sensors**HIGH BAY motion sensor**

- Motion sensor for ceiling heights up to 13m
- Energy saving potential up to 45% (in combination with daylight sensor)
- Detection zone up to 18 metres
- Ideal for ceiling heights between 3m and 10m to detect motion of people or between 3m and 13m to detect vehicle movement

| Product ID Code | EAN (Single Pack) | Product Description    |    | PPG |
|-----------------|-------------------|------------------------|----|-----|
| HIGHBAYSENS     | 4008321410078     | High Bay motion sensor | 20 | 39  |

**VISION motion sensor**

- Motion sensor for large areas
- Adjustable switch-off delay 30sec to 20min


| Product ID Code | EAN (Single Pack) | Product Description      |    | PPG |
|-----------------|-------------------|--------------------------|----|-----|
| VISIONSENSOR    | 4008321957047     | VISION presence detector | 20 | 39  |



All orders must be multiples of sales pack

## Light Management Systems

### Energy Saving – Mains Switching Sensors



#### **DUO daylight and presence detector**

- Energy saving solution for non dimmable luminaires/systems
- Daylight and presence detection
- Ceiling mounting or direct luminaire integration
- Energy saving potential up to 45%
- Ideal for office, residential, hospitality, retail, shop and industrial applications

| Product ID Code | EAN (Single Pack) | Product Description                |    |    |
|-----------------|-------------------|------------------------------------|----|----|
| DUOSENSOR       | 4008321496355     | DUO daylight and presence detector | 20 | 39 |



#### **Wall Switch**

- Motion sensor for recess in wall
- Contactless light switch for installation in pattress boxes
- 180° horizontal or 70° vertical detection angle up to 8 metres
- Energy saving potential up to 45%
- Ideal for new installations or as a retrofit solution for existing lighting systems


| Product ID Code | EAN (Single Pack) | Product Description          |    |    |
|-----------------|-------------------|------------------------------|----|----|
| WALLSWITCH      | 4008321467386     | Wall switch (81 x 81 x 24mm) | 20 | 39 |
| -               | -*                | Wall box (71 x 71 x 33mm)    | 1  | 39 |

\*In preparation at time of print. For further information please contact OSRAM

**NEW**



All orders must be multiples of sales pack

Light Management Systems  
Energy Saving – Mains Switching Sensors**OUTDOOR**

- Daylight, presence and motion detectors for LMS applications
- Ideal for outdoor LMS installations – IP55 rated


| Product ID Code | EAN (Single Pack) | Product Description                    | PPG |    |
|-----------------|-------------------|--|-----|----|
| OUTDOOR         | 4008321957061     | OUTDOOR Daylight and Presence Detector | 1   | 39 |

NEW

All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – ENERGY SAVING


### 1-10V Sensors



#### DIM PICO

- Clip on sensor for T8 and T5 lamps
- Energy savings up to 30% by compensating for 50% of the incoming daylight
- 1-10V dimming output

| Product ID Code | EAN (Single Pack) | Product Description                                    |   |    |
|-----------------|-------------------|--|---|----|
| HFDIMPICO       | 4050300554457     | DIM PICO clip on mini light sensor for T8 and T5 tubes | 1 | 39 |



#### DIM MICO

- Clip on sensor for T8 and T5 lamps
- Energy savings up to 40% by compensating for 100% of the incoming daylight
- 1-10V dimming output

| Product ID Code | EAN (Single Pack) | Product Description                           |   |    |
|-----------------|-------------------|---|---|----|
| HFDIMMICO       | 4050300464411     | DIM MICO mini light sensor for strip lighting | 1 | 39 |



All orders must be multiples of sales pack


Light Management Systems  
Energy Saving – 1-10V Sensors**DIM MULTI**

- Daylight dependent control with switch off delay from 5min to 20min
- Energy savings up to 70% by compensating for 100% of the incoming daylight
- Light and motion sensing
- 1-10V dimming output

| Product ID Code | EAN (Single Pack) | Product Description                      |  |  |
|-----------------|-------------------|--|---|---|
| HFDIMMULTI      | 4050300554471     | DIM MULTI light sensor/presence detector | 1   | 39  |

All orders must be multiples of sales pack


## LIGHT MANAGEMENT SYSTEMS – ENERGY SAVING



All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – ENERGY SAVING


### Touch DIM® System



#### Touch DIM® WCU

- 2 Channel radio wall transmitter
- No battery required and can be used up to 30m from the receiver in a building


| Product ID Code | EAN (Single Pack) | Product Description       |    |    |
|-----------------|-------------------|---------------------------|----|----|
| TOUCHDIMWCU     | 4008321032737     | Touch DIM WCU wall switch | 25 | 39 |



#### Touch DIM® RMC

- 4 Channel radio hand held transmitter
- No battery required and can be used up to 30m from the receiver in a building

| Product ID Code | EAN (Single Pack) | Product Description                    |    |    |
|-----------------|-------------------|--|----|----|
| TOUCHDIMRMC     | 4008321183033     | Touch DIM 4-Channel manual transmitter | 20 | 39 |



#### Touch DIM® RC

- 2 Channel radio receiver module
- Up to 15 QTi DALI® ECGs or HTi® transformers can be connected per output

| Product ID Code | EAN (Single Pack) | Product Description          |    |    |
|-----------------|-------------------|------------------------------|----|----|
| TOUCHDIMRC      | 4008321031938     | Touch DIM RC receiver module | 20 | 39 |

All orders must be multiples of sales pack

**Light Management Systems**  
**Energy Saving – Touch DIM® System**



**Touch DIM® LS/PD LI**

- Light and presence detector for luminaire installation
- Up to 4 QTi DALI® ECGs or 4 HTi transformers or 4 OTi DALI® LED dimmers can be connected
- Can be used as a purely presence detector
- Fully automatic operation possible

| Product ID Code | EAN (Single Pack) | Product Description                        | PPG   |
|-----------------|-------------------|--|-------|
| TOUCHDIMLSPD    | 4008321023025     | Touch DIM LS/PD LI light and motion sensor | 25 39 |



**Touch DIM® LS LI**


- Light sensor for luminaire installation
- Up to 4 QTi DALI® ECGs or 4 HTi transformers or 4 OTi DALI® LED dimmers can be connected
- Daylight dependent control can be set by double clicking

| Product ID Code | EAN (Single Pack) | Product Description          | PPG   |
|-----------------|-------------------|------------------------------|-------|
| TOUCHDIMLSLI    | 4008321023087     | Touch DIM LS LI light sensor | 25 39 |





All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – ENERGY SAVING



All orders must be multiples of sales pack


## LIGHT MANAGEMENT SYSTEMS – ENERGY SAVING MULTIeco and MULTI 3



### LS/PD MULTI 3

- Light and presence detector
- For installation in luminaires

| Product ID Code | EAN (Single Pack) | Product Description                                  |    |    |
|-----------------|-------------------|--|----|----|
| LSPDMULTI3      | 4050300802138     | LS/PD MULTI 3 standard light sensor/ motion detector | 25 | 39 |



### LS/PD MULTI 3 FL



- Light and presence detector
- Low profile casing
- For installation in luminaires

| Product ID Code | EAN (Single Pack) | Product Description                           |    |    |
|-----------------|-------------------|---|----|----|
| LSPDMULTI3FL    | 4008321047342     | LS/PD MULTI 3 FL light sensor/motion detector | 25 | 39 |



All orders must be multiples of sales pack


Light Management Systems  
Energy Saving – MULTileco and MULTI 3



### LS/PD MULTI 3 B

- Light and presence detector with moveable sensor
- For installation in luminaires

| Product ID Code | EAN (Single Pack) | Product Description                                   |    |    |
|-----------------|-------------------|---|----|----|
| LSPDMULTI3B     | 4050300803081     | LS/PD MULTI 3 B movable light sensor/ motion detector | 25 | 39 |



### LS/PD MULTI 3 CI

- Light and presence detector with moveable sensor
- Surface mounting with Sensor kit

| Product ID Code | EAN (Single Pack) | Product Description                                    |    |    |
|-----------------|-------------------|--|----|----|
| LSPDMULTI3CI    | 4008321916648     | LS/PD MULTI 3 CL recessed/surface mount ceiling sensor | 10 | 39 |



### DALI® MULTileco

- Suitable for daylight dependent control with presence function
- Up to 2 sensors and up to 6 DALI® ECGs can be connected
- 14 different operating modes can be set via DIP switches
- Up to 3 controllers can be synchronised for central presence function

| Product ID Code | EAN (Single Pack) | Product Description                        |    |    |
|-----------------|-------------------|--|----|----|
| DALIMULTIECO    | 4008321371300     | DALI MULTileco 100-240V AC (50...60Hz) /DC | 25 | 39 |

All orders must be multiples of sales pack

## Light Management Systems Energy Saving – MULTIEco and MULTI 3



### DIM MULTIEco

- Suitable for daylight dependent switching control with presence function
- Up to 2 sensors and up to six 1...10V ECGs can be connected
- 14 different operating modes can be set via DIP switches
- Up to 3 controllers can be synchronised for central presence function

| Product ID Code | EAN (Single Pack) | Product Description                  |  |  |
|-----------------|-------------------|--------------------------------------|--|---|
| DIMMULTIECO     | 4008321507273     | DIM MULTIEco 100V AC (50...60Hz) /DC | 25   | 39  |



### MULTIEco

- Suitable for daylight dependent switching control with presence function
- Up to 2 sensors and up to 6 ECGs can be connected
- 8 different operating modes can be set via DIP switches
- Up to 3 controllers can be synchronised for central presence function

| Product ID Code | EAN (Single Pack) | Product Description                  |  |  |
|-----------------|-------------------|--------------------------------------|--|---|
| MULTIECO        | 4008321405302     | MULTIEco 100-240V AC (50...60Hz) /DC | 25   | 39  |



All orders must be multiples of sales pack

## Light Management Systems Energy Saving – MULTileco and MULTI 3



### DALI® MULTI 3

- Suitable for daylight dependent control with presence function
- Up to 4 sensors and up to 32 ECGs can be connected
- Choice of 10 different operating modes can be set

| Product ID Code | EAN (Single Pack) | Product Description            |    |    |
|-----------------|-------------------|--------------------------------|----|----|
| DALIMULTI3      | 4050300802084     | DALI MULTI 3 DALI control unit | 25 | 39 |




### DIM MULTI 3

- Suitable for daylight dependent control with presence function
- Up to 4 sensors and up to 32 ECGs can be connected
- Choice of 10 different operating modes from manual control to fully automatic

| Product ID Code | EAN (Single Pack) | Product Description              |    |    |
|-----------------|-------------------|----------------------------------|----|----|
| DIMMULTI3       | 4050300802107     | DIM MULTI 3 1...10V control unit | 25 | 39 |

All orders must be multiples of sales pack


## LIGHT MANAGEMENT SYSTEMS – AMBIENCE



All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – AMBIENCE


### EASY Color Control



#### EASY RMC

- Infra-red remote control
- Control up to 4 lighting scenes, 4 lighting groups and 1 sequence

| Product ID Code | EAN (Single Pack) | Product Description             |    |    |
|-----------------|-------------------|---------------------------------|----|----|
| DALIEASYRMC     | 4008321053152     | DALI EASY RMC IR remote control | 25 | 39 |




#### EASY Hybrid Remote

- Hybrid technology for digital infra-red and radio remote control
- Control up to 8 lighting scenes, 8 lighting groups and 4 sequences
- LCD display with ability to customise the backlight colour

| Product ID Code | EAN (Single Pack) | Product Description    |   |    |
|-----------------|-------------------|------------------------|---|----|
| HYBRIDREMOTE    | 4008321421739     | LMS EASY Hybrid Remote | 5 | 39 |

All orders must be multiples of sales pack

## Light Management Systems Ambience – EASY Color Control



### EASY Color Drive

- Dual technology for connection via 4 wire signal line or wireless connection via radio transmitter
- Control up to 8 lighting scenes, 8 lighting groups and 4 sequences
- LCD display with ability to customise the backlight colour

| Product ID Code | EAN (Single Pack) | Product Description  |   |    |
|-----------------|-------------------|----------------------|---|----|
| COLORDRIVE      | 4008321421777     | LMS EASY Color Drive | 5 | 39 |



### EASY Touch Panel

- 5.7" display, 640 x 480 pixels
- Control up to 64 lighting scenes, 16 lighting groups, 4 sequences and 4 switchable loads or 2 louvre blinds
- Up to 32 DALI® ECGs can be directly connected

| Product ID Code | EAN (Single Pack) | Product Description  |   |    |
|-----------------|-------------------|----------------------|---|----|
| –               | 4008321956989*    | LMS EASY Touch Panel | 1 | 40 |



\*In preparation at time of print. For further information please contact OSRAM

**NEW**



All orders must be multiples of sales pack



## Light Management Systems Ambience – EASY Color Control



### **EASY IR CI**

- Infra-red receiver
- Surface mounting with SENSOR KIT

| Product ID Code | EAN (Single Pack) | Product Description                     |    |    |
|-----------------|-------------------|---|----|----|
| EASYIR          | 4008321915573     | EASY IR sensor for ceiling installation | 10 | 39 |



### **EASY IR**

- Infra-red receiver
- For installation in luminaires

| Product ID Code | EAN (Single Pack) | Product Description                       |    |    |
|-----------------|-------------------|---|----|----|
| DALIEASYIR      | 4008321053138     | EASY IR sensor for luminaire installation | 25 | 39 |



### **EASY RC**

- Radio receiver for use with EASY Hybrid Remote and EASY Color Drive
- For installation in luminaires

| Product ID Code | EAN (Single Pack) | Product Description    |    |    |
|-----------------|-------------------|------------------------|----|----|
| EASYRC          | 4008321421753     | EASY RC Radio Receiver | 18 | 39 |



All orders must be multiples of sales pack

## Light Management Systems Ambience – EASY Color Control



### EASY PB Coupler

- Push button coupler
- 8 inputs for floating make contacts


| Product ID Code | EAN (Single Pack) | Product Description |   |    |
|-----------------|-------------------|---------------------|---|----|
| EASYPB          | 4008321915597     | EASY PB COUPLER     | 1 | 39 |



### EASY PC Kit

- Simple creation of scenes and sequences on a PC
- Load, save and duplicate system settings
- Requires Windows PC with USB port

| Product ID Code | EAN (Single Pack) | Product Description                             |   |    |
|-----------------|-------------------|---|---|----|
| EASYPC          | 4008321915599     | PC Software EASY Color Control with USB Adapter | 1 | 39 |




### EASY SYS CP

- Coupler for connecting EASY systems and expansion to 64 controllers possible

| Product ID Code | EAN (Single Pack) | Product Description  |    |    |
|-----------------|-------------------|--|----|----|
| EASYSYSCP       | 4008321320902     | EASY SYSTEM Coupler for extension of up to 64 EASY control units | 25 | 39 |

All orders must be multiples of sales pack


## Light Management Systems Ambience – EASY Color Control



### OT EASY 60 II

- 60W ECG and configurable LED control unit for static and dynamic lighting applications
- Lighting scenes can be retrieved as sequences or static scenes
- Configuration via software or remote control


| Product ID Code | EAN (Single Pack) | Product Description                        |    |    |
|-----------------|-------------------|--|----|----|
| OTEASY60        | 4008321187796     | OT EASY 60/220-240/24 RGB LED control Unit | 10 | 38 |



### DALI EASY III

- Up to 32 DALI® ECGs can be connected
- 4 DALI® outputs
- Lighting scenes can be retrieved as sequences or static scenes
- Configuration via software or remote control

| Product ID Code | EAN (Single Pack) | Product Description    |    |    |
|-----------------|-------------------|------------------------|----|----|
| DALIEASY        | 4008321053046     | DALI EASY control unit | 25 | 39 |




### EASY DMX 16x4 SO

- Suitable for control of luminaires via 2,3 or 4 DMX addresses
- Individual control of 64 DMX channels
- Up to 64 lighting scenes and 4 sequences can be programmed

| Product ID Code | EAN (Single Pack) | Product Description                         |   |    |
|-----------------|-------------------|---|---|----|
| EASYDMX16       | 4008321441522     | EASY DMX 16x4 SO 110 – 240 V; 0, 50 – 60 Hz | 6 | 39 |

All orders must be multiples of sales pack


## Light Management Systems Ambience – EASY Color Control



### EASY DMX 32x4 SO

- Suitable for control of luminaires via 2,3 or 4 DMX addresses
- Individual control of 128 DMX channels
- Up to 64 lighting scenes and 4 sequences can be programmed

| Product ID Code | EAN (Single Pack) | Product Description                         |   |    |
|-----------------|-------------------|---|---|----|
| EASYDMX32       | 4008321441546     | EASY DMX 32x4 SO 110 – 240 V; 0, 50 – 60 Hz | 6 | 39 |



### EASY DMX 64x4 SO

- Suitable for control of luminaires via 2,3 or 4 DMX addresses
- Individual control of 256 DMX channels
- Up to 64 lighting scenes and 4 sequences can be programmed

| Product ID Code | EAN (Single Pack) | Product Description                         |   |    |
|-----------------|-------------------|---|---|----|
| EASYDMX64       | 4008321441560     | EASY DMX 64x4 SO 110 – 240 V; 0, 50 – 60 Hz | 6 | 39 |



### OT EASY 32

- EASY control unit for high flux LED requiring 350mA supply
- 4 independent constant current LED output channels

| Product ID Code | EAN (Single Pack) | Product Description           |    |    |
|-----------------|-------------------|-------------------------------|----|----|
| OTEASY 32       | 4008321547088     | OT EASY 32 CC/120-240/350 4CH | 20 | 39 |

NEW

All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – AMBIENCE OT DMX




### LED Dimmer OT DMX

- 3 and 9 channel DMX dimmers for constant voltage LED modules
- DMX output for fast chaining of multiple devices

| Product ID Code | EAN (Single Pack) | Product Description   |  | PPG   |
|-----------------|-------------------|-----------------------|--|-------|
| OT2DMX3         | 4008321533265     | OT DMX 3x2.5A DIM     |  | 10 39 |
| OT2DMX3PCB      | 4008321533289     | OT DMX 3x2.5A PCB DIM |  | 10 39 |
| OT2DMX9         | 4008321533302     | OT DMX 9x2A DIM SO    |  | 10 39 |



All orders must be multiples of sales pack

**LIGHT MANAGEMENT SYSTEMS – SCENES**

All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – SCENES



### DALI®/1-10V Manual dimmers



#### DALI MCU

- Up to 25 ECGs can be directly connected
- 4 DALI® MCUs can be connected in parallel – Up to 100 DALI® ECG

| Product ID Code | EAN (Single Pack) | Product Description            |    |    |
|-----------------|-------------------|--------------------------------|----|----|
| DALIMCU         | 4008321189721     | DALI MCU Digital potentiometer | 15 | 39 |




#### DIM MCU

- Up to 100 ECGs can be directly connected

| Product ID Code | EAN (Single Pack) | Product Description                            |   |    |
|-----------------|-------------------|--|---|----|
| HFDIMMCUP       | 4050300347424     | DIM MCU P manual control unit with cover plate | 1 | 39 |


All orders must be multiples of sales pack

**LIGHT MANAGEMENT SYSTEMS – SCENES**

All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – SCENES

### DALI® BASIC System



#### DALI® WCU 5 BASIC

- 5 Floating make contacts


| Product ID Code | EAN (Single Pack) | Product Description                                 |    |    |
|-----------------|-------------------|---|----|----|
| DALIWCU5        | 4050300771106     | DALI WCU 5 BASIC W white 5 push button switch array | 50 | 39 |



#### DALI® LS/PD BASIC

- Light and presence detector

| Product ID Code | EAN (Single Pack) | Product Description   |    |    |
|-----------------|-------------------|---|----|----|
| DALILSPD        | 4050300639949     | DALI LS/PD BASIC light sensor/ presence detector for surface mounting | 50 | 39 |




#### DALI® LS/PD BASIC LI

- Light and presence detector

| Product ID Code | EAN (Single Pack) | Product Description   |    |    |
|-----------------|-------------------|---|----|----|
| DALILSPDLI      | 4050300850184     | DALI LS/PD BASIC light sensor/ presence detector for luminaire installation | 20 | 39 |

All orders must be multiples of sales pack

## Light Management Systems SCENES – DALI® BASIC System



### DALI® RC BASIC SO


- Up to 64 ECGs can be directly connected
- Control up to 4 lighting scenes, 4 assignable scenes and 3 inputs for 3 light or presence sensors

| Product ID Code | EAN (Single Pack) | Product Description                                   |  |       |
|-----------------|-------------------|---|--|-------|
| DALIRC          | 4050300654973     | DALI RC BASIC SO snap on room controller for DIN rail |  | 18 39 |



All orders must be multiples of sales pack


## LIGHT MANAGEMENT SYSTEMS – SCENES



All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – SCENES

### DALI® PROFESSIONAL System




#### DALI® PRO Touch Panel

- 5.7" high resolution LCD screen
- All luminaires in system can be switched or dimmed
- Backgrounds, logos, keys can be inserted

| Product ID Code | EAN (Single Pack) | Product Description  |   |    |
|-----------------|-------------------|----------------------|---|----|
| -               | 4008321957092     | DALI Pro Touch Panel | 1 | 39 |

\*In preparation at time of print. For further information please contact OSRAM

NEW



#### Glass touch 6

- DALI Pro user interface for lighting management
- 6 Touch sensitive buttons on unit behind smooth glass

| Product ID Code | EAN (Single Pack) | Product Description |   |    |
|-----------------|-------------------|---------------------|---|----|
| GTOUCH6T        | 4008321957108     | Glass Touch 6       | 4 | 39 |

NEW



All orders must be multiples of sales pack

Light Management Systems  
SCENES – DALI® PROFESSIONAL System




### Glass touch 12

- DALI Pro user interface for lighting management
- 12 Touch sensitive buttons on unit behind smooth glass

| Product ID Code | EAN (Single Pack) | Product Description |   |    |
|-----------------|-------------------|---------------------|---|----|
| GTOUCH12T       | 4008321957115     | Glass Touch 12      | 4 | 39 |

NEW




### Glass touch 6 JW

- DALI Pro user interface for lighting management
- 6 Touch sensitive buttons and touch wheel unit behind smooth glass

| Product ID Code | EAN (Single Pack) | Product Description |   |    |
|-----------------|-------------------|---------------------|---|----|
| GTOUCH6TR       | 4008321957054     | Glass Touch 6 JW    | 4 | 39 |

NEW



### E:BUS DALI® Gateway

- DIN Rail gateway to communicate between DALI® Pro CONT-4 and e:bus interfaces


| Product ID Code | EAN (Single Pack) | Product Description                                       |   |    |
|-----------------|-------------------|---|---|----|
| DALIGATEWAY     | 4008321957085     | e:bus <-> DALI Gateway                                    | 8 | 39 |
| DALIGATEWAY     | 4008321555311     | PS30/100-240/24SO power supply for e:bus <-> DALI Gateway | 8 | 39 |

NEW



All orders must be multiples of sales pack


## Light Management Systems SCENES – DALI® PROFESSIONAL System



### DALI® PRO PB Coupler

- Suitable for integrating push buttons for switching, dimming for scene setting
- Switching and dimming of up to 256 DALI® ECGS
- Up to 4 existing push buttons can be integrated

| Product ID Code | EAN (Single Pack) | Product Description         |   |    |
|-----------------|-------------------|-----------------------------|---|----|
| DALIPROFPUSHB   | 4008321496461     | DALI PROFESSIONAL PBcoupler | 4 | 39 |




### DALI® PRO Sensor Coupler

- Suitable for lighting control with light and presence sensors
- Light sensor and presence sensor from the MULTI 3 range can be used

| Product ID Code | EAN (Single Pack) | Product Description             |    |    |
|-----------------|-------------------|---------------------------------|----|----|
| DALIPROFSENS    | 4008321379269     | DALI PROFESSIONAL Sensorcoupler | 25 | 39 |



All orders must be multiples of sales pack

Light Management Systems  
SCENES – DALI® PROFESSIONAL System**DALI® PRO CONT-4**

- Suitable for room control and daylight dependent control
- Intelligent module for controlling up to 256 ECGs
- 4 programmable switchover relays

| Product ID Code | EAN (Single Pack) | Product Description             | PPG  |
|-----------------|-------------------|---------------------------------|------|
| DALIPROCON4     | 4008321478948     | DALI PROFESSIONAL CONTROLLER -4 | 4 39 |
| -               | -*                | DALI PROFESSIONAL RF coupler    | - 39 |
| DALISWITCH      | 4008321533364     | DALI Switch                     | 8 39 |

\*In preparation at time of print. For further information please contact OSRAM


All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – COMPONENTS

### COMPONENTS



LMS CI BOX



ECO CI KIT



SENSOR KIT



MOUNTING ADAPTER



Y-CONNECTOR SCREW



Y-CONNECTOR



DIM SA



DALI® CON 1...10 SO



DALI® CON 1...10 LI



DALI® REPEATER SO



DALI® REPEATER LI

All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – COMPONENTS


### Interfaces and amplifiers



#### DALI® REPEATER LI

- Addressable signal amplifier for the extension of DALI® and Touch DIM® light control systems
- To control up to 64 DALI® ECG as one group
- Allows expansion of DALI® systems with more than 64 ECG per DALI® Line

| Product ID Code | EAN (Single Pack) | Product Description                  |    |    |
|-----------------|-------------------|--------------------------------------|----|----|
| DALIREPLI       | 4008321292599     | DALI REPEATER LI Long 100-240V AC DC | 25 | 39 |



#### DALI® REPEATER SO

- Addressable signal amplifier for the extension of DALI® and Touch DIM® light control systems
- Integrated load contact for disconnecting the ECG supply in standby (Greenswitch)
- Touch DIM® control of 64 DALI® ECGs

| Product ID Code | EAN (Single Pack) | Product Description                    |    |    |
|-----------------|-------------------|--|----|----|
| DALIREPSO       | 4008321301093     | DALI REPEATER SO Square 100-240V AC DC | 25 | 39 |

All orders must be multiples of sales pack

## Light Management Systems


### COMPONENTS – Interfaces and amplifiers



#### DALI® CON 1...10 LI

- Touch DIM® or DALI® control of 1-10V ECGs
- For luminaire installation

| Product ID Code | EAN (Single Pack) | Product Description                                      |    | PPG |
|-----------------|-------------------|--|----|-----|
| DALICONLI       | 4050300638973     | DALI CON 1...10V LI converter for luminaire installation | 40 | 39  |



#### DALI® CON 1...10 SO

- Touch DIM® or DALI® control of 1-10V ECGs
- For series installation

| Product ID Code | EAN (Single Pack) | Product Description                   |    | PPG |
|-----------------|-------------------|---------------------------------------|----|-----|
| DALICONSO       | 4050300639802     | DALI CON 1...10V SO snap on converter | 16 | 39  |



#### DIM SA

- Amplifies 1-10V control signals to operate larger numbers of ECG (up to 100 per unit)

| Product ID Code | EAN (Single Pack) | Product Description     |   | PPG |
|-----------------|-------------------|-------------------------|---|-----|
| HFDIMSA         | 4008321097095     | DIM SA signal amplifier | 1 | 39  |

All orders must be multiples of sales pack

Light Management Systems  
COMPONENTS – Interfaces and amplifiers**LMS DMX CON DALI® SO**

- Convert DMX signal into DALI®
- 6 DALI® outputs with up to 16 DALI® ballasts per output
- Manual and auto DMX addressing modes
- Automatic amplification of DMX out signal


| Product ID Code | EAN (Single Pack) | Product Description     | PPG   |
|-----------------|-------------------|-------------------------|-------|
| CONDMX          | 4008321532336     | DMX CON/100-240 DALI SO | 10 39 |

NEW!

All orders must be multiples of sales pack

## LIGHT MANAGEMENT SYSTEMS – COMPONENTS

### Accessories



#### Y-CONNECTOR

- Connections: 3 x modular 4p4c- socket
- 2 connecting cables included, modular 4p4c- connector on both ends, 2m long


| Product ID Code | EAN (Single Pack) | Product Description |    |    |
|-----------------|-------------------|---------------------|----|----|
| YCONNECTMULTI3  | 4050300803135     | Y-CONNECTOR MULTI 3 | 25 | 39 |



#### Y-CONNECTOR SCREW

- Connections: 2 x four pin screw terminal and 2 x 4p4c- socket
- 2 connecting cables included, modular 4p4c- connector on both ends, 2m long

| Product ID Code | EAN (Single Pack) | Product Description              |    |    |
|-----------------|-------------------|----------------------------------|----|----|
| YCON            | 4008321916686     | Y-CONNECTOR with screw terminals | 25 | 39 |




#### Mounting Adapter

- Adapter for surface mounting of sensor elements with a diameter 115.6mm

| Product ID Code | EAN (Single Pack) | Product Description |    |    |
|-----------------|-------------------|---------------------|----|----|
| MOUNTADAPTER    | 4008321480798     | Mounting Adapter    | 20 | 39 |

All orders must be multiples of sales pack


## Light Management Systems COMPONENTS – Accessories



### SENSOR KIT

- Adapter for surface mounting of sensor elements with a diameter of 50 mm

| Product ID Code | EAN (Single Pack) | Product Description                           |    |    |
|-----------------|-------------------|---|----|----|
| SENSORKIT       | 4008321916662     | Adapter for surface mounting of LS/PD MULTI 3 | 10 | 39 |



### ECO CI KIT

- Can be used for separate mounting of all OSRAM controllers with dimensions of (l)118mm x (w)30mm x (h)21 mm

| Product ID Code | EAN (Single Pack) | Product Description |   |    |
|-----------------|-------------------|---------------------|---|----|
| ECOCITKIT       | 4008321392091     | ECO CI KIT          | 1 | 39 |



### LMS CI BOX


- Can be used for separate mounting of all OSRAM controllers with dimensions of (l)189mm x (w)30mm x (h)21 mm

| Product ID Code | EAN (Single Pack) | Product Description         |    |    |
|-----------------|-------------------|-----------------------------|----|----|
| LMSCIBOX        | 4008321083692     | LMS CI BOX installation kit | 40 | 39 |



All orders must be multiples of sales pack

## LUMINAIRES



# Luminaires

## Contents.

### INDOOR LUMINAIRES

#### MODULAR SYSTEMS

|         |     |
|---------|-----|
| RFI E   | 311 |
| PASS II | 312 |

#### SURFACE MOUNTED LUMINAIRES

|                           |     |
|---------------------------|-----|
| LUMILUX® DUO® T5 F/P      | 313 |
| LUMILUX® DUO® T5 F/R      | 313 |
| OSRAM SOFTLITE® EL        | 314 |
| Pendant kit               | 314 |
| LUMILUX® FLATLITE® T5 F/P | 315 |
| DIADEM®                   | 315 |
| LUMILUX® DUO®EL F/P       | 316 |
| LUMILUX® DUO®EL F/R       | 316 |
| SCRIPTUS                  | 317 |
| OSRAM DULUX® RONDEL       | 317 |
| OSRAM DULUX® CARRE        | 318 |

#### BATTEN LUMINAIRES

|                       |     |
|-----------------------|-----|
| OSRAM ECOPACK®T5 DALI | 319 |
| OSRAM ECOPACK®T5 DIM  | 319 |
| OSRAM ECOPACK®FH DIM  | 320 |
| OSRAM ECOPACK® T5     | 320 |
| OSRAM ECOPACK® Louvre | 321 |
| OSRAM ECOPACK® FQ     | 321 |
| OSRAM ECOPACK® FH     | 322 |
| OSRAM MINIS ECO       | 323 |
| LUMILUX® COMBI EL     | 324 |
| LUMILUX® DECO EL      | 325 |
| OSRAM ECOPACK® DIM    | 325 |
| OSRAM ECOPACK®        | 326 |
| LUMILUX® COMBI EL-N   | 326 |
| LUMILUX® COMBI EL-F   | 327 |
| LUMILUX® COMBI EL-N/P | 328 |
| LUMILUX® COMBI EL-F/P | 328 |
| LUMILUX® COMBI EL-F/D | 329 |
| LUMILUX® COMBI EL-F/B | 329 |
| LUMILUX® COMBI EL-N   | 330 |
| LUMILUX® VARIO EL-F   | 330 |

#### FURNITURE LUMINAIRES

|                        |     |
|------------------------|-----|
| DRAGONPOINT® VARIO KIT | 331 |
| DRAGONPOINT® FIX KIT   | 332 |
| DRAGONPOINT® MOOD KIT  | 332 |
| DRAGONSPOT®            | 333 |
| LEDVANCE™ DOWNLIGHT S  | 334 |
| LEDVANCE™ Polybar      | 335 |
| LUMINESTRA® LED        | 336 |
| LUMINESTRA® EL         | 336 |
| SLIMLITE® EL           | 337 |
| PICOLINE® EL           | 337 |
| LUMILUX® VARIO FM      | 338 |

#### RECESSED LUMINAIRES

|                                  |     |
|----------------------------------|-----|
| LEDVANCE® Downlight M            | 339 |
| LEDVANCE® Downlight L            | 340 |
| LEDVANCE® Downlight XL           | 341 |
| KIT LED PRO                      | 342 |
| DLWNLIGHT KIT HCI® R111          | 343 |
| KIT DLWNLIGHT HQI®-TS EXCELLENCE | 344 |
| DLWNLIGHT KIT HALOSPOT® R111 ECO | 345 |
| KIT HALO ECO                     | 346 |
| KIT HALO PRO                     | 346 |
| KIT HALO PRO HYDRO               | 347 |
| JADE KTI ECO HF                  | 347 |
| OSRAM DEDRA plus® T5 KIT         | 348 |
| OSRAM DEDRA plus® T8 KIT         | 349 |
| DELTA                            | 350 |

#### DAMP PROOF LUMINAIRES

|                        |     |
|------------------------|-----|
| ORCA PLUS for T5       | 351 |
| ORCA PLUS for T8       | 352 |
| NEPTUNE® POLYCARBONATE | 353 |
| IGLOO II               | 353 |
| AQUALINE™ T5           | 354 |



## CONTENTS

### OUTDOOR LUMINAIRES

#### RECESSED LUMINAIRES

|                         |     |
|-------------------------|-----|
| AQUALED®                | 355 |
| AQUALED DRAGON®         | 356 |
| NAUTILUS® MIDI DR51 INC | 356 |
| NAUTILUS® MINI HAL      | 357 |

#### SURFACE MOUNTED LUMINAIRES

|                      |     |
|----------------------|-----|
| LUMILUX BRIK® EL     | 358 |
| OSRAM DULUX BRIK® EL | 358 |

### CONSUMER LUMINAIRES

#### FLASHLIGHTS

|                          |     |
|--------------------------|-----|
| SIRIUS Torch Range       | 359 |
| CROSSER Torch Range      | 359 |
| LED Clip on Lights       | 360 |
| LED MULTIFUNCTIONAL      | 360 |
| LED SAVER LIGHT          | 361 |
| LED HEADLAMP             | 361 |
| CAMPING LED              | 362 |
| CAMPING ENERGY AUTOMATIC | 362 |
| CAMPING HALOGEN DIM SI   | 363 |

#### NIGHT LIGHTS

|           |     |
|-----------|-----|
| SPYLUX™   | 364 |
| NIGHTLUX™ | 364 |

#### FUNCTIONAL DESIGN


|             |     |
|-------------|-----|
| LEDstixx™   | 365 |
| POWERstixx™ | 365 |
| QOD         | 366 |

#### PORTABLE LED LUMINAIRES

|                      |     |
|----------------------|-----|
| DOT-it® CLASSIC      | 367 |
| DOT-it® VARIO        | 368 |
| DOT-it® LINEAR VARIO | 368 |
| DOT-it® waterproof   | 369 |

**INDOOR****MODULAR SYSTEMS**

850 °C IK02 50-60 Hz  $\eta_{LB}$  0.78 G13 230V



Base light  
Energy saving  
Larger lumens

**RFI E**

- Ready to install thin low profile aluminium reflector
- Equipped with QTIS-E electronic control gear, suitable for LUMILUX® T8 58W tubes
- Ideal for high ceilings, cove lighting industrial and commercial settings

| Product ID Code                        | EAN (Single Pack) | Product Description       | FINISH | W    | $\frac{l}{[mm]}$ | $\frac{b}{[mm]}$ | $\frac{h}{[mm]}$ | PPG      |
|--|-------------------|---------------------------|--------|------|------------------|------------------|------------------|----------|
| <b>RFI E – Electronic Control Gear</b> |                   |                           |        |      |                  |                  |                  |          |
| SCHUTZGITTER258                        | 4050300117690     | RFI E 2 x 58W HE          | White  | 2x58 | 1523             | 207              | 94               | 1 38     |
| <b>RFI E – Accessories</b>             |                   |                           |        |      |                  |                  |                  |          |
| SCHUTZGITTER258                        | 4050300117690     | RFI E Louvre grid 2 x 58W | White  | –    | –                | –                | –                | 2 38     |
| GRILGYMNO58                            | 4050300820170     | RFI E grid 2 x 58W        | White  | –    | –                | –                | –                | 1 38     |
| 7NCTIONS2XRFE                          | 4008321083456     | RFI E connection element  | White  | –    | –                | –                | –                | 25 x2 38 |
| FLAQUES2RFE                            | 4008321083449     | RFI E end caps            | White  | –    | –                | –                | –                | 25 x2 38 |



Louvre grid



Grid



Connection element



End caps



All orders must be multiples of sales pack

## Indoor – Modular Systems

**PASS II**

- Prewired strip light with bracket and guide rail for ceiling or pendant mounting
- Equipped with QTIS-E electronic control gear, suitable for LUMILUX® T8 58W tubes
- Ideal for general illumination and route lighting in industrial and commercial settings

| Product ID Code              | EAN (Single Pack) | Product Description               | FINISH | W    | I [mm] | b [mm] | h [mm] | PPG      |
|------------------------------|-------------------|-----------------------------------|--------|------|--------|--------|--------|----------|
| <b>PASS II</b>               |                   |                                   |        |      |        |        |        |          |
| PASSIIHFGB1                  | 4050300910444     | PASS II 153 1 x 58W HE            | White  | 58   | 1530   | 140    | 60     | 1 38     |
| PASTICHE                     | 4050300910420     | PASS II 153 2 x 58W HE            | White  | 2x58 | 1530   | 140    | 60     | 1 38     |
| PASSIIHFGB2                  | 4050300910468     | PASS II 306 2 x 58W HE            | White  | 2x58 | 3060   | 140    | 60     | 1 38     |
| PASSIVITY                    | 4050300909455     | PASS II 306 4 x 58W HE            | White  | 4x58 | 3060   | 140    | 60     | 1 38     |
| <b>PASS II – Accessories</b> |                   |                                   |        |      |        |        |        |          |
| PASSIETRIER                  | 4050300909264     | Bracket for additional suspension | -      | -    | -      | -      | -      | 72 38    |
| PASSI2CAPS                   | 4008321188434     | END caps (supplied in pairs)      | -      | -    | -      | -      | -      | 18 x2 38 |
| BRANCARDPASS                 | 4008321302816     | Connector for cross mounting      | -      | -    | -      | -      | -      | 48 x2 38 |
| PASSICOUVERCLE               | 4050300772844     | Zinc-plated end sheet 153         | -      | -    | -      | -      | -      | 10 38    |



Bracket for additional suspension



End caps




Connector for cross mounting



All orders must be multiples of sales pack

**INDOOR****SURFACE MOUNTED LUMINAIRES**

|  |  |  |          |         |  |     |                  |    |
|--|--|--|----------|---------|--|-----|------------------|----|
|  |  |  | 230–240V | 50–60Hz |  | 840 | $\eta_{LB}$ 0.75 | G5 |
|--|--|--|----------|---------|--|-----|------------------|----|



Quick start  
Pleasant feel  
Energy saving  
Longer lifetime


**LUMILUX® DUO® T5 F/P**

- Twin T5 low profile electronic batten with LUMILUX® T5 HE/840 tubes for fixed connection
- Prismatic cover
- High quality casing made from anodised aluminium
- Ideal for strip lighting when used in conjunction with OSRAM ECOPACK® Pendant/suspension kit

| Product ID Code | EAN (Single Pack) | Product Description     | FINISH | W    | I [mm] | b [mm] | h [mm] | PPG |    |
|-----------------|-------------------|-------------------------|--------|------|--------|--------|--------|-----|----|
| 72098           | 4008321908797     | LUMILUX DUO T5 F/P 2x14 | Silver | 2x14 | 594    | 110    | 42     | 2   | 38 |
| 72099           | 4008321908803     | LUMILUX DUO T5 F/P 2x21 | Silver | 2x21 | 894    | 110    | 42     | 2   | 38 |
| 72100           | 4008321908810     | LUMILUX DUO T5 F/P 2x28 | Silver | 2x28 | 1194   | 110    | 42     | 2   | 38 |



|  |  |  |          |         |  |     |                  |    |
|--|--|--|----------|---------|--|-----|------------------|----|
|  |  |  | 230–240V | 50–60Hz |  | 840 | $\eta_{LB}$ 0.47 | G5 |
|--|--|--|----------|---------|--|-----|------------------|----|



Quick start  
Pleasant feel  
Energy saving  
Longer lifetime

**LUMILUX® DUO® T5 F/R**

- Twin T5 low profile electronic batten with LUMILUX® T5 HE/840 tubes for fixed connection
- Aluminium louvre and highly polished reflector
- High quality casing made from anodised aluminium
- Ideal for strip lighting when used in conjunction with OSRAM ECOPACK® Pendant/suspension kit

| Product ID Code | EAN (Single Pack) | Product Description    | FINISH | W    | I [mm] | b [mm] | h [mm] | PPG |    |
|-----------------|-------------------|------------------------|--------|------|--------|--------|--------|-----|----|
| 72102           | 4008321908827     | OSRAM DUO T5 F/R 2x14W | Silver | 2x14 | 594    | 110    | 50     | 2   | 38 |
| 72103           | 4008321908834     | OSRAM DUO T5 F/R 2x21W | Silver | 2x21 | 894    | 110    | 50     | 2   | 38 |
| 72104           | 4008321908841     | OSRAM DUO T5 F/R 2x28W | Silver | 2x28 | 1194   | 110    | 50     | 2   | 38 |


All orders must be multiples of sales pack



## Indoor – Surface Mounted Luminaires



|           |  |  |  |  |        |      |          |          |                  |    |     |
|-----------|--|--|--|--|--------|------|----------|----------|------------------|----|-----|
| <b>CE</b> |  |  |  |  | 850 °C | IK06 | 230–240V | 50–60 Hz |                  | ✓  | 840 |
|           |  |  |  |  |        |      |          |          | $\eta_{LB}$ 0.49 | G5 |     |




**electronic comfort light**

**OSRAM SOFTLITE® EL**

- T5 electronic batten with LUMILUX® T5 HO/ 840 tubes for fixed connection
- Perforated cover for glare free direct/indirect lighting
- QUICKTRONIC® QTP5 electronic control gear
- OSRAM ECOPACK® Pendant/suspension kit available which includes 2 x fixings, adjustable cable holders, steel cable for pendant lengths up to 2m and cable clamps.

| Product ID Code | EAN (Single Pack) | Product Description   | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG |    |
|-----------------|-------------------|-----------------------|--------|----|--------|--------|--------|-----|----|
| 72535W          | 4050300535630     | OSRAM SOFTLITE EL 24W | White  | 24 | 610    | 155    | 82     | 2   | 38 |
| 72536W          | 4050300535654     | OSRAM SOFTLITE EL 39W | White  | 39 | 910    | 155    | 82     | 2   | 38 |
| 72537W          | 4050300535678     | OSRAM SOFTLITE EL 54W | White  | 54 | 1210   | 155    | 82     | 2   | 38 |
| 72538W          | 4050300535692     | OSRAM SOFTLITE EL 80W | White  | 80 | 1510   | 155    | 82     | 2   | 38 |

**Pendant kit for LUMILUX® DUO® T5, OSRAM SOFTLITE® and ECOPACK®**


- Kit includes: 2 x fixings, adjustable cable holders, steel cable for pendant lengths up to 2m and cable clamps

| Product ID Code | EAN (Single Pack) | Product Description | FINISH | I [mm] | PPG  |
|-----------------|-------------------|---------------------|--------|--------|------|
| 72097           | 4050300792200     | Pendant Kit         | Silver | 2000   | 4 38 |




All orders must be multiples of sales pack

## Indoor – Surface Mounted Luminaires

**LUMILUX® FLATLITE® T5 F/P**

- Compact low profile through wired T5 luminaire with high luminous efficacy
- Prismatic cover for glare free light
- Includes LUMILUX® T5 830 HO and integrated QTP5 electronic control gear
- Ideal for general lighting or strip lighting with the appropriate accessory (double cap)

| Product ID Code | EAN (Single Pack) | Product Description                                   | FINISH | W  | I [mm] | b [mm] | h [mm] | Light No. | PPG |    |
|-----------------|-------------------|---|--------|----|--------|--------|--------|-----------|-----|----|
| 72491           | 4008321908537     | LUMILUX FLATLITE T5 F/P 24W 830                       | White  | 24 | 608    | 105    | 41     | 1         | 4   | 38 |
| 72492           | 4008321908544     | LUMILUX FLATLITE T5 F/P 39W 830                       | White  | 39 | 908    | 105    | 41     | 1         | 4   | 38 |
| 72493           | 4008321908551     | LUMILUX FLATLITE T5 F/P 54W 830                       | White  | 54 | 1208   | 105    | 41     | 1         | 4   | 38 |
| 72494           | 4008321908568     | LUMILUX FLATLITE T5 F/P 49W 830                       | White  | 49 | 1508   | 105    | 41     | 1         | 4   | 38 |
| 7249155         | 4008321917355     | Double Cap for strip lighting LUMILUX FLATLITE T5 F/P | White  | –  | 118    | 105    | 38     | 2         | 4   | 38 |

**DIADEM®**

- Attractive economical ceiling mounted luminaire with retaining cable for simple relamping
- Symmetrical V reflector in polished aluminium or white finishes
- Integrated QT-FIT8 or QT-FH 4x14W control gear, suitable for LUMILUX® T8 or T5 tubes
- Ideal for office, conference and amenity lighting


| Product ID Code | EAN (Single Pack) | Product Description | FINISH    | W  | I [mm] | b [mm] | h [mm] | PPG |    |
|-----------------|-------------------|---------------------|-----------|----|--------|--------|--------|-----|----|
| DIADEM2X36VB    | 4008321413390     | DIADEM 2 x 36W      | White     | 36 | 1265   | 210    | 80     | 1   | 38 |
| DIADEM2X36WT    | 4008321413406     | DIADEM 2 x 36W      | Aluminium | 36 | 1265   | 210    | 80     | 1   | 38 |
| DIADEM2X58VB    | 4008321413413     | DIADEM 2 x 58W      | White     | 58 | 1565   | 210    | 80     | 1   | 38 |
| DIADEM2X58WT    | 4008321413420     | DIADEM 2 x 58W      | Aluminium | 58 | 1565   | 210    | 80     | 1   | 38 |
| –               | 4008321926348*    | DIADEM 4 x 18W      | White     | 18 | 660    | 610    | 80     | 1   | 38 |
| DIADEM4X18VA    | 4008321962355     | DIADEM 4 x 18W      | Aluminium | 18 | 660    | 610    | 80     | 1   | 38 |
| –               | 4008321926324*    | DIADEM 4 x 14W VBAS | White     | 14 | 660    | 610    | 80     | 1   | 38 |
| DIADEM158       | 4008321962331     | DIADEM 4 x 58W ASM  | White     | 58 | 1565   | 210    | 80     | 1   | 38 |

\*In preparation at time of print. For further information please contact OSRAM

All orders must be multiples of sales pack




## Indoor – Surface Mounted Luminaires

**LUMILUX® DUO® EL F/P**

- Extremely low profile twin T8 electronic batten luminaire with LUMILUX® T8 830 tubes for fixed connection
- Prismatic cover for uniform light
- High quality casing made from anodised aluminium
- Integrated QTP electronic control gear
- Ideal for applications that require high lighting levels

| Product ID Code | EAN (Single Pack) | Product Description    | FINISH | W      | I<br>[mm] | b<br>[mm] | h<br>[mm] | PPG  |
|-----------------|-------------------|------------------------|--------|--------|-----------|-----------|-----------|------|
| 72085           | 4050300774206     | OSRAM DUO EL F/P 2x18W | Silver | 2 x 18 | 626       | 140       | 45        | 4 38 |
| 72086           | 4050300774237     | OSRAM DUO EL F/P 2x36W | Silver | 2 x 36 | 1235      | 140       | 45        | 4 38 |
| 72087           | 4050300774268     | OSRAM DUO EL F/P 2x58W | Silver | 2 x 58 | 1535      | 140       | 45        | 4 38 |

**LUMILUX® DUO® EL F/R**

- Extremely low profile twin T8 electronic batten luminaire with LUMILUX® T8 830 tubes for fixed connection
- Aluminium louvre and highly polished reflector
- High quality casing made from anodised aluminium
- Integrated QTP electronic control gear
- Ideal for applications that require high lighting levels

| Product ID Code | EAN (Single Pack) | Product Description    | FINISH | W      | I<br>[mm] | b<br>[mm] | h<br>[mm] | PPG  |
|-----------------|-------------------|------------------------|--------|--------|-----------|-----------|-----------|------|
| 72088           | 4050300774299     | OSRAM DUO EL F/R 2x18W | Silver | 2 x 18 | 626       | 140       | 50        | 4 38 |
| 72089           | 4050300774329     | OSRAM DUO EL F/R 2x36W | Silver | 2 x 36 | 1235      | 140       | 50        | 4 38 |
| 72090           | 4050300774350     | OSRAM DUO EL F/R 2x58W | Silver | 2 x 58 | 1535      | 140       | 50        | 4 38 |



All orders must be multiples of sales pack

## Indoor – Surface Mounted Luminaires



IP20 960 °C IK02 230–240V 50Hz X η<sub>LB</sub> 0,78 G13



electronic  
comfort light

Dickopf  
Rohwer & Co.  
Licht + Raum  
Leuchten + Lampen


**SCRIPTUS**

- T8 reflector luminaire for wall mounting
- Kit includes integrated ECG, brackets, ceiling rose and two cable routing rods
- Suitable for LUMILUX® T8
- Ideal for illuminating paintings, classroom boards, advertising panels and indirect lighting

| Product ID Code | EAN (Single Pack) | Product Description | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG |    |
|-----------------|-------------------|---------------------|--------|----|--------|--------|--------|-----|----|
| SCRIPTUS1L36C   | 4050300118185     | SCRIPTUS 1x36 HF    | White  | 36 | 1230   | 145    | 74     | 1   | 38 |
| SCRIPTUS1L58HF  | 4050300117638     | SCRIPTUS 1x58 HF    | White  | 58 | 1530   | 145    | 74     | 1   | 38 |



K10° IP43 IP43 F IK03 230V 50Hz ✓ G23



(sensor)

**OSRAM DULUX® RONDEL\***

- Super slim round energy saving luminaire suitable for indoors and outdoors (IP43)
- Sensor version available with adjustable dimmer switch
- Equipped with OSRAM DULUX® S compact fluorescent lamps


| Product ID Code                  | EAN (Single Pack) | Product Description          | FINISH | W     | h [mm] | d [mm] | PPG |    |
|----------------------------------|-------------------|------------------------------|--------|-------|--------|--------|-----|----|
| <b>OSRAM DULUX RONDEL</b>        |                   |                              |        |       |        |        |     |    |
| 73025W                           | 4050300361543     | RONDEL 9W DULUX S 827        | White  | 9     | 55     | 230    | 4x1 | 38 |
| 73030W                           | 4050300328737     | RONDEL 2 x 9W DULUX S 827    | White  | 2 x 9 | 55     | 270    | 4x1 | 38 |
| <b>OSRAM DULUX RONDEL SENSOR</b> |                   |                              |        |       |        |        |     |    |
| 7302575W                         | 4050300399133     | RONDEL SENSOR 9W DULUX S 830 | White  | 9     | 55     | 230    | 4x1 | 38 |

\*Changeover to electronic operation in preparation. For further information please contact OSRAM

All orders must be multiples of sales pack



## Indoor – Surface Mounted Luminaires

**OSRAM DULUX® CARRE\***


- Super slim rectangular energy saving luminaire suitable for indoors and outdoors (IP43)
- Sensor version available with adjustable dimmer switch
- Equipped with OSRAM DULUX® S compact fluorescent lamps

| Product ID Code                 | EAN (Single Pack) | Product Description         | FINISH | W    | $\frac{l}{[mm]}$ | $\frac{b}{[mm]}$ | $\frac{h}{[mm]}$ | PPG    |
|---------------------------------|-------------------|-----------------------------|--------|------|------------------|------------------|------------------|--------|
| <b>OSRAM DULUX CARRE</b>        |                   |                             |        |      |                  |                  |                  |        |
| 73040W                          | 4050300012117     | CARRE 9W DULUX S 827        | White  | 9    | 200              | 200              | 55               | 4x1 38 |
| 73045W                          | 4050300012100     | CARRE 11W DULUX S 827       | White  | 11   | 270              | 200              | 55               | 4x1 38 |
| 73050W                          | 4050300314921     | CARRE 2x11W DULUX S 827     | White  | 2x11 | 270              | 270              | 55               | 4x1 38 |
| <b>OSRAM DULUX CARRE SENSOR</b> |                   |                             |        |      |                  |                  |                  |        |
| 7304075W                        | 4050300424644     | CARRE SENSOR 9W DULUX S 830 | White  | 9    | 200              | 200              | 55               | 4x1 38 |

\*Changeover to electronic operation in preparation. For further information please contact OSRAM




All orders must be multiples of sales pack

**INDOOR****BATTEN LUMINAIRES****OSRAM ECOPACK® T5 DALI®**

- T5 batten luminaires with integrated QUICKTRONIC® QTi DALI® electronic control gear
- Large number of different light sources can be used
- For integration in DALI® installations, dimmable from 100% to 1%
- Supplied without cover and T5 lamp for fixed connection



| Product ID Code | EAN (Single Pack) | Product Description   | FINISH | W        | I [mm] | b [mm] | h [mm] | PPG |    |
|-----------------|-------------------|-----------------------|--------|----------|--------|--------|--------|-----|----|
| 7262199         | 4008321259578     | OSRAM ECOPACK T5 DALI | White  | 14/24    | 584    | 38     | 58     | 4   | 38 |
| 7262299         | 4008321259592     | OSRAM ECOPACK T5 DALI | White  | 21/39    | 884    | 38     | 58     | 4   | 38 |
| 7262399         | 4008321259615     | OSRAM ECOPACK T5 DALI | White  | 28/54    | 1184   | 38     | 58     | 4   | 38 |
| 7262499         | 4008321259639     | OSRAM ECOPACK T5 DALI | White  | 35/49/80 | 1484   | 38     | 58     | 4   | 38 |

**OSRAM ECOPACK® T5 DIM**


- Dimmable T5 batten luminaire with integrated QUICKTRONIC® QTi DIM electronic control gear
- Large number of different light sources can be used
- 1...10V dimmable from 100% to 1%
- Supplied without cover and T5 lamp for fixed connection




| Product ID Code | EAN (Single Pack) | Product Description  | FINISH | W        | I [mm] | b [mm] | h [mm] | PPG |    |
|-----------------|-------------------|----------------------|--------|----------|--------|--------|--------|-----|----|
| 7261199         | 4008321259493     | OSRAM ECOPACK T5 DIM | White  | 14/24    | 584    | 38     | 58     | 4   | 38 |
| 7261299         | 4008321259516     | OSRAM ECOPACK T5 DIM | White  | 21/39    | 884    | 38     | 58     | 4   | 38 |
| 7261399         | 4008321259530     | OSRAM ECOPACK T5 DIM | White  | 28/54    | 1184   | 38     | 58     | 4   | 38 |
| 7261499         | 4008321259554     | OSRAM ECOPACK T5 DIM | White  | 35/49/80 | 1484   | 38     | 58     | 4   | 38 |



All orders must be multiples of sales pack




## Indoor – Batten Luminaires

**OSRAM ECOPACK® FH DIM**

- Dimmable T5 batten luminaire equipped with LUMILUX® T5 HE 830 tube for fixed connection
- 1...10V dimmable from 100% to 1%
- Prismatic cover for uniform light
- With QUICKTRONIC® QTi DIM electronic control gear

| Product ID Code | EAN (Single Pack) | Product Description      | FINISH | W  | $\overrightarrow{l}$ [mm] | $\overrightarrow{b}$ [mm] | $\downarrow h$ [mm] | PPG |    |
|-----------------|-------------------|--------------------------|--------|----|---------------------------|---------------------------|---------------------|-----|----|
| 72611W          | 4050300659213     | OSRAM ECOPACK FH DIM 14W | White  | 14 | 584                       | 38                        | 58                  | 4   | 38 |
| 72612W          | 4050300659237     | OSRAM ECOPACK FH DIM 21W | White  | 21 | 884                       | 38                        | 58                  | 4   | 38 |
| 72613W          | 4050300659251     | OSRAM ECOPACK FH DIM 28W | White  | 28 | 1184                      | 38                        | 58                  | 4   | 38 |
| 72614W          | 4050300659275     | OSRAM ECOPACK FH DIM 35W | White  | 35 | 1484                      | 38                        | 58                  | 4   | 38 |

**OSRAM ECOPACK® T5**

- Dimmable T5 batten luminaire with integrated QUICKTRONIC® QTi electronic control gear
- Large number of different light sources can be used
- Supplied without cover and T5 lamp for fixed connection

| Product ID Code | EAN (Single Pack) | Product Description | FINISH | W        | $\overrightarrow{l}$ [mm] | $\overrightarrow{b}$ [mm] | $\downarrow h$ [mm] | PPG |    |
|-----------------|-------------------|---------------------|--------|----------|---------------------------|---------------------------|---------------------|-----|----|
| 7260199         | 4008321257413     | OSRAM ECOPACK FH    | White  | 14/24    | 584                       | 38                        | 58                  | 4   | 38 |
| 7260299         | 4008321257437     | OSRAM ECOPACK FH    | White  | 21/39    | 884                       | 38                        | 58                  | 4   | 38 |
| 7260399         | 4008321257451     | OSRAM ECOPACK FH    | White  | 28/54    | 1184                      | 38                        | 58                  | 4   | 38 |
| -               | 4008321257479*    | OSRAM ECOPACK FH    | White  | 35/49/80 | 1484                      | 38                        | 58                  | 4   | 38 |


\*In preparation at time of print. For further information please contact OSRAM



All orders must be multiples of sales pack




Indoor – Batten Luminaires



### OSRAM ECOPACK® Louvre

- Double parabolic louvres for all OSRAM ECOPACK® luminaires with or for T5 tubes
- Highly polished, aluminium finish
- Ideal for reducing glare

| Product ID Code | EAN (Single Pack) | Product Description             | FINISH | W        | $\frac{l}{[mm]}$ | $\frac{b}{[mm]}$ | $\frac{h}{[mm]}$ | PPG |    |
|-----------------|-------------------|---------------------------------|--------|----------|------------------|------------------|------------------|-----|----|
| 72650           | 4008321079886     | OSRAM ECOPACK Louvre for 14/24W | White  | 14/24    | 567              | 88               | 53               | 4   | 38 |
| 72651           | 4008321079909     | OSRAM ECOPACK Louvre for 21/39W | White  | 21/39    | 867              | 88               | 53               | 4   | 38 |
| 72652           | 4008321080424     | OSRAM ECOPACK Louvre for 28/54W | White  | 28/54    | 1167             | 88               | 53               | 4   | 38 |
| 72653           | 4008321080448     | OSRAM ECOPACK Louvre for 35/80W | White  | 35/49/80 | 1467             | 88               | 53               | 4   | 38 |



### OSRAM ECOPACK® FQ

- Extremely bright T5 electronic batten luminaire
- Complete with high output LUMILUX® T5 HO 840 tubes for fixed connection
- Without cover for maximum luminous flux
- With QUICKTRONIC® QTi electronic control gear



| Product ID Code | EAN (Single Pack) | Product Description  | FINISH | W  | $\frac{l}{[mm]}$ | $\frac{b}{[mm]}$ | $\frac{h}{[mm]}$ | PPG |    |
|-----------------|-------------------|----------------------|--------|----|------------------|------------------|------------------|-----|----|
| 72630           | 4050300797762     | OSRAM ECOPACK FQ 24W | White  | 24 | 584              | 38               | 58               | 4   | 38 |
| 72631           | 4050300859187     | OSRAM ECOPACK FQ 39W | White  | 39 | 884              | 38               | 58               | 4   | 38 |
| 72632           | 4050300859200     | OSRAM ECOPACK FQ 54W | White  | 54 | 1184             | 38               | 58               | 4   | 38 |
| 72633           | 4050300859385     | OSRAM ECOPACK FQ 80W | White  | 80 | 1484             | 38               | 58               | 4   | 38 |

All orders must be multiples of sales pack



## Indoor – Batten Luminaires



**CE**



830  $\eta_{LB}$  0,84 G5

**electronic comfort light**

**OSRAM ECOPACK® FH**


- Extremely economical T5 electronic batten luminaire
- Complete with high efficiency LUMILUX® T5 HE 830 tubes for fixed connection
- With prismatic cover for uniform light distribution
- With QUICKTRONIC® QTi electronic control gear

| Product ID Code | EAN (Single Pack) | Product Description  | FINISH | W  | [mm] | [mm] | [mm] | PPG  |
|-----------------|-------------------|----------------------|--------|----|------|------|------|------|
| 72601W          | 4050300513249     | OSRAM ECOPACK FH 14W | White  | 14 | 584  | 38   | 58   | 4 38 |
| 72602W          | 4050300513263     | OSRAM ECOPACK FH 21W | White  | 21 | 884  | 38   | 58   | 4 38 |
| 72603W          | 4050300513287     | OSRAM ECOPACK FH 28W | White  | 28 | 1184 | 38   | 58   | 4 38 |
| 72604W          | 4050300513300     | OSRAM ECOPACK FH 35W | White  | 35 | 1484 | 38   | 58   | 4 38 |



All orders must be multiples of sales pack

## Indoor – Batten Luminaires

**OSRAM MINI5 ECO**

- Compact pluggable T5 batten luminaire with LUMILUX® T5 tubes
- Equipped with or without LUMILUX® T5 8W/13W or LUMILUX® T5 HE 14W/28W/35W
- With prismatic cover for uniform light distribution
- Developed for installation in tight spaces
- Can be installed separately or combined to create strip lighting

| Product ID Code                       | EAN (Single Pack) | Product Description          | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG |    |
|---------------------------------------|-------------------|------------------------------|--------|----|--------|--------|--------|-----|----|
| <b>OSRAM MINI5 ECO – with lamp</b>    |                   |                              |        |    |        |        |        |     |    |
| 7281027                               | 4008321931399     | OSRAM MINI5 ECO 8W 827       | White  | 8  | 318    | 24     | 42     | 4   | 38 |
| 7281127                               | 4008321931412     | OSRAM MINI5 ECO 13W 827      | White  | 13 | 547    | 24     | 42     | 4   | 38 |
| 7281227                               | 4008321931436     | OSRAM MINI5 ECO 14W 827      | White  | 14 | 579    | 24     | 42     | 4   | 38 |
| 7281327                               | 4008321931450     | OSRAM MINI5 ECO 21W 827      | White  | 21 | 879    | 24     | 42     | 4   | 38 |
| 7281427                               | 4008321931474     | OSRAM MINI5 ECO 28W 827      | White  | 28 | 1179   | 24     | 42     | 4   | 38 |
| 7281527                               | 4008321931498     | OSRAM MINI5 ECO 35W 827      | White  | 35 | 1479   | 24     | 42     | 4   | 38 |
| 7281040                               | 4008321931511     | OSRAM MINI5 ECO 8W 840       | White  | 8  | 318    | 24     | 42     | 4   | 38 |
| 7281140                               | 4008321931535     | OSRAM MINI5 ECO 13W 840      | White  | 13 | 547    | 24     | 42     | 4   | 38 |
| 7281240                               | 4008321931559     | OSRAM MINI5 ECO 14W 840      | White  | 14 | 579    | 24     | 42     | 4   | 38 |
| 7281340                               | 4008321931573     | OSRAM MINI5 ECO 21W 840      | White  | 21 | 879    | 24     | 42     | 4   | 38 |
| 7281440                               | 4008321931597     | OSRAM MINI5 ECO 28W 840      | White  | 28 | 1179   | 24     | 42     | 4   | 38 |
| 7281540                               | 4008321931610     | OSRAM MINI5 ECO 35W 840      | White  | 35 | 1479   | 24     | 42     | 4   | 38 |
| <b>OSRAM MINI5 ECO – without lamp</b> |                   |                              |        |    |        |        |        |     |    |
| 72810                                 | 4008321300911     | OSRAM MINI5 ECO ex. lamp 8W  | White  | 8  | 318    | 24     | 42     | 4   | 38 |
| 72811                                 | 4008321300935     | OSRAM MINI5 ECO ex. lamp 13W | White  | 14 | 547    | 24     | 42     | 4   | 38 |
| 72812                                 | 4008321300959     | OSRAM MINI5 ECO ex. lamp 14W | White  | 18 | 579    | 24     | 42     | 4   | 38 |
| 72813                                 | 4008321300973     | OSRAM MINI5 ECO ex. lamp 21W | White  | 21 | 879    | 24     | 42     | 4   | 38 |
| 72814                                 | 4008321300997     | OSRAM MINI5 ECO ex. lamp 28W | White  | 28 | 1179   | 24     | 42     | 4   | 38 |
| 72815                                 | 4008321301154     | OSRAM MINI5 ECO ex. lamp 35W | White  | 35 | 1479   | 24     | 42     | 4   | 38 |

All orders must be multiples of sales pack



## Indoor – Batten Luminaires



**CE**



827

**electronic  
comfort light**

**LUMILUX® COMBI EL**

- General purpose T8 electronic batten luminaire
- Equipped with LUMILUX® tube colour 827
- Ready to install with 2m of cable and euro plug



| Product ID Code | EAN (Single Pack) | Product Description      | FINISH | W  | I [mm] | b [mm] | h [mm] |   | PPG |
|-----------------|-------------------|--------------------------|--------|----|--------|--------|--------|---|-----|
| 72032           | 4050300824765     | LUMILUX COMBI EL 827 8W  | White  | 8  | 323    | 21     | 50     | 4 | 38  |
| 72037           | 4050300824819     | LUMILUX COMBI EL 827 13W | White  | 13 | 551    | 21     | 50     | 4 | 38  |



All orders must be multiples of sales pack




Indoor – Batten Luminaires

**LUMILUX® DECO EL**

- Wall and mirror T8 batten luminaire for fixed connection
- Prismatic (EL/P) or Opal EL/D lamp cover
- Equipped with LUMILUX® T5 fluorescent tube and electronic control gear

| Product ID Code | EAN (Single Pack) | Product Description             | FINISH | W  | I [mm] | b [mm] | h [mm] | G5 | PPG |
|-----------------|-------------------|---------------------------------|--------|----|--------|--------|--------|----|-----|
| 72161W          | 4050300356846     | LUMILUX DECO EL/P 8W Prismatic  | White  | 8  | 310    | 42     | 54     | 4  | 38  |
| 72165W          | 4050300356860     | LUMILUX DECO EL/P 13W Prismatic | White  | 13 | 538    | 42     | 54     | 4  | 38  |
| 721644          | 4050300497822     | LUMILUX DECO EL/D 8W Opal       | White  | 8  | 310    | 42     | 54     | 4  | 38  |
| 7216544         | 4050300497846     | LUMILUX DECO EL/D 13W Opal      | White  | 13 | 538    | 42     | 54     | 4  | 38  |

**OSRAM ECOPACK® DIM**

- Low cost dimmable T8 electronic batten luminaire
- 1...10V dimmable from 100% to 1%
- Supplied with QUICKTRONIC® dimmable electronic control gear

| Product ID Code | EAN (Single Pack) | Product Description   | FINISH | W  | I [mm] | b [mm] | h [mm] | G5 | PPG |
|-----------------|-------------------|-----------------------|--------|----|--------|--------|--------|----|-----|
| 72561W          | 4050300561981     | OSRAM ECOPACK DIM 18W | White  | 18 | 618    | 38     | 66     | 4  | 38  |
| 72565W          | 4050300562025     | OSRAM ECOPACK DIM 36W | White  | 36 | 1228   | 38     | 66     | 4  | 38  |
| 72567W          | 4050300562070     | OSRAM ECOPACK DIM 58W | White  | 58 | 1528   | 38     | 66     | 4  | 38  |


All orders must be multiples of sales pack



## Indoor – Batten Luminaires



|  |                  |     |        |      |          |          |
|--|------------------|-----|--------|------|----------|----------|
|  |                  |     | 960 °C | IK07 | 230–240V | 50–60 Hz |
|  | $\eta_{LB}$ 0,90 | G13 |        |      |          |          |



Qualität  
Effizienz  
Technik  
Service  
Entwickelt für  
Büro, Fabrik,  
Handwerk und  
Commerzielle Anwendungen

**OSRAM ECOPACK®**

- Low cost electronic T8 batten luminaire
- Supplied with QUICKTRONIC® PROFESSIONAL electronic control gear

| Product ID Code | EAN (Single Pack) | Product Description | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|---------------------|--------|----|--------|--------|--------|------|
| 72581W          | 4050300562124     | OSRAM ECOPACK 18W   | White  | 18 | 618    | 38     | 66     | 4 38 |
| 72585W          | 4050300528359     | OSRAM ECOPACK 36W   | White  | 36 | 1228   | 38     | 66     | 4 38 |
| 72587W          | 4050300528373     | OSRAM ECOPACK 58W   | White  | 58 | 1528   | 38     | 66     | 4 38 |



|  |                  |     |        |           |          |
|--|------------------|-----|--------|-----------|----------|
|  |                  |     | 960 °C | 230–240 V | 50–60 Hz |
|  | $\eta_{LB}$ 0,83 | 827 | G13    |           |          |



Qualität  
Effizienz  
Technik  
Service  
Entwickelt für  
Büro, Fabrik,  
Handwerk und  
Commerzielle Anwendungen

**LUMILUX® COMBI EL-N**

- Low cost general purpose electronic T8 batten luminaire
- Supplied with or without LUMILUX® T8 tubes
- Ready to install with 2m of cable and euro plug

| Product ID Code                         | EAN (Single Pack) | Product Description             | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG    |
|---|-------------------|---------------------------------|--------|----|--------|--------|--------|--------|
| <b>LUMILUX® COMBI EL-N</b>              |                   |                                 |        |    |        |        |        |        |
| 72006W                                  | 4050300003443     | LUMILUX COMBI EL-N 10W          | White  | 10 | 501    | 30     | 50     | 4x1 38 |
| 72011W                                  | 4050300003474     | LUMILUX COMBI EL-N 18W          | White  | 18 | 621    | 30     | 50     | 4x1 38 |
| 72016W                                  | 4050300002163     | LUMILUX COMBI EL-N 30W          | White  | 30 | 926    | 30     | 50     | 4x1 38 |
| 72021W                                  | 4050300003511     | LUMILUX COMBI EL-N 36W          | White  | 36 | 1231   | 30     | 50     | 4x1 38 |
| 72026W                                  | 4050300986517     | LUMILUX COMBI EL-N 58W          | White  | 58 | 1531   | 30     | 50     | 4x1 38 |
| <b>LUMILUX® COMBI EL-N without lamp</b> |                   |                                 |        |    |        |        |        |        |
| 72011                                   | 4050300997650     | LUMILUX COMBI EL-N ex. lamp 18W | White  | 18 | 621    | 30     | 50     | 4x1 38 |
| 72016                                   | 4050300003504     | LUMILUX COMBI EL-N ex. lamp 30W | White  | 30 | 926    | 30     | 50     | 4x1 38 |
| 72021                                   | 4050300148663     | LUMILUX COMBI EL-N ex. lamp 36W | White  | 36 | 1231   | 30     | 50     | 4x1 38 |
| 72026                                   | 4050300993973     | LUMILUX COMBI EL-N ex. lamp 58W | White  | 58 | 1531   | 30     | 50     | 4x1 38 |



All orders must be multiples of sales pack



## Indoor – Batten Luminaires



**CE**

$\eta_{LB}$  0,83 827 ✓ G13



**electronic  
comfort light**

**LUMILUX® COMBI EL-F**

- Electronic general purpose T8 fluorescent batten luminaire
- For fixed connections with central, asymmetrical and side cable insertion
- Integrated switch
- Supplied with or without LUMILUX® T8 tubes

| Product ID Code                           | EAN (Single Pack) | Product Description               | FINISH | W  | $\frac{l}{[mm]}$ | $\frac{b}{[mm]}$ | $\frac{h}{[mm]}$ | PPG  |
|---|-------------------|-----------------------------------|--------|----|------------------|------------------|------------------|------|
| <b>LUMILUX® COMBI EL-F</b>                |                   |                                   |        |    |                  |                  |                  |      |
| 72106W                                    | 4050300003542     | LUMILUX COMBI EL-F 10W            | White  | 10 | 501              | 30               | 50               | 4 38 |
| 72111W                                    | 4050300003573     | LUMILUX COMBI EL-F 18W            | White  | 18 | 621              | 30               | 50               | 4 38 |
| 72116W                                    | 4050300003597     | LUMILUX COMBI EL-F 30W            | White  | 30 | 926              | 30               | 50               | 4 38 |
| 72121W                                    | 4050300003634     | LUMILUX COMBI EL-F 36W            | White  | 36 | 1231             | 30               | 50               | 4 38 |
| 72126W                                    | 4050300005195     | LUMILUX COMBI EL-F 58W            | White  | 58 | 1531             | 30               | 50               | 4 38 |
| <b>LUMILUX® COMBI EL-F – without lamp</b> |                   |                                   |        |    |                  |                  |                  |      |
| 72111                                     | 4050300148724     | LUMILUX COMBI EL-F – ex. lamp 18W | White  | 18 | 621              | 30               | 50               | 4 38 |
| 72116                                     | 4050300484679     | LUMILUX COMBI EL-F – ex. lamp 30W | White  | 30 | 926              | 30               | 50               | 4 38 |
| 72121                                     | 4050300148748     | LUMILUX COMBI EL-F – ex. lamp 36W | White  | 36 | 1231             | 30               | 50               | 4 38 |
| 72126                                     | 4050300993959     | LUMILUX COMBI EL-F – ex. lamp 58W | White  | 58 | 1531             | 30               | 50               | 4 38 |

All orders must be multiples of sales pack



## Indoor – Batten Luminaires



|  |  |  |  |  |  |  |     |                  |     |
|--|--|--|--|--|--|--|-----|------------------|-----|
|  |  |  |  |  |  |  |     |                  |     |
|  |  |  |  |  |  |  | 827 | $\eta_{LB}$ 0,76 | G13 |

**LUMILUX® COMBI EL-N/P**

- Low cost electronic T8 batten luminaire
- Equipped with LUMILUX® T8 827 tube
- Ready to install with 2m of cable and euro plug

| Product ID Code | EAN (Single Pack) | Product Description      | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|--------------------------|--------|----|--------|--------|--------|------|
| 72206W          | 4050300346540     | LUMILUX COMBI EL-N/P 10W | White  | 10 | 501    | 33     | 52     | 4 38 |
| 72211W          | 4050300346625     | LUMILUX COMBI EL-N/P 18W | White  | 18 | 621    | 33     | 52     | 4 38 |
| 72216W          | 4050300346663     | LUMILUX COMBI EL-N/P 30W | White  | 30 | 926    | 33     | 52     | 4 38 |
| 72221W          | 4050300346861     | LUMILUX COMBI EL-N/P 36W | White  | 36 | 1231   | 33     | 52     | 4 38 |
| 72226W          | 4050300346946     | LUMILUX COMBI EL-N/P 58W | White  | 58 | 1531   | 33     | 52     | 4 38 |

|  |  |  |  |  |  |  |     |                  |     |
|--|--|--|--|--|--|--|-----|------------------|-----|
|  |  |  |  |  |  |  |     |                  |     |
|  |  |  |  |  |  |  | 827 | $\eta_{LB}$ 0,76 | G13 |

**LUMILUX® COMBI EL-F/P**

- General purpose electronic T8 fluorescent batten
- Equipped with LUMILUX® T8 827 tube
- Prismatic cover provides glare free light
- For fixed connections with central, asymmetrical and side cable insertion
- Integrated switch

| Product ID Code | EAN (Single Pack) | Product Description      | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|--------------------------|--------|----|--------|--------|--------|------|
| 72306W          | 4050300346502     | LUMILUX COMBI EL-F/P 10W | White  | 10 | 501    | 33     | 51.5   | 4 38 |
| 72311W          | 4050300346588     | LUMILUX COMBI EL-F/P 18W | White  | 18 | 621    | 33     | 51.5   | 4 38 |
| 72316W          | 4050300346700     | LUMILUX COMBI EL-F/P 30W | White  | 30 | 926    | 33     | 51.5   | 4 38 |
| 72321W          | 4050300346908     | LUMILUX COMBI EL-F/P 36W | White  | 36 | 1231   | 33     | 51.5   | 4 38 |
| 72326W          | 4050300346984     | LUMILUX COMBI EL-F/P 58W | White  | 58 | 1531   | 33     | 51.5   | 4 38 |



All orders must be multiples of sales pack



Indoor – Batten Luminaires



|  |  |  |  |  |        |      |           |                          |
|--|--|--|--|--|--------|------|-----------|--------------------------|
|  |  |  |  |  | 650 °C | IK02 | 230–240 V | 50–60 Hz                 |
|  |  |  |  |  |        |      |           | 827 $\eta_{LB}$ 0,75 G13 |



### LUMILUX® COMBI EL-F/D

- Electronic wall and mirror batten luminaire
- Equipped with LUMILUX® T8 827 tube and QUICKTRONIC® electronic control gear
- With matt diffuser for uniform glare free light
- For fixed connections

| Product ID Code | EAN (Single Pack) | Product Description      | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|--------------------------|--------|----|--------|--------|--------|------|
| 7210644         | 4008321917454     | LUMILUX COMBI EL-F/D 10W | White  | 10 | 501    | 52     | 64     | 4 38 |
| 7211144         | 4008321917478     | LUMILUX COMBI EL-F/D 18W | White  | 18 | 621    | 52     | 64     | 4 38 |
| 7211644         | 4008321917492     | LUMILUX COMBI EL-F/D 30W | White  | 30 | 926    | 52     | 64     | 4 38 |
| 7212144         | 4008321917515     | LUMILUX COMBI EL-F/D 36W | White  | 36 | 1230   | 52     | 64     | 4 38 |
| 7212644         | 4008321917539     | LUMILUX COMBI EL-F/D 58W | White  | 58 | 1531   | 52     | 64     | 4 38 |



|  |  |  |  |  |        |      |           |          |
|--|--|--|--|--|--------|------|-----------|----------|
|  |  |  |  |  | 960 °C | IK02 | 230–240 V | 50–60 Hz |
|  |  |  |  |  |        |      |           | 827 G13  |



### LUMILUX® COMBI EL-F/B

- Electronic wall and mirror batten luminaire
- Equipped with LUMILUX® T8 827 tube and QUICKTRONIC® electronic control gear
- With rotary shade for directional or shielded light
- For fixed connections

| Product ID Code | EAN (Single Pack) | Product Description      | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|--------------------------|--------|----|--------|--------|--------|------|
| 7211145         | 4008321917379     | LUMILUX COMBI EL-F/B 18W | White  | 18 | 634    | 52     | 61     | 4 38 |
| 7211645         | 4008321917393     | LUMILUX COMBI EL-F/B 30W | White  | 30 | 939    | 52     | 61     | 4 38 |
| 7212145         | 4008321917416     | LUMILUX COMBI EL-F/B 36W | White  | 36 | 1243   | 52     | 61     | 4 38 |
| 7212645         | 4008321917430     | LUMILUX COMBI EL-F/B 58W | White  | 58 | 1544   | 52     | 61     | 4 38 |

All orders must be multiples of sales pack



## Indoor – Batten Luminaires



|                                 |           |  |  |  |  |        |           |          |  |
|---------------------------------|-----------|--|--|--|--|--------|-----------|----------|--|
|                                 | <b>CE</b> |  |  |  |  | 650 °C | 230–240 V | 50–60 Hz |  |
|                                 |           |  |  |  |  |        |           |          |  |
| <b>electronic comfort light</b> |           |  |  |  |  |        |           |          |  |
|                                 |           |  |  |  |  |        |           |          |  |
|                                 |           |  |  |  |  |        |           |          |  |

**LUMILUX® VARIO EL-N**

- Flat batten luminaire with special tubular reflector capable of rotating 360° for variable, directional light
- Ready to install with 2m of cable and euro plug
- 40% more light in the main beam direction compared with free burning lamps
- Equipped with LUMILUX® 827 tube and QUICKTRONIC® electronic control gear

| Product ID Code | EAN (Single Pack) | Product Description    | FINISH | W  | I<br>[mm] | b<br>[mm] | h<br>[mm] | PPG |    |
|-----------------|-------------------|------------------------|--------|----|-----------|-----------|-----------|-----|----|
| 72356           | 4008321908445     | LUMILUX VARIO EL-N 18W | White  | 18 | 617       | 35        | 59        | 4   | 38 |
| 72357           | 4008321908452     | LUMILUX VARIO EL-N 30W | White  | 30 | 922       | 35        | 59        | 4   | 38 |
| 72358           | 4008321908469     | LUMILUX VARIO EL-N 36W | White  | 36 | 1227      | 35        | 59        | 4   | 38 |

|                                 |           |  |  |  |  |        |           |          |  |
|---------------------------------|-----------|--|--|--|--|--------|-----------|----------|--|
|                                 | <b>CE</b> |  |  |  |  | 650 °C | 230–240 V | 50–60 Hz |  |
|                                 |           |  |  |  |  |        |           |          |  |
| <b>electronic comfort light</b> |           |  |  |  |  |        |           |          |  |
|                                 |           |  |  |  |  |        |           |          |  |
|                                 |           |  |  |  |  |        |           |          |  |

**LUMILUX® VARIO EL-F**

- Flat batten luminaire with special tubular reflector capable of rotating 360° for variable, directional light
- For fixed connection, with central, asymmetrical and side cable insertion
- 40% more light in the main beam direction compared with free burning lamps
- Equipped with LUMILUX® 827 tube and QUICKTRONIC® electronic control gear

| Product ID Code | EAN (Single Pack) | Product Description    | FINISH | W  | I<br>[mm] | b<br>[mm] | h<br>[mm] | PPG |    |
|-----------------|-------------------|------------------------|--------|----|-----------|-----------|-----------|-----|----|
| 72456           | 4008321908476     | LUMILUX VARIO EL-F 18W | White  | 18 | 617       | 35        | 59        | 4   | 38 |
| 72457           | 4008321908483     | LUMILUX VARIO EL-F 30W | White  | 30 | 922       | 35        | 59        | 4   | 38 |
| 72458           | 4008321908490     | LUMILUX VARIO EL-F 36W | White  | 36 | 1227      | 35        | 59        | 4   | 38 |




All orders must be multiples of sales pack



## INDOOR

### FURNITURE LUMINAIRES



**electronic comfort light** Quick night  
Fader function Energy efficient Longer lifetime

#### DRAGONPOINT® VARIO KIT


- Built in swivel LED light fixture in an aluminium casing
- Equipped with Golden DRAGON® LED 1.2W
- DRAGONPOINT® 1 LED KIT contains 3 luminaires with 1 LED, OPTOTRONIC® OT9 DIM
- DRAGONPOINT® 3 LED KIT contains 2 luminaires with 3 LED, OPTOTRONIC® OT9 DIM
- Extremely flat and narrow light fixture ideal for emphasising specific detail

| Product ID Code   | EAN (Single Pack) | Product Description             | FINISH   | A° | W   | h [mm] | d [mm] | Light No. | PPG |    |
|---|-------------------|---------------------------------|----------|----|-----|--------|--------|-----------|-----|----|
| <b>DRAGONPOINT® 2 X 3 LED KIT</b>                         |                   |                                 |          |    |     |        |        |           |     |    |
| DPVARIOKIT30LED3  | 4008321368775     | DP VARIO KIT 2 X 3 LED 830 L30° | Grey/Alu | 30 | 3.6 | 32.3   | 80     | 1         | 4   | 38 |
| 8021922   | 4008321291547     | DP VARIO KIT 2 X 3 LED 854 L30° | Grey/Alu | 30 | 3.6 | 32.3   | 80     | 1         | 4   | 38 |
| DPVARIOKITL12LED3   | 4008321368744     | DP VARIO KIT 2 X 3 LED 830 L12° | Grey/Alu | 12 | 3.6 | 32.3   | 80     | 1         | 4   | 38 |
| 8021921   | 4008321291516     | DP VARIO KIT 2 X 3 LED 854 L12° | Grey/Alu | 12 | 3.6 | 32.3   | 80     | 1         | 4   | 38 |
| <b>DRAGONPOINT® 3 X 1 LED KIT</b>                         |                   |                                 |          |    |     |        |        |           |     |    |
| DPVARIOKITL30   | 4008321368621     | DP VARIO KIT 3 X 1 LED 830 L30° | Grey/Alu | 30 | 1.2 | 16     | 52     | 2         | 4   | 38 |
| 8021722   | 4008321291455     | DP VARIO KIT 3 X 1 LED 854 L30° | Grey/Alu | 30 | 1.2 | 16     | 52     | 2         | 4   | 38 |
| DPVARIOKITL12   | 4008321368652     | DP VARIO KIT 3 X 1 LED 830 L12° | Grey/Alu | 12 | 1.2 | 16     | 52     | 2         | 4   | 38 |
| 8021721   | 4008321291578     | DP VARIO KIT 3 X 1 LED 854 L12° | Grey/Alu | 12 | 1.2 | 16     | 52     | 2         | 4   | 38 |
| <b>DRAGONPOINT® VARIO PRO 2 X 3 LED KIT (OEM version)</b> |                   |                                 |          |    |     |        |        |           |     |    |
| DPVARIPRO0830L30L3  | 4008321399663     | DP VARIO PRO 3 LED 830 L30°     | Grey/Alu | 30 | 3.6 | 32.3   | 80     | 1         | 4   | 38 |
| DPVARIPRO0854L30L3  | 4008321399434     | DP VARIO PRO 3 LED 854 L30°     | Grey/Alu | 30 | 3.6 | 32.3   | 80     | 1         | 4   | 38 |
| DPVARIPRO0830L12L3  | 4008321399632     | DP VARIO PRO 3 LED 830 L12°     | Grey/Alu | 12 | 3.6 | 32.3   | 80     | 1         | 4   | 38 |
| DPVARIPRO0854L12L3  | 4008321399403     | DP VARIO PRO 3 LED 854 L12°     | Grey/Alu | 12 | 3.6 | 32.3   | 80     | 1         | 4   | 38 |
| <b>DRAGONPOINT® VARIO PRO 1 X 3 LED KIT (OEM version)</b> |                   |                                 |          |    |     |        |        |           |     |    |
| DPVARIPRO0830L30L1  | 4008321399571     | DP VARIO PRO 1 LED 830 L30°     | Grey/Alu | 30 | 1.2 | 16     | 52     | 2         | 4   | 38 |
| DPVARIPRO0854L30L1  | 4008321399342     | DP VARIO PRO 1 LED 854 L30°     | Grey/Alu | 30 | 1.2 | 16     | 52     | 2         | 4   | 38 |
| DPVARIPRO0830L12L1  | 4008321399601     | DP VARIO PRO 1 LED 830 L12°     | Grey/Alu | 12 | 1.2 | 16     | 52     | 2         | 4   | 38 |
| DPVARIPRO0854L12L1  | 4008321399373     | DP VARIO PRO 1 LED 854 L12°     | Grey/Alu | 12 | 1.2 | 16     | 52     | 2         | 4   | 38 |

All orders must be multiples of sales pack



## Indoor – Furniture Luminaires




**electronic comfort light**

**DRAGONPOINT® FIX KIT**

- LED spotlight in a brushed aluminium casing
- Equipped with 1 Golden DRAGON® LED 1.2W
- Kit contains 3 spotlights, OT 9/200-240V/350 DIM and 1 metre connecting cables
- Ideal for illuminating work surfaces

| Product ID Code                           | EAN (Single Pack) | Product Description           | FINISH   | W  | h [mm] | d [mm] | PPG     |
|---|-------------------|-------------------------------|----------|----|--------|--------|---------|
| DPFIXKITL30                               | 4008321368713     | DP FIX KIT 3 X 1 LED 830 L30° | Grey/Alu | 30 | 1.2    | 19     | 42 4 38 |
| 8021822                                   | 4008321291608     | DP FIX KIT 3 X 1 LED 854 L30° | Grey/Alu | 30 | 1.2    | 19     | 42 4 38 |
| <b>DRAGONPOINT® FIX PRO (OEM version)</b> |                   |                               |          |    |        |        |         |
| DPFIXPRO830L30L1                          | 4008321400994     | DP FIX PRO 1 LED 830 L30°     | Grey/Alu | 30 | 1.2    | 19     | 42 4 38 |
| DPFIXPRO854L30L1                          | 4008321400901     | DP FIX PRO 1 LED 854 L30°     | Grey/Alu | 30 | 1.2    | 19     | 42 4 38 |

NEW  
NEW  
NEW  
NEW



**electronic comfort light**

**DRAGONPOINT® MOOD KIT**

- Compact recessed LED luminaire in a brushed aluminium casing
- Equipped with 1 Golden DRAGON® LED in amber or blue light colour
- Kit contains 3 spotlights. OT 9/200-240V power supply and 1 metre connecting cables
- Ideal for accent and background illumination

| Product ID Code                            | EAN (Single Pack) | Product Description              | FINISH   | W   | h [mm] | d [mm] | PPG     |
|--|-------------------|----------------------------------|----------|-----|--------|--------|---------|
| 8022083                                    | 4008321326553     | DP MOOD KIT 3 X 1 LED Amber 120° | Grey/Alu | 120 | 1.2    | 43     | 42 4 38 |
| 8022080                                    | 4008321326522     | DP MOOD KIT 3 X 1 LED Blue 120°  | Grey/Alu | 120 | 1.2    | 43     | 42 4 38 |
| <b>DRAGONPOINT® MOOD PRO (OEM version)</b> |                   |                                  |          |     |        |        |         |
| DPMOODPRORED                               | 4008321399540     | DP MOOD PRO 1 LED Amber 120°     | Grey/Alu | 120 | 1.2    | 43     | 42 4 38 |
| DPMOODPROBLUE                              | 4008321399519     | DP MOOD PRO 1 LED Blue 120°      | Grey/Alu | 120 | 1.2    | 43     | 42 4 38 |



All orders must be multiples of sales pack



Indoor – Furniture Luminaires



Long version



Short version

**DRAGONSPOT®**


- Practical, small and lightweight LED luminaire with an adjustable head
- Equipped with Golden DRAGON® LED 1.2W
- Kit contains 1 spotlight and connecting cable
- Accessories available: Connection kit to connect 6 luminaires and OT 9/200-240V DIM power supply
- Ideal as a reading light, accent or directional light source

| Product ID Code                                    | EAN (Single Pack) | Product Description                 | FINISH   |    | W   |     |    |       |
|--|-------------------|-------------------------------------|----------|----|-----|-----|----|-------|
| <b>DRAGONSPOT® long version</b>                    |                   |                                     |          |    |     |     |    |       |
| <b>NEW</b><br>DSPOTLONG                            | 4008321368805     | DRAGONSPOT LONG 1 LED 830 L12°      | Grey/Alu | 12 | 1.2 | 380 | 27 | 4 38  |
| 8022321  | 4008321326584     | DRAGONSPOT LONG 1 LED 854 L12°      | Grey/Alu | 12 | 1.2 | 380 | 27 | 4 38  |
| <b>DRAGONSPOT® short version</b>                   |                   |                                     |          |    |     |     |    |       |
| <b>NEW</b><br>DSPOTSHORT                           | 4008321368836     | DRAGONSPOT SHORT 1 LED 830 L12°     | Grey/Alu | 12 | 1.2 | 130 | 27 | 4 38  |
| 8022221  | 4008321326232     | DRAGONSPOT SHORT 1 LED 854 L12°     | Grey/Alu | 12 | 1.2 | 130 | 27 | 4 38  |
| <b>DRAGONSPOT® PRO long version (OEM version)</b>  |                   |                                     |          |    |     |     |    |       |
| <b>NEW</b><br><b>NEW</b><br>DSPOTLONG830L12L1      | 4008321399694     | DRAGONSPOT PRO LONG 1 LED 830 L12°  | Grey/Alu | 12 | 1.2 | 380 | 27 | 4 38  |
| DSPOTLONG854L12L1                                  | 4008321399465     | DRAGONSPOT PRO LONG 1 LED 854 L12°  | Grey/Alu | 12 | 1.2 | 380 | 27 | 4 38  |
| <b>DRAGONSPOT® PRO short version (OEM version)</b> |                   |                                     |          |    |     |     |    |       |
| <b>NEW</b><br><b>NEW</b><br>DSPOTSHORT830L12L1     | 4008321399717     | DRAGONSPOT PRO SHORT 1 LED 830 L12° | Grey/Alu | 12 | 1.2 | 130 | 27 | 4 38  |
| DSPOTSHORT854L12L1                                 | 4008321399489     | DRAGONSPOT PRO SHORT 1 LED 854 L12° | Grey/Alu | 12 | 1.2 | 130 | 27 | 4 38  |
| <b>Accessories for DRAGONSPOT®</b>                 |                   |                                     |          |    |     |     |    |       |
| DSPOTCONKIT  | 4008321326201     | DRAGONSPOT Connection kit           | -        | -  | -   | -   | -  | 8 38  |
| OT9/350  | 4050300888262     | OPTOTRONIC OT 9/200240/350          | -        | -  | -   | -   | -  | 50 38 |
| OT09350DIM   | 4008321187321     | OPTOTRONIC OT 9/200240/350 DIM      | -        | -  | -   | -   | -  | 20 38 |

All orders must be multiples of sales pack



## Indoor – Furniture Luminaires

**LEDVANCE® DOWNLIGHT S**

- LED downlight fitting for replacement of 20W low voltage halogen
- Integrated ECG for direct connection to mains
- Ideal for furniture and under cabinet lighting

| Product ID Code | EAN (Single Pack) | Product Description             | FINISH | $\Delta$ | W   | $h$ [mm] | $\varnothing$ [mm] | d [mm] | PPG |
|-----------------|-------------------|---------------------------------|--------|----------|-----|----------|--------------------|--------|-----|
| LDVS830         | 4008321968623     | LEDVANCE DOWNLIGHT S 830 L80 AL | Alu    | 80       | 6.5 | 23       | 88                 | 4      | 38  |
| LDVS830WT       | 4008321968630     | LEDVANCE DOWNLIGHT S 830 L80 WT | White  | 80       | 6.5 | 23       | 88                 | 4      | 38  |
| LDVS840         | 4008321968647     | LEDVANCE DOWNLIGHT S 840 L80 AL | Alu    | 80       | 6.5 | 23       | 88                 | 4      | 38  |
| LDVS840WT       | 4008321968654     | LEDVANCE DOWNLIGHT S 840 L80 WT | White  | 80       | 6.5 | 23       | 88                 | 4      | 38  |

NEW  
NEW  
NEW  
NEW



All orders must be multiples of sales pack



Indoor – Furniture Luminaires



### LEDVANCE® Polybar

- Modular LED fixture in lengths of 250mm, 500mm, 750mm
- 60° or 120° optics and can be connected up to 20m serially
- Slimline fitting for under shelf and cove lighting

| Product ID Code                           | EAN (Single Pack) | Product Description | FINISH   | lm | W   | $\frac{l}{[mm]}$ | $\frac{b}{[mm]}$ | $\frac{h}{[mm]}$ | PPG        |
|---|-------------------|---------------------|----------|----|-----|------------------|------------------|------------------|------------|
| <b>LEDVANCE® Polybar – 250mm version</b>  |                   |                     |          |    |     |                  |                  |                  |            |
| LDVPBS830                                 | 4008321963338     | LEDVANCE POLYBAR S  | Grey/Alu | 80 | 300 | 6                | 250              | 40               | 26/42 4 38 |
| LDVPBS840                                 | 4008321962393     | LEDVANCE POLYBAR S  | Grey/Alu | 80 | 300 | 6                | 250              | 40               | 26/42 4 38 |
| LDVPBS854                                 | 4008321962423     | LEDVANCE POLYBAR S  | Grey/Alu | 80 | 300 | 6                | 250              | 40               | 26/42 4 38 |
| <b>LEDVANCE® Polybar – 500mm version</b>  |                   |                     |          |    |     |                  |                  |                  |            |
| LDVPBM830                                 | 4008321963345     | LEDVANCE POLYBAR M  | Grey/Alu | 80 | 600 | 12               | 500              | 40               | 26/42 4 38 |
| LDVPBM840                                 | 4008321962409     | LEDVANCE POLYBAR M  | Grey/Alu | 80 | 600 | 12               | 500              | 40               | 26/42 4 38 |
| LDVPBM854                                 | 4008321962430     | LEDVANCE POLYBAR M  | Grey/Alu | 80 | 600 | 12               | 500              | 40               | 26/42 4 38 |
| <b>LEDVANCE® Polybar – 750mm version</b>  |                   |                     |          |    |     |                  |                  |                  |            |
| LDVPBL830                                 | 4008321962386     | LEDVANCE POLYBAR L  | Grey/Alu | 80 | 900 | 18               | 750              | 40               | 26/42 4 38 |
| LDVPBL840                                 | 4008321962416     | LEDVANCE POLYBAR L  | Grey/Alu | 80 | 900 | 18               | 750              | 40               | 26/42 4 38 |
| LDVPBL854                                 | 4008321962447     | LEDVANCE POLYBAR L  | Grey/Alu | 80 | 900 | 18               | 750              | 40               | 26/42 4 38 |
| <b>LEDVANCE® Polybar – accessories</b>    |                   |                     |          |    |     |                  |                  |                  |            |
| LEDVANCE Polybar adjustable base S*       |                   |                     | Grey/Alu | –  | –   | –                | –                | 40               | 12 4 38    |
| LEDVANCE Polybar adjustable base M*       |                   |                     | Grey/Alu | –  | –   | –                | –                | 40               | 12 4 38    |
| LEDVANCE Polybar adjustable base L*       |                   |                     | Grey/Alu | –  | –   | –                | –                | 40               | 12 4 38    |
| LEDVANCE Polybar Entry Cable 2m*          |                   |                     | –        | –  | –   | –                | 2000             | –                | –          |
| LEDVANCE Polybar Connection Cable 250mm*  |                   |                     | –        | –  | –   | –                | 250              | –                | –          |
| LEDVANCE Polybar Connection Cable 500mm*  |                   |                     | –        | –  | –   | –                | 500              | –                | –          |
| LEDVANCE Polybar Connection Cable 1000mm* |                   |                     | –        | –  | –   | –                | 1000             | –                | –          |
| LEDVANCE Polybar On/Off Switch*           |                   |                     | –        | –  | –   | –                | 50               | 38               | 28         |

\*In preparation at time of print. For further information please contact OSRAM



Adjustable base



Power supply connector

All orders must be multiples of sales pack



## Indoor – Furniture Luminaires



|  |  |  |  |  |        |          |                              |
|--|--|--|--|--|--------|----------|------------------------------|
|  |  |  |  |  | 650 °C | 230–240V | 50Hz                         |
|  |  |  |  |  | 402 lm |          | 120°                         |
|  |  |  |  |  |        |          | Energy saving Longer lasting |

**LUMINESTRA® LED**

- Low profile LED luminaire in an aluminium housing with prismatic cover for glare free light
- Ready to install with 1.6m of cable and euro plug

| Product ID Code | EAN (Single Pack) | Product Description   | FINISH        | A°  | W | I [mm]  | b [mm] | h [mm] | PPG |    |
|-----------------|-------------------|-----------------------|---------------|-----|---|---------|--------|--------|-----|----|
| 73092           | 4008321524461     | LUMINESTRA LED 8W 830 | Silver/ White | 120 | 8 | 448/343 | 55     | 24/10  | 4   | 38 |
| 73093           | 4008321524485     | LUMINESTRA LED 8W 840 | Silver/ White | 120 | 8 | 448/343 | 55     | 24/10  | 4   | 38 |

NEW  
NEW



|  |  |  |  |        |                  |          |                              |
|--|--|--|--|--------|------------------|----------|------------------------------|
|  |  |  |  | 650 °C | IK03             | 230–240V | 50-60 Hz                     |
|  |  |  |  |        | $\eta_{LB}$ 0.62 |          | G5                           |
|  |  |  |  |        |                  |          | Energy saving Longer lasting |

**LUMINESTRA® EL**

- Low profile T5 fluorescent luminaire with prismatic cover for glare free light
- Ready to install with 2m of cable and euro plug
- Equipped with LUMILUX® T5 tube and integrated electronic control gear. Also available without lamp
- Up to 10 LUMINESTRA® EL luminaires can be combined to create strip lighting

| Product ID Code                     | EAN (Single Pack) | Product Description           | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG |    |
|-------------------------------------|-------------------|-------------------------------|--------|----|--------|--------|--------|-----|----|
| <b>LUMINESTRA EL</b>                |                   |                               |        |    |        |        |        |     |    |
| 73071W                              | 4050300008738     | LUMINESTRA LUMILUX T5 8W 827  | White  | 8  | 342    | 70     | 20     | 4   | 38 |
| 73081W                              | 4050300008745     | LUMINESTRA LUMILUX T5 13W 827 | White  | 13 | 555    | 70     | 20     | 4   | 38 |
| 73271                               | 4008321962690     | LUMINESTRA LUMILUX T5 8W 840  | White  | 8  | 342    | 70     | 20     | 4   | 38 |
| 73281                               | 4008321962706     | LUMINESTRA LUMILUX T5 13W 840 | White  | 13 | 555    | 70     | 20     | 4   | 38 |
| <b>LUMINESTRA EL - without lamp</b> |                   |                               |        |    |        |        |        |     |    |
| 73371                               | 4008321962751     | LUMINESTRA without lamp       | White  | 8  | 342    | 70     | 20     | 4   | 38 |
| 73381                               | 4008321962768     | LUMINESTRA without lamp       | White  | 13 | 555    | 70     | 20     | 4   | 38 |



All orders must be multiples of sales pack



## Indoor – Furniture Luminaires



|  |  |  |  |  |        |      |                  |          |
|--|--|--|--|--|--------|------|------------------|----------|
|  |  |  |  |  | 650 °C | IK03 | 230–240V         | 50–60 Hz |
|  |  |  |  |  |        | 827  | $\eta_{LB}$ 0.84 | G5       |

Quick start  
Programmable  
Energy saving  
Longer lamp life

**SLIMLITE® EL**

- Compact low profile furniture luminaire
- Equipped with LUMILUX® T5 tube
- Ready to install with 2m of cable and euro plug

| Product ID Code | EAN (Single Pack) | Product Description | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|---------------------|--------|----|--------|--------|--------|------|
| 73073W          | 4050300620145     | SLIMLITE EL 8W 827  | White  | 8  | 320    | 78     | 26     | 4 38 |
| 73083W          | 4050300620121     | SLIMLITE EL 13W 827 | White  | 13 | 550    | 78     | 26     | 4 38 |



|  |  |  |  |  |  |          |      |    |
|--|--|--|--|--|--|----------|------|----|
|  |  |  |  |  |  | 230–240V | 50Hz |    |
|  |  |  |  |  |  | 827      |      | G5 |

Quick start  
Programmable  
Energy saving  
Longer lamp life

**PICOLINE® EL**


- Miniature furniture luminaire brings light into the tightest of spaces
- Rotates through 360°
- Ready to install with 2m of cable and euro plug
- Equipped with LUMILUX® T5 tube or LUMILUX® T5 HE tube

| Product ID Code | EAN (Single Pack) | Product Description           | FINISH | W  | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|-------------------------------|--------|----|--------|--------|--------|------|
| 72041W          | 4050300499543     | PICOLINE EL 8W LUMILUX T5     | White  | 8  | 374    | 21     | 30     | 4 38 |
| 72042W          | 4050300499567     | PICOLINE EL 13W LUMILUX T5    | White  | 13 | 602    | 21     | 30     | 4 38 |
| 72043W          | 4050300593975     | PICOLINE EL 21W LUMILUX T5 HE | White  | 21 | 990    | 23     | 30     | 4 38 |

All orders must be multiples of sales pack



## Indoor – Furniture Luminaires


**LUMILUX® VARIO FM**

- Compact low profile furniture luminaire with integrated QUICKTRONIC® QT-FM electronic control gear
- With 360° rotary tube reflector for variable directional light
- Ready to install with 2m of cable and euro plug
- Equipped with LUMILUX® T2 FM® tube

| Product ID Code | EAN (Single Pack) | Product Description  | FINISH | W  | I<br>[mm] | b<br>[mm] | h<br>[mm] | PPG |    |
|-----------------|-------------------|----------------------|--------|----|-----------|-----------|-----------|-----|----|
| 72292W          | 4050300636351     | LUMILUX VARIO-FM 8W  | White  | 8  | 335       | 23        | 41        | 4   | 38 |
| 72293W          | 4050300636382     | LUMILUX VARIO-FM 11W | White  | 11 | 437       | 23        | 41        | 4   | 38 |
| 72294W          | 4050300636405     | LUMILUX VARIO-FM 13W | White  | 13 | 538       | 23        | 41        | 4   | 38 |



All orders must be multiples of sales pack

**INDOOR****RECESSED LUMINAIRES****LEDVANCE® Downlight M**

- Adjustable LED downlight fitting for replacement of classic MR16 50W low voltage halogen
- Average lifetime 50,000 hours
- 36° or 12° beam angle with external power supply
- Accessories: Decorative rings in anodized aluminium
- Ideal for halogen replacement downlighting

| Product ID Code                              | EAN (Single Pack) | Product Description                 | FINISH    | A° | W    | h [mm] | d [mm] | PPG |    |
|--|-------------------|-------------------------------------|-----------|----|------|--------|--------|-----|----|
| <b>LEDVANCE® Downlight M</b>                 |                   |                                     |           |    |      |        |        |     |    |
| LDV830WTL12                                  | 4008321968661     | LEDVANCE DOWNLIGHT M 830 L12 WT     | White     | 12 | 13.5 | 103    | 80     | 4   | 38 |
| LDV830WTL36                                  | 4008321968678     | LEDVANCE DOWNLIGHT M 830 L36 WT     | White     | 36 | 13.5 | 99     | 80     | 4   | 38 |
| LDV840WTL12                                  | 4008321968685     | LEDVANCE DOWNLIGHT M 840 L12 WT     | White     | 12 | 13.5 | 103    | 80     | 4   | 38 |
| LDV840WTL36                                  | 4008321968692     | LEDVANCE DOWNLIGHT M 840 L36 WT     | White     | 36 | 13.5 | 99     | 80     | 4   | 38 |
| <b>LEDVANCE® Downlight M DIM*</b>            |                   |                                     |           |    |      |        |        |     |    |
| -  | 4008321968708*    | LEDVANCE DOWNLIGHT M 830 L12 WT DIM | White     | 12 | 13.5 | 103    | 80     | 4   | 38 |
| -  | 4008321968715*    | LEDVANCE DOWNLIGHT M 830 L36 WT DIM | White     | 36 | 13.5 | 99     | 80     | 4   | 38 |
| -  | 4008321968722*    | LEDVANCE DOWNLIGHT M 840 L12 WT DIM | White     | 12 | 13.5 | 103    | 80     | 4   | 38 |
| -  | 4008321968739*    | LEDVANCE DOWNLIGHT M 840 L36 WT DIM | White     | 36 | 13.5 | 99     | 80     | 4   | 38 |
| <b>Accessories for LEDVANCE® Downlight M</b> |                   |                                     |           |    |      |        |        |     |    |
| LDVMRING                                     | 4008321968746     | LEDVANCE DOWNLIGHT M RING AL        | Aluminium | -  | -    | 8      | 80     | 4   | 38 |

\*In preparation at time of print. For further information please contact OSRAM


## LEDVANCE™ DOWNLIGHT M

Lighting Association's Domestic  
Product of the Year 2010

All orders must be multiples of sales pack



## Indoor – Recessed Luminaires



960 °C



220–240V

50-60 Hz

1000 lm

50 lm/W

&lt;1.5 years

**LEDVANCE® Downlight L**

- Adjustable LED downlight fitting for replacement of 1 x 26W compact fluorescent downlights
- 60° or 100° beam angles with integrated power supply
- Accessories: Decorative rings in anodized aluminium
- Ideal for downlighting

| Product ID Code | EAN (Single Pack) | Product Description              | FINISH       | W   | h [mm] | Ø [mm] | PPG |   |    |
|-----------------|-------------------|----------------------------------|--------------|-----|--------|--------|-----|---|----|
| LDVL830WTL60    | 4008321968753     | LEDVANCE DOWNLIGHT L 830 L60 WT  | White        | 60  | 20     | 102    | 140 | 4 | 38 |
| LDVL830WTL100   | 4008321968760     | LEDVANCE DOWNLIGHT L 830 L100 WT | White        | 100 | 20     | 102    | 140 | 4 | 38 |
| LDVL840WTL60    | 4008321968777     | LEDVANCE DOWNLIGHT L 840 L60 WT  | White        | 60  | 20     | 102    | 140 | 4 | 38 |
| LDVL840WTL100   | 4008321968784     | LEDVANCE DOWNLIGHT L 840 L100 WT | White        | 100 | 20     | 102    | 140 | 4 | 38 |
| LDVLRING        | 4008321968791     | LEDVANCE DOWNLIGHT L RING AL     | Alu          | —   | —      | 10     | 140 | 4 | 38 |
| —               | 4008321968807*    | LEDVANCE DOWNLIGHT L RING LA     | Anodised Alu | —   | —      | —      | —   | 4 | 38 |
| —               | 4008321968814*    | LEDVANCE DOWNLIGHT L RING LB     | Black        | —   | —      | —      | —   | 4 | 38 |



\*In preparation at time of print. For further information please contact OSRAM


All orders must be multiples of sales pack



Indoor – Recessed Luminaires



50-60 Hz



## LEDVANCE® Downlight XL

- Adjustable and dimmable LED downlight fitting for replacement of 2 x 26W compact fluorescent downlights
- 60° or 100° beam angles with integrated power supply
- Accessories: Decorative rings in anodized aluminium
- Ideal for downlighting

| Product ID Code                               | EAN (Single Pack) | Product Description                     | FINISH       | $\Delta$ | Im   | W  | $h$ [mm] | $d$ [mm] | PPG  |
|---|-------------------|---|--------------|----------|------|----|----------|----------|------|
| <b>LEDVANCE® Downlight XL</b>                 |                   |   |              |          |      |    |          |          |      |
| LDVXL830WTL60                                 | 4008321968821     | LEDVANCE DOWNLIGHT XL 830 L60 WT        | White        | 60       | 1600 | 32 | 150      | 195      | 4 38 |
| LDVXL830WTL100                                | 4008321968838     | LEDVANCE DOWNLIGHT XL 830 L100 WT       | White        | 100      | 1600 | 32 | 150      | 195      | 4 38 |
| LDVXL840WTL60                                 | 4008321968845     | LEDVANCE DOWNLIGHT XL 840 L60 WT        | White        | 60       | 1600 | 32 | 150      | 195      | 4 38 |
| LDVXL840WTL100                                | 4008321968852     | LEDVANCE DOWNLIGHT XL 840 L100 WT       | White        | 100      | 1600 | 32 | 150      | 195      | 4 38 |
| <b>LEDVANCE® Downlight XL DALI</b>            |                   |   |              |          |      |    |          |          |      |
| -   | 4008321968869     | LEDVANCE DOWNLIGHT XL 830 L60 WT DALI*  | White        | 60       | 2000 | 32 | 150      | 195      | 4 38 |
| -   | 4008321968876     | LEDVANCE DOWNLIGHT XL 830 L100 WT DALI* | White        | 100      | 2000 | 32 | 150      | 195      | 4 38 |
| -   | 4008321968883     | LEDVANCE DOWNLIGHT XL 840 L60 WT DALI*  | White        | 60       | 2000 | 32 | 150      | 195      | 4 38 |
| -   | 4008321968890     | LEDVANCE DOWNLIGHT XL 840 L100 WT DALI* | White        | 100      | 2000 | 32 | 150      | 195      | 4 38 |
| <b>Accessories for LEDVANCE® Downlight XL</b> |                   |   |              |          |      |    |          |          |      |
| LDVXLRING                                     | 4008321968906     | LEDVANCE DOWNLIGHT XL RING AL           | Alu          | -        | -    | -  | 6        | 195      | 4 38 |
| -   | 4008321968913*    | LEDVANCE DOWNLIGHT XL RING LA           | Anodised Alu | -        | -    | -  | -        | 4        | 38   |
| -   | 4008321968920*    | LEDVANCE DOWNLIGHT XL RING LB           | Black        | -        | -    | -  | -        | 4        | 38   |


\*In preparation at time of print. For further information please contact OSRAM

50 lm/W

70 lm/W



## Indoor – Recessed Luminaires

**KIT LED PRO**

- Ready to install luminaire kit (pre wired luminaire containing lamp and ECG)
- Containing one white GU10 LED PARATHOM® PAR 16 4.5W
- Two versions round or square
- Ideal for interior illumination in retail, hotel and restaurant lighting

| Product ID Code | EAN (Single Pack) | Product Description    | FINISH         | W   | I [mm] | b [mm] | h [mm] | Ø [mm] | d [mm] | PPG |
|-----------------|-------------------|------------------------|----------------|-----|--------|--------|--------|--------|--------|-----|
| LEDPROKITRBRN15 | 4008321963284     | KIT LED PRO R 1 X 4.5W | Brushed Nickel | 4.5 | –      | –      | 90     | 91     | 6      | 38  |
| LEDPROKITSBRN15 | 4008321963291     | KIT LED PRO S 1 X 4.5W | Brushed Nickel | 4.5 | 91     | 91     | 90     | –      | 6      | 38  |


NEW  
NEW



All orders must be multiples of sales pack



## Indoor – Recessed Luminaires

**DOWNLIGHT KIT HCI® R111**

- Ready to install kit containing a downlight, POWERBALL® HCI R111 metal halide lamp and POWERTRONIC® PTi ECG
- Provides flicker free light with brilliant colour rendering
- Simple to install due to twist and lock interlock for the lamp
- Ideal for shoplighting, museums and exhibition lighting

| Product ID Code | EAN (Single Pack) | Product Description                      | FINISH | A  | W  | h [mm] | d [mm] | PPG  |
|-----------------|-------------------|--|--------|----|----|--------|--------|------|
| 7608125         | 4008321929594     | DOWNLIGHT KIT HCI R111 White 35W WDL 10° | White  | 10 | 35 | 90     | 155    | 2 38 |
| 7608126         | 4008321929624     | DOWNLIGHT KIT HCI R111 White 35W WDL 24° | White  | 24 | 35 | 90     | 155    | 2 38 |
| 7608127         | 4008321929655     | DOWNLIGHT KIT HCI R111 White 35W WDL 40° | White  | 40 | 35 | 90     | 155    | 2 38 |
| 7608225         | 4008321929860     | DOWNLIGHT KIT HCI R111 Grey 35W WDL 10°  | Grey   | 10 | 35 | 90     | 155    | 2 38 |
| 7608226         | 4008321929891     | DOWNLIGHT KIT HCI R111 Grey 35W WDL 24°  | Grey   | 24 | 35 | 90     | 155    | 2 38 |
| 7608227         | 4008321929921     | DOWNLIGHT KIT HCI R111 Grey 35W WDL 40°  | Grey   | 40 | 35 | 90     | 155    | 2 38 |
| 7608121         | 4008321929778     | DOWNLIGHT KIT HCI R111 White 35W NDL 10° | White  | 10 | 35 | 90     | 155    | 2 38 |
| 7608122         | 4008321929839     | DOWNLIGHT KIT HCI R111 White 35W NDL 24° | White  | 24 | 35 | 90     | 155    | 2 38 |
| 7608123         | 4008321929808     | DOWNLIGHT KIT HCI R111 White 35W NDL 40° | White  | 40 | 35 | 90     | 155    | 2 38 |
| 7608221         | 4008321929952     | DOWNLIGHT KIT HCI R111 Grey 35W NDL 10°  | Grey   | 10 | 35 | 90     | 155    | 2 38 |
| 7608222         | 4008321929983     | DOWNLIGHT KIT HCI R111 Grey 35W NDL 24°  | Grey   | 24 | 35 | 90     | 155    | 2 38 |
| 7608223         | 4008321930019     | DOWNLIGHT KIT HCI R111 Grey 35W NDL 40°  | Grey   | 40 | 35 | 90     | 155    | 2 38 |
| 7608325         | 4008321929617     | DOWNLIGHT KIT HCI R111 White 70W WDL 10° | White  | 10 | 70 | 90     | 155    | 2 38 |
| 7608326         | 4008321929679     | DOWNLIGHT KIT HCI R111 White 70W WDL 24° | White  | 24 | 70 | 90     | 155    | 2 38 |
| 7608327         | 4008321929730     | DOWNLIGHT KIT HCI R111 White 70W WDL 40° | White  | 40 | 70 | 90     | 155    | 2 38 |
| 7608425         | 4008321929884     | DOWNLIGHT KIT HCI R111 Grey 70W WDL 10°  | Grey   | 10 | 70 | 90     | 155    | 2 38 |
| 7608426         | 4008321929945     | DOWNLIGHT KIT HCI R111 Grey 70W WDL 24°  | Grey   | 24 | 70 | 90     | 155    | 2 38 |
| 7608427         | 4008321930002     | DOWNLIGHT KIT HCI R111 Grey 70W WDL 40°  | Grey   | 40 | 70 | 90     | 155    | 2 38 |
| 7608321         | 4008321929686     | DOWNLIGHT KIT HCI R111 White 70W NDL 10° | White  | 10 | 70 | 90     | 155    | 2 38 |
| 7608322         | 4008321929716     | DOWNLIGHT KIT HCI R111 White 70W NDL 24° | White  | 24 | 70 | 90     | 155    | 2 38 |
| 7608323         | 4008321929747     | DOWNLIGHT KIT HCI R111 White 70W NDL 40° | White  | 40 | 70 | 90     | 155    | 2 38 |
| 7608421         | 4008321930040     | DOWNLIGHT KIT HCI R111 Grey 70W NDL 10°  | Grey   | 10 | 70 | 90     | 155    | 2 38 |
| 7608422         | 4008321930071     | DOWNLIGHT KIT HCI R111 Grey 70W NDL 24°  | Grey   | 24 | 70 | 90     | 155    | 2 38 |
| 7608423         | 4008321930101     | DOWNLIGHT KIT HCI R111 Grey 70W NDL 40°  | Grey   | 40 | 70 | 90     | 155    | 2 38 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack



## Indoor – Recessed Luminaires



Rx7s



1)

**KIT DOWNLIGHT HQI®-TS EXCELLENCE**

- Non dimmable luminaire kit consisting of a downlight, POWERSTAR® HQI® TS excellence metal halide lamp and POWERTRONIC® ECG
- In 3 versions: Round, Square and Mini Round in 3 light colours 3000K (WDL), 4200K (NDL) 5600K (D)
- Square version swivels through 45°
- Ideal for shop illumination and foyers

| Product ID Code | EAN (Single Pack) | Product Description | FINISH | W | I [mm] | b [mm] | h [mm] | d [mm] | PPG |
|-----------------|-------------------|---------------------|--------|---|--------|--------|--------|--------|-----|
|-----------------|-------------------|---------------------|--------|---|--------|--------|--------|--------|-----|

**Square Version**

|         |               |   |       |     |     |     |     |   |   |    |
|---------|---------------|---|-------|-----|-----|-----|-----|---|---|----|
| 7609521 | 4008321391766 | KIT DOWNLIGHT HQI-TS EXCELLENCE SQUARE 70W WDL  | White | 70  | 240 | 142 | 130 | – | 2 | 38 |
| 7609523 | 4008321391780 | KIT DOWNLIGHT HQI-TS EXCELLENCE SQUARE 70W NDL  | White | 70  | 240 | 142 | 130 | – | 2 | 38 |
| 7609525 | 4008321391803 | KIT DOWNLIGHT HQI-TS EXCELLENCE SQUARE 70W D    | White | 70  | 240 | 142 | 130 | – | 2 | 38 |
| 7609721 | 4008321391841 | KIT DOWNLIGHT HQI-TS EXCELLENCE SQUARE 150W WDL | White | 150 | 240 | 142 | 130 | – | 2 | 38 |
| 7609723 | 4008321391865 | KIT DOWNLIGHT HQI-TS EXCELLENCE SQUARE 150W WDL | White | 150 | 240 | 142 | 130 | – | 2 | 38 |
| 7609725 | 4008321391889 | KIT DOWNLIGHT HQI-TS EXCELLENCE SQUARE 150W D   | White | 150 | 240 | 142 | 130 | – | 2 | 38 |

**Round Version**

|         |               |  |       |     |   |   |     |     |   |    |
|---------|---------------|--|-------|-----|---|---|-----|-----|---|----|
| 7609121 | 4008321391605 | KIT DOWNLIGHT HQI-TS EXCELLENCE ROUND 70W WDL  | White | 70  | – | – | 110 | 230 | 2 | 38 |
| 7609123 | 4008321391629 | KIT DOWNLIGHT HQI-TS EXCELLENCE ROUND 70W NDL  | White | 70  | – | – | 110 | 230 | 2 | 38 |
| 7609125 | 4008321391643 | KIT DOWNLIGHT HQI-TS EXCELLENCE ROUND 70W D    | White | 70  | – | – | 110 | 230 | 2 | 38 |
| 7609321 | 4008321391667 | KIT DOWNLIGHT HQI-TS EXCELLENCE ROUND 150W WDL | White | 150 | – | – | 110 | 230 | 2 | 38 |
| 7609323 | 4008321391704 | KIT DOWNLIGHT HQI-TS EXCELLENCE ROUND 150W NDL | White | 150 | – | – | 110 | 230 | 2 | 38 |
| 7609325 | 4008321391728 | KIT DOWNLIGHT HQI-TS EXCELLENCE ROUND 150W D   | White | 150 | – | – | 110 | 230 | 2 | 38 |

**Mini Round Version**

|         |               |  |       |    |   |   |    |     |   |    |
|---------|---------------|--|-------|----|---|---|----|-----|---|----|
| 7609921 | 4008321391902 | KIT DOWNLIGHT HQI-TS EXCELLENCE MINI ROUND 70W WDL | WDL   | 70 | – | – | 93 | 166 | 4 | 38 |
| 7609923 | 4008321391926 | KIT DOWNLIGHT HQI-TS EXCELLENCE MINI ROUND 70W NDL | White | 70 | – | – | 93 | 166 | 4 | 38 |
| 7609925 | 4008321391940 | KIT DOWNLIGHT HQI-TS EXCELLENCE MINI ROUND 70W D   | White | 70 | – | – | 93 | 166 | 4 | 38 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack



Indoor – Recessed Luminaires



## DOWNLIGHT KIT HALOSPOT® R111 ECO

- Downlight Kit containing HALOSPOT® R111 ECO and HALOTRONIC® MOUSE HTM
- Available in 8°, 24°, 45° beam angle
- Two luminaire colours: white and silver grey
- Ideal for accent lighting, shoplighting, museums and exhibitions

| Product ID Code | EAN (Single Pack) | Product Description                    | FINISH      | Α° | W  | h [mm] | Ø [mm] | PPG  |
|-----------------|-------------------|--|-------------|----|----|--------|--------|------|
| 7608521         | 4008321330734     | DOWNLIGHT KIT HALOSPOT 111 ES 35W, 8°  | White       | 8  | 35 | 90     | 155    | 2 38 |
| 7608522         | 4008321335920     | DOWNLIGHT KIT HALOSPOT 111 ES 35W, 24° | White       | 24 | 35 | 90     | 155    | 2 38 |
| 7608523         | 4008321335944     | DOWNLIGHT KIT HALOSPOT 111 ES 50W, 8°  | White       | 8  | 50 | 90     | 155    | 2 38 |
| 7608524         | 4008321335968     | DOWNLIGHT KIT HALOSPOT 111 ES 50W, 24° | White       | 24 | 50 | 90     | 155    | 2 38 |
| 7608525         | 4008321335982     | DOWNLIGHT KIT HALOSPOT 111 ES 50W, 45° | White       | 45 | 50 | 90     | 155    | 2 38 |
| 7608526         | 4008321336002     | DOWNLIGHT KIT HALOSPOT 111 ES 65W, 8°  | White       | 8  | 65 | 90     | 155    | 2 38 |
| 7608527         | 4008321336026     | DOWNLIGHT KIT HALOSPOT 111 ES 65W, 24° | White       | 24 | 65 | 90     | 155    | 2 38 |
| 7608528         | 4008321336040     | DOWNLIGHT KIT HALOSPOT 111 ES 65W, 45° | White       | 45 | 65 | 90     | 155    | 2 38 |
| 7608621         | 4008321330758     | DOWNLIGHT KIT HALOSPOT 111 ES 35W, 8°  | Silver Grey | 8  | 35 | 90     | 155    | 2 38 |
| 7608622         | 4008321336064     | DOWNLIGHT KIT HALOSPOT 111 ES 35W, 24° | Silver Grey | 24 | 35 | 90     | 155    | 2 38 |
| 7608623         | 4008321336088     | DOWNLIGHT KIT HALOSPOT 111 ES 50W, 8°  | Silver Grey | 8  | 50 | 90     | 155    | 2 38 |
| 7608624         | 4008321336101     | DOWNLIGHT KIT HALOSPOT 111 ES 50W, 24° | Silver Grey | 24 | 50 | 90     | 155    | 2 38 |
| 7608625         | 4008321336125     | DOWNLIGHT KIT HALOSPOT 111 ES 50W, 45° | Silver Grey | 45 | 50 | 90     | 155    | 2 38 |
| 7608626         | 4008321336149     | DOWNLIGHT KIT HALOSPOT 111 ES 65W, 8°  | Silver Grey | 8  | 65 | 90     | 155    | 2 38 |
| 7608627         | 4008321336163     | DOWNLIGHT KIT HALOSPOT 111 ES 65W, 24° | Silver Grey | 24 | 65 | 90     | 155    | 2 38 |
| 7608628         | 4008321336187     | DOWNLIGHT KIT HALOSPOT 111 ES 65W, 45° | Silver Grey | 45 | 65 | 90     | 155    | 2 38 |

1) For more information go to [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

All orders must be multiples of sales pack



## Indoor – Recessed Luminaires



|  |  |  |      |  |        |      |  |           |          |
|--|--|--|------|--|--------|------|--|-----------|----------|
|  |  |  | IP23 |  | 960 °C | IK02 |  | 220–240 V | 50–60 Hz |
|  |  |  |      |  |        |      |  | GU5.3     |          |
|  |  |  |      |  |        |      |  |           |          |

**KIT HALO ECO**

- Cost effective ready to install luminaire kit (Prewired luminaire containing 50W DECASTAR® standard)
- Lamp swivels through 40°
- Ideal for illuminating shop windows, retail outlets and corridor lighting

| Product ID Code | EAN (Single Pack) | Product Description        | FINISH |    | W  |    |    |      |    |
|-----------------|-------------------|----------------------------|--------|----|----|----|----|------|----|
| HALEOKIT150WT   | 4008321390806     | KIT HALO ECO ROUND 1 X 50W | White  | 40 | 50 | 74 | 82 | 24X1 | 38 |

NEW

|  |  |  |      |  |        |      |  |           |          |
|--|--|--|------|--|--------|------|--|-----------|----------|
|  |  |  | IP23 |  | 960 °C | IK02 |  | 220–240 V | 50–60 Hz |
|  |  |  |      |  |        |      |  | GU5.3     |          |
|  |  |  |      |  |        |      |  |           |          |

**KIT HALO PRO**

- Ready to install luminaire kit (Pre wired luminaire containing lamp and ECG)
- Containing a halogen DECASTAR® GU5.3 35W ECO
- Two versions round or square
- Ideal for interior illumination in retail, hotel and restaurant lighting


| Product ID Code       | EAN (Single Pack) | Product Description     | FINISH         |    | W  |    |    |    |    |   |    |
|-----------------------|-------------------|-------------------------|----------------|----|----|----|----|----|----|---|----|
| <b>Round version</b>  |                   |                         |                |    |    |    |    |    |    |   |    |
| HALPROKITRW735        | 4008321398628     | KIT HALO PRO R 1 X 35 W | White          | 36 | 35 | —  | —  | 74 | 91 | 6 | 38 |
| HALPROKITRW735        | 4008321445537     | KIT HALO PRO R 3 X 35 W | White          | 36 | 35 | —  | —  | 74 | 91 | 6 | 38 |
| HALPROKITRBRN135      | 4008321398642     | KIT HALO PRO R 1 X 35 W | Brushed Nickel | 36 | 35 | —  | —  | 74 | 91 | 6 | 38 |
| HALPROKITRBRN135      | 4008321445551     | KIT HALO PRO R 3 X 35 W | Brushed Nickel | 36 | 35 | —  | —  | 74 | 91 | 6 | 38 |
| <b>Square version</b> |                   |                         |                |    |    |    |    |    |    |   |    |
| HALPROKITSWT35        | 4008321398987     | KIT HALO PRO S 1 X 35 W | White          | 36 | 35 | 91 | 91 | 74 | —  | 6 | 38 |
| HALPROKITSWT35        | 4008321445575     | KIT HALO PRO S 3 X 35 W | White          | 36 | 35 | 91 | 91 | 74 | —  | 6 | 38 |
| HALPROKITSBRN135      | 4008321399007     | KIT HALO PRO S 1 X 35 W | Brushed Nickel | 36 | 35 | 91 | 91 | 74 | —  | 6 | 38 |
| HALPROKITSBRN135      | 4008321445599     | KIT HALO PRO S 3 X 35 W | Brushed Nickel | 36 | 35 | 91 | 91 | 74 | —  | 6 | 38 |



All orders must be multiples of sales pack




## Indoor – Recessed Luminaires

DOLCE MARE  
Ricchezza  
Eleganza  
Lusso**KIT HALO PRO HYDRO**

- Ready to install luminaire kit (Pre wired luminaire containing lamp and ECG)
- Containing a halogen DECOSTAR® GU5.3 35W 12V energy saver
- New recessed spot for fix illumination in humidity areas
- IP24 rated for humid areas
- Two versions round or square
- Ideal for bathroom lighting, showers, kitchens, changing rooms

| Product ID Code       | EAN (Single Pack) | Product Description        | FINISH | W  | $\overline{I}$ [mm] | b [mm] | $\overline{h}$ [mm] | d [mm] | PPG |   |    |
|-----------------------|-------------------|----------------------------|--------|----|---------------------|--------|---------------------|--------|-----|---|----|
| <b>Round version</b>  |                   |                            |        |    |                     |        |                     |        |     |   |    |
| HALHYDROKITRWT35      | 4008321399045     | KIT HP HYDRO R 1 X 35      | White  | 36 | 35                  | —      | —                   | 74     | 91  | 6 | 38 |
| HALHYDRKITRWT355      | 4008321445636     | KIT HP HYDRO R 3 X 35      | White  | 36 | 35                  | —      | —                   | 74     | 91  | 6 | 38 |
| HALHYDROKITRBRNI35    | 4008321399069     | KIT HP HYDRO R 1 X 35      | Nickel | 36 | 35                  | —      | —                   | 74     | 91  | 6 | 38 |
| HALHYDRKITRBRNI355    | 4008321445650     | KIT HP HYDRO R 3 X 35      | Nickel | 36 | 35                  | —      | —                   | 74     | 91  | 6 | 38 |
| <b>Square version</b> |                   |                            |        |    |                     |        |                     |        |     |   |    |
| HALHYDROKITSWT35      | 4008321399083     | KIT HP HYDRO S 1 X 35      | White  | 36 | 35                  | 91     | 91                  | 74     | —   | 6 | 38 |
| HALHYDRKITSWT355      | 4008321445674     | KIT HP HYDRO S 3 X 35      | White  | 36 | 35                  | 91     | 91                  | 74     | —   | 6 | 38 |
| HALHYDROKITSBRNI35    | 4008321399106     | KIT HP HYDRO S 1 X 35      | Nickel | 36 | 35                  | 91     | 91                  | 74     | —   | 6 | 38 |
| HALHYDRKITSBRNI355    | 4008321445698     | KIT HP HYDRO S 3 X 35      | Nickel | 36 | 35                  | 91     | 91                  | 74     | —   | 6 | 38 |
| KITHALHYDRO135        | 4008321552570     | KIT HP HYDRO FIX 1X35 IP65 | White  | 36 | 35                  | —      | —                   | —      | —   | 6 | 38 |

NEW

DOLCE MARE  
Ricchezza  
Eleganza  
Lusso**JADE KIT ECO HF**


- Ready to install low profile luminaire kit
- Containing 1 QT ECO T/E electronic control gear and two OSRAM DULUX® D/E lamps
- Ideal for retail outlets, reception areas, offices and corridors

| Product ID Code   | EAN (Single Pack) | Product Description           | FINISH | W    | $\overline{h}$ [mm] | d [mm] | PPG    |
|-------------------|-------------------|-------------------------------|--------|------|---------------------|--------|--------|
| JADEKITECO218     | 4008321963246     | JADE KIT ECO WT 2X18W IP20    | White  | 2X18 | 110                 | 225    | 2x1 38 |
| JADEKITECO218DIFF | 4008321963260     | JADE KIT ECO Shield 2X18 IP40 | White  | 2X18 | 110                 | 225    | 2x1 38 |
| JADEKITECO226     | 4008321387660     | JADE KIT ECO WT 2X26W IP20    | White  | 2X18 | 110                 | 225    | 2x1 38 |
| JADEKITECO226DIFF | 4008321391513     | JADE KIT ECO Shield 2X26 IP40 | White  | 2X18 | 110                 | 225    | 2x1 38 |

All orders must be multiples of sales pack



## Indoor – Recessed Luminaires

**OSRAM DEDRA plus® T5 KIT**

- Ready to install luminaire kit (Pre wired luminaire containing lamp and ECG)
- Double parabolic optics for a symmetrical reflector
- Available in frosted and polished versions for very low luminance
- Containing three or four LUMILUX® T5 HE high efficiency tubes
- Ideal for background lighting in offices, schools and conference rooms

| Product ID Code | EAN (Single Pack) | Product Description | FINISH | W | I<br>[mm] | b<br>[mm] | h<br>[mm] | PPG |
|-----------------|-------------------|---------------------|--------|---|-----------|-----------|-----------|-----|
|-----------------|-------------------|---------------------|--------|---|-----------|-----------|-----------|-----|

**DPB DALI version**

- Comprising a symmetrical longitudinal reflector and louvre with a polished finish
- Integrated QTi DALI DIM control gear

|                     |               |                                  |       |      |     |     |    |   |    |
|---------------------|---------------|----------------------------------|-------|------|-----|-----|----|---|----|
| DEDT5DPB3X14DALI    | 4008321380852 | DEDRA T5 DPB KIT 3 x 14/840 DALI | White | 3x14 | 596 | 596 | 52 | 1 | 38 |
| DEDT5DPB4X14DALI    | 4008321380883 | DEDRA T5 DPB KIT 4 x 14/840 DALI | White | 4x14 | 596 | 596 | 52 | 1 | 38 |
| DEDT5DPB4X14830DALI | 4008321533555 | DEDRA T5 DPB KIT 4 x 14/830 DALI | White | 4x14 | 596 | 596 | 52 | 1 | 38 |

**DPB-C WIELAND version**

- Comprising a symmetrical longitudinal reflector and louvre with a frosted finish
- DPB C kit with WIELAND connector
- Integrated electronic control gear QT-FH 3x14W or 4x14W

|                    |               |  |       |      |     |     |    |   |    |
|--------------------|---------------|--|-------|------|-----|-----|----|---|----|
| DEDT5DPBC3X14WIELA | 4008321380890 | DEDRA T5 DPB-C kit 3x14W/840 WIELAND Frosted | White | 3x14 | 596 | 596 | 52 | 1 | 38 |
|--------------------|---------------|--|-------|------|-----|-----|----|---|----|

**DPB version**

- Comprising a symmetrical longitudinal reflector and louvre in a polished or frosted finish
- Integrated electronic control gear QT-FH 3X14W or 4X14W

|                  |               |  |       |      |     |     |    |   |    |
|------------------|---------------|--|-------|------|-----|-----|----|---|----|
| DEDT5DPBC3X14840 | 4008321366696 | DEDRA T5 DPB C kit 3x14W/840 – Frosted | White | 3x14 | 596 | 596 | 52 | 1 | 38 |
| DEDT5DPBC4X14840 | 4008321366726 | DEDRA T5 DPB C kit 4x14W/840 – Frosted | White | 4x14 | 596 | 596 | 52 | 1 | 38 |
| DEDT5DPB3X14830  | 4008321366689 | DEDRA T5 DPB kit 3x14W/830 – Polished  | White | 3x14 | 596 | 596 | 52 | 1 | 38 |
| DEDT5DPB3X14840  | 4008321366672 | DEDRA T5 DPB kit 3x14W/840 – Polished  | White | 3x14 | 596 | 596 | 52 | 1 | 38 |
| DEDT5DPB4X14830  | 4008321366719 | DEDRA T5 DPB kit 4x14W/830 – Polished  | White | 4x14 | 596 | 596 | 52 | 1 | 38 |
| DEDT5DPB4X14840  | 4008321366702 | DEDRA T5 DPB kit 4x14W/840 – Polished  | White | 4x14 | 596 | 596 | 52 | 1 | 38 |

**DPB -VABS version**

- Double parabolic optics for a symmetrical V reflector
- Integrated electronic control gear QT-FH 3X14W or 4X14W


|               |               |                             |       |      |     |     |    |   |    |
|---------------|---------------|-----------------------------|-------|------|-----|-----|----|---|----|
| DEDT5VABS4X14 | 4008321380937 | DEDRA T5 VABS kit 4x14W/840 | White | 4x14 | 596 | 596 | 52 | 1 | 38 |
|---------------|---------------|-----------------------------|-------|------|-----|-----|----|---|----|



All orders must be multiples of sales pack



## Indoor – Recessed Luminaires



|  |  |      |  |          |      |           |
|--|--|------|--|----------|------|-----------|
|  |  | IP20 |  | 850 °C   | IK07 | 230–240 V |
|  |  |      |  | 50–60 Hz |      | G13       |

**OSRAM DEDRA plus® T8 KIT**

- Ready to install luminaire kit (Pre wired luminaire containing lamp and ECG)
- Double parabolic optics for a symmetrical reflector
- Available in frosted and polished versions for very low luminance
- Containing LUMILUX® T8 lamps
- Ideal for background lighting in offices, schools and conference rooms

| Product ID Code | EAN (Single Pack) | Product Description | FINISH | W |  |  |  | PPG |
|-----------------|-------------------|---------------------|--------|---|--|--|--|-----|
|-----------------|-------------------|---------------------|--------|---|--|--|--|-----|

**OSRAM DEDRA plus® T8 KIT- DPTB**

- Double parabolic optics for a symmetrical reflector
- Integrated electronic control gear QTP 4X18W

|                  |               |                                     |       |      |     |     |     |   |    |
|------------------|---------------|-------------------------------------|-------|------|-----|-----|-----|---|----|
| DEDT8DPTB4X18830 | 4008321526502 | DEDRA T8 DPTB KIT 4x18/830 polished | White | 4x18 | 596 | 596 | 130 | 1 | 38 |
| DEDT8DPTB4X18840 | 4008321526496 | DEDRA T8 DPTB KIT 4x18/840 polished | White | 4x18 | 596 | 596 | 130 | 1 | 38 |

**OSRAM DEDRA plus® T8 KIT (VATS/VABS/VB)**

- Double parabolic optics for a symmetrical V reflector
- Integrated electronic control gear QTP 4X18W
- Available in brilliant aluminium reflector finish, satin aluminium or white finish

|                  |               |   |       |      |     |     |     |   |    |
|------------------|---------------|---|-------|------|-----|-----|-----|---|----|
| -                | 4008312526526 | DEDRA T8 VATS KIT 4x18W/830 Satin Alu reflector*    | White | 4x18 | 596 | 596 | 130 | 1 | 38 |
| -                | 4008312526519 | DEDRA T8 VATS KIT 4x18W/840 Satin Alu reflector*    | White | 4x18 | 596 | 596 | 130 | 1 | 38 |
| DEDT8VABS4X18830 | 4008321526540 | DEDRA T8 VABS KIT 4x18W/830 Brilliant Alu reflector | White | 4x18 | 596 | 596 | 130 | 1 | 38 |
| DEDT8VABS4X18840 | 4008321526533 | DEDRA T8 VABS KIT 4x18W/840 Brilliant Alu reflector | White | 4x18 | 596 | 596 | 130 | 1 | 38 |
| DEDT8VB4X18840   | 4008321526557 | DEDRA T8 VB KIT 4x18W/840 White reflector           | White | 4x18 | 596 | 596 | 130 | 1 | 38 |

\*In preparation at time of print. For further information please contact OSRAM




All orders must be multiples of sales pack

## Indoor – Recessed Luminaires



**CE** **IP20** **850 °C** **IK07** **230V** **50Hz**  $\eta_{LB}$  **0.45** **2G11**



**electronic comfort light** Smart Light Faster Response Energy Saving Longer Lifespan

**DELTA**

- Recessed ceiling luminaire with integrated electronic control gear for compact fluorescent lamps
- Suitable for two OSRAM DULUX® L 36W or 55W lamps
- Kit version includes lamps with light colour 840 or 830
- White painted parabolic reflector

| Product ID Code              | EAN (Single Pack) | Product Description       | FINISH | W    | I<br>[mm] | b<br>[mm] | h<br>[mm] | PPG  |
|------------------------------|-------------------|---------------------------|--------|------|-----------|-----------|-----------|------|
| <b>DELTA KIT – with lamp</b> |                   |                           |        |      |           |           |           |      |
| DELTAKIT36840                | 4008321126504     | DELTA KIT 2 x 36W Col 840 | White  | 2x36 | 596       | 596       | 118       | 1 38 |
| DELTAKIT36830                | 4008321126511     | DELTA KIT 2 x 36W Col 830 | White  | 2x36 | 596       | 596       | 118       | 1 38 |
| DELTAKIT55840                | 4008321126924     | DELTA KIT 2 x 55W Col 840 | White  | 2x55 | 596       | 596       | 118       | 1 38 |
| DELTAKIT55830                | 4008321126931     | DELTA KIT 2 x 55W Col 830 | White  | 2x55 | 596       | 596       | 118       | 1 38 |
| <b>DELTA – without lamp</b>  |                   |                           |        |      |           |           |           |      |
| DELTAIID2X36                 | 4050300188850     | DELTA 2 x 36W             | White  | 2x36 | 596       | 596       | 118       | 1 38 |
| DELTAIID2X55                 | 4050300188867     | DELTA 2 x 55W             | White  | 2x55 | 596       | 596       | 118       | 1 38 |
| DELTAIID2X36DIM              | 4050300188836     | DELTA 2 x 36W DIM         | White  | 2x36 | 596       | 596       | 118       | 1 38 |
| DELTAIID2X55DIM              | 4050300188843     | DELTA 2 x 55W DIM         | White  | 2x55 | 596       | 596       | 118       | 1 38 |



All orders must be multiples of sales pack



## INDOOR

### DAMP PROOF LUMINAIRES



**electronic comfort light**

#### ORCA PLUS for T5


- Extremely robust jet proof luminaire for suspended or ceiling mounting
- Suitable for LUMILUX® T5 HO CONSTANT fluorescent lamps and equipped with QTP5 ECG
- Polyester casing with 22% fibre glass, PMMA coating with stainless steel fastenings
- Ideal for functional lighting in wet or damp and dusty rooms such as workshops, garages, swimming pools and petrol stations

| Product ID Code | EAN (Single Pack) | Product Description      | FINISH           | W    | I [mm] | b [mm] | h [mm] | PPG |    |
|-----------------|-------------------|--------------------------|------------------|------|--------|--------|--------|-----|----|
| ORCAPMMA1X54    | 4008321193124     | ORCA PLUS for T5 54W     | Grey/Transparent | 54   | 1276   | 115    | 105    | 1   | 38 |
| ORCAPMMA1X80    | 4008321193131     | ORCA PLUS for T5 80W     | Grey/Transparent | 80   | 1576   | 115    | 105    | 1   | 38 |
| ORCAPMMA2X54    | 4008321193148     | ORCA PLUS for T5 2 x 54W | Grey/Transparent | 2x54 | 185    | 185    | 105    | 1   | 38 |
| ORCAPMMA2X80    | 4008321193155     | ORCA PLUS for T5 2 x 80W | Grey/Transparent | 2x80 | 185    | 185    | 105    | 1   | 38 |



All orders must be multiples of sales pack

## Indoor – Damp Proof Luminaires



**electronic comfort light**

**ORCA PLUS for T8**

- Extremely robust jet proof luminaire for suspended or ceiling mounting
- Suitable for LUMILUX® T8 fluorescent lamps and equipped with QTP8 ECG
- Polyester casing with 22% fibre glass, PMMA coating with stainless steel fastenings
- Ideal for functional lighting in wet or damp and dusty rooms such as workshops, garages, swimming pools and petrol stations

| Product ID Code         | EAN (Single Pack) | Product Description                       | FINISH           | W    | I<br>[mm] | b<br>[mm] | h<br>[mm] | PPG  |
|-------------------------|-------------------|---|------------------|------|-----------|-----------|-----------|------|
| <b>Polyester Casing</b> |                   |   |                  |      |           |           |           |      |
| ORCAPP1X36              | 4008321193087     | ORCA PLUS for T8 36W Polyester Casing     | Grey/Transparent | 36   | 1276      | 115       | 105       | 1 38 |
| ORCAPP1X58              | 4008321193094     | ORCA PLUS for T8 58W Polyester Casing     | Grey/Transparent | 58   | 1576      | 115       | 105       | 1 38 |
| ORCAPP2X36              | 4008321193100     | ORCA PLUS for T8 2 x 36W Polyester Casing | Grey/Transparent | 2x36 | 185       | 185       | 105       | 1 38 |
| ORCAPP2X58              | 4008321193117     | ORCA PLUS for T8 2 x 58W Polyester Casing | Grey/Transparent | 2x58 | 185       | 185       | 105       | 1 38 |
| <b>PMMA coating</b>     |                   |   |                  |      |           |           |           |      |
| ORCAPMMA1X36            | 4008321193049     | ORCA PLUS for T8 36W PMMA coating         | Grey/Transparent | 36   | 1276      | 115       | 105       | 1 38 |
| ORCAPMMA1X58            | 4008321193056     | ORCA PLUS for T8 58W PMMA coating         | Grey/Transparent | 58   | 1576      | 115       | 105       | 1 38 |
| ORCAPMMA2X36            | 4008321193063     | ORCA PLUS for T8 2 x 36W PMMA coating     | Grey/Transparent | 2x36 | 185       | 185       | 105       | 1 38 |
| ORCAPMMA2X58            | 4008321193070     | ORCA PLUS for T8 2 x 58W PMMA coating     | Grey/Transparent | 2x58 | 185       | 185       | 105       | 1 38 |



All orders must be multiples of sales pack



## Indoor – Damp Proof Luminaires



## NEPTUNE® POLYCARBONATE

- Extremely robust jet proof luminaire providing permanent seals, high resistance with a functional design
- Suitable for LUMILUX® T8 fluorescent lamps and equipped with QTS or QTP ECG
- Ideal for industrial and storage facilities, car parks and underpasses

| Product ID Code                               | EAN (Single Pack) | Product Description             | FINISH | W    | I [mm] | b [mm] | h [mm] | PPG       |
|---|-------------------|---------------------------------|--------|------|--------|--------|--------|-----------|
| <b>NEPTUNE® POLYCARBONATE QTIS</b>            |                   |                                 |        |      |        |        |        |           |
| NEPPOLY1X36                                   | 4008321910752     | NEPTUNE POLY QTIS 1x36W         | Grey   | 1x36 | 1275   | 104    | 108    | 1 38      |
| NEPPOLY2X36                                   | 4008321910776     | NEPTUNE POLY QTIS 2x36W         | Grey   | 2x36 | 1275   | 164    | 108    | 1 38      |
| NEPPOLY1X58                                   | 4008321910790     | NEPTUNE POLY QTIS 1x58W         | Grey   | 1x58 | 1575   | 104    | 108    | 1 38      |
| NEPPOLY2X58                                   | 4008321910813     | NEPTUNE POLY QTIS 2x58W         | Grey   | 2x58 | 1575   | 164    | 108    | 1 38      |
| <b>NEPTUNE® POLYCARBONATE QTP</b>             |                   |                                 |        |      |        |        |        |           |
| NEPTPOLY1X58HFQTP                             | 4008321098108     | NEPTUNE POLY QTP 1x58W          | Grey   | 1x58 | 1575   | 104    | 108    | 1 38      |
| NEPTPOLY2X58HFQTP                             | 4008321098115     | NEPTUNE POLY QTP 2x58W          | Grey   | 2x58 | 1575   | 164    | 108    | 1 38      |
| <b>Accessories for NEPTUNE® POLYCARBONATE</b> |                   |                                 |        |      |        |        |        |           |
| STAINLESS8                                    | 4008321391162     | Fastening clips for 36W version | Grey   | –    | –      | –      | –      | 100x8 38  |
| STAINLESS10                                   | 4008321391186     | Fastening clips for 58W version | Grey   | –    | –      | –      | –      | 100x10 38 |



## IGLOO II

- Damp proof luminaire for low temperatures down to -30°C
- Suitable for two or four OSRAM DULUX® L SP lamps with integrated QTP ECG
- Ideal for illuminating cold stores and winter sports facilities

| Product ID Code | EAN (Single Pack) | Product Description    | FINISH | W    | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|------------------------|--------|------|--------|--------|--------|------|
| IGLOOIIGR       | 4050300774626     | IGLOO II 2x24W (DULUX) | Grey   | 2x24 | 1270   | 100    | 102    | 1 38 |
| IGLOOII         | 4050300774619     | IGLOO II 4x24W (DULUX) | Grey   | 4x24 | 1270   | 100    | 102    | 1 38 |


All orders must be multiples of sales pack



## Indoor – Damp Proof Luminaires



**CE**



X G5

**electronic comfort light**

**AQUALINE™ T5**

- Jet proof luminaire for use in damp and dusty environments
- Suitable for LUMILUX® T5 HO CONSTANT fluorescent lamps equipped with QTP5 ECG
- Ideal for industrial and storage facilities, swimming pools, car parks and underpasses


| Product ID Code | EAN (Single Pack) | Product Description          | FINISH            | W      | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|------------------------------|-------------------|--------|--------|--------|--------|------|
| RTP1X24         | 4008321173744     | AQUALINE 1 x 24W HO CONSTANT | Grey/ Transparent | 24     | 661    | 65     | 115    | 1 38 |
| RTP1X54         | 4008321173751     | AQUALINE 1 x 54W HO CONSTANT | Grey/ Transparent | 54     | 1271   | 65     | 115    | 1 38 |
| RTP1X80         | 4008321173768     | AQUALINE 1 x 80W HO CONSTANT | Grey/ Transparent | 80     | 1571   | 65     | 115    | 1 38 |
| RTP2X54         | 4008321173799     | AQUALINE 2 x 54W HO CONSTANT | Grey/ Transparent | 2 x 54 | 1271   | 117    | 115    | 1 38 |
| RTP2X80         | 4008321173829     | AQUALINE 2 x 80W HO CONSTANT | Grey/ Transparent | 2 x 80 | 1571   | 117    | 115    | 1 38 |

**Accessories for AQUALINE™ T5**

| Product ID Code  | EAN (Single Pack) | Product Description                       | FINISH      | PPG  |
|--|-------------------|---|-------------|------|
| <b>Round protective tube made from PC for IK08</b>                           |                   |   |             |      |
| SLPCR24AQUA  | 4008321185372     | Round PC tube with fastening rings – 24W  | Grey        | 1 38 |
| SLPCR54AQUA  | 4008321185402     | Round PC tube with fastening rings – 54W  | Grey        | 1 38 |
| SLPCR80AQUA  | 4008321185419     | Round PC tube with fastening rings – 80W  | Grey        | 1 38 |
| <b>Oval protective tube made from PMMA with parabolic reflector for IK08</b> |                   |   |             |      |
| OVAL24SR   | 4008321193919     | OVAL PMMA tube with fastening rings – 24W | Transparent | 1 38 |
| OVAL54SR   | 4008321193926     | OVAL PMMA tube with fastening rings – 54W | Transparent | 1 38 |
| OVAL80SR   | 4008321193971     | OVAL PMMA tube with fastening rings – 80W | Transparent | 1 38 |



Round protective tube made from PC



Oval protective tube made from PMMA with parabolic reflector



All orders must be multiples of sales pack

**OUTDOOR****RECESSED LUMINAIRES****AQUALED®**

- IP68 LED luminaires for decoration and orientation
- Chrome, granite look or stainless steel finish
- Ideal for outdoor lighting

| Product ID Code       | EAN (Single Pack) | Product Description | FINISH          | W   |    |    |   | PPG |
|-----------------------|-------------------|---------------------|-----------------|-----|----|----|---|-----|
| <b>AQUALED® White</b> |                   |                     |                 |     |    |    |   |     |
| 4700570               | 4050300160580     | AQUALED White LED   | Granite         | 0.4 | 84 | 88 | 4 | 38  |
| 4700571               | 4050300160603     | AQUALED White LED   | Chrome          | 0.4 | 84 | 88 | 4 | 38  |
| 4700574               | 4008321100276     | AQUALED White LED   | Stainless Steel | 0.4 | 84 | 88 | 4 | 38  |
| <b>AQUALED® Blue</b>  |                   |                     |                 |     |    |    |   |     |
| 4700572               | 4050300160566     | AQUALED Blue LED    | Granite         | 0.5 | 84 | 88 | 4 | 38  |
| 4700573               | 4050300160627     | AQUALED Blue LED    | Chrome          | 0.5 | 84 | 88 | 4 | 38  |
| 4700575               | 4008321100290     | AQUALED Blue LED    | Stainless Steel | 0.5 | 84 | 88 | 4 | 38  |

**Accessories for AQUALED®**

- ECG for AQUALED®

|           |               |                                  |   |   |   |   |    |    |
|-----------|---------------|----------------------------------|---|---|---|---|----|----|
| OT6/240CE | 4008321113306 | OPTOTRONIC OT 6/200240/10 CE ECG | — | — | — | — | 20 | 38 |
| OT12      | 4050300609232 | OPTOTRONIC OT 12/230240/10 ECG   | — | — | — | — | 20 | 38 |

All orders must be multiples of sales pack



## Outdoor – Recessed Luminaires

**LED****AQUALED DRAGON®**


- IP 68 recessed stainless steel LED luminaire with Golden DRAGON® LED
- Ideal for swimming pools and orientation light

| Product ID Code | EAN (Single Pack) | Product Description        | FINISH | W   | h [mm] | d [mm] | PPG  |
|-----------------|-------------------|----------------------------|--------|-----|--------|--------|------|
| 4700674         | 4008321213433     | OSRAM AQUALED DRAGON White | Inox   | 1.7 | 84     | 88     | 4 38 |
| 4700675         | 4008321213457     | OSRAM AQUALED DRAGON Blue  | Inox   | 1.7 | 84     | 88     | 4 38 |

**Accessories for AQUALED DRAGON®**

- ECG for AQUALED DRAGON®

|      |               |                              |   |   |   |   |    |    |
|------|---------------|------------------------------|---|---|---|---|----|----|
| OT08 | 4008321040169 | OPTOTRONIC OT8/200240/24 ECG | - | - | - | - | 50 | 38 |
|------|---------------|------------------------------|---|---|---|---|----|----|

**NAUTILUS® MIDI DR51 INC**

- Decorative recessed spotlights equipped with 1m cable for connecting to ECG
- Suitable for DECOSTAR® 51mm lamps or DRAGONSTAR® 500
- Ideal for architectural illumination, facades and monuments


| Product ID Code    | EAN (Single Pack) | Product Description       | FINISH | A°          | W  | h [mm] | d [mm] | PPG     |
|--------------------|-------------------|---------------------------|--------|-------------|----|--------|--------|---------|
| NAUTILUSMIDI50     | 4008321154439     | NAUTILUS MIDI DR 51       | Grey   | 10,24,38,60 | 50 | 224    | 147    | 4 38    |
| KITSECUFIXNAUTMIDI | 4008321153470     | NAUTILUS MIDI KIT SECUFIX | -      | -           | -  | -      | -      | 10X2 38 |



All orders must be multiples of sales pack



## Outdoor – Recessed Luminaires

**NAUTILUS® MINI HAL**

- Decorative space saving luminaire
- Suitable for DECOSTAR® halogen lamps
- Ideal for architectural illumination, gardens, facades and monuments

| Product ID Code | EAN (Single Pack) | Product Description    | FINISH | $\Delta^\circ$ | W  | $\uparrow h \text{ [mm]}$ | $d \text{ [mm]}$ |   | PPG |
|-----------------|-------------------|------------------------|--------|----------------|----|---------------------------|------------------|---|-----|
| NAUTILUSMINI20  | 4008321154415     | NAUTILUS MINI DR51 FIX | Grey   | 10,38,60       | 20 | 150                       | 100              | 4 | 38  |

All orders must be multiples of sales pack





## OUTDOOR

### SURFACE MOUNTED LUMINAIRES



|  |  |  |  |        |      |      |          |                  |     |
|--|--|--|--|--------|------|------|----------|------------------|-----|
|  |  |  |  | 850 °C | IK03 | 230V | 50–60 Hz |                  | 840 |
|  |  |  |  |        |      |      |          | $\eta_{LB}$ 0.69 | G5  |

Osram electronic comfort light Energy Saving Longer Lamp Life

#### LUMILUX BRIK® EL

- Slim splash proof wall and ceiling luminaire
- Ideal for garages and damp locations

| Product ID Code | EAN (Single Pack) | Product Description       | FINISH | W  | I<br>[mm] | b<br>[mm] | ↑h<br>[mm] |   | PPG |
|-----------------|-------------------|---------------------------|--------|----|-----------|-----------|------------|---|-----|
| 72181GR         | 4050300440880     | 72181 LUMILUX BRIK EL 8W  | Grey   | 8  | 330       | 42        | 58         | 4 | 38  |
| 72185GR         | 4050300440903     | 72185 LUMILUX BRIK EL 13W | Grey   | 13 | 560       | 42        | 58         | 4 | 38  |



|  |  |  |  |      |      |      |          |                  |     |
|--|--|--|--|------|------|------|----------|------------------|-----|
|  |  |  |  | IP54 | IK07 | 230V | 50–60 Hz |                  | 840 |
|  |  |  |  |      |      |      |          | $\eta_{LB}$ 0.62 | 2G7 |

Osram electronic comfort light Energy Saving Longer Lamp Life

#### OSRAM DULUX BRIK® EL

- Compact energy saving exterior luminaire
- With colour 840 OSRAM DULUX® S/E lamps
- Ideal for garages and damp locations

| Product ID Code | EAN (Single Pack) | Product Description           | FINISH | W  | I<br>[mm] | b<br>[mm] | ↑h<br>[mm] |   | PPG |
|-----------------|-------------------|-------------------------------|--------|----|-----------|-----------|------------|---|-----|
| 74121GR         | 4050300440927     | 74121 OSRAM DULUX BRIK EL 9W  | Grey   | 9  | 224       | 68        | 58         | 4 | 38  |
| 74125GR         | 4050300440941     | 74125 OSRAM DULUX BRIK EL 11W | Grey   | 11 | 294       | 68        | 58         | 4 | 38  |



All orders must be multiples of sales pack




## CONSUMER FLASHLIGHTS



### SIRIUS Torch Range

- High quality aluminium torches
- High Power DRAGON® PLUS LEDs
- Batteries not included

| Product ID Code | EAN (Single Pack) | Product Description | FINISH    | W   | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|---------------------|-----------|-----|--------|--------|--------|------|
| SIRIUSLARGE     | 4008321957429     | SIRIUS – Large      | Aluminium | 2.7 | 278    | 69     | 69     | 6 38 |
| SIRIUSMEDIUM    | 4008321957399     | SIRIUS – Medium     | Aluminium | 2.2 | 228    | 55     | 55     | 6 38 |
| SIRIUSSMALL     | 4008321957368     | SIRIUS – Small      | Aluminium | 1.2 | 131    | 48     | 48     | 6 38 |



### CROSSER Torch Range

- Robust LED plastic torches
- High Power DRAGON® PLUS LEDs
- Batteries not included

| Product ID Code | EAN (Single Pack) | Product Description            | FINISH       | W   | I [mm] | b [mm] | h [mm] | PPG  |
|-----------------|-------------------|--------------------------------|--------------|-----|--------|--------|--------|------|
| CROSSERLARGE    | 4008321957542     | CROSSER – Large                | Grey plastic | 2.7 | 258    | 60     | 60     | 6 38 |
| CROSSERMEDIUM   | 4008321957511     | CROSSER – Medium               | Grey plastic | 2.2 | 217    | 52     | 52     | 6 38 |
| CROSSERSMALL    | 4008321957481     | CROSSER – Small                | Grey plastic | 1.2 | 134    | 42     | 42     | 6 38 |
| CROSSERMICRO    | 4008321957450     | CROSSER – Micro                | Grey plastic | 0.5 | 73     | 20     | 20     | 6 38 |
| CROSSTERTUBE    | 4008321957603     | CROSSER – Tube Camping Lantern | Grey plastic | 2.2 | 150    | 91     | 91     | 6 38 |
| CROSSERMULTIFU  | 4008321957573     | CROSSER – Multifunction        | Grey plastic | 1.2 | 134    | 44     | 44     | 6 38 |
| CROSSERSPOTLG   | 4008321957634     | CROSSER – Spotlight            | Grey plastic | 3.3 | 216    | 135    | 135    | 6 38 |

All orders must be multiples of sales pack




## Consumer – Flashlights

**LED Clip on Lights**

- Easy clip on night safety LED light
- With both red and white LED
- Ideal as a personal mobile safety light (children's backpacks, jackets, clothing)

| Product ID Code | EAN (Single Pack) | Product Description                 |   | PPG |
|-----------------|-------------------|-------------------------------------|---|-----|
| 80198           | 4008321371324     | LED clip on Lights (Double blister) | 6 | 38  |

NEW


**LED MULTIFUNCTIONAL**

- Versatile LED torch
- Extendable flexible arm with adjustable head
- Button cell batteries included
- Ideal for use as a reading light

| Product ID Code | EAN (Single Pack) | Product Description                  |             | PPG  |
|-----------------|-------------------|--------------------------------------|-------------|------|
| 4648201         | 4008321040237     | LED MULTIFUNCTIONAL (Single blister) | Silver/Blue | 6 38 |




All orders must be multiples of sales pack







Consumer – Flashlights

**LED****LED SAVER LIGHT**

- Krypton torch
- 12 Flashing Red LEDs in the handle to act as a warning light
- 3 magnets to attach to metal surfaces
- Emergency hammer for breaking windscreens and seat belt cutter
- Ideal accessory for all cars

| Product ID Code | EAN (Single Pack) | Product Description       | FINISH      | PPG  |
|-----------------|-------------------|---------------------------|-------------|------|
| 46474           | 4050300884882     | LED SAVER LIGHT (Blister) | Silver/Blue | 6 38 |

**LED****LED HEADLAMP**


- Adjustable headlamp
- Light from three bright white LEDs and one Xenon lamp
- Ideal for providing localised light

| Product ID Code | EAN (Single Pack) | Product Description           | FINISH     | PPG  |
|-----------------|-------------------|-------------------------------|------------|------|
| 4645201         | 4008321047106     | LED HEADLAMP (Single blister) | Grey/Black | 6 38 |

All orders must be multiples of sales pack



## Consumer – Flashlights

**CAMPING LED**

- Economical compact camping lantern
- Super bright OSRAM Golden DRAGON® LED
- Two brightness levels: 100% and 25%

| Product ID Code | EAN (Single Pack) | Product Description | FINISH      | PPG  |
|-----------------|-------------------|---------------------|-------------|------|
| 46473           | 4050300884943     | CAMPING LED         | Silver/Blue | 6 38 |

**CAMPING ENERGY AUTOMATIC**

- Energy saving camping lantern
- With 7W energy saving lamp for wide area work light
- Remote control for standby mode
- Robust steel/plastic casing
- Practical carrying handle and hanging hook
- Ideal for camping and picnics


| Product ID Code | EAN (Single Pack) | Product Description      | FINISH      | PPG  |
|-----------------|-------------------|--------------------------|-------------|------|
| 46471           | 4050300776057     | CAMPING ENERGY AUTOMATIC | Silver/Blue | 6 38 |



All orders must be multiples of sales pack



Consumer – Flashlights



### CAMPING HALOGEN DIM SI

- Halogen camping lantern
- Four dimming levels: 100%, 70%, 35% and 8%
- Robust steel/plastic casing
- Practical carrying handle and hanging hook
- Ideal for camping and picnics


| Product ID Code | EAN (Single Pack) | Product Description | COLOR       | PPG  |
|-----------------|-------------------|---------------------|-------------|------|
| 46475           | 4050300900063     | CAMPING HALOGEN DIM | Silver/Blue | 6 38 |

All orders must be multiples of sales pack





## CONSUMER NIGHT LIGHTS




**CE** **III** **IP43** **4.5V**

### SPYLUX®

- Automatic Night time Motion Sensor Mode
- 70° rotational head including 3 LED
- Auto motion features 12 second energy saving timer
- Functions as a stand alone torchlight
- Includes 3 x AAA batteries
- Ideal for outdoor security, sheds, garages, children's rooms

| Product ID Code | EAN (Single Pack) | Product Description                   | FINISH | W    | I [mm] | b [mm] | h [mm] | d [mm]      | PPG |
|-----------------|-------------------|---------------------------------------|--------|------|--------|--------|--------|-------------|-----|
| 80191BL1        | 4008321935021     | SPYLUX                                | White  | 0.23 | 99     | 68     | 68     | 6           | 38  |
| 501632EU        | 4008321935052     | SPYLUX Counter display (10 x Blister) | White  | -    | -      | -      | -      | 1 (display) | 38  |

**NEW**  
**NEW**



**CE** **III** **IP54** **4.5V**

### NIGHTLUX®


- Automatic wireless LED night light
- Turns on at dark when motion sensor is activated
- Directional LED light can rotate up and down 60°
- Functions as a stand alone torchlight
- Includes 3 x AAA batteries
- Ideal as a night time orientation light in the home

| Product ID Code | EAN (Single Pack) | Product Description                     | FINISH | W   | I [mm] | b [mm] | h [mm] | d [mm]      | PPG |
|-----------------|-------------------|---|--------|-----|--------|--------|--------|-------------|-----|
| 80193           | 4008321376596     | NIGHTLUX                                | White  | 0.6 | 86     | 69     | 28     | 88          | 38  |
| 501689EU        | 4008321377982     | NIGHTLUX Counter display (10 x Blister) | White  | -   | -      | -      | -      | 1 (display) | 38  |

**NEW**  
**NEW**



All orders must be multiples of sales pack

**CONSUMER****FUNCTIONAL DESIGN****LEDstixx®**

- Multi directional mobile LED light stick
- Equipped with Golden DRAGON® PLUS LEDs
- Numerous mounting options
- Includes X 3 AAA batteries
- Ideal for home decoration, shelf, cupboard and orientation light

| Product ID Code | EAN (Single Pack) | Product Description                | FINISH           | W   | I [mm] | b [mm] | h [mm] | d [mm] | PPG            |
|-----------------|-------------------|------------------------------------|------------------|-----|--------|--------|--------|--------|----------------|
| 80189           | 4008321951236     | LEDstixx (Blister)                 | Silver Aluminium | 0.3 | 70     | 70     | 225    | 16     | 6 38           |
| 501687EU        | 4008321951250     | LEDstixx Counter display (Blister) | Silver Aluminium | -   | -      | -      | -      | -      | 1 (display) 38 |

**POWERstixx™**



- Modular LED light sticks
- Equipped with four white LEDs
- For fixed or mobile use
- Ideal for home decoration, shelf, cupboard and orientation light

| Product ID Code  | EAN (Single Pack) | Product Description      | FINISH           | W      | I [mm] | d [mm] | PPG  |
|------------------|-------------------|--------------------------|------------------|--------|--------|--------|------|
| 40000            | 4008321962874     | POWERSTIXX SET           | Silver Aluminium | 3x 4.7 | 750    | 16     | 4 38 |
| 40001            | 4008321962898     | POWERSTIXX ADD ON        | -                | 4.7    | 250    | 16     | 6 38 |
| PSTIXXPENDANT    | 4008321960559     | POWERSTIXX PENDANT KIT   | -                | -      | -      | -      | 6 38 |
| PSTIXXCONNECTORS | 4008321960566     | POWERSTIXX CONNECTOR SET | -                | -      | -      | -      | 6 38 |

All orders must be multiples of sales pack



## Consumer – Functional design

**QOD™**

- Stylish slim LED luminaire
- Includes connector box for up to 5 modules
- Ideal for under shelf and cupboard lighting

| Product ID Code | EAN (Single Pack) | Product Description | FINISH           | W      | I<br>[mm] | b<br>[mm] | h<br>[mm] | PPG  |
|-----------------|-------------------|---------------------|------------------|--------|-----------|-----------|-----------|------|
| 40012           | 4008321962911     | QOD SET             | Silver/Aluminium | 3x 3.5 | 70        | 70        | 8         | 6 38 |
| 40013           | 4008321962935     | QOD ADD ON          | Silver/Aluminium | 3.5    | 70        | 70        | 8         | 6 38 |

**NEW**  
**NEW**

All orders must be multiples of sales pack

**CONSUMER****PORTRABLE LED LUMINAIRES****LED****DOT-it® CLASSIC**

- Portable LED light with three white LEDs
- Simple click on/off
- Mounting through adhesive pad, hook and loop pad or magnet
- Three replaceable batteries included
- Counter display version is shelf ready and includes twelve DOT-ITs, 6 x Platinum, 2 X Black/Blue/Red


| Product ID Code | EAN (Single Pack) | Product Description                             | FINISH        | W    | PPG         |    |
|-----------------|-------------------|---|---------------|------|-------------|----|
| 80142           | 4008321930491     | DOT-it CLASSIC Platinum                         | Platinum      | 0.23 | 6           | 38 |
| 80143           | 4008321930521     | DOT-it CLASSIC Piano Black                      | Piano Black   | 0.23 | 6           | 38 |
| 80144           | 4008321930583     | DOT-it CLASSIC Oxygen Blue                      | Oxygen Blue   | 0.23 | 6           | 38 |
| 80145*          | 4008321930613     | DOT-it CLASSIC Princess Pink                    | Princess Pink | 0.23 | 6           | 38 |
| 80146           | 4008321930644     | DOT-it CLASSIC Diva Red                         | Diva Red      | 0.23 | 6           | 38 |
| 80147*          | 4008321930675     | DOT-it CLASSIC Mint Green                       | Mint Green    | 0.23 | 6           | 38 |
| 501606EU        | 4008321932761     | DOT-it CLASSIC Counter display (inc. 12xDOT-it) | Mixed colours | 0.23 | 1 (display) | 38 |

\* Available on request



All orders must be multiples of sales pack

## Consumer – Portable LED Luminaires



LED

**DOT-it® VARIO**

- Portable 360° rotational and tiltable head for directional light
- With three super bright LEDs
- Mounting through adhesive pad, hook and loop pad or magnet
- Three replaceable batteries included

| Product ID Code | EAN (Single Pack) | Product Description      | FINISH      | W    | PPG  |
|-----------------|-------------------|--------------------------|-------------|------|------|
| 80160           | 4008321930705     | DOT-it VARIO Platinum    | Platinum    | 0.23 | 6 38 |
| 80161           | 4008321930736     | DOT-it VARIO Piano Black | Piano Black | 0.23 | 6 38 |
| 80162           | 4008321930767     | DOT-it VARIO White       | White       | 0.23 | 6 38 |

NEW  
NEW  
NEW

LED

**DOT-it® LINEAR VARIO**

- Portable linear 360° rotational and tiltable head for directional light
- With three super bright LEDs
- Mounting through adhesive pad, hook and loop pad or magnet
- Three replaceable batteries included

| Product ID Code | EAN (Single Pack) | Product Description             | FINISH      | W    | PPG  |
|-----------------|-------------------|---------------------------------|-------------|------|------|
| 80170           | 4008321930880     | DOT-it LINEAR VARIO Ice White   | Ice White   | 0.23 | 6 38 |
| 80169           | 4008321930859     | DOT-it LINEAR VARIO Piano Black | Piano Black | 0.23 | 6 38 |
| 80168           | 4008321930828     | DOT-it LINEAR VARIO Platinum    | Platinum    | 0.23 | 6 38 |

NEW  
NEW  
NEW

All orders must be multiples of sales pack



## Consumer – Portable LED Luminaires



LED

**DOT-it® waterproof**

- Portable waterproof LED light containing 3 LED
- Works up to 2 m / 9ft underwater and also floats
- Mounting through adhesive pad, hook and loop pad or magnet
- Three replaceable batteries included
- Ideal for use both indoors and out such as camping or skiing

Product  
ID CodeEAN  
(Single Pack)

Product Description

FINISH

W



PPG

NEW  
NEW  
NEW  
NEW

|       |               |                                  |                |      |   |    |
|-------|---------------|----------------------------------|----------------|------|---|----|
| 80175 | 4008321930910 | DOT-it waterproof Amazon Green   | Amazon Green   | 0.23 | 6 | 38 |
| 80176 | 4008321930941 | DOT-it waterproof Sunbeam Yellow | Sunbeam Yellow | 0.23 | 6 | 38 |
| 80177 | 4008321930972 | DOT-it waterproof Pepper White   | Pepper White   | 0.23 | 6 | 38 |
| 80179 | 4008321931030 | DOT-it waterproof Spa Blue       | Spa Blue       | 0.23 | 6 | 38 |

All orders must be multiples of sales pack





## Double the power for new ideas in lighting: OSRAM and Traxon Technologies.

Traxon Technologies Ltd., the OSRAM joint venture, is a world leader in architainment installations and LED lighting systems that are marketed through a global partner and sales network. The know-how of a specialist in high-end RGB and white-light installations Traxon and its subsidiary for professional lighting control e:cue, combined with the power of a innovation leader and global player OSRAM results in a portfolio that ranges from innovative LED lighting systems to highly advanced system control solutions. As a leading supplier, the joint venture has the aim of becoming the number one innovator in the world. The expertise can be seen in more than 3000 prestige lighting installations throughout the world – including famous landmarks such as London's Tower Bridge and the Guggenheim Museum in New York.

[www.traxontechnologies.com](http://www.traxontechnologies.com)

# Traxon LED Luminaires

## Contents.

### ARCHITECTURAL

|                |     |
|----------------|-----|
| WALL WASHER XB | 372 |
| LINEAR XB      | 373 |

### PROFESSIONAL MOOD AND TASK LIGHTING

|                    |     |
|--------------------|-----|
| NANOLINER XB       | 374 |
| SPOT XB            | 375 |
| 1PXL STRIP         | 375 |
| 1PXL COVE LIGHT XR | 376 |
| 1PXL BOARD         | 377 |
| 1PXL MODULE        | 378 |

### CONTROLS

|                 |     |
|-----------------|-----|
| LIGHT-DRIVE RGB | 379 |
| LIGHT-DRIVE JOG | 379 |

### CONNECTION ACCESSORIES

|                         |     |
|-------------------------|-----|
| POWER SUPPLIES          | 380 |
| TX CONNECT Data Cables  | 380 |
| TX CONNECT XB Cables    | 381 |
| TX CONNECT SMART Cables | 381 |



## TRAXON LED LUMINAIRES

### ARCHITECTURAL



#### Wall Washer XB

- Stylish, compact high power LED fixture
- Dynamic White™ (3400 K – 6700 K) option allows you to adjust and optimise the colour temperature depending on the current conditions/usage
- Aluminium finish acts as an efficient heatsink for the 700mA high performance LEDs
- IP65 so it can be used in both indoor and outdoor installations
- Integrated thermal management system
- Ideal for creating a rich wall washing effect

| Product ID Code          | EAN (Single Pack) | Traxon No.    | Product Description            | FINISH    | W   | PPG    |
|--------------------------|-------------------|---------------|--------------------------------|-----------|-----|--------|
| <b>Wall Washer XB-18</b> |                   |               |                                |           |     |        |
| XB18RGB30DEG             | 4006584524075     | XB.WD.4213100 | TX WALLWASHER XB18 OUTDOOR RGB | Aluminium | 30° | 54     |
| XB18RGB10DEG             | 4006584524051     | XB.WD.4211100 | TX WALLWASHER XB18 OUTDOOR RGB | Aluminium | 10° | 54     |
| XB18DW30DEG              | 4006584524211     | XB.WD.4283100 | TX WALLWASHER XB18 OUTDOOR DW  | Aluminium | 30° | 54     |
| XB18DW10DEG              | 4006584524174     | XB.WD.4281100 | TX WALLWASHER XB18 OUTDOOR DW  | Aluminium | 10° | 54     |
| <b>Wall Washer XB-36</b> |                   |               |                                |           |     |        |
| XB36RGB30DEG             | 4006584524112     | XB.WE.4213100 | TX WALLWASHER XB36 OUTDOOR RGB | Aluminium | 30° | 54     |
| XB36RGB10DEG             | 4006584524099     | XB.WE.4211100 | TX WALLWASHER XB36 OUTDOOR RGB | Aluminium | 10° | 54     |
| XB36DW30DEG              | 4006584524297     | XB.WE.4283100 | TX WALLWASHER XB36 OUTDOOR DW  | Aluminium | 30° | 54     |
| XB36DW10DEG              | 4006584524259     | XB.WE.4281100 | TX WALLWASHER XB36 OUTDOOR DW  | Aluminium | 10° | 54     |
| <b>Accessories</b>       |                   |               |                                |           |     |        |
| MOUNTINGBRACKETS         | 4006584619061     | XB.AC.0000500 | TX XB MOUNTING BRACKET         | -         | -   | 20 X 1 |
|                          |                   |               |                                |           |     | 38     |

#### Accessories

##### TX CONNECT™

|               |                                       |
|---------------|---------------------------------------|
| XI.IC.1000000 | XB Interconnection Cable (10m/32.8ft) |
| XI.IC.2000000 | XB Interconnection Cable (20m/65.6ft) |
| XE.AC.0200000 | XB Interconnection Sleeve             |
| XI.AC.0200200 | XB Splitter                           |
| XI.AC.0200100 | XB Coupler                            |
| DI.IC.0020000 | Data Cable (20cm/0.65ft)              |
| DI.IC.0100000 | Data Cable (1m/3.28ft)                |
| DI.IC.0300000 | Data Cable (3m/9.84ft)                |
| DI.IC.0500000 | Data Cable (5m/16.44ft)               |
| DI.IC.1000000 | Data Cable (10m/32.84ft)              |
| DI.IC.2000000 | Data Cable (20m/65.6ft)               |

##### TX POWER

|                    |               |                                       |
|--------------------|---------------|---------------------------------------|
| LED Engine XB-SD   | PX.IC.5030100 | 700mA-108 220V/Input voltage 200-260V |
| PX.IC.5030200      |               | 700mA-108 110V                        |
| LED Engine XB Mini | PX.IB.5010000 | 700mA-36 90-260V                      |
| PX.AC.0000002      |               | PSU 60W 24VDC                         |
| PX.AC.0000000      |               | PSU 150W 48VDC                        |
| PS.AC.0000x00      |               | AC Power Cord (2m/6.6ft)              |

For more details refer to pages 379/380 and 381] or contact OSRAM for further information



All orders must be multiples of sales pack



## Traxon LED Luminaires – Architectural

**LINEAR XB**

- High output Linear LED fixture equipped with 700 mA high performance LEDs
- Projects an intense even light spread to brightly colour wash any flat surface
- Dynamic White™ (3400 K – 6700 K) option allows you to adjust and optimise the colour temperature depending on the current conditions/usage
- IP65 rated so it can be used in both indoor and outdoor installations
- Ideal for a variety of lighting applications from floodlighting to display lighting

| Product ID Code    | EAN (Single Pack) | Traxon No.    | Product Description       | FINISH    |        |    |       | PPG |
|--------------------|-------------------|---------------|---------------------------|-----------|--------|----|-------|-----|
| XB9RGB40X10DEG     | 4006584524136     | XB.LF.4214100 | TX LINER XB9 OUTDOOR RGB  | Aluminium | 40°x10 | 27 | 4 X 1 | 38  |
| XB27RGB40X10DEG    | 4006584524150     | XB.LH.4214100 | TX LINER XB27 OUTDOOR RGB | Aluminium | 40°x10 | 81 | 4 X 1 | 38  |
| XB9DW40X10DEG      | 4006584524310     | XB.LF.4284100 | TX LINER XB9 OUTDOOR DW   | Aluminium | 40°x10 | 27 | 4 X 1 | 38  |
| XB27DW             | 4006584524358     | XB.LH.4284100 | TX LINER XB27 OUTDOOR DW  | Aluminium | 40°x10 | 81 | 4 X 1 | 38  |
| <b>Accessories</b> |                   |               |                           |           |        |    |       |     |
| OUNTINGBRACKETS    | 4006584619061     | XB.AC.0000500 | TX XB MOUNTING BRACKET    | –         | –      | –  | 20X1  | 38  |

RGB = Colour Change

DW = Dynamic White™

**Accessories****TX CONNECT™**

|               |                                       |
|---------------|---------------------------------------|
| XI.IC.1000000 | XB Interconnection Cable (10m/32.8ft) |
| XI.IC.2000000 | XB Interconnection Cable (20m/65.6ft) |
| XE.AC.0200000 | XB Interconnection Sleeve             |
| XI.AC.0200200 | XB Splitter                           |
| XI.AC.0200100 | XB Coupler                            |
| DI.IC.0020000 | Data Cable (20cm/0.65ft)              |
| DI.IC.0100000 | Data Cable (1m/3.28ft)                |
| DI.IC.0300000 | Data Cable (3m/9.84ft)                |
| DI.IC.0500000 | Data Cable (5m/16.44ft)               |
| DI.IC.1000000 | Data Cable (10m/32.84ft)              |
| DI.IC.2000000 | Data Cable (20m/65.6ft)               |

**TX POWER**

|                    |                          |                                       |
|--------------------|--------------------------|---------------------------------------|
| LED Engine XB-SD   | PX.IC.5030100            | 700mA-108 220V/Input voltage 200-260V |
| PX.IC.5030200      | 700mA-108 110V           |                                       |
| LED Engine XB Mini | PX.IB.5010000            | 700mA-36 90-260V                      |
| PX.AC.0000002      | PSU 60W 24VDC            |                                       |
| PX.AC.0000000      | PSU 150W 48VDC           |                                       |
| PS.AC.0000x00      | AC Power Cord (2m/6.6ft) |                                       |

For more details refer to pages 379/380 and 381 or contact OSRAM for further information

All orders must be multiples of sales pack





## TRAXON LED LUMINAIRES

### PROFESSIONAL MOOD AND TASK LIGHTING



#### NANO LINER XB

- Slim profile high power linear LED fixtures
- Equipped with 350mA LEDs
- Dynamic White™ (3400K – 6700K) option allows you to adjust and optimise the colour temperature depending on the current conditions/usage
- Available in two different lengths
- Ideal for interior installations with restricted space that require an intense and even light output on walls or other flat surfaces

| Product ID Code  | EAN (Single Pack) | Traxon No.    | Product Description           | FINISH    | W      | PPG |
|------------------|-------------------|---------------|-------------------------------|-----------|--------|-----|
| NANOLINERXB9RGB  | 4006584524631     | XB.NF.2114100 | TX NANO LINER XB9 INDOOR RGB  | Aluminium | 40°x10 | 11  |
| NANOLINERXB27RGB | 4006584524679     | XB.NH.2114100 | TX NANO LINER XB27 INDOOR RGB | Aluminium | 40°x10 | 33  |
| NANOLINERXB9DW   | 4006584524877     | XB.NF.2184100 | TX NANO LINER XB9 INDOOR DW   | Aluminium | 40°x10 | 14  |
| NANOLINERXB27DW  | 4006584524891     | XB.NH.2184100 | TX NANO LINER XB27 INDOOR DW  | Aluminium | 40°x10 | 41  |

RGB = Colour Change

DW = Dynamic White™

WW = Warm White

CW = Cool White

#### Accessories

##### TX CONNECT™

|               |                                       | TX POWER  |
|---------------|---------------------------------------|---|
| XI.IC.1000000 | XB Interconnection Cable (10m/32.8ft) | LED Engine XB-SD                                    |
| XI.IC.2000000 | XB Interconnection Cable (20m/65.6ft) | PX.IC.5060100 350mA-216 220V/Input voltage 200-260V |
| XI.AC.0200200 | XB Splitter                           | PX.IC.5060200 350mA-108 110V                        |
| X1.AC.0200100 | XB Coupler                            | LED Engine XB Mini                                  |
| DL.IC.0020000 | Data Cable (20cm/0.65ft)              | PX.IA.5010000 350mA-36 90-260V                      |
| DL.IC.0100000 | Data Cable (1m/3.28ft)                | PX.AC.0000002 PSU 60W 24VDC                         |
| DL.IC.0300000 | Data Cable (3m/9.84ft)                | PX.AC.0000000 PSU 150W 48VDC                        |
| DL.IC.0500000 | Data Cable (5m/16.44ft)               | PS.AC.0000x00 AC Power Cord (2m/6.6ft)              |
| DL.IC.1000000 | Data Cable (10m/32.84ft)              |   |
| DL.IC.2000000 | Data Cable (20m/65.6ft)               |   |

For more details refer to pages 379/380 and 381 or contact OSRAM for further information



All orders must be multiples of sales pack



## Traxon LED Luminaires – Professional Mood and Task Lighting

**SPOT XB**

- High power LED fixture designed to fit into standard MR16 fittings
- Highly efficient alternative to conventional halogen downlights
- Aluminium finish acts as an efficient heatsink for the 350mA high performance LEDs
- Dynamic White™ (3400K – 6700K) option allows you to adjust and optimise the colour temperature depending on the current conditions/usage
- Controlled by an easy to use plug and play LED engine XB or XB Mini
- Ideal for interior spotlighting applications

| Product ID Code | EAN (Single Pack) | Traxon No.    | Product Description         | FINISH    |     |     |      | PPG |
|-----------------|-------------------|---------------|-----------------------------|-----------|-----|-----|------|-----|
| SPOTXBRGB       | 4006584922635     | XB.SP.2113100 | TX SPOT XB RGB INDOOR 350mA | Aluminium | 30° | 4.7 | 25X1 | 38  |
| SPOTXBDW        | 4006584922673     | XB.SP.2183000 | TX SPOT XB DW INDOOR 350mA  | Aluminium | 30° | 4.7 | 25X1 | 38  |
| SPOTXBWW        | 4006584922666     | XB.SP.2173000 | TX SPOT XB WW INDOOR 350mA  | Aluminium | 30° | 4.7 | 25X1 | 38  |
| SPOTXBCW        | 4006584922659     | XB.SP.2163000 | TX SPOT XB CW INDOOR 350mA  | Aluminium | 30° | 4.7 | 25X1 | 38  |

For a full listing of appropriate accessories please refer to page 372

**1PXL STRIP**

- High performance Linear LED strip equipped with onboard DMX enhancement
- Smart Chip™ technology offers integrated DMX enhancement, including auto addressing and flicker free technology
- Dynamic White™ (3400K – 6700K) option allows you to adjust and optimise the colour temperature depending on the current conditions/usage
- Ideal solution for interior installations with restricted space that require colour changing lighting effects

| Product ID Code | EAN (Single Pack) | Traxon No.   | Product Description             | FINISH |      |    |      | PPG |
|-----------------|-------------------|--------------|---------------------------------|--------|------|----|------|-----|
| STRIPLIGHTRGB   | 4006584524594     | MB.ST.501000 | TX 1PXL STRIPLIGHT RGB          | White  | 120° | 6  | 10X1 | 38  |
| STRIP24DW       | 4006584524853     | MB.ST.508000 | TX 1PXL STRIPLIGHT XR DW 24 LED | White  | 120° | 10 | 10X1 | 38  |
| STRIPLIGHT12WW  | 4006584524839     | MB.ST.507000 | TX 1PXL STRIPLIGHT XR WW 12 LED | White  | 120° | 5  | 10X1 | 38  |
| STRIP12CW       | 4006584524792     | MB.ST.506000 | TX 1PXL STRIPLIGHT XR CW 12 LED | White  | 120° | 5  | 10X1 | 38  |

For a full listing of appropriate accessories please refer to page 374

All orders must be multiples of sales pack



## Traxon LED Luminaires – Professional Mood and Task Lighting

**1PXL COVE LIGHT XR**

- High performance RGB LED cove light with onboard DMX capabilities
- 180° free locking rotation
- Smart Chip™ technology offers integrated DMX enhancement, including auto addressing and flicker free technology
- Dynamic White™ (3400K – 6700K) option allows you to adjust and optimise the colour temperature depending on the current conditions/usage
- Ideal decorative solution for highlighting alcoves and other recessed borders in both hospitality and commercial applications

| Product ID Code | EAN (Single Pack) | Traxon No.    | Product Description             |                   |      |    |      | PPG |
|-----------------|-------------------|---------------|---------------------------------|-------------------|------|----|------|-----|
| COVELIGHTRGB    | 4006584524532     | MB.CL.5010100 | TX 1PXL COVELIGHT XR RGB        | TRANSPARENT/BEIGE | 120° | 6  | 10X1 | 38  |
| COVELIGHT24DW   | 4006584524778     | MB.CL.5080100 | TX 1PXL COVE LIGHT XR DW 24 LED | TRANSPARENT/BEIGE | 120° | 10 | 10X1 | 38  |
| COVELIGHT12WW   | 4006584524754     | MB.CL.5070100 | TX 1PXL COVE LIGHT XR WW 12 LED | TRANSPARENT/BEIGE | 120° | 5  | 10X1 | 38  |
| COVELIGHT12CW   | 4006584524655     | MB.CL.5060100 | TX 1PXL COVELIGHT XR CW 12 LED  | TRANSPARENT/BEIGE | 120° | 5  | 10X1 | 38  |

**Accessories****TX CONNECT™ SMART**

|               |   | TX POWER      |                              |
|---------------|---|---------------|------------------------------|
| 0000100       | Power/Data Injector Box                           | PS.IA001000   | LED Engine Smart 100W Indoor |
| TI.DO.0000100 | Data Extractor Box                                | PS.AC.0000X00 | AC Power Cord (2m/6.6ft)     |
| TI.PI.0000100 | Power Injector Cable 8.20cm/3.15:7.88"            |               |                              |
| TI.IC.0008000 | Interconnection Cable 8cm/3.15"                   |               |                              |
| TI.IC.0030000 | Interconnection Cable 30cm/11.82"                 |               |                              |
| TI.IC.0060000 | Interconnection Cable 60cm/23.64"                 |               |                              |
| TI.EC.0050000 | Extension Cable 0.5m/1.64ft                       |               |                              |
| TI.EC.0100000 | Extension Cable 1m/3.28ft                         |               |                              |
| TI.EC.0300000 | Extension Cable 3m/9.84ft                         |               |                              |
| TI.EC.0500000 | Extension Cable 5m/16.4ft                         |               |                              |
| TI.EC.1000000 | Extension Cable 10m/32.8ft                        |               |                              |
| DI.C.0020000  | Data Cable 0.2m/0.65ft                            |               |                              |
| DI.C.0100000  | Data Cable 1m/3.28ft                              |               |                              |
| DI.C.0300000  | Data Cable 3m/9.84ft                              |               |                              |
| DI.C.0500000  | Data Cable 5m/16.4ft                              |               |                              |
| DI.C.1000000  | Data Cable 10m/32.8ft                             |               |                              |
| DI.C.2000000  | Data Cable 20m/65.6ft                             |               |                              |
| DI.AC.0200100 | Data (DMX) Active Splitter, Booster and Addresser |               |                              |


For more details refer to pages 379/380 and 381 or contact OSRAM for further information



All orders must be multiples of sales pack



## Traxon LED Luminaires – Professional Mood and Task Lighting

**1PXL BOARD**

- High performance RGB LED board with onboard DMX capabilities
- Can be applied as a backdrop installation
- Smart Chip™ technology offers integrated DMX enhancement, including auto addressing and flicker free technology
- Interconnectable via TX Connect Smart with any other Traxon Smart products
- Dynamic White™ (3400K – 6700K) option allows you to adjust and optimise the colour temperature depending on the current conditions/usage
- Ideal solution for interior design within exhibitions, hospitality, commercial and architectural applications

| Product ID Code | EAN (Single Pack) | Traxon No.    | Product Description     | FINISH |      |    |     | PPG |
|-----------------|-------------------|---------------|-------------------------|--------|------|----|-----|-----|
| BOARDRGB        | 4006584524495     | MB.B0.5010000 | TX 1PXL BOARD RGB       | White  | 120° | 9  | 4X1 | 38  |
| BOARDDW         | 4006584524617     | MB.B0.5080000 | TX 1PXL BOARD DW 32 LED | White  | 120° | 15 | 4X1 | 38  |
| BOARDWW         | 4006584524570     | MB.B0.5070000 | TX 1PXL BOARD WW 16 LED | White  | 120° | 8  | 4X1 | 38  |
| BOARDCW         | 4006584524556     | MB.B0.5060000 | TX 1PXL BOARD CW 16 LED | White  | 120° | 8  | 4X1 | 38  |

For a full listing of appropriate accessories please refer to page 374

RGB = Colour Change

DW = Dynamic White™


WW = Warm White

CW = Cool White

All orders must be multiples of sales pack



## Traxon LED Luminaires – Professional Mood and Task Lighting

**1PXL MODULE**

- High performance RGB LED module with a plastic cover equipped with onboard DMX capabilities
- Design inlays can be inserted behind the protective cover to provide bespoke lighting effects
- Suitable for both temporary and permanent installations due to Quick Clip mounting system
- Smart Chip™ technology offers integrated DMX enhancement, including auto addressing and flicker free technology
- Dynamic White™ (3400K – 6700K) option allows you to adjust and optimise the colour temperature depending on the current conditions/usage
- Ideal solution for front and backlighting applications

| Product ID Code | EAN (Single Pack) | Traxon No.    | Product Description      | FINISH            |      |    |     | PPG |
|-----------------|-------------------|---------------|--------------------------|-------------------|------|----|-----|-----|
| MODULERGB       | 4006584524419     | MB.MO.5010000 | TX 1PXL MODULE RGB       | TRANSPARENT/WHITE | 120° | 9  | 4x1 | 38  |
| MODULEDW        | 4006584524471     | MB.MO.5080000 | TX 1PXL MODULE DW 32 LED | TRANSPARENT/WHITE | 120° | 15 | 4x1 | 38  |
| MODULEWW        | 4006584524457     | MB.MO.5070000 | TX 1PXL MODULE WW 16 LED | TRANSPARENT/WHITE | 120° | 8  | 4x1 | 38  |
| MODULECW        | 4006584524433     | MB.MO.5060000 | TX 1PXL MODULE CW 16 LED | TRANSPARENT/WHITE | 120° | 8  | 4x1 | 38  |

For a full listing of appropriate accessories please refer to page 374

RGB = Colour Change

DW = Dynamic White™

WW = Warm White

CW = Cool White



All orders must be multiples of sales pack



## TRAXON LED LUMINAIRES

### CONTROLS



#### LIGHT-DRIVE RGB

- Innovative plug and play DMX based stand alone controller for RGB LED fixtures
- Wall mounted device in a black or white finish provides direct access to connected fixtures
- Six memory slots allow you to save individual settings
- Use the Light Drive IR remote control to recall all functions on the Light-Drive from a distance
- Tune colour and brightness by the turn of the Light Drive wheel

| Product ID Code      | EAN (Single Pack) | Traxon No.    | Product Description                  | FINISH  | PPG |
|----------------------|-------------------|---------------|--------------------------------------|---------|-----|
| LIGHTDRIVERGBTWT     | 4006584524198     | SC.CD.5000100 | TX LIGHT-DRIVE RGB                   | White 2 | 38  |
| LIGHTDRIVERGBTBK     | 4006584524037     | SC.CD.5000000 | TX LIGHT-DRIVE RGB                   | Black 2 | 38  |
| LIGHTDRIVERGBTIRRCMC | 4006584524396     | SC.AC.0100100 | TX LIGHT-DRIVE RGB IR REMOTE CONTROL | Black 4 | 38  |



#### LIGHT-DRIVE JOG

- DMX based plug and play stand alone controller for RGB or Dynamic White™ LED fixtures
- Wall mounted device in a black or white finish provides direct access to connected fixtures
- Memory function allows you to save two settings (Dynamic White™) or continuous replay of preset colour phases (RGB)
- Tune colour and brightness by the turn of the jog wheel

| Product ID Code    | EAN (Single Pack) | Traxon No.    | Product Description    | FINISH   | PPG |
|--------------------|-------------------|---------------|------------------------|----------|-----|
| LIGHTDRIVERGBJOGWT | 4006584524273     | SC.JD.5010100 | TX LIGHT-DRIVE RGB JOG | White 20 | 38  |
| LIGHTDRIVERGBJOGBK | 4006584524235     | SC.JD.5010000 | TX LIGHT-DRIVE RGB JOG | Black 20 | 38  |
| LIGHTDRIVEDWJOGWT  | 4006584524372     | SC.JD.5080100 | TX LIGHT-DRIVE DW JOG  | White 20 | 38  |
| LIGHTDRIVEDWJOGBK  | 4006584524334     | SC.JD.5080000 | TX LIGHT-DRIVE DW JOG  | Black 20 | 38  |

All orders must be multiples of sales pack





## TRAXON LED LUMINAIRES

### CONNECTION ACCESSORIES



#### POWER SUPPLIES

| Product ID Code  | EAN (Single Pack) | Traxon No.    | Product Description                    | W   | PPG   |
|------------------|-------------------|---------------|--|-----|-------|
| LEXBSD350MA200   | 4006584525447     | PX.IC.5060100 | TX LED ENGINE XB-SD 350MA-216 200-260V | –   | 1 38  |
| LEXBSD700MA200   | 4006584525454     | PX.IC.5030100 | TX LED ENGINE XB-SD 700MA-108 200-260V | –   | 1 38  |
| LEXBMINI350MA110 | 4006584922710     | PX.IA.5010000 | TX LED ENGINE XB-MINI 350MA 110-220V   | –   | 1 38  |
| LEXBMINI700MA110 | 4006584922727     | PX.IB.5010000 | TX LED ENGINE XB-MINI 700MA 110-220V   | –   | 1 38  |
| XBMINIPSU15048   | 4006584922734     | PX.AC.0000000 | TX LED ENGINE XB Mini PSU 150W 48 Vdc  | 150 | 12 38 |
| XBMINIPSU6048    | 4006584922741     | PX.AC.0000001 | TX LED ENGINE XB Mini PSU 60W 48 Vdc   | 60  | 18 38 |
| XBMINIPSU6024    | 4006584922758     | PX.AC.0000002 | TX LED ENGINE XB Mini PSU 60W 24 Vdc   | 60  | 18 38 |
| LESSMART100      | 4006584525423     | PX.IA.0010000 | TX LED ENGINE SMART 100W INDOOR        | 100 | 15 38 |
| LEXBSD700MA108   | 4006584558513     | –             | LED ENGINE XB-SD 700MA-108 110V        | –   | 1 38  |
| LEXBSD350MA216   | 4006584558506     | –             | LED ENGINE XB-SD 350MA-216 110V        | –   | 1 38  |
| ACPOWERCORDUK    | 4006584922581     | PX.AC.0000300 | AC POWER CORD (UK)                     | –   | 1 38  |
| ACPOWERCORDEU    | 4006584922529     | PX.AC.0000100 | AC POWER CORD (EU)                     | –   | 1 38  |



#### TX CONNECT Data Cables


| Product ID Code | EAN (Single Pack) | Traxon No.    | Product Description        | PPG   |
|-----------------|-------------------|---------------|----------------------------|-------|
| CONDATA0.2M     | 4006584525102     | DI.IC.0020000 | TX CONNECT Data Cable 0.2m | 10 38 |
| CONDATA1M       | 4006584525126     | DI.IC.0100000 | TX CONNECT Data Cable 1m   | 10 38 |
| CONDATA3M       | 4006584525140     | DI.IC.0300000 | TX CONNECT Data Cable 3m   | 10 38 |
| CONDATA5M       | 4006584525164     | DI.IC.0500000 | TX CONNECT Data Cable 5m   | 10 38 |
| CONDATA10M      | 4006584525188     | DI.IC.1000000 | TX CONNECT Data Cable 10m  | 10 38 |
| CONDATA20M      | 4006584525201     | DI.IC.2000000 | TX CONNECT Data Cable 20m  | 10 38 |



All orders must be multiples of sales pack



## Traxon LED Luminaires – Connection Accessories

**TX CONNECT XB Cables**

| Product ID Code | EAN (Single Pack) | Traxon No.    | Product Description              |    |    |
|-----------------|-------------------|---------------|----------------------------------|----|----|
| CONXBINTERCON10 | 4006584525041     | XIIC.1000000  | TX CONNECT XB Intercon cable 10m | 10 | 38 |
| CONXBINTERCON20 | 4006584525065     | XIIC.2000000  | TX CONNECT XB Intercon cable 20m | 10 | 38 |
| CONXBCOUPLER    | 4006584922567     | XIAC.0200100  | TX CONNECT XB Coupler            | 1  | 38 |
| CONXBSPPLITTER  | 4006584922574     | XIAC.0200200  | TX CONNECT XB Splitter           | 1  | 38 |
| XBINTERCONSL    | 4006584922796     | XE.AC.0200000 | TX XB Interconnection sleeve     | 1  | 38 |


**TX CONNECT SMART Cables**


| Product ID Code    | EAN (Single Pack) | Traxon No.    | Product Description                         |    |    |
|--------------------|-------------------|---------------|---|----|----|
| CONSMARTPOWER8     | 4006584525089     | TI.PI.0000100 | TX CONNECT SMART Power cable 8-20cm         | 10 | 38 |
| CONSMARTINTERCON8  | 4006584525249     | TI.IC.0008000 | TX CONNECT SMART Interconnection cable 8cm  | 10 | 38 |
| CONSMARTINTERCON30 | 4006584525263     | TI.IC.0030000 | TX CONNECT SMART Interconnection cable 30cm | 10 | 38 |
| CONSMARTINTERCON60 | 4006584525287     | TI.IC.0060000 | TX CONNECT SMART Interconnection cable 60cm | 10 | 38 |
| CONSMARTEXT50      | 4006584525300     | TI.EC.0050000 | TX CONNECT SMART Extension cable 0.5m       | 10 | 38 |
| CONSMARTEXT1       | 4006584525324     | TI.EC.0100000 | TX CONNECT SMART Extension cable 1m         | 10 | 38 |
| CONSMARTEXT3       | 4006584525362     | TI.EC.0300000 | TX CONNECT SMART Extension cable 3m         | 10 | 38 |
| CONSMARTEXT5       | 4006584525386     | TI.EC.0500000 | TX CONNECT SMART Extension cable 5m         | 10 | 38 |
| CONSMARTEXT10      | 4006584525409     | TI.EC.1000000 | TX CONNECT SMART Extension cable 10m        | 10 | 38 |
| CONSMARTPINJECTOR  | 4006584922598     | TI.ZI.0000100 | TX CONNECT SMART Power/Data Injector Box    | 20 | 38 |
| CONSMARTTRACTOR    | 4006584922604     | TI.DO.0000100 | TX CONNECT SMART Data extractor             | 20 | 38 |
| DMXBOOSTSPLITAD    | 4006584525348     | DI.AC.0200100 | TX DMX Booster Splitter Addresser           | 10 | 38 |
| CONSMARTSPLITTER20 | 4006584525225     | -             | TX CONNECT SMART Data cable 20m             | 10 | 38 |

All orders must be multiples of sales pack



## GLOSSARY





**Glossary of Lighting Terms  
Symbols and Abbreviations  
Common Lamp caps  
Cross Reference Charts  
Conditions of Sale.**

# Glossary of the most important lighting terms

As with any technical or scientific discipline, lighting technology has its own special terms and concepts for defining the characteristics of lamps and luminaires and for standardising the units of measurement.

The most important of these are described here.


## Luminous flux $\Phi$

Unit of measurement: lumen [lm]

Luminous flux  $\Phi$  is all the radiated power emitted by a light source evaluated with the spectral sensitivity of the eye and the photometric radiation equivalent  $k_m$ .

## Light and radiation

Light is taken to mean the electromagnetic radiation that the human eye perceives as brightness, in other words that part of the spectrum that can be seen. This is the radiation between 360 and 830 nm, a tiny fraction of the known spectrum of electromagnetic radiation.




**Luminous intensity I**  
is a measure of the  
luminous flux  $\Phi$   
emitted in solid  
angle  $\Omega$ .

## Luminous intensity I

Unit of measurement: candela [cd].

Generally speaking, a light source emits its luminous flux  $\Phi$  in different directions and at different intensities.

The visible radiant intensity in a particular direction is called luminous intensity I.




## Polar diagram

## Illuminance E


Unit of measurement: lux [lx].

Illuminance E is the ratio between the luminous flux and the area being illuminated.

An illuminance of 1lx occurs when a luminous flux of 1 lm is evenly distributed over an area of 1 m<sup>2</sup>.



## Illuminance E



## Luminance L

## Luminance L

Unit of measurement: candelas per square metre [cd/m<sup>2</sup>].

The luminance L of a light source or an illuminated area is a measure of the brightness.


### The most important photometric formulae:

|                            |   |
|----------------------------|---|
| Luminous intensity<br>[cd] | I |
| Illuminance<br>[lx]        | E |

|   |        |
|---|--------|
| Luminous flux in solid angle<br>Solid angle $\Omega$ [sr] | $\Phi$ |
| Luminous flux falling on area [lm]                        |        |
| Illuminated area [m <sup>2</sup> ]                        |        |

|                                   |        |
|-----------------------------------|--------|
| Luminance<br>[cd/m <sup>2</sup> ] | L      |
| Luminous efficacy<br>[lm/W]       | $\eta$ |

|   |                      |
|---|----------------------|
| Luminous intensity [cd]<br>Viewed luminous area [m <sup>2</sup> ] | $E = \frac{\Phi}{A}$ |
| Generated luminous flux [lm]<br>Electrical power consumed [W]     | $\eta = \frac{E}{P}$ |



**Luminous efficacy  $\eta$** 

Unit of measurement : lumens per watt [lm/W].

Luminous efficacy  $\eta$  indicates the efficiency with which the electrical power consumed is converted into light.

**Colour temperature**

Unit of measurement : Kelvin [K].

The colour temperature of a light source is defined in comparison with a "black body radiator" and plotted on what is known as the "Planckian curve". The higher the temperature of this "black body radiator" the greater the blue component in the spectrum and the smaller the red component. An incandescent lamp with a warm white light, for example, has a colour temperature of 2700 K, whereas a daylight fluorescent lamp has a colour temperature of 6000 K.

**Colour appearance**

The colour appearance of a lamp can be neatly defined in terms of colour temperature. There are three main categories here:

Warm White < 3300 K

Cool White 3300–5000 K

Daylight > 5000 K

Despite having the same colour appearance, lamps may have very different colour rendering properties owing to the spectral composition of their light.

**Colour rendering**

As a rule, artificial light should enable the human eye to perceive colours correctly, as it would in natural daylight. Obviously, this depends to some extent on the location and purpose for which light is required.

The criterion here is the colour rendering property of a light source. This is expressed as a "general colour rendering index" ( $R_a$ ).

The colour rendering index is a measure of the correspondence between the colour of an object (its "self-luminous colour") and its appearance under a reference light source. To determine the  $R_a$  values, eight test colours defined in accordance with DIN 6169 are illuminated with the reference light source and the light source under test. The smaller the discrepancy, the better the colour rendering property of the lamp being tested.

A light source with an  $R_a$  value of 100 displays all colours exactly as they appear under the reference light source.

The lower the  $R_a$  value, the worse the colours are rendered.

**Luminaire efficiency**

Luminaire efficiency (also known as light output ratio) is an important criterion in gauging the energy efficiency of a luminaire. This is the ratio between the luminous flux emitted by the luminaire and the luminous flux of the lamp (or lamps) installed in the luminaire.




For detailed information on indoor lighting with artificial light, see DIN 5035.

**Average life**


The average life of a lamp is an average of the lives of individual lamps operated under standard conditions (50% failure = average life).

**Service life**

Service life is a simple practical measure of the economical life of a lamp. It is the number of hours of operation after which the system luminous flux (i.e. the product of the relative luminous flux and the relative proportion of lamps still in operation) is still around 80% of the initial value.



**Daylight spectrum of a BIOLUX® fluorescent lamp. The radiation is very evenly distributed over the entire visible range.**




## Symbols and Abbreviations

- Discontinued items. Please check availability.
- New and future additions to the OSRAM range of products. Please check availability.
- Lamps with a reduced UV output.
- NAV (SON) lamps requiring an external ignitor.
- NAV (SON) lamps with an internal ignitor.
- Products affected by the WEEE Directive

### Colour appearance and colour rendering properties of fluorescent tubes, compact fluorescent lamps and LEDs.

| OSRAM Colour ref | Colour temp | Colour appearance  | Colour rendering group | Lamp type |                    |
|------------------|-------------|--------------------|------------------------|-----------|--------------------|
| 880              | 8000 K      | Skywhite           | Very good              | 1B        | Triphosphor        |
| 865              | 6500 K      | Cool Daylight      | Very good              | 1B        | Triphosphor        |
| 840              | 4000 K      | Cool White         | Very good              | 1B        | Triphosphor        |
| 835              | 3500 K      | White              | Very good              | 1B        | Triphosphor        |
| 830              | 3000 K      | Warm White         | Very good              | 1B        | Triphosphor        |
| 827              | 2700 K      | INTERNA            | Very good              | 1B        | Triphosphor        |
| 825              | 2500 K      | Warm Comfort light | Very good              | 1B        | CFLi               |
| 965              | 6500 K      | Cool Daylight      | Excellent              | 1A        | Deluxe Triphosphor |
| 954              | 5400 K      | Daylight           | Excellent              | 1A        | Deluxe Triphosphor |
| 940              | 3800 K      | Cool White         | Excellent              | 1A        | Deluxe Triphosphor |
| 930              | 3000 K      | Warm White         | Excellent              | 1A        | Deluxe Triphosphor |
| 30/530           | 3000 K      | Warm White         | Acceptable             | 3         | Basic phosphor     |
| 25/740           | 4000 K      | Universal White    | Good                   | 2A        | Basic phosphor     |
| 23/535           | 3500 K      | White              | Acceptable             | 3         | Basic phosphor     |
| 20/640           | 4000 K      | Cool White         | Fair                   | 2B        | Basic phosphor     |
| 10/765           | 6500 K      | Cool Daylight      | Good                   | 2A        | Basic phosphor     |
| 60               | N/A         | Red                | N/A                    |           |                    |
| 62               | N/A         | Yellow             | N/A                    |           |                    |
| 66               | N/A         | Green              | N/A                    |           |                    |
| 67               | N/A         | Blue               | N/A                    |           |                    |
| 76               | N/A         | NATURA DELUXE      | N/A                    |           |                    |
| 827              | 2700 K      | Fine White         | Very good              | 1B        | LED                |
| 830              | 3000 K      | Fine White         | Very good              | 1B        | LED                |
| 835              | 3500 K      | Fine White         | Very good              | 1B        | LED                |
| 840              | 4000 K      | Fine White         | Very good              | 1B        | LED                |
| 854              | 5400 K      | Fine White         | Very good              | 1B        | LED                |
| 727              | 2700 K      | White              | Good                   | 2A        | LED                |
| 730              | 3000 K      | White              | Good                   | 2A        | LED                |
| 733              | 3300 K      | White              | Good                   | 2A        | LED                |
| 847              | 4700 K      | White              | Very good              | 1B        | LED                |
| 854              | 5400 K      | White              | Very good              | 1B        | LED                |
| 865              | 6500 K      | White              | Very good              | 1B        | LED                |


|                               |   |                        |                    |
|-------------------------------|---|------------------------|--------------------|
| Type of sensor                | Type of sensor                                  | Appliance class        | Starter            |
| No. of ECGs                   | No. of Electronic Control Gears                 | Type of protection     | Equipped with Lamp |
| COLOR                         | Color   |                        |                    |
|                               | Light color                                     |                        |                    |
| <b>W</b>                      | Rated output in Watts                           |                        |                    |
| <b>V</b>                      | Voltage in Volts                                | Flame protection class | Light colour       |
| <b>V<sub>AC</sub> min-max</b> | Permitted sinusoidal operating voltage in Volts | Glowing wire test      | Beam angle         |
| <b>V<sub>IN</sub></b>         | Primary voltage in Volts                        |                        | Base               |
| <b>V<sub>OUT</sub></b>        | Secondary voltage in Volts                      | Mechanical stress      |                    |
| <b>A</b>                      | Rated current in Amperes                        |                        |                    |
| <b>°C min-max</b>             | Temperature range                               | Load capacity          | Approval           |
| <b>IP</b>                     | Type of protection                              |                        |                    |
| Reflector type                | Type of reflector                               |                        |                    |
| <b>cd</b>                     | Luminous intensity in candela                   | Ambient temperature    |                    |
| <b>K</b>                      | Color temperature in Kelvins                    | Mounting diameter      |                    |
| <b>λ</b>                      | Beam angle in degrees                           |                        |                    |
| <b>d [mm]</b>                 | Diameter d in mm                                |                        |                    |
| <b>l [mm]</b>                 | Length l in mm                                  | Voltage                |                    |
| <b>b [mm]</b>                 | Width b in mm                                   |                        |                    |
| <b>h [mm]</b>                 | Height h in mm                                  |                        |                    |
| <b>a [mm]</b>                 | Hole spacing a in mm                            |                        |                    |
| <b>No. of LEDs per module</b> | No. of LEDs per module                          |                        |                    |
| Appliance class               | Electrical appliance class                      |                        |                    |
| <b>Base</b>                   | Base  | Current                |                    |
| <b>Standard pack/pcs.</b>     | Standard pack/pcs.                              | Frequency              |                    |
| <b>PPG</b>                    | Product Purchase Group                          | Dimmable               |                    |
|                               |   |                        |                    |




## Common lamp caps

| Standard Designation | IEC Designation | Description             |
|----------------------|-----------------|-------------------------|
| BC                   | B22d            | Bayonet Cap             |
| SBC                  | B15d            | Small Bayonet Cap       |
| 3 pin BC             | B22d-3          | Bayonet Cap - 3 pin     |
| ES                   | E27             | Edison Screw            |
| SES                  | E14             | Small Edison Screw      |
| GES                  | E40             | Goliath Edison Screw    |
| -                    | GU5.3           | Bi-pin                  |
| -                    | R7s             | Recessed Single Contact |
| -                    | G4/GU4/GY4      | Small Bi-pin            |


Bases – GLS, Halogen, CFLi







Bases – Halogen



Bases – CFL



**Bases – Fluorescent Tubes****Bases – High Pressure Discharge****Bases – Special Lamps**

# Lamp Cross Reference Chart

The chart represents the nearest equivalent OSRAM lamp brand to other manufacturers

| <b>OSRAM</b>                                    | <b>Philips</b>        | <b>GE</b>                        | <b>SLI</b>             |
|---|-----------------------|----------------------------------|------------------------|
| <b>Mains voltage halogen</b>                    |                       |                                  |                        |
| HALOPIN®  | CLICKline             | Tech                             | –                      |
| HALOPAR® 16                                     | Twistline             | PAR 16                           | Hi-Spot 50             |
| HALOPAR® 20                                     | HalogenA PAR 20       | PAR 20                           | Hi-Spot 63             |
| HALOPAR® 30                                     | HalogenA PAR 30       | PAR 30                           | Hi-Spot 95             |
| <b>Low voltage halogen</b>                      |                       |                                  |                        |
| DECOSTAR® IRC                                   | Master Line ES        | –                                | –                      |
| DECOSTAR® TITAN                                 | Brilliantline Pro     | Dichroic Precise Constant Colour | Superia                |
| DECOSTAR® STANDARD                              | Accentline            | MR 16 Precise Standard           | –                      |
| DECOSTAR® ALU                                   | Brilliantline Pro ALU | Precise Alutech                  | Coolfit                |
| <b>Pin-based compact fluorescent</b>            |                       |                                  |                        |
| OSRAM DULUX® S                                  | PLS                   | Biax S 2pin                      | Lynx-S                 |
| OSRAM DULUX® S/E                                | PLS                   | Biax S/E 4pin                    | Lynx-SE                |
| OSRAM DULUX® D                                  | PL-C                  | Biax D 2pin                      | Lynx-D                 |
| OSRAM DULUX® D/E                                | PL-C                  | Biax D/E 4pin                    | Lynx-DE                |
| OSRAM DULUX® T                                  | PL-T                  | Biax T 2pin                      | Lynx-S                 |
| OSRAM DULUX® T/E                                | PL-T                  | Biax T/E 4pin                    | Lynx-TE                |
| OSRAM DULUX® L                                  | PL-L                  | Biax L                           | Lynx-L                 |
| <b>Electronic compact fluorescent</b>           |                       |                                  |                        |
| OSRAM DULUX® EL LONGLIFE                        | MASTER PL             | Electronic Biax EXTRA MINI       | Mini-Lynx Professional |
| OSRAM DULUX® EL ECONOMY                         | PL Electronic Pro     | Electronic Biax ECO              | Mini-Lynx Economy      |
| OSRAM DULUX® EL CLASSIC                         | Ambiance Pro          | Electronic Biax MINI GLS         | –                      |
| OSRAM DULUX® EL ECONOMY CLASSIC                 | Ambiance 6000 hour    | Electronic GLS                   | Mini-Lynx Ambience GLS |
| <b>Linear fluorescent</b>                       |                       |                                  |                        |
| LUMILUX® T5 HE High Efficiency                  | MASTER TL5            | Starcoat T5 HE                   | T5 Miniature           |
| LUMILUX® T5 HO High Output                      | MASTER TL5            | Starcoat T5 HE                   | T5 Miniature           |
| LUMILUX® DE LUXE T5 HO High Output +Triphosphor | –                     | –                                | T5 FHO Luxline         |
| LUMILUX® T5 FC                                  | Circular TL5          | –                                | –                      |
| LUMILUX® T8                                     | MASTER TL Super 80    | T8 Polylux                       | Luxline plus           |
| LUMILUX® DE LUXE T8                             | De Luxe               | T8 Polylux XL                    | –                      |
| BASIC T8  | T8 Standard           | T8 Standard                      | T8 Standard            |
| NATURA  | –                     | –                                | –                      |
| FLUORA®   | –                     | –                                | Gro-Lux                |
| SPS   | MASTER TLD Secura     | –                                | –                      |
| UVS   | –                     | –                                | –                      |
| <b>Ceramic metal halide</b>                     |                       |                                  |                        |
| POWERBALL® HQI®-T                               | CDM T                 | CMH T                            | CMI-T                  |
| POWERBALL® HQI®-TC                              | CDM TC                | CMH TC                           | CMI-TC                 |
| POWERBALL® HQI®-TS                              | CDM TD                | CMH TD                           | CMI-TD                 |
| POWERBALL® HQI®-PAR                             | CDM R PAR             | CMH PAR                          | –                      |
| POWERBALL® HQI®-TT                              | CDM TT                | CMH TT                           | –                      |
| POWERBALL® HQI®-E                               | CDM ET                | CMH E                            | –                      |
| <b>Quartz metal halide</b>                      |                       |                                  |                        |
| POWERSTAR® HQI®-T                               | MHN-T                 | ARC T                            | HSI-T                  |
| POWERSTAR® HQI®-TS                              | MHN-TD                | ARC TD                           | Britelux HSI-TD        |
| POWERSTAR® HQI®-E                               | –                     | –                                | Britelux HSI-SX        |
| <b>High pressure sodium</b>                     |                       |                                  |                        |
| VIALOX® NAV® (SON) SUPER 4Y                     | MASTER SON PIA Plus   | Lucalox Superlife                | SHP SUPER              |
| VIALOX® NAV® (SON) 4Y                           | MASTER SON PIA        | Lucalox XD                       | SHP                    |
| VIALOX® (SON) standard                          | SON Pro               | Lucalox                          | SHP Standard           |

# General Conditions of Sale

Unless otherwise stated by OSRAM LIMITED (the "Company") in writing, the Company's General Conditions of Sale set out below shall apply to all sales of goods by the Company to any other party (the "Customer"):

## 1 General

All quotations are made and all orders are accepted subject to the following terms and conditions and no addition thereto or variation therein shall be made or apply unless agreed in writing.

## 2 Orders

- (2.1) The Company reserves the right to accept or refuse orders. The Company also reserves the right (without prejudice to any other remedy) to cancel any uncompleted order or to suspend delivery in the event of any of the Customer's commitments with the Company not being met or if the Company is of the opinion that such commitment will not be met by the Customer.
- (2.2) With regard to orders for goods which the Company does not stock and therefore makes or procures specifically for the Customer, the Company can accept neither the cancellation of any such order nor the return of any such goods except under Clause 16 (Defects after delivery).

## 3 Validity of quotations

- (3.1) The contract will be on these conditions which shall override any terms and conditions which the Customer purports to apply, including those contained or referred to in the order and shall supersede all prior agreements, offers and discussions (oral or written) between the parties regarding the subject matter of the contract. The order shall be deemed to be an offer by the Customer to purchase goods and/or services subject to these conditions. No order shall be deemed to be accepted by the Company until a written acknowledgement of the order is issued by the Company or (if earlier) the Company delivers goods and/or services to the Customer. These conditions shall be binding on the Customer when the Company accepts the order whether or not the Customer has executed the contract.
- (3.2) Unless expressly agreed in writing to the contrary, these conditions shall apply to all orders placed by the Customer with the Company until further notice from the Company to the Customer.

## 4 Acceptance of quotations

The acceptance of a quotation must be accompanied by sufficient information to enable the Company to proceed with the order forthwith, otherwise the Company will be at liberty to amend the quoted price to cover any increase in cost which has taken place after acceptance. Any sample submitted with the Company's quotation is returnable.

## 5 Catalogues etc

Catalogues, price lists and other advertising matter and descriptions, specifications or samples are only an indication of the type of goods offered and no particulars therein or attributes thereof shall be binding on the Company. All prices quoted therein are subject to alteration or withdrawal from time to time without notice.

## 6 Price

- (6.1) All quotations and orders for the general range of goods in current demand are subject to relevant prices and relevant discounts ruling at date of despatch.
- (6.2) Except as provided in Clause 6.1 above, all prices are based on the cost of material, labour, transport and of conforming to statutory obligations ruling at the date of quotation or tender, and if between that date and the date on which the goods are despatched, variations, either by rise or fall, shall occur in these costs the Company may amend the price to provide for these variations. The Company shall be entitled to charge an additional cost for the impact of specific legislation, coming into force either before or after the contract with the Customer is concluded, such as laws or regulations on waste electrical and electronic equipment, use of hazardous substances, packaging or disposal.
- (6.3) All amounts payable pursuant to the Contract are expressed exclusive of Value Added Tax (VAT) and any VAT shall be paid at the rate applying at the date of the Company's invoice.



## **7 Description of goods**

- (7.1) All goods will be supplied as specified subject to reasonable availability to the Company of materials. Where specified materials are not so available the Company reserves the right without further notice to substitute other materials.
- (7.2) All descriptive specifications and drawings, all particulars of weights and dimensions and all forwarding specifications issued by the Company are approximate only.

## **8 Rejection and Return**

- (8.1) Unless otherwise agreed in writing, goods rejected by the Customer as not complying with the contract must be rejected within 14 days.
- (8.2) Due to the fragile nature of the goods the Company will not accept goods for return unless previously inspected and confirmed as fit for re-sale by an employee of the Company. For this reason the Company does not operate a "sale or return" option, nor does it operate a stock cleanse facility. Any and all returns may only be made with the full agreement and authorisation of a manager of the Company. The Company will not accept any responsibility for goods returned by the Customer without full authorisation.

## **9 RISK/TITLE**

- (9.1) The goods are at the risk of the Customer from the time of delivery.
- (9.2) Ownership of the goods shall not pass to the Customer until the Company has received in full (in cash or cleared funds) all sums due to it in respect of:
  - (9.2.1) the goods; and
  - (9.2.2) all other sums which are or which become due to the Company from the Customer on any account.
- (9.3) Until ownership of the goods has passed to the Customer, the Customer must:
  - (9.3.1) hold the goods on a fiduciary basis as the Company's bailee;
  - (9.3.2) store the goods (at no cost to the Company) separately from all other goods of the Customer or any third party in such a way that they remain readily identifiable as the Company's property;
  - (9.3.3) not destroy, deface or obscure any identifying mark or packaging on or relating to the goods;
  - (9.3.4) maintain the goods in satisfactory condition and keep them insured on the Company's behalf for their full price against all risks to the reasonable satisfaction of the Company. On request the Customer shall produce the policy of insurance to the Company; and
  - (9.3.5) hold the proceeds of the insurance referred to in Clause 9.3.4 or of sale of any of the goods on trust for the Company and not mix them with any other money, nor pay the proceeds into any overdrawn bank account.
- (9.4) The Customer's right to possession of the goods shall terminate immediately if:
  - (9.4.1) the Customer has a bankruptcy order made against him or makes an arrangement or composition with his creditors, or otherwise takes the benefit of any statutory provision for the time being in force for the relief of insolvent debtors, or (being a body corporate) convenes a meeting of creditors (whether formal or informal), or enters into liquidation (whether voluntary or compulsory) except a solvent voluntary liquidation for the purpose only of reconstruction or amalgamation, or has a receiver and/or manager, administrator or administrative receiver appointed of its undertaking or any part thereof, or a resolution is passed or a petition presented to any court for the winding up of the Customer or for the granting of an administration order in respect of the Customer, or any proceedings are commenced relating to the insolvency or possible insolvency of the Customer; or (9.4.2) the Customer suffers or allows any execution, whether legal or equitable, to be levied on his/its property or obtained against him/it, or fails to observe/perform any of his/its obligations

- under the Contract or any other contract between the Company and the Customer, or is unable to pay its debts within the meaning of section 123 of the Insolvency Act 1986 or the Customer ceases to trade; or
- (9.4.3) the Customer encumbers or in any way charges any of the goods.
  - (9.5) The Company shall be entitled to recover payment for the goods notwithstanding that ownership of any of the goods has not passed from the Company.
  - (9.6) The Customer grants the Company, its agents and employees an irrevocable licence at any time to enter any premises where the goods are or may be stored in order to inspect them, or, where the Customer's right to possession has terminated, to recover them.

## **10 Despatch**

Any times quoted for despatch are to be treated as estimates only and the Company shall not be liable in any manner whatsoever for failure to despatch within such time unless the Customer has suffered loss thereby and the amount payable in respect thereof shall have been agreed in writing prior to despatch as liquidated damages, in which case the Company's liability shall be limited to the amount so agreed to be paid. In all cases, whether a time for despatch be quoted or not, the time for despatch shall not be of the essence and shall be extended by a reasonable period and for so long as the Company's having regard to all circumstances if delay in despatch is caused by instructions or lack of instructions or other necessary particulars from the Customer, or by industrial dispute, or by any cause whatsoever beyond the Company's reasonable control.

## **11 Storage**

If by reason of instructions or lack of instructions from the Customer or failure of the Customer to accept delivery, despatch in accordance with the contract is delayed for 7 days after the Customer has been notified that the goods are ready for despatch, the risk in the goods shall pass to the Customer who shall take delivery or arrange for storage and for the purposes of Clause 15 (Payment) the goods shall thereupon be deemed to have been delivered. If storage facilities permit, the Company may store the goods and the Customer shall pay a reasonable charge therefor.

## **12 Delivery**


- (12.1) Unless otherwise specified the price quoted includes delivery.
- (12.2) The Company reserves the right to choose the method of transport.
- (12.3) The Customer will sign, at the time of delivery, the Delivery Note, International Delivery Note (CMR) or other delivery documentation for receipt of the goods. If the Customer signs "unexamined" or similar, the Company will deem this to be an acknowledgement of receipt of all cartons or packages specified on the Delivery Note.

## **13 Loss or damage in transit**

- (13.1) Shortages and/or damages in transit, must be clearly stated by the Customer on the Delivery Note, CMR or other delivery documentation at the time of delivery. The Company undertakes to investigate, and credit where appropriate.
- (13.2) Where shortages and/or damages are not apparent at the time of delivery, the Customer must notify the company, in writing, within 3 working days of receipt of delivery. The Company undertakes to investigate, and credit where appropriate.
- (13.3) Where an entire delivery has not been received, the Customer must notify the company, in writing, within 10 working days of the date of the invoice. The Company undertakes to investigate, and credit where appropriate.

## **14 Packing**

Packing cases, pallets, drums and/or packing materials, will be charged extra if not returned in good condition carriage paid to the Company within one month of delivery of the goods if requested by the Company. If no such request is made by the Company, the Customer shall be responsible for proper disposal of such items.



## **15 Payment**

- (15.1) Unless otherwise agreed in writing, payment in full is due on or before the last banking day of the calendar month following the month of the invoice.
- (15.2) If the price of the goods is not paid in full by the due date all other sums owing or incurred by the Customer to the Company but not already due for payment shall thereupon become due and immediately payable in full and the Company may suspend any further deliveries due to the Customer.
- (15.3) In the event any amount payable is overdue, the Company may, without prejudice to any other right, charge simple interest on overdue amounts at a rate of 2% per annum above the then current base rate published by Barclays Bank PLC. The Company reserves the right to charge interest at the rate set out in the Late Payment of Commercial Debts (Interest) Act 1998.

## **16 Defects after delivery**

The Company will make good, by repair or at the Company's option by the supply of a replacement or refund, defects which, under proper use, appear in the goods within a period of twelve calendar months after the goods have been delivered and arise solely from faulty design, materials or workmanship (other than a design made, furnished or specified by or on behalf of the Customer): provided always that defective parts have been returned to the Company if the Company shall have so required. The Company shall refund the cost of carriage of such returned parts and the repaired or new parts will be delivered by the Company free of charge as provided in Clause 12 (Delivery). The Company shall be under no liability for the fitting or installation of the repaired part or for service charges incurred in respect thereof. In respect of goods not of the Company's manufacture, the Customer is entitled only to such benefits as the Company may receive under any guarantee given to it in respect thereof.

The Company's liability under this clause shall be in lieu of any warranty or condition implied by law as the quality or fitness for any particular purpose of the goods, and save as provided in this clause the Company shall not be under any liability, whether in contract, tort or otherwise, in respect of defects in goods delivered or for any damage or loss resulting from such defects or from any work done in connection therewith. Provided however that nothing in this clause shall operate to exclude any warranty or condition implied by law as to the quality of the goods in the event that the goods when sold by the Customer or when sold by any person or persons to whom the Customer may sell the goods shall become the subject of a consumer sale as defined in the Sale of Goods Act 1979, or any statutory reenactment or modification thereof, except to the extent that any claim under such warranty or condition shall have arisen from any act or omission by the Customer or by any other persons selling the goods by a way of a consumer sale.

## **17 Patents etc**

- (17.1) The Company will defend the Customer against any claim of infringement of Letters Patent, Registered Design, Trade Mark or Copyright (published at date of the contract) by the use or sale of any article or material supplied by the Company to the Customer and will indemnify the Customer against all third party costs and damages awarded against the Customer as a result of such claim; provided always that this indemnity shall not apply to any infringement which is due to the Company having followed a design or instruction furnished or given by the Customer or in a foreign country not specified by or disclosed to the Company, or to any infringement which is due to the use of such article or material in association or combination with any article or material not supplied by the Company; and provided also that this indemnity is conditional on the Customer giving to Company the earliest possible notice in writing of any claim being made or action threatened or brought against the Customer and on the Customer's permitting the Company at the Company's own expense to conduct any litigation that may ensue and all negotiations for a settlement of the claim and giving the Company all reasonable assistance. The Customer on his part warrants that any design or instruction furnished or given by him shall not be such as will cause the Company to infringe any Letters Patent, Registered Design, Trade Mark or Copyright in execution of the Customer's order.

- (17.2) The Customer shall not use any registered or unregistered trade marks, trade names, brand names, product names, images, logos, designs, get-ups or materials of the Company except those provided by the Company to the Customer for the purposes for which they were supplied and shall cease using them if required by the Company in writing at any time.

## **18 Reservation Clause**

The fulfilment of the agreement on the Company's part is subject to the proviso that this shall not be prevented by impediments on the grounds of national and international legal requirements, in particular export control provisions.

## **19 Limitation of Liability**


- (19.1) Nothing in these conditions excludes or limits the liability of the Company:

- (19.1.1) for death or personal injury caused by the Company's negligence; or
  - (19.1.2) under section 2(3), Consumer Protection Act 1987; or
  - (19.1.3) for any matter which it would be illegal for the Company to exclude or attempt to exclude its liability; or
  - (19.1.4) for fraud or fraudulent misrepresentation.
- (19.2) Subject to Clause 19.1:
- (19.1.1) the Company's total liability in contract, tort (including negligence or breach of statutory duty), misrepresentation, restitution or otherwise, arising in connection with the performance or contemplated performance of the contract with the Customer shall be limited to the contract price; and
  - (19.1.1) the Company shall not be liable to the Customer for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the agreement.

## **20 Legal construction**

The contract shall in all respects be construed and operate as an English contract and in conformity with English law.

(Revised August 2009)



# Notes

## 1. Minimum Order Values

All orders must be in multiples of the Sales Pack detailed for each product.

Orders for part Sales Packs will be rounded up to the next full Sales Pack quantity.

Prices are carriage paid to UK on shore locations subject to a Minimum Order Value of £250 net invoice value (excluding WEEE or other charges).

A Small Order Charge of £10 will be made for freight and handling of orders less than £250 net invoice value.

## 2. CE Marking

In order to show compliance with the EMC Directive (89/336/EEC) and the Low Voltage Directive (73/23/EEC) all OSRAM high frequency electronic control gear, transformers and integrally ballasted compact fluorescent lamps carry the 'CE' mark.

All other lamps that operate above 50V are CE marked to show compliance with the Low Voltage Directive (73/23/EEC)

## 3. Energy Efficiency Classification

Mains operated household lamps (e.g. GLS, TH, integral ballasted CFLs, Fluorescent tubes) are energy labelled to show compliance with the Energy Labelling Directive (98/11/EEC).

The energy label indicates the energy efficiency index of the lamp and is classified on a scale from A (the highest) to G (the lowest).

## 4. Compliance with Standards

Compliance with relevant EN and IEC Standards is a priority in the design, manufacture and quality control of our products.

## 5. OSRAM will, upon request, provide CE Declarations of Conformity.

## 6. All OSRAM products are manufactured and supported under Quality Systems Management designed to meet EN ISO 9001 2000.

## 7. Since July 2006 all OSRAM products are compliant with Directive 2002/95/EC on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS).

## 8. Collection, Disposal and Recycling of End of Life Lamps & Luminaires

From 1st July 2007 The Waste Electrical and Electronic Regulations 2006 – S.I. 2006 No. 3289 (commonly referred to as the WEEE Directive) became effective in the UK. Under the terms of the regulations OSRAM Ltd. is classed as a Producer for OSRAM branded products and is responsible for the financing of the collection, treatment, recovery and disposal of WEEE that we put onto the UK market. As required by the regulations OSRAM Ltd. is registered as a Producer with the Environment Agency, our UK Producer Registration Number (PRN) is WEE/FEO081UW and this will be clearly displayed on all OSRAM Ltd. invoices.

All OSRAM branded products affected by the WEEE Directive are marked with the "crossed out wheelie bin" symbol  These products are also identified within this publication by the same symbol.

To fulfil our obligations OSRAM Ltd. has joined the Recolight Compliance Scheme [www.recolight.co.uk](http://www.recolight.co.uk).

All enquiries or questions relating to the collection, treatment, recovery and recycling of OSRAM branded products affected by the WEEE Directive in the UK should be directed to Recolight Ltd. at [info@recolight.co.uk](mailto:info@recolight.co.uk)

OSRAM strives to achieve the highest possible standards of customer service and to provide a co-ordinated product range.

# Contact Details

## OSRAM Customer Service Centre

OSRAM Ltd.

Neills Road

Bold Industrial Park

St Helens WA9 4XG

Tel: 01744 812221

Fax: 01744 831900

E-mail: [csc@osram.co.uk](mailto:csc@osram.co.uk)

## Notes