

500W XENON COMPACT-SOURCE
D.C. ARC LAMP WITH
ELLIPSOIDAL COLD-MIRROR
REFLECTOR BULB

G.E. ORDER ABBREVI.

WATTS	500
CURRENT	APPROX. 27 AMP DC
OPERATING VOLTS	185± 1.5V
OPEN CIRCUIT STARTING VOLTS	90V MINIMUM
IGNITION VOLTAGE	APPROX. 20KV
ARC GAP	APPROX. 2.3 MM HOT
2000 HR. LUMEN MAINTENANCE AVG.	80% OF INITIAL LUMEN
AVG. LIFE	1500 HR (AT 3HRS. ON, BETWEEN 25 MINUTES OFF) NONHORIZONTAL AND STRAIGHT UP
OPERATING POSITION	QUARTZ
ARC TUBE	ELLIPSOIDAL COLD MIRROR
OUTER BULB	INS GLASS HEAT-RESIST.
TERMINALS	#12 STRANDED LEAD WIRES, 5" LONG

NOTE 1
EFFECTIVE DIAMETER OF THE
ELLIPSOIDAL REFLECTOR IS 4 1/2"

REMARKS

GENERAL ELECTRIC
LARGE LAMP DEPARTMENT
NELA PARK • CLEVELAND 12 • OHIO

Form No. 239

